


# **TECHNICAL DATA SHEET**




## NL4040

Thermoelectric Cooler RoHS EU Compliant

## TYPICAL PERFORMANCE VALUES

Hot Side Temperature (°C)	27°C	50°C
Δ Tmax (°C-dry N <sub>2</sub> ):	120	136
Qmax (watts):	2.7	3.0
Imax (amps):	4.0	4.0
Vmax (vdc):	6.8	7.7
AC Resistance (ohms):	1.62	

## MECHANICAL CHARACTERISTICS



## **ORDERING OPTIONS**


Model Options	Metallization	Elevated Temperature Burn-In with test data
NL4040-01BC-36	Both	Yes
NL4040-02BC-36	Base	Yes
NL4040-03BC	None	No
NL4040-04BC	Both	No
NL4040-05BC	Base	No


## PRODUCT FEATURES

- Pretinned metallized ceramic surface(s) with 117°C solder.
- Thermistor mounted on edge of cold side ceramic. (Calibration available.)
- Elevated temperature burn-in with test data provided.

# **LYPICAL PERFORMANCE CURVES**

## ENVIRONMENT: ONE ATMOSPHERE DRY NITROGEN





For performance information in a vacuum or with hot side temperatures other than 27°C or 50°C, contact one of our Applications Engineers at 877-627-5691.

## Installation

Recommended mounting methods: Bonding with thermal epoxy or soldering with metallized ceramics. For additional information, please refer to our TEC Installation Guide.

## **Operation Cautions**

For maximum reliability, storage and operation below 85°C in a non-condensing environment is recommended. To minimize thermal stress, use linear/proportional temperature control or a similar method rather than an ON/OFF method.

## **CONTACT US:**

For customer support or general questions please contact a local office below or visit our website at www.marlow.com.

Marlow Industries, Inc. 10451 Vista Park Road Dallas Texas 75238-1645 214-340-4900 (tel) 214-341-5212 (fax) 877-627-5691 (tech support)

www.marlow.com

II-VI Japan Inc. WBG Marive East 17F 2-6 Nakase, Mihama-ku Chiba-Shi, Chiba 261-7117 Japan 81 43 297 2693 (tel) 81 43 297 3003 (fax) center@ii-vi.co.jp www.ii-vi.co.jp Marlow Industries Europe GmbH Brunnenweg 19-21 64331 Weiterstadt

Germany

www.ii-vi.com.sg

Tel.: +49 (0) 6150 5439 - 403 Fax: +49 (0) 6150 5439 - 400 info@marlow-europe.eu

II-VI Singapore Pte., Ltd.
Blk. 5012, Techplace II
#04-07 & 05-07/12, Ang Mo Kio Ave. 5
Singapore 569876
(65) 6481 8215 (tel)
(65) 6481 8702 (fax)
info@ii-vi.com.sq

Marlow Industries China, II-VI Technologies Beijing A subsidiary of II-VI Incorporated Rm 202, 1# Lize 2nd Middle Road Wangjing, Chaoyang District Beijing 100102 China 010-64398226 ext 105 (tel) 010-64399315 (fax) info@iivibj.com