

Data Structures

Lists II

CS284

Structure of this week's classes

- ▶ Change of office hour?
- ▶ Double-Linked List
- ▶ Exercises on SingleLinkedList
- ▶ LeetCode question: Finding the intersection node of two linked lists

List


- ▶ Last class we introduced lists
- ▶ We studied an array based implementation
- ▶ We also studied a linked-list based implementation (Single Linked Lists)
- ▶ Next we present a double-linked list implementation (Double Linked Lists)
- ▶ Also, we present Iterators

Limitations of a single-linked list

- ▶ Insertion at the front is $O(1)$; insertion at other positions is $O(n)$
- ▶ Insertion is convenient only after a referenced node
- ▶ Removing a node requires a reference to the previous node
- ▶ We can traverse the list only in the forward direction
- ▶ **We can overcome these limitations by:**
 - ▶ Add a reference in each node to the previous node, creating a double-linked list

Node Class

```
private static class Node<E> {  
    private E data;  
    private Node<E> next = null;  
    private Node<E> prev = null;  
    private Node(E dataItem) {  
        data = dataItem;  
    }  
    private Node(E dataItem, Node<E> p, Node<E> n ) {  
        data = dataItem;  
        prev = p;  
        next = n;  
    }  
}
```




Inserting into a Double-Linked List

```
Node<String> sam = new Node<String>("Sam");  
Node<String> harry = new Node<String>("Harry");  
harry.next = sam;  
sam.prev = harry;
```

► Let's draw a diagram

Inserting into a Double-Linked List


```
Node<String> sharon = new Node<String>("Sharon");  
sharon.next = sam;  
sharon.prev = sam.prev;  
sam.prev.next = sharon;  
sam.prev = sharon
```



How do we remove a node?

Consider the execution of the following additional lines

```
harry.prev.next = harry.next  
harry.next.prev = harry.next
```



The class `DLList<E>`

```
public class DLList<E> {  
  
    private class Node<E> {  
        /* As defined above */  
        ...  
    }  
    /** The first element in the list */  
    private Node<E> head;  
    /** The last element in the list */  
    private Node<E> tail;  
    /** The size of the list */  
    private int size = 0;  
  
    // Operations should follow  
}
```

Implement `public void add(E item)`

- ▶ This operation should add the item in a new node at the beginning of the list

Double-Linked List

- ▶ So far we have worked only with internal nodes
- ▶ As with the single-linked class, it is best to access the internal nodes with a double-linked list object
- ▶ A double-linked list object has data fields:
 - ▶ `head` (a reference to the first list Node)
 - ▶ `tail` (a reference to the last list Node)
 - ▶ `size`
- ▶ Insertion at either end is $\mathcal{O}(1)$; insertion elsewhere is still $\mathcal{O}(n)$

Iterators

- ▶ An iterator can be viewed as a moving place marker that keeps track of the current position in a particular linked list
- ▶ An Iterator object for a list starts at the list head
- ▶ The programmer can move the Iterator by calling its next method
- ▶ The Iterator stays on its current list item until it is needed

Iterator interface

- ▶ The Iterator interface is defined in `java.util`
- ▶ The List interface declares the method `iterator()` which returns an Iterator object that iterates over the elements of that list

Method

boolean `hasNext()`

`E next()`

void `remove()`

Behavior


Returns true if the next method returns a value

Returns the next value. If there are now more elements, throws the `NoSuchElementException`

Removes the last element returned by the next method

Iterator interface

An Iterator is conceptually between elements; it does not refer to a particular object at any given time



Iterator interface

In the following loop, we process all items in `List<Integer>` through an `Iterator`

```
Iterator<Integer> iter = aList.iterator();  
while (iter.hasNext()) {  
    int value = iter.next();  
    // Do something with value  
    ...  
}
```

Demo: SingleLinkedList

```
/**
 * @return a boolean indicating whether all the
 * elements in the list are non-null
 */
public SingleLinkedList<E> clone() {
    if (this.head != null) {
        Node<E> previous = new Node<E>(head.data);
        Node<E> head_2 = previous;
        Node<E> node = this.head;
        while (node.next != null) {
            node = node.next;
            Node<E> node_2 = new Node<E>(node.data);
            previous.next = node_2;
            previous = node_2;
        }
        return new SingleLinkedList<E>(head_2);
    }
    else {
        return null;
    }
}
```


Demo: SingleLinkedList

```
/**
 *
 * @return appends the two lists
 */
public void append(SingleLinkedList<E> l2){
    if (this.head != null) {
        Node<E> node = this.head;
        while (node.next != null) {
            node = node.next;
        }
        node.next = l2.head;
    }
    else {
        this.head = l2.head;
    }
}
```

Demo: SingleLinkedList

```
/**
 * returns a new list in which n copies of the
 * original list have been juxtaposed
 * @param n
 */
public void repeatLN(int n){
    SingleLinkedList<E> sll_clone = this.clone();
    for (int i = 0; i < n - 1; i ++){
        this.append(sll_clone);
    }
}
```

Demo: SingleLinkedList

```
/**
 * repeats each element in the list n times
 * @param n
 */
public void stutterNL(int n){
    if (this.head != null) {
        Node<E> node = this.head;
        Node<E> node_next = node.next;
        ArrayList<Node<E>> sub_list = this.sub_copy(node, n);
        Node<E> all_head = sub_list.get(0);
        Node<E> new_tail = sub_list.get(1);
        while (node_next != null) {
            node = node_next;
            node_next = node.next;
            sub_list = this.sub_copy(node, n);
            Node<E> new_head = sub_list.get(0);
            new_tail.next = new_head;
            new_tail = sub_list.get(1);
        }
        this.head = all_head;
    }
}
```

Demo: SingleLinkedList

```
public ArrayList<Node<E>> sub_copy(Node<E> node, int n) {  
    Node<E> head = node;  
    for (int j = 0; j < n - 1; j++) {  
        Node<E> copy_node = new Node<E>(node.data);  
        node.next = copy_node;  
        node = copy_node;  
    }  
    ArrayList<Node<E>> ret_array = new ArrayList<Node<E>>();  
    ret_array.add(head);  
    ret_array.add(node);  
    return ret_array;  
}
```

Demo: SingleLinkedList

```
/**
 * removing the adjacent duplicate items
 */
public void removeAdjacentDuplicates() {
    if (this.head != null) {
        Node<E> node = this.head;
        Node<E> new_head = node;
        Node<E> current_node = node;
        E prev_Data = node.data;
        while (node.next != null) {
            node = node.next;
            if (node.data.equals(prev_Data) == false) {
                current_node.next = node;
                current_node = node;
            }
            prev_Data = node.data;
        }
        this.head = new_head;
    }
}
```

Demo: SingleLinkedList

```
/**
 * Provide a solution in which a new list is constructed
 * @param l2
 */
public void zipL(SingleLinkedList<E> l2) {
    if (this.head != null) {
        Node<E> node = this.head;
        Node<E> new_head = node;
        Node<E> node_2 = l2.head;
        Node<E> node_next = node.next;
        Node<E> node_next_2 = node_2.next;

        while (node_next != null) {
            node.next = node_2;
            node_2.next = node_next;


            node = node_next;
            node_2 = node_next_2;

            node_next = node.next;
            node_next_2 = node_2.next;
        }
    }
}
```

Finding Intersection of Two Lists

Write a program to find the node at which the intersection of two singly linked lists begins.


For example, the following two linked lists:



Finding Intersection of Two Lists (Non-Overlap)

Write a program to find the node at which the intersection of two singly linked lists begins.


For example, the following two linked lists:



Ideas and Thoughts


Linear time complexity is necessary:

- ▶ The list is only singly linked;
- ▶ In the worst case, have to traverse the entire lists to reach the intersection;
- ▶ We can traverse the linked list for constant number of times;



Ideas and Thoughts

- ▶ The problem with a single linked list is we don't know how far the pointer is to the intersection node;
- ▶ Synchronized two pointers: make the pointer the same distance to the intersection, and they will meet;
- ▶ Idea: move the pointer for list B for n positions, where $n = B.length - A.length$;



Algorithms

Steps:

- ▶ For each list, traverse and get $A.length$ and $B.length$;
- ▶ If $A.length > B.length$, move pointer of list A for n positions, where $n = A.length - B.length$;
- ▶ Otherwise, move pointer of list B for n positions, where $n = B.length - A.length$;
- ▶ Make synchronized move for list A and B;
- ▶ If they meet somewhere, return that node; otherwise, return null;

Implementation

Traverse and get the lengths:

```
/**
 * get the intersection node between list starting
 * with head1 and head2
 * @param head1
 * @param head2
 * @return
 */
public Node<E> getIntersectionNode(Node<E> head1,
Node<E> head2) {
    if (head1 == null || head2 == null)
        return null;
    Node<E> node1 = head1;
    Node<E> node2 = head2;
    int len1 = len2 = 0;
    while (node1 != null) {
        node1 = node1.next;
        len1++;
    }
    while (node2 != null) {
        node2 = node2.next;
        len2++;
    }
```

Implementation

Shift the pointers:

```
node1 = head1;
node2 = head2;

if (len1 > len2) {
    // shift node1 for len1 - len2 times;
    int steps = len1 - len2;

    for (int i = 0; i < steps; i++)
        node1 = node1.next;
}
else if (len2 > len1){
    int steps = len2 - len1;

    for (int i = 0; i < steps; i++)
        node2 = node2.next;
}
```

Implementation

Make synchronized moves:

```
// now make sync move for node 1 and node2

while (node1 != null) {
    if (node1.equals(node2) == true)
        return node1;
    node1 = node1.next;
    node2 = node2.next;
}

return null;
}
```