

DECLARATION OF CONFORMITY (EU)

No. 20538/2025

1. Product Name and Model:

Banana Plug (4mm Banana Plug / Stackable Banana Plug)

Model No.: BP-2501

2. Importer:

VATSPEEDSL

Calle Antonio Salvador N99.1, 28026 Madrid, Spain

Email: services@vatspeed-eu.com

3. This declaration of conformity is issued under the sole responsibility of the importer:

VATSPEEDSL

Calle Antonio Salvador N99.1, 28026 Madrid, Spain

4. Product Name and Photo:

Banana Plug



5. Product complies with the directives:

- RoHS Directive 2011/65/EU – Restriction of Hazardous Substances
- REACH Regulation EC No 1907/2006 (chemical safety)
- Low Voltage Directive (LVD) 2014/35/EU (if rated for >50V AC or >75V DC applications)
- General Product Safety Regulation (GPSR) EU 2019/1020

6. Product complies with the standards:

- IEC 60417 – Graphical symbols for use on equipment (polarity identification)

symbols)

- EN 61010-1:2010 – Safety requirements for electrical equipment for measurement, control and laboratory use (for test leads and accessories, if applicable)
- IEC 60352-2:2020 – Solderless connections – Part 2: Crimped connections (for crimp-type banana plugs)
- EN 60512-9-3:2011 – Connectors for electronic equipment – Mating and unmating forces
- EN 60512-5-2:2002 – Connectors – Current-carrying capacity tests
- IEC 62321 Series – Determination of six regulated substances (RoHS)
- ISO 9001:2015 – Quality management systems

7. Additional Notes:

This banana plug has been tested and found to comply with the applicable EU directives and harmonized standards. It is designed for use in electrical and electronic test equipment (multimeters, power supplies, speakers, amplifiers, laboratory instruments) for safe and reliable connection of 4mm banana jacks.

Product meets requirements for:

- Hazardous substance restrictions (RoHS) – Lead-free, cadmium-free, mercury-free
- Chemical safety (REACH) – No SVHC above 0.1% (including phthalates, heavy metals)
- Electrical safety (LVD) – Rated for up to 1000V DC / 1000V AC (or as specified), with insulation category CAT II / CAT III / CAT IV depending on model
- Current rating – 10A to 30A continuous (gold-plated/ nickel-plated/ bare brass versions)
- Contact resistance – $<1\text{m}\Omega$ (gold-plated/beryllium copper contacts)
- Durability – 10,000+ insertion cycles
- Dielectric strength – 2,000V AC for 1 minute (insulated versions)
- Insulation resistance – $>100\text{M}\Omega$ @ 500V DC (nylon/ABS/PVC insulated versions)

Materials (typical):

- Conductor: Brass / Phosphor bronze / Beryllium copper
- Plating: Gold / Nickel / Tin / Silver
- Insulation: Nylon / ABS / PVC / PTFE / Silicone rubber (color-coded: red/black/blue/yellow/green)

Applications:

- Multimeter test leads
- Power supply connections
- Speaker / amplifier banana jacks
- Laboratory and educational equipment
- Battery and charger connections
- Electrical testing and measurement

Date: 2025-01-01

Place: Madrid, Spain

Authorized Signatory:

Name: Carlos Fernández

Position: Compliance Officer



Signature:

