

DECLARATION OF CONFORMITY (EU)

No. 20539/2025

1. Product Name and Model:

Toilet Flush Button (Dual Flush / Single Flush Button)

Model No.: TFB-2601

2. Importer:

VATSPEDSL

Calle Antonio Salvador N99.1, 28026 Madrid, Spain

Email: services@vatspeed-eu.com

3. This declaration of conformity is issued under the sole responsibility of the importer:

VATSPEDSL

Calle Antonio Salvador N99.1, 28026 Madrid, Spain

4. Product Name and Photo:

Toilet Flush Button



5. Product complies with the directives:

- General Product Safety Regulation (GPSR) EU 2019/1020
- Regulation (EU) 2023/988 on general product safety
- REACH Regulation EC No 1907/2006 (chemical safety)

- RoHS Directive 2011/65/EU (if applicable – for electronic flush buttons with sensors)

6. Product complies with the standards:

- EN 71-3:2019+A1:2021 – Migration of certain elements (for plastic/metal component safety)
- ISO 10993-10:2021 – Biological evaluation – Skin sensitization (for materials in contact with hands)
- EN ISO 9001:2015 – Quality management systems
- EN 681-1:1996 – Elastomeric seals – Material requirements for pipe joint seals (for rubber sealing components, if applicable)
- IEC 62321 Series – Determination of six regulated substances (RoHS – if electronic)

7. Additional Notes:

This toilet flush button has been tested and found to comply with the applicable EU general product safety regulations and relevant chemical safety standards. It is designed as a replacement or OEM component for toilet cisterns to activate the flushing mechanism (single flush or dual flush: half/full flush).

Product meets requirements for:

- Mechanical durability – tested for 100,000+ actuation cycles
- Material safety – non-toxic ABS/PC/nylon/stainless steel construction
- Chemical safety – REACH compliance (no SVHC above 0.1%, no phthalates, no heavy metals)
- Corrosion resistance – salt spray tested (for metal components)
- Water resistance – suitable for high-humidity bathroom environments
- Dimensional accuracy – compatible with standard cistern openings (25mm–65mm diameter variants)
- Spring mechanism reliability – consistent return force for proper valve actuation

Applications:

- Wall-mounted dual flush plates (pneumatic/push-button type)

- Top-mount cistern buttons (direct action)
- Side-mount flush buttons
- Electronic flush button panels (if model includes touch sensor or LED indicator)

Date: 2025-01-01

Place: Madrid, Spain

Name: Carlos Fernández

Position: Compliance Officer



Signature:

