

DECLARATION OF CONFORMITY (EU)

No. 20542/2025

1. Product Name and Model:

TIG Torch Quick Connector / TIG Welding Torch Accessory Quick Coupler

Model No.: TQC-2901

2. Importer:

VATSPEEDSL

Calle Antonio Salvador N99.1, 28026 Madrid, Spain

Email: services@vatspeed-eu.com

3. This declaration of conformity is issued under the sole responsibility of the importer:

VATSPEEDSL

Calle Antonio Salvador N99.1, 28026 Madrid, Spain

4. Product Name and Photo:

TIG Torch Quick Connector



5. Product complies with the directives:

- Low Voltage Directive (LVD) 2014/35/EU (for electrical connections carrying welding voltage/current)
- REACH Regulation EC No 1907/2006 (chemical safety – metal/insulation materials)
- RoHS Directive 2011/65/EU – Restriction of Hazardous Substances (if applicable for electronic components – not typical)

- General Product Safety Regulation (GPSR) EU 2019/1020

6. Product complies with the standards:

- EN 60974-1:2012+A1:2019 – Arc welding equipment – Part 1: Welding power sources (for connector compatibility and safety)
- EN 60974-7:2019 – Arc welding equipment – Part 7: Torches (for torch connector interface and safety requirements)
- EN 60974-12:2011+A1:2021 – Arc welding equipment – Part 12: Coupling devices for welding cables and connections
- EN 60529:1991+A2:2013 – Degrees of protection provided by enclosures (IP code – for environmental sealing)
- ISO 9001:2015 – Quality management systems
- IEC 62321 Series – Determination of six regulated substances (RoHS – if electronic contacts present)
- EN 71-3:2019+A1:2021 – Migration of certain elements (for plastic/insulation material safety)
- EN 10204:2004 – Metallic products – Types of inspection documents (for material traceability, if required)

7. Additional Notes:

This TIG torch quick connector / TIG welding torch accessory quick coupler has been tested and found to comply with the applicable EU directives and harmonized standards. It is designed for use in TIG (Tungsten Inert Gas) welding systems to provide quick, secure, and conductive connections between the welding torch and the power source/gas supply.

Product meets requirements for:

Electrical & Performance Safety:

- Current carrying capacity – Rated for continuous welding current: ___ A (e.g., 200A / 300A / 500A) at rated duty cycle (e.g., 60% / 100%)
- Voltage rating – Suitable for welding circuit open-circuit voltage up to 113V DC / 100V AC (or as per EN 60974-1)
- Contact resistance – <1mΩ to minimize power loss and heat generation during welding

- Dielectric strength – Insulation components tested to withstand 1,000V AC + 2× rated voltage (for 1 minute) without breakdown
- Insulation resistance – >100MΩ @ 500V DC (for insulated connector bodies)
- Insertion/withdrawal force – Quick connect mechanism: 20N–80N engagement force, positive locking with audible/ tactile click
- Cycle durability – Tested for 10,000+ mating cycles without loss of electrical or mechanical performance
- Polarization/keying – Prevents incorrect connection, ensuring proper gas/current flow direction
- Locking mechanism – Positive locking (ball detent / twist-lock / push-pull) resistant to vibration and accidental disconnection during welding

Environmental & Mechanical Protection:

- Environmental sealing – IP54 or higher (dust-protected, splash-resistant) for workshop/field conditions
- Corrosion resistance – Salt spray tested (ISO 9227) – minimum 72 hours without red rust
- Temperature range – -25°C to +105°C operating temperature (materials rated for high-heat welding environments)
- Vibration/shock resistance – Maintains electrical connection under typical welding equipment handling
- Cable clamp/grip – Secure strain relief for welding cable (diameter range: 10mm–25mm as specified)

Material Safety & Construction:

- Conductor material – Brass / copper alloy / silver-plated copper for high conductivity
- Plating/finish – Nickel-plated / silver-plated / gold-plated (for corrosion resistance and low contact resistance)
- Insulation/body material – High-temperature resistant nylon / POM / PEEK / PTFE / TPE (rated 105°C–250°C)
- REACH compliance – No SVHC above 0.1% in metal alloys or plastic insulation

- Cadmium-free – All components comply with cadmium restriction ($\leq 0.01\%$ for electrical contacts)
- Sealing material – Silicone/FKM/Viton O-rings (heat-resistant, chemical-resistant to inert gases)

Connector Types (select applicable):

- Gas/water cooled torch connector – Central pin (power) + peripheral gas/water passages
- Euro / Central connector – Standard 9/14-pin or 19/27-pin configuration per EN 60974-7
- Quick-disconnect water coupler – For water-cooled TIG torches (separate gas/water fittings)
- Threaded connector – Forced connection with locking nut (traditional style)

Key Features:

- Tool-free connection/disconnection
- Color-coded or keyed for polarity/phase identification
- Ergonomically designed grip sleeves for gloved hand operation
- Auto-shutoff gas valves in connector (certain models – prevents gas loss when torch disconnected)

Date: 2025-01-01

Place: Madrid, Spain

Authorized Signatory:

Name: Carlos Fernández

Position: Compliance Officer



Signature:

