

14. Find grammars for  $\Sigma = \{a, b\}$  that generate the sets of

- (a) all strings with exactly two  $a$ 's.
- (b) all strings with at least two  $a$ 's.
- (c) all strings with no more than three  $a$ 's.
- (d) all strings with at least three  $a$ 's.
- (e) all strings that start with  $a$  and end with  $b$ .

(b)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow S a S a S', S' \rightarrow a S' | b S' | \lambda$

(c)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow S a S a S' | S a S a S' | S a S' | s', S' \rightarrow b S' | \lambda$

(d)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow S a S a S' a S', S' \rightarrow a S' | b S' | \lambda$

(e)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow a S' b, S' \rightarrow a S' | b S' | \lambda$

17. Let  $\Sigma = \{a, b\}$ . For each of the following languages, find a grammar that generates it.

(a)  $L_1 = \{a^n b^m : n \geq 0, m < n\}$ .

(b)  $L_2 = \{a^{3n} b^{2n} : n \geq 2\}$ .

(c)  $L_3 = \{a^{n+3} b^n : n \geq 2\}$ .

(d)  $L_4 = \{a^n b^{n-2} : n \geq 3\}$ .

(e)  $L_1 L_2$ .

(f)  $L_1 \cup L_2$ .

(g)  $L_1^3$ .

(h)  $L_1^*$ .

(i)  $L_1 - L_4$ .

(a)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow a S', S' \rightarrow a S' b | a S' | \lambda$

(b)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow a a a a a S' b b b b b, S' \rightarrow a a a S' b b | \lambda$

(c)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow a a a a a S' b b, S' \rightarrow a S' b | \lambda$

(d)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow a a a S' b, S' \rightarrow a S' b | \lambda$

(e)  $G = \{ \{s, A, B, C, D\}, \{a, b\}, S, P \}, P = S \rightarrow A B, A \rightarrow a C, C \rightarrow a C b | a C | \lambda, B \rightarrow a a a a a D b b b b b, D \rightarrow a a a D b b | \lambda$

(f)  $G = \{ \{s, s'\}, \{a, b\}, S, P \}, P = S \rightarrow a S', S' \rightarrow a S' b | a S' | \lambda$

(g)  $G = \{ \{s, s', s''\}, \{a, b\}, S, P \}, P = S \rightarrow S S' S', S' \rightarrow a S'', S'' \rightarrow a S' b | a S'' | \lambda$

(h)  $G = \{ \{s, A, B, C, D\}, \{a, b\}, S, P \}, P = S \rightarrow A | \lambda, A \rightarrow B A | B, B \rightarrow a C, C \rightarrow a C b | a C | \lambda$

(i)  $G = \{ \{s, A, B, C, D\}, \{a, b\}, S, P \}, P = S \rightarrow a a A b | a a b | a C, A \rightarrow a B b | B, B \rightarrow a C | b D, C \rightarrow a C | \lambda, D \rightarrow b D | \lambda$

19. Find a grammar that generates the language



$$L \{ ww^R : w \in \{a, b\}^+ \}.$$

Give a complete justification for your answer.

$$G = \{ S \}, \{ a, b \}, S \rightarrow aSb \mid bSb \mid \lambda \Rightarrow \text{長度為偶數的迴文}$$




4. For  $\Sigma = \{a, b\}$ , construct dfa's that accept the sets consisting of

- (a) all strings with exactly one  $a$ .
- (b) all strings with at least two  $a$ 's.
- (c) all strings with no more than two  $a$ 's.
- (d) all strings with at least one  $b$  and exactly two  $a$ 's.
- (e) all the strings with exactly two  $a$ 's and more than three  $b$ 's.




11. Consider the set of strings on  $\{0, 1\}$  defined by the requirements below. For each, construct an accepting dfa.


- (a) Every 00 is followed immediately by a 1. For example, the strings 101, 0010, 0010011001 are in the language, but 0001 and 00100 are not.
- (b) All strings that contain the substring 000, but not 0000.
- (c) The leftmost symbol differs from the rightmost one.
- (d) Every substring of four symbols has, at most, two 0's. For example, 001110 and 011001 are in the language, but 10010 is not because one of its substrings, 0010, contains three zeros.
- (e) All strings of length five or more in which the third symbol from the right end is different from the leftmost symbol.
- (f) All strings in which the leftmost two symbols and the rightmost two symbols are identical.



13. Show that the language  $L = \{vuv : v, w \in \{a, b\}^*, |v| = 3\}$  is regular.




8. Design an nfa with no more than five states for the set  $\{abab^n : n \geq 0\} \cup \{aba^n : n \geq 0\}$ .




11. (a) Find an nfa with three states that accepts the language

$$L = \{a^n : n \geq 1\} \cup \{b^m a^k : m \geq 0, k \geq 0\}.$$

(b) Do you think the language in part (a) can be accepted by an nfa with fewer than three states?




12. Find an nfa with four states for  $L = \{a^n : n \geq 0\} \cup \{b^n a : n \geq 1\}$ .



2. Convert the nfa in Exercise 13, Section 2.2, into an equivalent dfa.

13. Which of the strings 00, 01001, 10010, 000, 0000 are accepted by the following nfa?



4. Convert the nfa defined by

$$\begin{aligned}\delta(q_0, a) &= \{q_0, q_1\} \\ \delta(q_1, b) &= \{q_0, q_2\} \\ \delta(q_2, a) &= \{q_1\} \\ \delta(q_0, \lambda) &= \{q_2\}\end{aligned}$$

with initial state  $q_0$  and final state  $q_2$  into an equivalent dfa.

