FIT2099 Assignment 3 Design Rationale

Requirement	Author
REQ 1: Second Spring	Poyee Tan 36641162
REQ 3: Infestation and Pest Control	Jingyu Zhang 37033956
REQ 4: Enchanted Tools	Yuanshu Liu 36226173
REQ 5: The Wanderer (API, HD)	Jingyu Zhang, Yuanshu Liu, Poyee Tan

Poyee Tan 36641162 – REQ 1: Second Spring

Class diagram: `docs/A3_UML/A3_REQ1_UML.drawio`. Feature proposal: `feature-proposal.md`.

REQ1 makes plants alive. Every plant has its own age, which starts at 0 and goes up by 1 each turn. Each turn the plant tries its abilities in priority order (grow, spread, or drop produce) and stops at the first one that succeeds, so a plant does at most one thing per turn. Only tilled Soil accepts new plants. Every effect changes the map, never only prints text.

Class	Abstraction	Effect	Game state it changes
`Plant`	`Ground`, `Regressible`	Ages each turn, tries its abilities, can be set back one stage	Its own age; the ground on its tile
`PeriodicAbility`	`PlantAbility`	Acts every N turns of age with a given chance	— (template only)
`Grow`	`PeriodicAbility`, uses `Growing`	Replaces the plant with a new instance of its next stage	The ground on the tile
`SelfReplicate`	`PeriodicAbility`, uses `Spreading`	Plants a new plant on a random adjacent Soil tile	The ground on a nearby tile
`Produce`	`PeriodicAbility`, uses `Producing`	Drops a new item on a random adjacent tile	Items on a nearby tile
`StrawberrySeedling`, `StrawberrySprout`, `CauliflowerSprout`, `MelonSprout`	`Plant`	The young stages, which grow and (sprouts) spread	—
`Plantable`, `PlantableTile`	interface, `TileCondition`	Say which ground a plant may be planted on	—
`GrowthPausedStatus`	`TimedStatus`	Stops a plant's abilities for a few turns	Whether the plant acts

Plant	Abilities, highest priority first	Capabilities	Regresses to
`StrawberrySeedling`	Grow (every 5 turns, 50%)	`Growing`	Dirt
`StrawberrySprout`	Grow (10, 50%), SelfReplicate (5)	`Growing`, `Spreading`	`StrawberrySeedling`
`CauliflowerSprout`	Grow (15, 25%)	`Growing`	Dirt
`MelonSprout`	Grow (15, 25%), SelfReplicate (10)	`Growing`, `Spreading`	Dirt
`Strawberry`	Produce (5)	`Producing`	`StrawberrySprout`
`Melon`	SelfReplicate (20)	`Spreading`	`MelonSprout`
`Tomato`	Produce (7), SelfReplicate (20, 10%)	`Producing`, `Spreading`	Dirt
`Parsnip`	Produce (15)	`Producing`	Dirt
`Cauliflower`	none	none	`CauliflowerSprout`

Each decision compares rejected and chosen designs, with pros, cons and a future example. Each decision ends with a principles check covering SOLID, DRY, KISS, connascence and code smells. Sections I and K list every place a reader may see as a weakness, and say why we chose it.

A. One class per growth stage

Rejected 1: one class per crop with a `stage` field and a `switch` that picks the character, abilities and rules.

Pros	Cons
KISS: one class holds a crop's whole life.	OCP: a new stage edits every `switch` (the "switch statement" smell).

Pros	Cons
No new classes.	SRP: one class owns several display characters, ability lists and harvest rules.
	A sprout would still offer watering and harvesting, guarded by `if (stage == SPROUT)` checks.

Rejected 2: one class per crop holding a separate stage object (State pattern) that it swaps as it grows.

Pros	Cons
The crop keeps one identity on the tile.	The spec says growing creates "a brand new plant with age 0"; a swapped state would have to reset the age by hand (Connascence of Execution).
	The tile object would have to change its character, name and allowed actions at run time.

Chosen: one `Plant` subclass per stage. `Plant` is a new abstract class between `Ground` and `Crop`, and `Crop` now extends it. Growing replaces the ground with a new object, so the new stage starts at age 0 with no reset code. The young stages extend `Plant`, not `Crop`: as `Crop`s they would inherit watering and harvesting they must refuse.

Pros	Cons
OCP: a new stage is one new class. No existing stage changes.	Four small classes that mostly hold constants.
LSP: every `Crop` really can be watered and harvested; no sprout refuses a `Crop` method.	Stages name each other, e.g. `StrawberrySprout.nextStage()` returns `new Strawberry(...)` (Connascence of Name, kept inside `game.crops`).
SRP: each class has one character, one ability list and one set of rules.	

Package placement. The young stages live in `game.crops`, beside the crops they grow into, not in `game.plants`. Otherwise `game.plants` would import `game.crops`, which imports `game.plants`: a cycle (Acyclic Dependencies Principle). `game.plants` now depends on no crop.

Foresight: a Pumpkin Sprout that grows into a Pumpkin is one new class; no other class changes except `StackQueueValleyWorld`, which places it.

Principles check.

Principle	How this decision applies it
SOLID	OCP: a new stage is one new class. LSP: every `Crop` can really be watered and harvested, so no subclass refuses a parent method. SRP: each class has one character, one ability list and one set of rules.
DRY	Shared behaviour lives once in `Plant` and `Crop`.
KISS	Growing replaces the ground, so the new stage starts at age 0 with no reset code.
Connascence	Stages name their next stage (Connascence of Name), kept inside `game.crops`. The rejected State pattern would add Connascence of Execution: the age must be reset by hand on every swap.
Code smells	Avoided: Switch Statements on a stage field, and Refused Bequest (a sprout inheriting watering and harvesting it must refuse). Accepted: small classes that mostly hold constants.

B. Plant behaviour as a list of abilities

Rejected: each plant overrides `tick` with its own if-else.

Pros	Cons
Each plant's rules sit in one place.	DRY: "every N turns, roll a chance, stop at the first success" is copied into nine classes. A bug fix needs nine edits (Connascence of Algorithm).
	Easy to break the "one thing per turn" rule in one plant without noticing.

Chosen: `Plant` holds a `List<PlantAbility>` in priority order, passed to `super(...)`. `PlantAbility` has one method, `tryPerform(plant, location)`, which returns a report, or `""` when nothing happened. `Plant.tick` ages the plant, then `attemptGrowth` tries the abilities from the top and stops at the first non-empty report.

`PeriodicAbility` implements the timing once: its `tryPerform` is `final` (Template Method). It checks `age % interval`, rolls the chance, then calls the abstract `perform`. `Grow`, `SelfReplicate` and `Produce` write only their effect.

Pros	Cons
DRY: the timing rule and the priority loop each exist once.	A reader opens two classes (the plant and the ability) to see one behaviour.
OCP: a new ability, e.g. "wither", is one new class.	Priority is the order of the constructor arguments (Connascence of Position). Each plant's class comment lists its abilities in priority order.
DIP: `Plant` depends only on `PlantAbility`.	`final tryPerform` stops an ability from changing the timing; an ability with different timing would implement `PlantAbility` directly.
SRP: `Plant` decides when to act; each ability decides what happens.	

`PeriodicAbility` rejects an interval below 1 or a chance outside 0 to 100 in its constructor; an interval of 0 used to crash on `age % 0`. `attemptGrowth` is `public` and does not age the plant, so REQ4's Bounty Enchantment reuses it to force an extra growth attempt instead of copying the loop (DRY across requirements).

Foresight: a Rose that withers after 30 turns is one new `PeriodicAbility` subclass placed first in its list.

Principles check.

Principle	How this decision applies it
SOLID	SRP: `Plant` decides when to act; each ability decides what happens. OCP: a new ability is one class. DIP: `Plant` depends on `PlantAbility`. Template Method: `tryPerform` is `final`.
DRY	The timing rule and the priority loop each exist once, instead of nine times.
KISS	A list in priority order; the plant tries it from the top.
Connascence	Priority is the order of the constructor arguments: Connascence of Position, documented in each plant's class comment. It replaces Connascence of Algorithm across nine copies of the loop.
Code smells	Avoided: Duplicate Code and Long Method (nine hand-written `tick` methods). Accepted: the Connascence of Position above.

C. Plant capabilities: `Growing`, `Spreading`, `Producing`

Each ability must ask the plant what to create: `Grow` needs the next stage, `SelfReplicate` the offspring, `Produce` the item. The plant knows this, and already holds the `RandomUtils` and `AreaFactory` the new object needs.

Option	Pros	Cons
A `Supplier` per ability, e.g. `new Grow(..., StrawberrySprout::new)` (our first version)	The ability is given exactly what it creates.	The team removed method references and functional style everywhere after A2 feedback. The supplier also needed the plant's `RandomUtils` and `AreaFactory`.
Three methods on `Plant` whose defaults throw `UnsupportedOperationException` (our draft)	One abstract class; each plant overrides only the methods its abilities call.	ISP, Refused Bequest: Parsnip only produces, yet carried `nextStage()` and `offspring()` that could only throw. The Javadoc had to say "the default throws".
An abstract class per capability	Shared code could live in it.	Java has single inheritance: `Strawberry` already extends `Crop`, so it could not also extend a `ProducingPlant`.
One single-method interface per capability (chosen)	See below.	See below.

Chosen: `Growing` (`nextStage()`), `Spreading` (`offspring()`) and `Producing` (`produce()`). Each plant implements only what it can do. An ability finds its capability with `location.getGroundAs(Growing.class)` and does nothing if it is missing, the same way pests find `Regressible`.

Pros	Cons
ISP: no plant carries a method it cannot honour, and nothing throws.	Three more interfaces.
No `instanceof`: `getGroundAs` is the engine's capability lookup.	A plant given `Grow` but not `Growing` silently never grows instead of failing. `PlantCapabilityTest` and the per-plant tests catch this.
Consistent with `Regressible` and `Plantable`, so a reader learns one pattern.	The capability methods must be `public`, as interface methods are.
DIP: abilities depend on three small interfaces, not on `Plant` subclasses.	

Under Design by Contract, the throwing draft was not strictly an LSP violation (no override weakened a postcondition, and no path reached the throw), so we describe it as an ISP problem.

Foresight: a Sunflower that drops seeds implements `Producing` and is given `Produce`; no ability changes.

Principles check.

Principle	How this decision applies it
SOLID	ISP: each capability has one method, so no plant carries a method it cannot honour. LSP: nothing throws. DIP: abilities depend on three small interfaces.
DRY	The lookup uses `getGroundAs`, the same pattern as `Regressible` and `Plantable`.
KISS	Three one-method interfaces instead of an abstract class per capability.
Connascence	Abilities share only Connascence of Type with the capabilities. The rejected draft had Connascence of Meaning: "the default throws" had to be known from the Javadoc.
Code smells	Removed: Refused Bequest (methods that could only throw). Avoided: method references and functional style.

D. Counting turns

Option	Pros	Cons
The engine's `Status` countdown	Already exists.	Statuses tick and expire independently, so they cannot express "stop at the first success".
A global turn counter	One number for the whole game.	The engine has none; adding one would need a static field, which A2 feedback penalised.
The engine's `Behaviour<Plant, String>` as the ability type	No new interface.	Its contract returns `null` for "nothing", and it is shared with actors; our contract is plant-specific and returns `""`.
`Plant` keeps its own `age` (chosen)	Each plant counts from 0 when placed, as the spec says; no setter, so only the plant changes it.	A plant spread right of or below its parent ages once in its first turn, because the engine ticks tiles row by row.

Randomness comes from a constructor-injected `RandomUtils`, so every test passes a `FixedRandom` and is deterministic.

Principles check.

Principle	How this decision applies it
SOLID	SRP: the plant owns its age, with no setter.
DRY	The age changes in one place, `Plant.tick`.
KISS	One `int` per plant instead of a global counter or a status.
Connascence	Ageing before trying abilities is Connascence of Execution, kept inside one method. A global counter would have spread Connascence of Value across every plant.
Code smells	Avoided: global static state. Accepted: the engine ticks tiles row by row, which shifts a new plant's timing by one turn.

E. Where plants can grow

Rejected: `instanceof Soil` wherever something is planted.

Chosen: a `Plantable` interface with `plant(ground, location)`, and a `PlantableTile` condition for `Area.filter`. `Soil` implements it. `plant` takes a `Ground`, not a `Plant`, so `game.positions` does not depend on `game.plants` (no package cycle).

Pros	Cons
OCP: a new plantable ground, e.g. fertilised soil, only implements the interface.	One more interface and one more condition class.
DRY: `SelfReplicate`, the Merchant's `Crop.plantNextTo` and REQ5's Sowing omen all plant through it, so they follow one rule.	
Reused by REQ3: the mole and the snail find bare Soil through it.	

In Assignment 2 the Merchant could plant on Dirt; now it plants only on Soil, as the spec requires.

Foresight: a Greenhouse floor that accepts plants implements `Plantable`; every planting path accepts it at once.

Principles check.

Principle	How this decision applies it
SOLID	OCP: a new plantable ground only implements `Plantable`. DIP: planting code depends on the interface. ISP: one method.
DRY	`SelfReplicate`, the Merchant's `Crop.plantNextTo` and REQ5's Sowing omen all plant through one rule.
KISS	One interface and one `TileCondition`.
Connascence	Only Connascence of Type. `plant` takes a `Ground`, so `game.positions` does not depend on `game.plants` (no package cycle).
Code smells	Avoided: type checks for `Soil` and Shotgun Surgery when a new ground can be planted.

F. Regressing, for REQ3 pests

Rejected: pests call `Crop` methods directly.

Pros	Cons
No new interface.	Pests would name every crop and stage; a new stage would edit every pest (OCP).

Chosen: `Plant` implements `Regressible`, whose `regress` replaces the plant with `previousStage()`. By default a regressed plant dies and leaves `Dirt`, matching A2's `Crop.removeCrop`; later stages override `previousStage()` to return their earlier stage.

Pros	Cons
DIP: pests depend on `Regressible`, so `game.pests` does not import `game.crops`.	A pest cannot treat one crop differently.
OCP: a new plant is eaten by every pest with no change.	`previousStage()` is `protected`, so classes in the same package could call it. None does.

Principles check.

Principle	How this decision applies it
SOLID	DIP: pests depend on `Regressible`. OCP: a new plant is eaten with no change. LSP: every stage either regresses or dies, through the same method.
DRY	The regress logic exists once, in `Plant`; stages only override `previousStage`.
KISS	One method and one hook with a safe default (`Dirt`).
Connascence	Only Connascence of Name (`regress`) crosses to `game.pests`.
Code smells	Avoided: Feature Envy and Shotgun Surgery on the pest side.

G. Pausing growth, for REQ5

Option	Pros	Cons
The status removes the plant's abilities and puts them back (push)	The plant needs no check.	The status would reach into `Plant`'s private list and must restore it exactly (Connascence of Identity).
The plant checks for `GrowthPausedStatus` (pull, chosen)	Deciding whether to act stays the plant's job (SRP); the status only counts down.	`applyEffect` is empty on purpose, which a reader may see as a do-nothing override; a comment says why.

While paused, the plant still ages. REQ5's Frost omen applies the status; `TimedStatus` (A2) supplies the countdown, so no timer code is repeated.

Principles check.

Principle	How this decision applies it
SOLID	SRP: the plant decides whether to act; the status only counts down.
DRY	`TimedStatus` supplies the countdown, so no timer code is repeated.
KISS	One check at the start of `Plant.tick`.
Connascence	Avoided Connascence of Identity: the rejected design had the status remove the plant's abilities and put the same list back.
Code smells	Accepted: an empty `applyEffect`, which looks like Refused Bequest; a comment explains it.

H. Printing without a Display parameter

`Ground.tick` returns nothing, so a plant prints its own report.

Option	Pros	Cons
`private static final Display` (our draft)	One shared object.	Shared static state, which A2 feedback penalised.
A `Display` injected through the constructor	Strict DIP.	Nine constructors, every `nextStage()` and `offspring()`, `StackQueueValleyWorld` and every test gain a parameter, yet `Display` is the engine's console writer with no alternative to swap in.
Return the report and let someone else print it	No `Display` in `Plant`.	Nothing calls `Ground.tick` except the engine, which ignores any result.
`private final Display` per plant (chosen)	No static state; KISS.	Each plant creates a `Display`, a small DIP gap.

The collaborators that do vary, `RandomUtils` and `AreaFactory`, are injected.

Principles check.

Principle	How this decision applies it
SOLID	DIP is only partly met: each plant creates its own engine `Display`.
DRY	The printing rule is in `Plant` once.
KISS	`private final Display` per plant, instead of threading a parameter through every constructor.
Connascence	No shared static state, so no Connascence of Value between plants.
Code smells	Avoided: a static field (global state). Accepted: a small DIP gap, because `Display` has no alternative to swap in.

I. Visibility, `final`, `protected` and `static`

Choice	Where	Why	Cost
Every field is `private`	All REQ1 classes	Implementation details stay inside (A2 feedback).	Each plant keeps its own `RandomUtils` and `AreaFactory` to pass to the plants it creates.
Constants are `private static final`	e.g. `GROW_INTERVAL`, `PRICE`	A name explains each number; Java does not allow instance fields in `super(...)`.	Tests repeat the numbers.
No static methods and no mutable static fields	—	A2 feedback penalised static methods.	—
`protected` constructors	`Plant`, `PeriodicAbility`	They are abstract; only subclasses construct them.	—
`protected` hooks	`perform`, `previousStage`	Subclasses override them; callers must go through the template.	Same-package classes could call them; none does.
`final` methods	`tryPerform`, `plantNextTo`, `noRoomToPlant`	Fix the shared rule so a subclass cannot change it.	A plant needing different timing implements `PlantAbility` directly.
`public` capability methods	`nextStage`, `offspring`, `produce`	Interface methods must be public.	Any class could ask a plant for its next stage; only the abilities do.
Classes are not `final`	e.g. `Grow`, `Soil`	Open for extension (OCP).	Private fields and `final` templates limit the damage.

Principles check.

Principle	How this decision applies it
SOLID	ISP: hooks are `protected`, so callers see only the public contract. OCP: classes are not `final`.
DRY	One visibility rule for all REQ1 classes.
KISS	Every member states its access.
Connascence	`private` fields keep connascence on state inside each class.
Code smells	Avoided: public attributes and missing modifiers.

J. Changes to Assignment 2

Change	Why	Cost
`Crop` extends `Plant` instead of `Ground`	Every crop gets an age, abilities and `Regressible`.	`Crop` constructors take abilities. Watering and harvesting are unchanged.
`Unplanted` checks for any `Plant`	Watering a Cauliflower used to flood sprouts into puddles.	—
The Merchant plants through `PlantableTile`	The spec says only Soil accepts plants.	A Merchant surrounded by Dirt cannot sell crops; the message says so.
`RandomUtils` and `AreaFactory` are injected instead of static	A2 feedback; tests pass `FixedRandom`.	Every plant constructor has two more parameters ("tramp data" smell).
Fixed farm layout with one of every plant	Every plant is visible when the game starts.	—
Unique characters: Crow `b`, Cauliflower `K`	The spec gives `v` to the Strawberry Sprout, and `C` is the Cow.	Players of A2 see new characters.

K. Known minor violations and why we accept them

Violation or cost	Why it is acceptable
`SelfReplicate` and `Crop.plantNextTo` repeat the two lines that find an adjacent Plantable tile and plant on it. DRY is not fully met.	They build different messages. A third use would be the signal to extract it.
`Crop` also builds the Merchant's "no room to plant" message, mixing trading into a ground (SRP).	It keeps one wording for both purchasable crops, Tomato and Parsnip.
Each plant creates its own `Display` (Section H).	Injecting it adds parameters everywhere without making anything replaceable (KISS).
A plant given an ability without the matching capability does nothing (Section C).	Safer than a crash; tests check every plant's abilities.
The engine ticks tiles row by row, so a plant spread right of or below its parent ages once in its first turn.	Engine behaviour; it shifts timing by one turn and breaks no rule.
`StackQueueValleyWorld` registers the map characters with method references, `Dirt::new` (base code) and `Soil::new` (REQ1), although the team avoids functional style.	The engine's `DefaultGroundCreator.registerGround(char, Supplier<? extends Ground>)` needs a `Supplier`, and the engine cannot be changed. A named class that implements `Supplier` for each ground would be a class used once, only to avoid one line (KISS). These are the only two method references in the game code.

Testing

`GrowTest`, `SelfReplicateTest`, `ProduceTest`, `PlantStateTest`, `PeriodicAbilityTest` and `PlantCapabilityTest` cover every plant at the right age, one turn early, with a failed chance, with no free tile, while paused, when regressed, with invalid intervals and chances, and with an ability on a plant that lacks the capability. `FixedRandom` makes them repeatable, and `mvn test` runs them all.

Summary

Principle	Where it shows	Change it absorbs	Where it is only partly met, and why
SRP	Timing, each effect, planting, regressing and pausing each have one class.	A new timing rule edits only `PeriodicAbility`.	`Crop` holds one Merchant message (Section K).
OCP	A new stage, ability, capability or plantable ground is one new class.	A Pumpkin, a wither ability, a Greenhouse floor: no existing class changes.	New plants are placed in `StackQueueValleyWorld`, the composition root.
LSP	Every `Crop` can be watered and harvested; abilities never check the plant's type.	A new stage works wherever `Plant` is expected.	—
ISP	`Growing`, `Spreading`, `Producing`, `Plantable`, `Regressible` and `PlantAbility` each have one method.	Parsnip carries only `produce()`.	—
DIP	Abilities depend on capabilities, pests on `Regressible`, `Plant` on `PlantAbility`; `RandomUtils` and `AreaFactory` are injected.	A new plant or pest needs no change to the other side.	Each plant creates its own engine `Display`; stages create their next stage directly (Connascence of Name, one outcome each, so a factory would be a parameter nobody varies).

DRY and KISS. Each rule exists once: the timing, the priority loop, planting and the countdown. We added no layer that only one class uses. **Connascence.** Between packages it is only of Name and Type, through

`Regressible`, `Plantable` and the capability interfaces. Stronger forms (Position for ability priority, Execution for age before abilities) stay inside one class each.

Jingyu Zhang 37033956 – REQ 3: Infestation and Pest Control

Class diagram: `docs/A3_UML/A3_REQ3_Infestation_UML.drawio`. Feature proposal: `feature-proposal.md`.

Pests move towards plants and eat them. The Farmer fights back with three defences: one pulls pests in, one hunts them, and one pushes them out. Every effect changes the map or an actor, never only prints text.

Class	Abstraction	Effect	Game state it changes
`SlimeSnail`	`Infestation` (`feedOn`)	Sets the plant back and slimes the bare ground around it	Plant stage; ground over an area, restored later
`LocustSwarm`	`Infestation`	Sets back every plant on and around it; may split; leaves when full	Plant stages over an area; spawns and removes actors
`BurrowingMole`	`Infestation`	Sets the plant back and caves the four straight neighbours into Dirt	Plant stage; ground
`PestTrap`	`PestDeterrent` (`deterAround`)	Becomes a trap that pulls pests closer and captures them	Ground; forced movement; removes actors
`LadybugJar`	`PestDeterrent`	Releases up to three ladybugs that eat pests	Spawns actors
`SaltBarrier`	`PestDeterrent`	Salts the bare ground around the Farmer; burns and pushes out pests on it	Ground over an area; hit points; forced movement

Each decision compares rejected and chosen designs, with pros, cons and a future example. Each decision ends with a principles check covering SOLID, DRY, KISS, connascence and code smells. Sections H and J list every place a reader may see as a weakness, and say why we chose it.

A. Two interfaces, and one pest turn written once

Why interfaces. Rejected: `Infestation` and `PestDeterrent` as abstract classes.

Pros	Cons
One type fewer on each side.	Java has single inheritance. `Pest` already extends `WanderingActor` (from A2) and `DeterrentItem` extends the engine's `Item`, so neither could also extend an abstract `Infestation` or `PestDeterrent`.

Chosen: both are one-method interfaces. A pest is an actor and an `Infestation` at once, and defences find it through `asCapability(Infestation.class)`, not through the `Pest` class (DIP, ISP). **Foresight:** a cursed scarecrow that is not a `Pest` could implement `Infestation`, and every trap, jar and salt bag would find it unchanged.

The pest turn. Rejected: one `Pest` class with a `PestKind` enum and a `switch` in `feedOn`.

Pros	Cons
KISS: one file holds every pest.	OCP: a new pest edits the switch, and every other switch on the enum.
A reader sees all pest rules side by side.	SRP: one method mixes slime, area damage and cave-ins. This is the "switch statement" smell.
	Each case would need its own fields (meals left only for the swarm), so the class carries fields most pests never use.

Chosen: `Pest` is an abstract class (Template Method). Its turn is written once: if the pest can feed here, it returns an `InfestAction`; otherwise its `SeekPlantBehaviour` moves it. A subclass gives only its landing offsets and its `feedOn`. One hook, `canFeedAt(Location)`, is true when a plant is underfoot. `LocustSwarm` overrides it, because a swarm also feeds on the plants next to it.

Pros	Cons
OCP: a new pest is one new class. `Pest`, `InfestAction` and the defences do not change.	A reader must open two classes to see one pest's full turn.

Pros	Cons
LSP: the turn never asks which pest it is. The hook replaces `if (this instanceof LocustSwarm)`, which would make the parent know its children.	A subclass could override `canFeedAt` badly, for example return true where `feedOn` finds nothing. `feedOn` then returns an empty report, so the game does not break.
DRY: "feed or move" exists once. `Pest` extends the existing `WanderingActor`, so the unconscious check from A2 is reused, not copied.	

Why `feedOn` is not a template. We considered a template on `Pest` where each pest gives only a per-tile step. But the three effects touch different tiles (the area around the swarm, the mole's four straight neighbours, the bare ground around the snail), do different things to them, and only the swarm changes itself (meals, splitting). A template would wrap three different effects without removing repeated code (KISS).

Connascence: `InfestAction` knows a pest only through `Infestation` (Connascence of Name). **Foresight:** an Aphid that hops three tiles and poisons the soil is one class: a new offset table and a new `feedOn`.

Principles check.

Principle	How this decision applies it
SOLID	OCP: a new pest is one new class. LSP: the hook `canFeedAt` replaces a type check, so the turn works for any pest. ISP: `Infestation` has one method. DIP: `InfestAction` and the defences depend on `Infestation`, not on `Pest` or its subclasses.
DRY	"Feed or move" is written once in `Pest`, and the unconscious check is inherited from `WanderingActor` instead of being copied.
KISS	One abstract class and one hook. We did not add a feeding template, because the three effects share no steps.
Connascence	Between packages, the defences know a pest only by Name (`feedOn`) and Type (`Infestation`). No class depends on a concrete pest class, so there is no Connascence of Type on `SlimeSnail`, `LocustSwarm` or `BurrowingMole`.
Code smells	Avoided: Switch Statements (a `PestKind` enum) and Speculative Generality (a template for effects that share nothing). Accepted: `InfestAction` is close to a Middle Man, because the engine needs an `Action` object for every turn.

B. Movement as data, not as classes

Option	Pros	Cons
Each pest overrides `move()`	Easy to read in one class.	DRY: "find the nearest plant, pick a landing, fall back" is copied three times. A bug fix needs three edits (Connascence of Algorithm).
Three classes (`KnightMove`, `CrawlMove`, `BurrowMove`)	Each move has a name.	Three classes that differ only in a table of numbers. The A2 marker called one class per variant "architectural bloat".
One `SeekPlantBehaviour` with offsets (chosen)	DRY: one copy of the search. OCP: a new movement is one new array. KISS: no new type per pest.	The offsets are a raw `int[][]`, a mild "primitive obsession" smell.

We accept the smell because the array never leaves its pest class, and the behaviour validates and copies it in its constructor. So a pest cannot pass `{1}` or change the table later. The fallback is typed as the engine's `Behaviour`, not `WanderBehaviour` (DIP). The pest lands on a tile and does not walk through the tiles between, so a jumping pest can pass a wall or a salted tile.

Two rules came from running the game. A mole that only moved two tiles could never reach a plant one tile away, so it now moves one or two. A knight jump rarely lands on a plant, so the swarm feeds from the tiles next to it. Unit tests cover both.

Foresight: a grasshopper that leaps three tiles in a straight line is one new offset table; `SeekPlantBehaviour` stays the same.

Principles check.

Principle	How this decision applies it
SOLID	SRP: `SeekPlantBehaviour` only chooses a landing tile. OCP: a new movement is a new offset table. DIP: the fallback is typed as the engine's `Behaviour`.
DRY	"Find the nearest plant, pick a landing, fall back" exists once instead of three times.
KISS	A table of numbers per pest instead of three behaviour classes.
Connascence	Avoided Connascence of Algorithm between three copies of the search. The offsets carry Connascence of Meaning (each row is a `{dx, dy}` pair), but it stays local: only `SeekPlantBehaviour` reads them, and its constructor rejects rows that are not pairs.
Code smells	Avoided: Duplicate Code, and one class per variant, which the A2 marker called "architectural bloat". Accepted: Primitive Obsession (`int[][]`), local to each pest class and copied defensively.

C. Pests depend on `Regressible`, not on crops

Pests never name a crop. They ask the ground for `Regressible` (from REQ1) with `getGroundAs` and call `regress`.

Pros	Cons
DIP: `game.pests` does not import `game.crops`, so there is no package cycle.	A pest cannot treat one crop differently, for example a snail that prefers Strawberries. That would need a new method on `Regressible`.
OCP: a new plant that can regress is eaten without any change to the pests.	
No `instanceof`: `getGroundAs` is the engine's capability lookup.	

Principles check.

Principle	How this decision applies it
SOLID	DIP: pests depend on the `Regressible` abstraction. OCP: a new plant is eaten with no pest edited. ISP: `Regressible` has one method.
DRY	The rule for going back a stage lives once, in `Plant` (REQ1), not in each pest.
KISS	One existing interface, reused; no pest-specific crop API.
Connascence	Only Connascence of Name (`regress`) crosses from `game.pests` to `game.plants`, and the pests never name a crop.
Code smells	Avoided: Shotgun Surgery (a new crop would otherwise edit every pest) and Feature Envy (pests reaching into crop internals).

D. One deploy action for all defences

Rejected: three actions, `SetTrapAction`, `OpenJarAction` and `ThrowSaltAction`.

Pros	Cons
Each action can have its own menu text.	DRY: each repeats "remove the item, act, report". If the rule for using an item changed, three classes change (Connascence of Algorithm).
	OCP: each new defence also needs a new action.

Chosen: `DeterrentItem` is an abstract item. While the Farmer carries it, it offers one `DeployDeterrentAction`, which calls `deterAround` and removes the item. The action holds a `PestDeterrent`, not a `PestTrap` (DIP). The hook `canDeployAt(Location)` hides the option where it cannot work: a trap is not offered on a plant, so a failed attempt never wastes the item.

Pros	Cons
OCP/DIP: a new defence is one subclass. The action never changes.	The action keeps two fields for one object: the `Item` (the engine's inventory only removes an `Item`) and the `PestDeterrent`. They must be the same object (Connascence of Identity). `DeterrentItem` passes `this` twice in one place, so callers cannot mix them up.
SRP: the item says what it does; the action says how an item is used.	

Rejected fixes for the two fields: a cast breaks type safety; a generic `<T extends Item & PestDeterrent>` adds a type parameter that only removes one field.

Foresight: a Scarecrow that scares pests away for ten turns is one `DeterrentItem` subclass plus one `TemporaryGround` subclass.

Principles check.

Principle	How this decision applies it
SOLID	SRP: the item says what it does; the action says how an item is used. OCP: a new defence is one subclass. LSP: any `DeterrentItem` works in the action. DIP: the action holds a `PestDeterrent`.
DRY	"Remove the item, act, report" exists once.
KISS	One action class for every defence; `canDeployAt` hides the option instead of failing at run time.
Connascence	The action's two fields must be the same object (Connascence of Identity). It is kept local: `DeterrentItem` passes `this` twice in one line, so no caller can mix them up.
Code smells	Avoided: Duplicate Code and a parallel hierarchy of one action per item. Accepted: two fields for one object, which is cheaper than a cast.

E. Finding pests without `instanceof`

The trap, the salt and the ladybug all need to tell a pest from the Farmer, a cow or another ladybug. `PestPresent` is a `TileCondition` (the area filter from A2). It checks `actor.asCapability(Infestation.class)`, which only pests have.

Option	Pros	Cons
`instanceof Pest` in each defence	Short.	A type check is a code smell, and each defence names the pest class. A pest that is not a `Pest` subclass would be missed.
A list of pest classes	Explicit.	Every new pest edits the list (OCP).
`PestPresent` (chosen)	DRY: one check, used in three places. OCP: a new pest is found by every defence at once.	One more small class.

Principles check.

Principle	How this decision applies it
SOLID	SRP: one class answers "is a pest here?". OCP: a new pest is found by every defence with no change. DIP: the check uses the `Infestation` capability.
DRY	One check, used by the trap, the salt and the ladybug.
KISS	A tiny `TileCondition` that plugs into the existing `Area.filter`.
Connascence	The defences share only Connascence of Type on `Infestation`, instead of Connascence of Type on every pest class.
Code smells	Avoided: type checks (`instanceof`), the smell the Week 10 lecture says polymorphism should replace. Accepted: a very small class, justified by three users (rule of three).

F. Temporary ground

Slime, salt and the trap replace a tile's ground for a while and then put the old ground back.

Rejected: each ground keeps its own counter.

Pros	Cons
No abstract class to learn.	DRY: the same countdown in three classes. A change such as "rain shortens every temporary ground" edits three classes.
	A ground can forget to restore the old ground, a bug the compiler cannot catch.

Chosen: `TemporaryGround` is abstract. Its `tick` is `final`: run `tickEffect` (empty by default), stop if the effect already replaced this ground, then count down and restore the original ground.

Pros	Cons
The order "effect, check, count down" is fixed in one place (Connascence of Execution kept local).	`final` stops a subclass from changing the countdown itself, for example a ground that never expires. Such a ground would extend `Ground` directly.
KISS: `SlimeGround` and `SaltGround` are only constants.	

Package placement. `TemporaryGround` sits in `game.positions`. `SlimeGround` sits in `game.pests`, and `SaltGround` and `TrapGround` in `game.pestcontrol`. If all three were in `game.positions`, that package would import `game.pests`, which already imports `game.positions`: a cycle. Each ground sits beside the feature that creates it (Acyclic Dependencies Principle).

Principles check.

Principle	How this decision applies it
SOLID	SRP: the countdown has one owner. OCP: a new temporary ground is one subclass (REQ5's storm shelter reuses it). LSP: the `final` `tick` guarantees every subclass restores its ground.
DRY	The countdown exists once, used by slime, salt, the trap and the storm shelter.
KISS	`SlimeGround` and `SaltGround` hold only constants (and `SaltGround` one `canActorEnter`).
Connascence	The order "effect, check, count down" is Connascence of Execution. It is kept inside one `final` method, so no subclass can get it wrong. Placing each ground beside its feature keeps package dependencies one way.
Code smells	Avoided: Duplicate Code and Shotgun Surgery (a timing change would edit three grounds). Accepted: `final` stops a subclass from changing the countdown.

G. The three defences

PestTrap and TrapGround (pull in). Each turn the trap pulls every pest within two tiles one step closer, then captures pests on or next to it, up to two. Grounds tick before actors move. In our first version the trap captured first; a pulled mole then walked away on its own turn, and the trap never caught it. Pulling first fixed this (Connascence of Timing, explained in the class comment and locked in by a test).

A ground's `tick` returns nothing, so the trap cannot hand its report to the engine as an action does.

Option	Pros	Cons
A `static Display`	One shared object.	A static field; the A2 marker penalised statics.
A `private final Display` field, as `Plant` does	Matches REQ1.	Every trap holds a `Display` it rarely uses, and the diagram gains an association with no state.
A `Display` passed into the constructor	Testable.	The `Display` would travel through the item and the action, which have nothing to print.
Make the trap an actor	Uses the engine's normal message path.	A trap is not a creature; it changes the TA-approved design.
A local `Display` when there is news (chosen)	No static state; a dependency, not an association.	Tests check the map, not the printed text.

LadybugJar and Ladybug (hunt). The jar releases up to three ladybugs around the Farmer. A ladybug eats a pest next to it, or wanders. It loses one hit point a turn, so it lives five turns, and the existing `ConsciousActor`

removes it at zero (DRY). The cost: lifespan and health are one number. If something healed a ladybug, it would live longer. Nothing in the game does.

SaltBarrier and SaltGround (push out). The bag salts bare Soil and Dirt around the Farmer, burns any pest on those tiles and pushes it out. All of this happens once, inside `deterAround`. After that, `SaltGround` only refuses pests in `canActorEnter` (KISS).

Why an item and a ground for the trap and the salt. This looks like a "parallel hierarchy" smell. But the engine keeps carried things (`Item`) and map tiles (`Ground`) as separate types, and one object cannot be both. The item lives in the inventory; the ground lives on the map with its own timer.

Principles check.

Principle	How this decision applies it
SOLID	SRP: each defence owns one effect. `TrapGround` both pulls and captures, because the brief describes one trap doing both.
DRY	The ladybug reuses `ConsciousActor`'s removal at zero hit points; salt and trap reuse `TemporaryGround`.
KISS	Salt acts once, inside `deterAround`; afterwards `SaltGround` only refuses pests.
Connascence	Grounds tick before actors move: Connascence of Timing. Pulling and capturing in the same tick keeps it inside one class, explained in its comment and locked in by a test.
Code smells	Avoided: a static `Display` (global state). Accepted: the item-and-ground pairs look like a Parallel Inheritance Hierarchy, but the engine keeps carried things and map tiles as different types.

H. Visibility, `final`, `protected` and `static`

A2 feedback said package-private helpers (`CrowSensing`, `CrowNavigation`) can be good encapsulation, but the rationale must say so. Here is each choice in REQ3.

Choice	Where	Why	Cost and when we would change it
Every class is `public`	All 20 REQ3 types, including the small `PestPresent`, `InfestAction` and `EatPestAction`	A3 is the last assignment, so package-private would be safe today. We still chose `public`, because extensibility is a design goal and other features already live in other packages. A defence in another package, for example a frog in `game.actors`, should reuse `PestPresent` and `EatPestAction` without moving them.	A wider public API. We considered package-private for `InfestAction` (only `Pest` uses it) but chose one rule for the whole feature, so a reader never wonders whether a hidden class was forgotten.
Every field is `private`	All classes	Implementation details stay inside (A2 feedback). Subclasses use hooks, not fields.	`SlimeSnail`, `BurrowingMole` and `LocustSwarm` each keep their own `AreaFactory`, although `Pest` also receives it. A `protected` getter on `Pest` would remove three fields but expose a tool that `Pest` itself does not use.

Choice	Where	Why	Cost and when we would change it
Constants are `private static final`	e.g. `LocustSwarm.SPLIT_CHANCE_PERCENT`, `SlimeSnail.HIT_POINTS`	A fixed rule belongs to the class, not to one object. A name such as `SPLIT_CHANCE_PERCENT` explains the number, so there are no magic numbers. Java does not allow instance fields in `super(...)`, so names, characters and hit points must be static to be named.	A test cannot read them, so tests repeat the number.
No static methods, no `public` constants and no mutable static fields	—	This is what the A2 marker penalised: static methods are "function thinking", and `public` constants leak details. A `private static final` constant does neither: it cannot change and is not seen outside the class.	—
`protected` constructors	`Pest`, `DeterrentItem`, `TemporaryGround`	They are abstract; only subclasses construct them.	—
`protected` hooks	`canFeedAt`, `canDeployAt`, `tickEffect`	Subclasses must override them; callers must not skip the template.	Classes in the same package can also call them. No class does.
`protected final`	`TemporaryGround.revertAt`	A subclass may end its ground early (the trap after two captures) but cannot change how it ends.	—
`final` method	`TemporaryGround.tick`	Fixes the order of the countdown (Section F).	See Section F.
Classes are not `final`	e.g. `LadybugJar`, `SaltGround`	Open for extension (OCP), e.g. a larger jar.	A subclass could break a rule. Private fields and the final `tick` limit the damage.
`private` constructor	`LocustSwarm(int meals, ...)`	Only a split may create a smaller swarm. The public constructor always gives four meals, so a half-empty swarm cannot be built by mistake.	A future "hungry swarm" difficulty would need a new public constructor.
`private` helpers	e.g. `pullPests`, `splitAt`, `copyOf`	They are steps, not contracts. Making them `protected` would freeze their signatures for every subclass.	A subclass that wants a different pull must override `tickEffect`.
Non-final fields	`mealsLeft`, `capturesLeft`, `remainingTurns`	These values change every turn.	—

Explicit modifiers, and why we keep `protected`. Two pieces of advice pull in different directions. The Week 9 lecture and our tutor suggest a narrow API: keep a class package-private when no other package needs it, and try not to use `protected`, because in Java it also opens a member to every class in the same package. But Java has no keyword for package-private: it means writing no modifier at all, and the A2 marker penalised exactly that ("missing modifier" on `CrowSensing` and `ForageableItems`).

Option	Pros	Cons
Package-private classes and hooks (no modifier) where every user is in the same package	The narrowest API; fewer dependencies across packages.	A reader cannot tell a deliberate choice from a forgotten modifier, which A2 penalised. A pest or defence in another package could not extend `Pest` or `DeterrentItem`.

Option	Pros	Cons
Replace the template hooks with strategy objects, so no `protected` is needed	No `protected` at all.	A new interface and class for each hook (`canFeedAt`, `canDeployAt`, `tickEffect`) only to avoid a modifier: needless complexity (KISS).
Explicit `public` classes and `protected` hooks (chosen)	Every class and member states its access, so nothing looks forgotten. `protected` is used only for constructors of abstract classes and for hooks that subclasses override; no field is `protected`.	A wider API than strictly needed, and classes in the same package could call a hook. None does, and the template methods that call the hooks are `final` or fixed in the parent, so a hook cannot skip the rules.

Principles check.

Principle	How this decision applies it
SOLID	OCP: `public` classes can be extended from other packages. ISP: hooks are `protected`, so callers see only the public contract.
DRY	One visibility rule for the whole feature, not a choice per class.
KISS	Every class and member states its access; nothing is left implicit.
Connascence	`private` fields keep connascence on state inside each class. `protected` hooks create connascence only with subclasses, never with callers.
Code smells	Avoided: public attributes, which make a Data Class that others manipulate, and missing modifiers. Accepted: a wider API than strictly needed (see the table above).

I. Changes to the earlier design

REQ3 is new in A3. The only earlier class it changes is `StackQueueValleyWorld`, which places the pests and gives the Farmer the defences.

Statics replaced by injection. REQ3's first version called the A2 static helpers `Area.within`, `Area.adjacentTo` and `RandomUtils.rollPercent`. The A2 marker called static helpers "function thinking". Following that feedback, the team now creates one `RandomUtils` and one `AreaFactory` in `StackQueueValleyWorld.initialise`, and every REQ3 class that needs them receives them through its constructor.

Pros	Cons
DIP: a pest depends on the objects it is given, not on global classes. Tests pass `FixedRandom` directly.	Every pest and defence constructor gained one or two parameters, and `Pest` must pass them on (a "tramp data" smell).
No hidden global state, so two tests cannot affect each other.	Connascence of Position in the constructors. Each has at most two such parameters, so the order is easy to check.

Display character. `SaltBarrier` first used `k`, which clashed with the A2 `CauliflowerItem`. Earlier characters are fixed, so the new class changed to `f`.

Principles check.

Principle	How this decision applies it
SOLID	DIP: classes receive `RandomUtils` and `AreaFactory` instead of calling static methods. OCP: a test or a variant passes another instance without editing the class.
DRY	One `RandomUtils` and one `AreaFactory` for the whole game.
KISS	Plain constructor injection, with no framework.
Connascence	Connascence of Position in the constructors, with at most two such parameters.
Code smells	Avoided: global static state. Accepted: Tramp Data and a small Data Clump, because the same two objects travel together through constructors.

J. Known minor violations and why we accept them

Violation or cost	Why it is acceptable
`SlimeSnail` and `SaltBarrier` both ask "is this tile bare Soil or Dirt?" (two lines each). DRY is not fully met.	Rule of three: two short copies are cheaper to read than a new class. A third use would be the signal to extract a `BareFarmGround` condition.
`LadybugJar` catches `GameEngineException` and moves on. An empty catch is a smell.	The tile is checked with `canActorEnter` first; the catch only covers a tile taken in between. A comment says so.
`Ladybug`, `LadybugJar` and `SaltBarrier` use `getExits()`, while other classes use `AreaFactory`.	`getExits()` is the engine's own list of neighbours and needs no extra dependency. `AreaFactory` is used where we filter or search an area.
`TrapGround` moves actors, which is more than most grounds do.	Acting on the pests around it is the trap's whole job. Only the trap does this each turn, and the logic stays in one class.
Pests (except the swarm) never leave on their own.	On purpose: the defences are the counter to the pests. A meal limit could be added in `feedOn` only.

Summary

Principle	Where it shows	Change it absorbs	Where it is only partly met, and why
SRP	Moving (`SeekPlantBehaviour`), the turn (`Pest`), finding pests (`PestPresent`), using an item (`DeployDeterrentAction`) and timing ground (`TemporaryGround`) each have one class.	A new landing rule edits `SeekPlantBehaviour` only; a new countdown rule edits `TemporaryGround` only.	`TrapGround` pulls, captures and prints. `LocustSwarm` feeds, splits and leaves. Each is one rule from the brief, and splitting them would add classes used once.
OCP	A new pest, defence or temporary ground is one new class.	An Aphid, a Scarecrow or a Frost ground: no existing class changes.	The new class must still be placed in `StackQueueValleyWorld`. That is the composition root, so this is expected.
LSP	Every pest works wherever `Pest` or `Infestation` is expected; every defence wherever `PestDeterrent` is. Hooks replace type checks.	A new pest is fed, found and trapped with no new branch.	`canFeedAt` and `feedOn` must agree. If they do not, `feedOn` returns an empty report, so the game stays correct. `final tick` stops a ground from breaking the countdown.
ISP	`Infestation`, `PestDeterrent` and `Regressible` each have one method. Defences never see a pest's movement or health.	A pest that moves differently does not touch any defence.	`PestPresent` uses `Infestation` only to recognise a pest and never calls `feedOn`. This is not a marker interface: `InfestAction` calls `feedOn`.
DIP	`DeployDeterrentAction` depends on `PestDeterrent`, pests on `Regressible`, `SeekPlantBehaviour` on `Behaviour`; `RandomUtils` and `AreaFactory` are injected.	A new crop, defence or fallback behaviour needs no change to the classes that use it.	`Pest` creates `SeekPlantBehaviour` and `WanderBehaviour`; `SlimeSnail` creates `SlimeGround`; `LadybugJar` creates `Ladybug`. Each has one outcome, so an injected factory would be a parameter nobody varies (YAGNI).

DRY and KISS. Each rule exists once: the pest turn, the landing search, finding a pest and the countdown. We added no layer that only one class uses. **Connascence.** Between packages it is only of Name and Type. Stronger forms (Timing, Identity, Execution) stay inside one class each, with a comment and a test.

Testing. Every class has normal, edge and invalid tests. `FixedRandom` makes them repeatable, and `mvn test` runs them all.

Yuanshu Liu 36226173 – REQ 4: Enchanted Tools

Feature proposal: `feature-proposal.md`.

The Farmer can enchant a carried Hoe, Watering Can or Pickaxe with one of three Enchantments. The next time the tool does its normal job, two effects fire in the same turn: the tool's own spread effect, which is the same whichever Enchantment is attached, and the Enchantment's effect on every tile the spread touched. Then the Enchantment is spent. An unenchanted tool works exactly as in A1 and A2.

The brief asks for two abstractions with three new classes and up to three retrofitted ones. Every effect changes the map or an actor, never only prints text.

Class	Abstraction	New or retrofitted	Effect	Game state it changes
`Hoe`	`Enchantable`	Retrofitted (A1)	Also tills every adjacent tillable tile	Ground over an area
`WateringCan`	`Enchantable`	Retrofitted (A1)	Also waters one random adjacent waterable tile	Ground or crop watering count
`Pickaxe`	`Enchantable`	Retrofitted (A2)	40% chance to also break one random adjacent breakable tile	Ground; drops items
`BlazeEnchantment`	`Enchantment`	New	Lights a `Fire` on every affected tile	Spawns items; burns actors
`BountyEnchantment`	`Enchantment`	New	Gives every plant on an affected tile an extra growth attempt	Plant stage
`ShatterEnchantment`	`Enchantment`	New	Stuns every actor on an affected tile for 2 turns	Status on actors

Each decision compares rejected and chosen designs, with pros, cons and a future example. Each decision ends with a principles check covering SOLID, DRY, KISS, connascence and code smells. Sections H and J list every place a reader may see as a weakness, and say why we chose it.

A. Finding an enchanted tool without `instanceof`

`CapabilityToolAction` (tilling and watering) and `BreakAction` must fire the Enchantment of the tool they just used.

Rejected: check the tool's class, for example `if (tool instanceof Hoe)`, and read its enchantment directly.

Pros	Cons
Short; no new interface.	OCP: every new enchantable tool adds a branch to two actions.
	Connascence of Type between two actions and every tool class.

Chosen: a capability interface, `Enchantable`, with `enchant(Enchantment)` and `triggerEnchantment(Actor, Location)`.

Pros	Cons
DIP: both actions depend only on `Enchantable`.	One more interface to read.
OCP: a new enchantable tool needs no change to either action.	
The tool decides whether it has anything to fire (encapsulation).	

This is the same idiom the codebase already uses for `Tillable`, `Waterable`, `Breakable` and `Harvestable`, so a reader needs no new pattern. **Foresight:** an enchantable Scythe implements `Enchantable` through the base class in Section B, and the actions stay the same.

Principles check.

Principle	How this decision applies it
SOLID	DIP: both actions depend on `Enchantable`. OCP: a new tool needs no change to them. ISP: two methods, both used.
DRY	The same capability idiom as `Tillable`, `Waterable` and `Breakable`.
KISS	One interface instead of type checks in two actions.
Connascence	Connascence of Type on one interface replaces Connascence of Type between two actions and three tool classes.
Code smells	Avoided: type checks (`instanceof`) and Switch Statements on the tool's class.

B. Sharing "can be enchanted" in one base class

All three tools must store the Enchantments they offer, offer one `EnchantAction` per Enchantment, and hold the one currently attached. None of this depends on the tool.

Rejected: each tool implements `Enchantable` on its own.

Pros	Cons
No new abstract class.	DRY: the same storage and menu code three times ("duplicated code" smell).
	A change to how `EnchantAction`s are offered needs three edits ("divergent change" risk).

Chosen: `AbstractEnchantableTool extends Item implements Enchantable`. It owns the offered Enchantments, the attached one (through `EnchantmentSlot`, Section C), `enchant()` and the menu. `Hoe`, `WateringCan` and `Pickaxe` extend it and write only `triggerEnchantment()`.

Pros	Cons
DRY: written once.	A tool that should offer only some Enchantments must override `allowableActions()`. No tool needs this today (YAGNI).
SRP: each tool changes only when its own spread changes.	

An interface default method cannot hold a field, so sharing the stored Enchantment needs a class. This is a language limit, not a style choice. **Foresight:** a fourth enchantable tool writes only its `triggerEnchantment()`.

Principles check.

Principle	How this decision applies it
SOLID	SRP: each tool changes only when its own spread changes. OCP: a fourth tool writes only `triggerEnchantment`. LSP: any tool works in `EnchantAction`.
DRY	Storage and the menu are written once.
KISS	One base class; an interface default method cannot hold the stored Enchantment, so a class is the simplest option.
Connascence	Subclasses reach the slot only through `enchantmentSlot()` (Connascence of Name), not through a field.
Code smells	Avoided: Duplicate Code and Divergent Change (one menu change, three edits).

C. Storing, firing and clearing one Enchantment

Firing is the same for every tool: if an Enchantment is attached, apply it to the affected tiles, then clear it. What differs is which tiles the tool's own spread touches.

Rejected: write the store, fire and clear steps inside each tool's `triggerEnchantment()`.

Pros	Cons
One class fewer.	SRP: one method mixes the bookkeeping with the tool's spread.
	DRY: the "check, apply, clear" steps three times.

Chosen: `EnchantmentSlot`, a small helper that holds at most one Enchantment and offers `enchant()`, `isEmpty()` and `fire(tiles, activator, origin)`, which applies the effect and clears itself.

Pros	Cons
Each tool reads as "build my list of tiles, hand it to the slot".	One more step to follow when tracing a turn: tool, then slot, then Enchantment.
The same role as other helpers in the codebase, such as `StatisticAdjuster` and `MerchantContext`.	

Principles check.

Principle	How this decision applies it
SOLID	SRP: firing bookkeeping is separate from each tool's spread.
DRY	"Check, apply, clear" exists once.
KISS	A small `final` helper with three methods.
Connascence	"Apply, then clear" is Connascence of Execution, kept inside one method.
Code smells	Avoided: Duplicate Code. Accepted: one extra step to trace (tool, slot, Enchantment).

D. Finding which tool was used

`CapabilityToolAction` and `BreakAction` both need the same lookup after their own effect: find the tool instance just used among the actor's `Enchantable` items, and fire it.

Rejected: write the lookup loop inside each action.

Pros	Cons
No new class.	DRY: the same loop in two actions. If the lookup changes, both copies must change together (Connascence of Algorithm).

Chosen: `EnchantmentTrigger.fire(Actor, Object usedTool, Location)`, used by both actions. In the first version only `CapabilityToolAction` needed the lookup. When `BreakAction` needed the same loop, we moved it into one class. So the class was created for a real second user, not "just in case".

Pros	Cons
One place knows how to go from a tool in hand to its `Enchantable` view.	The `usedTool` parameter is typed `Object` (Section J).
A future action that uses a tool reuses it with no new code.	

Principles check.

Principle	How this decision applies it
SOLID	SRP: one class finds the tool that was used. DIP: it works through `Enchantable`.
DRY	The lookup loop exists once for both actions.
KISS	Extracted only when a second caller appeared, not in advance.
Connascence	Avoided Connascence of Algorithm between two copies of the loop in two actions.
Code smells	Avoided: Duplicate Code. Accepted: the `Object` parameter, a weak type that the Week 10 lecture would replace with generics (Section J).

E. Why `==` is used, and why it is not a hidden `instanceof`

The engine's `Inventory.getItemsAs(Class)` returns views narrowed to one capability. A tool held as a `TillingTool` cannot be asked for a second capability, and the engine cannot be changed. So `EnchantmentTrigger` takes a second view, `getItemsAs(Enchantable.class)`, and looks for the entry that is the same object as the tool in hand (`enchantable == usedTool`).

This is Connascence of Identity, the strongest kind, because the two references must be the same object. We accept it because:

- it is the real question: "is this the tool used this turn?";
- it is fully local: both references are found and compared inside one method, in one turn, and never stored;
- `instanceof` plus a cast would ask a different question ("what class is this?") and bring back the Connascence of Type that Section A removed.

Principles check.

Principle	How this decision applies it
SOLID	LSP: any `Enchantable` view is accepted; no subclass is singled out.
DRY	One comparison instead of a cast in each action.
KISS	`==` is the simplest test for "this exact tool".
Connascence	Connascence of Identity, the strongest kind, kept local: both references are found and compared in one method and never stored.
Code smells	Avoided: `instanceof` with a cast, which would bring back Connascence of Type.

F. Reusing existing classes for the Enchantment effects

Enchantment	Reuses	Instead of
`BlazeEnchantment`	The existing `Fire` item	A new burning mechanism
`ShatterEnchantment`	The existing `StunnedStatus`	A new stun status
`BountyEnchantment`	REQ1's public `Plant.attemptGrowth()`, which tries the plant's abilities without ageing it or printing	A copy of the plant's ability loop

Pros	Cons
DRY: each effect already exists and is already tested.	`game.enchantments` depends on `game.items`, `game.status` and `game.plants`. These are ordinary dependencies on existing classes and form no cycle.

Principles check.

Principle	How this decision applies it
SOLID	OCP: a new Enchantment is one class that reuses existing effects.
DRY	`Fire`, `StunnedStatus` and `Plant.attemptGrowth` are reused, not copied.
KISS	No new burning, stun or growth mechanism.
Connascence	Connascence of Name across packages, on stable public APIs of existing classes.
Code smells	Avoided: Duplicate Code and parallel mechanisms for the same effect.

G. The empty-string contract

`Enchantable.triggerEnchantment`, `EnchantmentSlot.fire` and `Enchantment.applyTo` never return `null`. They return `""` when nothing fired, the same rule REQ1's abilities use.

Option	Pros	Cons
Return `null` for "nothing happened"	Common in Java.	Connascence of Meaning: every caller must remember what `null` means, and a forgotten check crashes.
Return `""` (chosen)	Every caller simply joins the strings. One rule for the whole codebase.	A reader must know that `""` means "nothing happened"; the Javadoc says so.

Every message still names a location: when there are no affected tiles, each Enchantment reports "near" the origin, and both actions start their message with "At" plus the location.

Principles check.

Principle	How this decision applies it
SOLID	LSP: every `Enchantment`, slot and tool keeps the same contract, so callers treat them alike.

Principle	How this decision applies it
DRY	One convention for "nothing happened", shared with REQ1's abilities.
KISS	Callers simply join strings.
Connascence	Avoided Connascence of Meaning: callers would otherwise need to remember what `null` means.
Code smells	Avoided: scattered `null` checks.

H. Visibility, `final`, `protected` and `static`

Choice	Where	Why	Cost
Every class is `public`	All REQ4 classes	Another package can reuse them, for example a new action that uses `EnchantmentTrigger`.	A wider public API.
Every field is `private`	All classes	Subclasses use `enchantmentSlot()`, not the field.	—
`protected` accessor	`AbstractEnchantableTool.enchantmentSlot()`	Only the tools need the slot to fire it; callers use `Enchantable`.	Classes in `game.items.tools` could also call it. None does.
`protected` constructor	`AbstractEnchantableTool`	It is abstract; only tools construct it.	—
`final` classes	`EnchantmentSlot`, `EnchantmentTrigger`	Small helpers used by composition, not by inheritance. A subclass could break "fire once, then clear".	A variant slot, such as one holding two Enchantments, would be a new class.
Constants are `private static final`	e.g. `CHAIN_BREAK_CHANCE_PERCENT`, `STUN_DURATION_TURNS`	A name explains each number; no public constants (A2 feedback).	Tests repeat the numbers.
No static methods	—	A2 feedback penalised static methods.	—

Principles check.

Principle	How this decision applies it
SOLID	ISP: tools reach the slot through a `protected` accessor; callers use `Enchantable` only. OCP: classes are not `final` except two small helpers.
DRY	One visibility rule for all REQ4 classes.
KISS	Every member states its access.
Connascence	`private` fields keep connascence on state inside each class.
Code smells	Avoided: public attributes and missing modifiers.

I. Changes to the earlier design

Change	Why	Cost
`Hoe`, `WateringCan` and `Pickaxe` extend `AbstractEnchantableTool` instead of `Item`.	They are the three retrofitted classes (Section B).	An unenchanted tool behaves as before; its menu gains the enchant options.
`CapabilityToolAction` and `BreakAction` call `EnchantmentTrigger` after their own effect.	So every tool use can fire its Enchantment (Section D).	One more call in each action.

Change	Why	Cost
`TillingTool` and `WateringTool` declare `canTill(Tillable)` and `canWater(Waterable)`.	A2 feedback: empty marker interfaces are not good OO design.	Every tool returns `true` today.
`Enchantment` and `EnchantAction` live in `game.items.tools`.	Keeping them there removes a package cycle between `game.items.tools` and `game.enchantments`.	The interface sits beside the tools, not beside its implementations.
The tools receive their Enchantments through the constructor.	No hard-coded list inside the tools; `StackQueueValleyWorld` decides what is offered.	One more constructor parameter.

J. Known minor violations and why we accept them

Violation or cost	Why it is acceptable
`EnchantmentTrigger.fire` takes `Object usedTool`, so a wrong argument fails silently (no match, `""`) instead of at compile time.	The two callers hold tools of different types (`T extends HasStaminaCost` and `BreakingTool`), and `HasStaminaCost` does not say the tool is an `Item`. A narrower type needs a new shared interface or a new generic bound on `CapabilityToolAction`, only to tighten one parameter (YAGNI).
The three `triggerEnchantment()` bodies share a shape: check the slot, build a tile list, fire, join the messages.	Their spreads differ in kind: every adjacent tile, one random tile, or one random tile behind a chance roll. What they share, the slot logic, is already in `EnchantmentSlot`. With three different shapes, a common template would be a guess (rule of three).
`game.enchantments` depends on three other packages (Section F).	Reuse is the point; there is no cycle.

Summary

Principle	Where it shows	Change it absorbs	Where it is only partly met, and why
SRP	Offering (`AbstractEnchantableTool`), storing and firing (`EnchantmentSlot`), finding the used tool (`EnchantmentTrigger`), each spread (the tools) and each effect (the Enchantments) each have one class.	A new firing rule edits only `EnchantmentSlot`.	—
OCP	A new tool or Enchantment is one new class.	A Scythe or a Frost Enchantment: no existing class changes.	New Enchantments are listed in `StackQueueValleyWorld`, the composition root.
LSP	Any `Enchantable` works in both actions; any `Enchantment` works in any slot.	A new tool fires with no new branch.	—
ISP	`Enchantable` has two methods and `Enchantment` one; the actions see only `Enchantable`.	—	—
DIP	The actions depend on `Enchantable`, the tools on `Enchantment`; `RandomUtils` and `AreaFactory` are injected.	A new Enchantment needs no change to the tools.	`EnchantmentTrigger` is created with `new` in each action; it has no state and one possible behaviour.

DRY and KISS. The menu, the slot and the lookup each exist once, and the Enchantments reuse `Fire`, `StunnedStatus` and `Plant.attemptGrowth`. **Connascence.** Between packages it is only of Name and Type. The one Connascence of Identity (`==`) stays inside one method.

Testing. `HoeTest`, `WateringCanTest`, `PickaxeTest`, `EnchantmentSlotTest` and one test class per Enchantment cover each tool's own spread, tools with and without an Enchantment, Enchantments with and without affected tiles, and that an Enchantment is spent after one use. `FixedRandom` makes them repeatable, and `mvn test` runs them all.

Jingyu Zhang 37033956, Yuanshu Liu 36226173, Poyee Tan 36641162 – REQ 5: The Wanderer (API, HD)

Feature proposal: `feature-proposal.md` (thresholds, request and response schema).

A Wanderer roams the farm, and the real weather where it stands decides what it does. Its tile is turned into a real latitude and longitude, so every step changes the place it asks about. Every 5 turns it reacts to the current weather. A Farmer next to it can ask for tomorrow's forecast, and an omen follows. Every effect changes the map or an actor, never only prints text.

Class	Abstraction	Effect	Game state it changes
`StormShelterReaction`	`WeatherReaction`	Builds a shelter (`StormShelterGround`) on every free adjacent tile; stronger wind lasts longer	Ground over an area, restored later
`RainDanceReaction`	`WeatherReaction`	Tills bare Dirt and gives crops a free watering in an area that grows with the rainfall	Ground; crop watering counts
`CampfireReaction`	`WeatherReaction`	Lights `Fire` on 1 to 8 adjacent tiles; colder means more tiles	Spawns items; burns actors
`FrostOmen`	`ForecastOmen`	Pauses the growth of every plant within 2 tiles	Status on plants
`SowingOmen`	`ForecastOmen`	Plants a Strawberry Seedling on every bare Soil tile within 2 tiles	Spawns plants
`DroughtOmen`	`ForecastOmen`	Drains the asker's stamina for a few turns	Status on an actor

`Wanderer`, `ReactToWeatherAction` and `AskForecastAction` are the higher-level classes. They depend only on `WeatherReaction` and `ForecastOmen` and never name a concrete reaction or omen.

Each decision compares rejected and chosen designs, with pros, cons and a future example. Each decision ends with a principles check covering SOLID, DRY, KISS, connascence and code smells. Sections I and K list every place a reader may see as a weakness, and say why we chose it.

A. Keeping the game independent of the weather API

Rejected: `Wanderer` and `AskForecastAction` build the URL, send the request and read the JSON themselves.

Pros	Cons
One interface and one class fewer.	DIP: game classes would depend on `HttpClient` and on OpenWeatherMap's JSON shape.
	Every test of the Wanderer would need the network or a fragile HTTP mock.
	Changing the provider would mean editing `Wanderer`.

Chosen: a `WeatherSource` interface with `currentWeatherAt(lat, lon)` and `tomorrowWeatherAt(lat, lon)`, both returning `Optional<WeatherReading>`. `OpenWeatherClient` is the real one and is injected through the constructor. Tests inject `FixedWeatherSource`.

Pros	Cons
DIP: game classes depend on an interface the game owns.	One more interface and one more class.
No REQ5 test uses the network.	
OCP: another provider, or a cached one, needs no change to `Wanderer`, `AskForecastAction` or `WeatherInterpreter`.	

The package `game.weather` imports nothing from the rest of the game, so it could be reused by any feature.
Foresight: a weather source that replays saved readings for a demo is one new class.

Principles check.

Principle	How this decision applies it
SOLID	DIP: game classes depend on `WeatherSource`, which the game owns. OCP: another provider is one new class. LSP: `FixedWeatherSource` replaces the real client in every test.
DRY	One path to the weather for both the Wanderer and the forecast.
KISS	Two methods, both needed.
Connascence	Connascence of Algorithm with OpenWeatherMap's JSON layout stays inside `game.weather`; the rest of the game shares only Connascence of Type on `WeatherSource`.
Code smells	Avoided: Shotgun Surgery (changing provider would otherwise edit game classes) and network calls in tests.

B. Choosing which reaction today's weather triggers

Option	Pros	Cons
An if-chain inside `Wanderer.playConsciousTurn` that also performs each effect	No extra class.	SRP: the actor would also hold every weather rule. OCP: a new reaction edits `Wanderer`. The bare numbers would need a reader to guess their meaning (Connascence of Meaning).
A configurable rule engine: a list of (condition, effect) pairs, perhaps read from a file	Rules could change without recompiling.	The six rules are fixed by the proposal. A generic list is harder to read than a few `if`s, and solves a problem we do not have (YAGNI, KISS).
`WeatherInterpreter` with `reactionFor(reading)` (chosen)	`Wanderer` sees only `WeatherReaction`. The thresholds are named constants that exist only here. The priority order (wind, then rain, then cold) can be read in a few lines.	One more class to learn.

`WeatherInterpreter` is the only class that creates the six concrete classes. It works as a simple factory. `CampfireReaction` and `FrostOmen` size their effect by how far the temperature is below the threshold that chose them, so `WeatherInterpreter` passes that threshold into their constructors. Our first version repeated 10°C and 2°C as constants in those two classes (Connascence of Value across classes): changing a threshold in one place would have left the effect sized against the old number. Passing it in leaves one source for each number.
Foresight: a `HeatwaveReaction` above 35°C is one new class and one new `if` in `WeatherInterpreter`; `Wanderer` and the other reactions do not change.

Principles check.

Principle	How this decision applies it
SOLID	SRP: `WeatherInterpreter` holds the rules; the Wanderer only acts. OCP is partly met: a new rule adds one `if` here (Section K).
DRY	Each threshold exists once; the interpreter passes the cold and frost thresholds to the classes that size their effect by them.
KISS	A few ordered `if`s instead of a rule engine.
Connascence	Named constants avoid Connascence of Meaning. Passing the thresholds in removed Connascence of Value between the interpreter and two effect classes.
Code smells	Avoided: Switch Statements inside `Wanderer`, magic numbers and Speculative Generality (a configurable rule engine). Accepted: one factory class names the six concrete classes.

C. Two interfaces, not one

Rejected: one interface for both sides, with `reactAround(Location)` and `bringUpon(Actor, Location)`.

Pros	Cons
One interface to learn.	ISP: every reaction would carry an omen method it cannot use, and every omen a reaction method. The unused bodies would do nothing or throw, so a caller could not trust every implementation (LSP risk).

Chosen: `WeatherReaction` (`reactAround(Location)`) and `ForecastOmen` (`bringUpon(Actor, Location)`). Both are chosen in the same `WeatherInterpreter`, because "which effect does this reading trigger" is one job for today's and tomorrow's weather.

Pros	Cons
ISP: each class implements only the method it needs.	Two interfaces that look alike.
DIP: `AskForecastAction` depends only on `ForecastOmen`; `Wanderer` and `ReactToWeatherAction` only on `WeatherReaction`.	
DRY: `isRainy` and the condition names are shared by both methods inside one class.	

Principles check.

Principle	How this decision applies it
SOLID	ISP: each interface has one method. LSP: no implementation has a dummy method. DIP: each action depends on one interface.
DRY	`isRainy` and the condition names are shared inside one interpreter.
KISS	Two small interfaces instead of one with unused methods.
Connascence	Each action has Connascence of Type with one interface only.
Code smells	Avoided: Refused Bequest (reactions forced to implement an omen method, and the reverse).

D. When the sky cannot be read

With no key, no network or a bad reply, there is no reading.

Option	Pros	Cons
Throw a checked exception	Conventional Java.	Every caller must remember the `try/catch` in the right place.
Return `null`	Short.	A forgotten check crashes the game. The rule "`null` means no reading" is invisible to the compiler (Connascence of Meaning).
Return `Optional<WeatherReading>` (chosen)	"No reading" is part of the return type, so a caller sees it.	Call sites use `isEmpty()` and `get()`.

When there is no reading, `Wanderer` wraps its normal wandering in `UnreadableSkyAction`, which reports "The sky is unreadable, and the Wanderer only wanders." `AskForecastAction` reports that tomorrow's weather is unreadable. The game never stops, and the player always sees what happened. We use `Optional` only with `isEmpty()` and `get()`, with no chained calls.

Principles check.

Principle	How this decision applies it
SOLID	LSP: every `WeatherSource` keeps the same contract, so the Wanderer never needs to know which one it has.
DRY	One pattern for "no reading", also used for "no reaction" and "no omen".
KISS	`isEmpty()` and `get()`, no chained calls.
Connascence	Avoided Connascence of Meaning: a `null` result would need every caller to know what it means.
Code smells	Avoided: `null` checks and a crash when the network fails.

E. Turning the Wanderer's tile into a real place

Rejected: always ask about one fixed place, such as Melbourne.

Pros	Cons
Trivial.	Breaks the brief's rule that the request cannot be a static URL. The game state would not affect the query.

Chosen: `MapGeography` turns a tile's (x, y) into a latitude and longitude from an origin (Melbourne, -37.81, 144.96) and a scale (2 degrees per tile). `Wanderer` and `AskForecastAction` ask it about the tile the Wanderer stands on, so every move changes the query. Latitude stops at the poles and longitude wraps past 180, so any tile gives a valid place.

Pros	Cons
The query is driven by the game state.	One more small class.
SRP: one class knows how map tiles relate to the real world. Moving the farm changes only the constructor arguments.	
`latitudeOf` and `longitudeOf` name the two numbers, so callers cannot swap them (less Connascence of Position).	

Principles check.

Principle	How this decision applies it
SOLID	SRP: one class maps tiles to the real world.
DRY	The conversion exists once, used by the Wanderer and the forecast action.
KISS	Plain arithmetic from an origin and a scale.
Connascence	`latitudeOf` and `longitudeOf` name the two numbers, reducing Connascence of Position. The three-`double` constructor still has it (Section K).
Code smells	Avoided: a static URL and magic numbers; the origin and the scale are named in `StackQueueValleyWorld`.

F. Keeping the API key out of the code

Rejected: `OpenWeatherClient` calls `System.getenv("OPENWEATHER_API_KEY")` itself.

Pros	Cons
One class fewer.	SRP: the client would also decide where secrets live.
	A test could not control the key without changing the real environment.

Chosen: `ApiKeyLoader` takes the key's name, an environment map and a `.env` path. It checks the environment first, then a `NAME=value` line in `.env`, and returns `Optional<String>`. The client receives a loader through its constructor.

Pros	Cons
SRP: the loader finds the key; the client calls the API.	One more class.
A test passes a plain map and a temporary file.	
Security: the key is never in the source, and `.env` is in `.gitignore`.	

Principles check.

Principle	How this decision applies it
SOLID	SRP: the loader finds the key; the client calls the API. DIP: the client receives a loader.
DRY	The key's name is written once, in `StackQueueValleyWorld`.
KISS	Environment first, then `.env`; nothing more.
Connascence	Only Connascence of Name on the key's name, in one place.
Code smells	Avoided: a secret in the source code, and Divergent Change in the client when the key's location changes.

G. Reading the reply

Rejected: read the JSON inside `OpenWeatherClient`.

Pros	Cons
One class fewer.	SRP: the client would both talk to the network and know the JSON layout. A layout change and a network change would edit the same class.

Chosen: `OpenWeatherParser` turns a reply into a `WeatherReading`. The weather condition and the temperature are required; wind and rain default to 0, because OpenWeatherMap leaves out `rain` on dry days. For the forecast it reads the last of nine 3-hour steps (about 24 hours ahead) and divides `rain.3h` by 3 to get an hourly amount. A reply missing a required field gives no reading. `WeatherReading` is a small value object: its fields are `private final`, and its constructor rejects a blank condition and negative wind or rain.

Pros	Cons
The parser is tested with saved JSON text, with no network.	Gson is an extra library, added through Maven.
A bad reading cannot exist, so the reactions need no checks of their own.	

Principles check.

Principle	How this decision applies it
SOLID	SRP: the parser knows the JSON; `WeatherReading` holds checked values; the client knows the network.
DRY	The JSON layout is read in one class.
KISS	Required and optional fields are explicit; missing optional fields count as 0.
Connascence	Connascence of Algorithm with the API's format is confined to the parser.
Code smells	Avoided: Primitive Obsession (four loose numbers) and a passive Data Class, because `WeatherReading` validates itself and describes itself.

H. Letting the Farmer ask about tomorrow

Rejected: give `Farmer` a method that searches the map for a Wanderer and asks it.

Pros	Cons
No new action.	"Feature envy" smell: the data (`WeatherSource`, `MapGeography`, `WeatherInterpreter`) belongs to the Wanderer, not the Farmer.
	Any other actor that wants to ask would copy the same code (DRY).

Chosen: `Wanderer.allowableActions` offers an `AskForecastAction` to whoever stands next to it. This is the engine's normal way for one actor to offer an action to another. `ReactToWeatherAction` and `AskForecastAction` only pass the turn on to the reaction or omen they hold.

Pros	Cons
Reuses the engine's protocol, like every other interactive entity.	Any adjacent actor is offered the action (Section K).
SRP: each action has one job, and neither names a concrete class.	

The engine only asks an actor that is on the map for its actions, so `AskForecastAction` never needs to check that the Wanderer is still there.

Principles check.

Principle	How this decision applies it
SOLID	SRP: each action has one job. DIP: neither action names a concrete reaction or omen.
DRY	The engine's normal "offer an action to a nearby actor" protocol is reused.
KISS	`allowableActions` returns one action.
Connascence	Only Connascence of Name with the engine's existing API.

Principle	How this decision applies it
Code smells	Avoided: Feature Envy (a Farmer method using the Wanderer's data). Accepted: `ReactToWeatherAction` and `UnreadableSkyAction` are close to Middle Men, because the engine needs an `Action` object.

I. Visibility, `final`, `protected` and `static`

Choice	Where	Why	Cost
Every class is `public`	All REQ5 classes	`game.weather` is meant to be reused by other features.	A wider public API.
Every field is `private`, and `final` where it never changes	All classes; `WeatherReading` is fully immutable	A reading is shared by the interpreter and the effect it creates, so it must not change.	`Wanderer.turnsSinceLastReaction` is the only changing field.
`protected` method	`OpenWeatherClient.fetch(URI)`	The one seam a test overrides to return saved replies without the network.	A subclass could replace the network call. The class comment says it exists for tests.
`private` helpers	e.g. `OpenWeatherParser.readingFrom`, `WeatherInterpreter.isRainy`	They are steps, not contracts.	—
Constants are `private static final`	e.g. `STORM_WIND_THRESHOLD_MPS`, `TIMEOUT`	A name explains each number; no public constants (A2 feedback).	Tests repeat the numbers.
No static methods	—	A2 feedback penalised static methods.	—

Principles check.

Principle	How this decision applies it
SOLID	OCP: `public` classes, so `game.weather` can be reused by other features. ISP: only `fetch` is `protected`, as a test seam.
DRY	One visibility rule for all REQ5 classes.
KISS	Every member states its access.
Connascence	`private` fields keep connascence on state inside each class; `WeatherReading` is immutable.
Code smells	Avoided: public attributes and missing modifiers.

J. Changes to the earlier design

REQ5 is new in A3. It builds on earlier classes without changing them, except `StackQueueValleyWorld`.

Earlier class	How REQ5 uses it
`WanderingActor` (A2)	`Wanderer` extends it, so the unconscious check and wandering are reused.
`TemporaryGround` (REQ3)	`StormShelterGround` extends it, so the shelter restores the old ground with no new countdown code.
`Fire` (A2)	`CampfireReaction` lights the same `Fire` item.
`GrowthPausedStatus` (REQ1), `TimedStatus` (A2)	`FrostOmen` pauses plants; `DroughtWearinessStatus` reuses the countdown.
`Plantable`, `StrawberrySeedling` (REQ1)	`SowingOmen` plants through the same rule as everything else.

Earlier class	How REQ5 uses it
`StackQueueValleyWorld`	Builds the client, the key loader and `MapGeography`, and places one Wanderer.

K. Known minor violations and why we accept them

Violation or cost	Why it is acceptable
The Wanderer can be burnt by its own campfire if it later walks onto a burning tile.	On purpose: `Fire` burns any actor and never asks who lit it, so it needs no type check. A Wanderer that stays somewhere cold pays for its fires, and it has 50 hit points.
`OpenWeatherClient` creates its own `HttpClient`, a small DIP gap.	Tests replace `fetch`, not the `HttpClient`, so injecting it would add a parameter nobody varies.
The weather condition is a `String` such as `"Rain"`, so the code depends on OpenWeatherMap's names (Connascence of Meaning).	The names are named constants in `WeatherInterpreter`, and the parser is the only class that reads them from JSON.
`AskForecastAction` holds the same three collaborators as `Wanderer` (a small "data clump").	They are passed once, in `allowableActions`. A holder class for three fields would be a class used once.
Any actor next to the Wanderer is offered `AskForecastAction`, not only the Farmer.	Only the player picks menu actions; other actors never choose it.
`WeatherInterpreter` names all six concrete classes, so a new reaction edits it. OCP is only partly met.	It is the one factory point (Section B). Everything else stays closed.
`ApiKeyLoader` and `OpenWeatherParser` turn errors into an empty result.	The game must keep running without weather. Tests cover the missing key, the missing file and the broken JSON.

Summary

Principle	Where it shows	Change it absorbs	Where it is only partly met, and why
SRP	The API call (`OpenWeatherClient`), the JSON (`OpenWeatherParser`), the key (`ApiKeyLoader`), the place (`MapGeography`), the rules (`WeatherInterpreter`) and each effect each have one class.	A new JSON layout edits only the parser.	—
OCP	A new reaction, omen or weather provider is one new class.	A Heatwave reaction or a cached weather source.	`WeatherInterpreter` gains one `if` per new rule (Section K).
LSP	Any `WeatherReaction` or `ForecastOmen` works in its action; any `WeatherSource` works in the Wanderer.	`FixedWeatherSource` replaces the real client in every test.	—
ISP	`WeatherReaction` and `ForecastOmen` each have one method; `WeatherSource` has the two the Wanderer needs.	—	—
DIP	`Wanderer` depends on `WeatherSource` and `WeatherReaction`; `AskForecastAction` on `ForecastOmen`; the client on `ApiKeyLoader`.	A different provider needs no change to the game.	`OpenWeatherClient` creates its own `HttpClient` (Section K).

DRY and KISS. The rules live in one interpreter, the countdowns reuse `TemporaryGround` and `TimedStatus`, and the effects reuse `Fire`, `GrowthPausedStatus` and `Plantable`. Six fixed rules are a few `if`s, not a rule engine.
Connascence. Between packages it is only of Name and Type, through `WeatherSource`, `WeatherReaction` and `ForecastOmen`. Each threshold exists once, in `WeatherInterpreter`, which passes the cold and frost thresholds to the classes that size their effect by them.

Testing. Each reaction, omen, action and API-layer class has its own test class, for example `WeatherInterpreterTest`, `WandererTest`, `OpenWeatherParserTest` and `ApiKeyLoaderTest`. They cover readings that meet or miss each rule, the priority between rules, and invalid input such as a missing key, broken

JSON and negative wind. No test uses the network: `FixedWeatherSource` replaces the client, and `OpenWeatherClientTest` overrides `fetch`. `mvn test` runs them all. Separately, `WandererStressHarness` is a manual tool, not part of `mvn test`: it plays many seeded games through the real classes with fake weather to look for rare crashes.