


## Spring Cloud+Dubbo对Feign进行RPC改造

Spring Cloud Feign是基于Http Restful的调用，在高并发下的性能不够理想（基于Ribbon以及带有熔断机制，可以防止雪崩），成为性能瓶颈，对Feign进行Dubbo的RPC改造。

Spring Cloud的项目结构如下 web 调用 service 为例



公共打印接口

```
package com.chinacri.cloud.client;
```

```
import ...
```

```
/**
```

```
 * @author zhiwei.liu003
```

```
 * @date 2019/3/2016:49
```

```
 */
```

```
@FeignClient("o2o-agent")
```

```
public interface PubDocumentPrintClient extends PubDocumentPrintService {  
}
```

```
package com.chinacri.cloud.service;
```

```
import ...
```

```
/**
```

```
 * 公共打印
```

```
 * @author zhiwei.liu003
```

```
 * @date 2019/3/2016:40
```

```
 */
```

```
@Api
```

```
@RequestMapping("pubDocumentPrint")
```

```
public interface PubDocumentPrintService {
```


```
    @RequestMapping(value = "/printCanceled", method = RequestMethod.POST)
```

```
    Map<String, Object> printCanceled(@RequestBody Map<String, Object> params) throws Exception;
```


```
    @RequestMapping(value = "/processPrintShow", method = RequestMethod.POST)
```

```
    Map<String, Object> processPrintShow(@RequestBody Map<String, Object> params) throws Exception;
```


@FeignClient("o2o-agent") 指定为Service application name



Service 作为Dubbo提供者 pom 添加Dubbo引用



修改启动配置



添加common-dubbo，根据名称会去取配置服务器对应配置文件

```

@SpringBootApplication
@EnableTransactionManagement
@MapperScan("com.chinacri.cloud.mapper")
@EnableAutoConfiguration(exclude = {SecurityAutoConfiguration.class,
    DubboRelaxedBinding2AutoConfiguration.class})
@PrepareConfigurations({"common-eureka", "common-database-base",
    "common-redis", "common-dubbo"})
@EnableCaching
@EnableDubbo(scanBasePackages = {"com.chinacri.cloud.biz.impl"})
@WebServletComponentScan("com.chinacri.cloud.sdk")
public class CarServiceApplication {

```

## dubbo配置

```

chinacri-base-configurations / common-dubbo.yml
Project
bpm-sys-web.yml
bpm-wf.yml
bpm-wf-web.yml
chinacri-base-configurations.iml
common-database.yml
common-database2.yml
common-database3.yml
common-database4.yml
common-database-base.yml
common-database-fescar.yml
common-dubbo.yml
common-dubbo-exa.yml
common-eureka.yml
common-feign.yml
common-hystrix.yml
common-job.yml
common-rabbit.yml
common-redis.yml
common-ribbon.yml
common-rokectmq.yml
common-zookeeper.yml
echannel-prenew.yml
hystrix-dashboard.yml
o2o-admin.yml
1 dubbo:
2 application:
3 id: ${spring.application.name}
4 name: ${spring.application.name}
5 qos:
6 enable: false
7 protocol:
8 name: dubbo
9 port: -1
10 registry:
11 register: false
12 address: zookeeper://192.168.26.50:2181
13 simplified: true
14 file: "/mmwbase/applogs/rtlog/${spring.application.name}/dubbo.c
15 metadata-report:
16 address: zookeeper://192.168.26.50:2181
17 consumer:
18 timeout: 3000
19 check: false
20 provider:

```

## Service 接口放置在 spi 中


```

china-cri-b2b / china-cri-b2b-car / china-cri-b2b-car-spi / src / main / java / com / chinacri / cloud / service / PubDocumentPrintService
Project
china-cri-b2b D:\backup\platform\ideaWork\china-cri-b2b
idea
china-cri-b2b develop
china-cri-b2b-car develop
china-cri-b2b-car-service develop
china-cri-b2b-car-spi develop
src
main
java
com.chinacri.cloud
service
ProposalConfirmService
PubDocumentPrintService
value
target
chinacri-b2b-car-spi.iml
pom.xml
china-cri-b2b-car-web develop
src
1 import java.util.Map;
2
3 /**
4  * 公共打印
5  * @author zhiwei.liu003
6  * @date 2019/3/8
7  */
8
9 public interface PubDocumentPrintService {
10
11     Map<String, Object> printCanceled( Map<String, Object> params) thro
12
13     Map<String, Object> processPrintShow( Map<String, Object> params) ti
14
15     Map<String, Object> querySaleMakeInvoice( Map<String, Object> param

```

接口实现类的标签修改 其中这个@Service已经不再是spring的标签，而需要使用，


```
import com.alibaba.dubbo.config.annotation.Service;
```



```
import lombok.extern.slf4j.Slf4j;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import org.springframework.web.bind.annotation.RequestBody;
import org.springframework.web.bind.annotation.RestController;

import java.util.Map;

/**
 * 投保确认单
 *
 * @author lzw
 * @date 2019/03/21
 */
@Service
@RestController
@Slf4j;
```




```
import com.chinacri.cloud.service.PubDocumentPrintService;
import com.chinacri.cloud.utils.CommonUtils;
import lombok.extern.slf4j.Slf4j;
import org.apache.dubbo.config.annotation.Service;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.web.bind.annotation.RequestBody;

import java.util.Map;

/**
 * 公共打印
 *
 * @author lzw
 * @date 2019/03/21
 */
@Slf4j
@Service(version = "${b2b.version.car}")
public class PubDocumentPrintBizImpl extends BaseImplBiz implements PubDocumentPrintS
```

在使用的Controller中注释掉之前的feign注入，使用Dubbo的接口



```
@RestController
@RequestMapping("web/pubDocumentPrint")
@Slf4j

public class PubDocumentPrintRestController extends BaseController {

    @Autowired
    private PubDocumentPrintClient pubDocumentPrintClient;
```



```
@RestController
@RequestMapping("web/pubDocumentPrint")
@Slf4j
public class PubDocumentPrintRestController extends BaseController {

    @Reference(version = "${b2b.version.car}", timeout = 40000 )
    private PubDocumentPrintService pubDocumentPrintService;
```