上线准备

1、jenkins环境ant 1.7.1版本

tomcat 6的

copy $tomcat_home\server\lib\catalina-ant.jar 到 $ant_home\lib目录下即可

[?] catalina-ant.jar
   53.38KB

/mwbase/appsystem/Ant/apache-ant-1.7.1/lib

2、ivy

异常：Problem: failed to create task or type antlib:org.apache.ivy.ant:configure

Cause: The name is undefined.

处理方式

复制 /mwbase/appsystem/Ant/apache-ant-1.7.1/lib

[?] ivy-2.3.0-rc1.jar
     1.15MB

3、pcore-service部署位置创建com.sinolife.stoge.basedir=/mwbase/apptemp目录

☐ pcore上线准备
　　☑ 接口权限梳理
　　☐ jar同步 测试 http://192.168.26.50:8081/nexus/content/repositories/thirdparty/ =>生产 对应
　　☐ 平台监管地址

CARPCIP 部署jenkins

问题：SCP命令异常

```
           [javac] 10 warnings
            [copy] Copying 152 files to /var/lib/jenkins/workspace/carpcip_int_0.1.0/src/main/webapp/WEB-INF/classes

    war-uat-deploy:
           [mkdir] Created dir: /var/lib/jenkins/workspace/carpcip_int_0.1.0/dist
             [jar] Building jar: /var/lib/jenkins/workspace/carpcip_int_0.1.0/dist/SL_CARPCIP.war
            [echo] 上传打包文件...开始

    BUILD FAILED
    /var/lib/jenkins/workspace/carpcip_int_0.1.0/build.xml:227: Problem: failed to create task or type scp
    Cause: Could not load a dependent class com/jcraft/jsch/UserInfo
           It is not enough to have Ant's optional JARs
           you need the JAR files that the optional tasks depend upon.
           Ant's optional task dependencies are listed in the manual.
    Action: Determine what extra JAR files are needed, and place them in one of:
           -/mwbase/appsystem/Ant/apache-ant-1.7.1/lib
           -/home/jenkins/.ant/lib
           -a directory added on the command line with the -lib argument

    Do not panic, this is a common problem.
    The commonest cause is a missing JAR.

    This is not a bug; it is a configuration problem
```

处理方式：复制到jenkins 安装路径lib

?	jsch-0.1.55.jar
	274.1KB

☐ 4、新建临时目录

```
#临时目录💡
com.sinolife.stoge.basedir=/mwbase/apptemp    Liu003, 2019/9/4 16:22 • 临时文件路径修改
```

日志配置

SZ-CX-Spring-PCARCORE-001

SZ-CX-Spring-PCARCORE-002

1、修改jenkins service,platform 启动配置，增加参数

2、指定日志路径

/mwbase/applogs/rtlog/PCARCORE_SERVICE_PRD_1/common-all.log

实例名			日志路径
SZ-CX-Spring-PCARCORE-001	service日志名称	PCARCORE_SERVICE_PRD_1	/mwbase/applogs/[ommon-all.log
	platform日志名称	PCARCORE_PLATFORM_PRD_1	/mwbase/applogs/[1/common-all.log
SZ-CX-Spring-PCARCORE-002	service日志名称	PCARCORE_SERVICE_PRD_2	/mwbase/applogs/[ommon-all.log
	platform日志名称	PCARCORE_PLATFORM_PRD_2	/mwbase/applogs/[1/common-all.log

```
appsystem/chinacri-pcarcore/chinacri-pcarcore-service-service/ ./tools.sh stop"
chinacri-pcarcore-service-service/target/chinacri-pcarcore-service-service.jar dest=/mwbase/app
chinacri-pcarcore-service-service/tools.sh dest=/mwbase/appsystem/chinacri-pcarcore/chinacri-pc
system/chinacri-pcarcore/chinacri-pcarcore-service-service/tools.sh start dev 1"
```