

**TUGAS AKHIR
SISTEM INFORMASI EVENT ORGANIZER
LARAVEL DAN REACT**

PEMROGRAMAN BERBASIS FRAMEWORK





Disusun oleh:
Livia Yurike Khuril Maula
D4 TI – 3F / 15
NIM : 1841720025

**POLITEKNIK NEGERI MALANG
JURUSAN TEKNOLOGI INFORMASI
PROGRAM STUDI D4 TEKNIK INFORMATIKA**

MEI 2021

Langkah – Langkah

No	Keterangan
1.	Gunakan composer untuk melakukan instalasi Laravel 7
2.	<p>Ketik command berikut ini jika menggunakan Laravel Installer:</p> <pre>composer global require laravel/installer laravel new eventorganizer</pre> <p>atau bisa juga menggunakan Composer Create Project seperti command di bawah ini:</p> <pre>composer create-project --prefer-dist laravel/laravel:^7.0 eventorganizer</pre> 
3.	<p>Setelah proses berjalan dengan benar dan lancar maka saatnya kalian jalankan laravelnya dengan cara masuk ke dalam folder project laravel kalian kemudian ketikan perintah berikut ini :</p> <p>php artisan serve</p> <p>kemudian buka browser anda ketikan alamat berikut ini : http://localhost:8000/</p> <p>Jika berhasil maka muncul tampilan seperti dibawah ini :</p> 

4. Kemudian install react js:

```
PS C:\xampp\htdocs\eventorganizer> php artisan ui react
React scaffolding installed successfully.
Please run "npm install && npm run dev" to compile your fresh scaffolding.
PS C:\xampp\htdocs\eventorganizer>
```

5. Lalu install NodeJsnya:

npm install && npm run dev

Instalasi npm berfungsi untuk generate view dan assets yang dibutuhkan pada auth :

```
PS C:\xampp\htdocs\eventorganizer> npm install
npm WARN deprecated axios@0.19.2: Critical security vulnerability fixed in v0.21.1. For more information, see https://github.com/axios/axios/pull/3410
npm WARN deprecated chokidar@2.1.8: Chokidar 2 will break on node v14+, Upgrade to chokidar 3 with 15x less dependencies.
npm WARN deprecated fsevents@2.2.13: fsevents 1 will break on node v14+ and could be using insecure binaries. Upgrade to fsevents 2.
npm WARN deprecated urix@0.1.0: Please see https://github.com/lydell/urix#deprecated
npm WARN deprecated resolve-url@0.2.1: https://github.com/lydell/resolve-url#deprecated
npm notice created a lockfile as package-lock.json. You should commit this file.
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.7 (node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.1 (node_modules\watchpack\node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.1 (node_modules\sass\node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
added 1114 packages from 492 contributors and audited 1118 packages in 110.077s
57 packages are looking for funding
  run `npm fund` for details
found 42 vulnerabilities (39 moderate, 3 high)
  run `npm audit fix` to fix them, or `npm audit` for details
PS C:\xampp\htdocs\eventorganizer>

PS C:\xampp\htdocs\eventorganizer> npm run dev
> @ dev C:\xampp\htdocs\eventorganizer
> npm run development

> @ development C:\xampp\htdocs\eventorganizer
> cross-env NODE_ENV=development node_modules\webpack\bin\webpack.js --progress --hide-modules --config=node_modules/laravel-mix/setup/webpack.config.js

Additional dependencies must be installed. This will only take a moment.

Running: npm install vue-template-compiler --save-dev --production=false

npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\sass\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.13 (node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.1 (node_modules\watchpack\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

Okay, done. The following packages have been installed and saved to your package.json dependencies list:

- vue-template-compiler

98% after emitting SizeLimitsPlugin
DONE Compiled successfully in 3975ms

Asset      Size  Chunks  Chunk Names
/css/app.css 0 bytes    /js/app [emitted]  /js/app
/js/app.js 596 KiB    /js/app [emitted]  /js/app
PS C:\xampp\htdocs\eventorganizer>
```

6. Kemudian install react router dom nya:

npm install react-router-dom

```
PS C:\xampp\htdocs\eventorganizer> npm install react-router-dom
npm WARN react-router-dom@5.2.0 requires a peer of react@>=15 but none is installed. You must install peer dependencies yourself.
npm WARN react-router@5.2.0 requires a peer of react@>=15 but none is installed. You must install peer dependencies yourself.
npm WARN mini-create-react-context@0.4.1 requires a peer of react@^0.14.0 || ^15.0.0 || ^16.0.0 || ^17.0.0 but none is installed. You must install peer dependencies you
react-router-dom@5.2.0
added 1125 packages from 491 contributors and audited 1132 packages in 53.682s
57 packages are looking for funding
  run `npm fund` for details
found 42 vulnerabilities (39 moderate, 3 high)
  run `npm audit fix` to fix them, or `npm audit` for details
PS C:\xampp\htdocs\eventorganizer>
```

7. terakhir sweat alertnya:
npm i react-bootstrap-sweetalert

```
PS C:\xampp\htdocs\eventorganizer> npm i react-bootstrap-sweetalert
npm WARN mini-create-react-context@0.4.1 requires a peer of react@^15.0.0 || ^16.0.0 || ^17.0.0 but none is installed. You must install peer dependencies yourself.
npm WARN react-router-dom@5.2.0 requires a peer of react@^15 but none is installed. You must install peer dependencies yourself.
npm WARN react-bootstrap-sweetalert@5.2.0 requires a peer of react@^16.0.0 but none is installed. You must install peer dependencies yourself.
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.13 (node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\sass\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\watchpack\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

+ react-bootstrap-sweetalert@5.2.0
added 1 package from 1 contributor and audited 1133 packages in 9.789s

57 packages are looking for funding
  run `npm fund` for details

found 42 vulnerabilities (39 moderate, 3 high)
  run `npm audit fix` to fix them, or `npm audit` for details
PS C:\xampp\htdocs\eventorganizer>
```

Persiapan Database dan Migration

8. Buatlah sebuah database baru di dalam phpmyadmin dengan nama eo. Lalu edit nama database di dalam file **.env**

Setelah membuat sebuah database baru, selanjutnya masuk ke dalam project dan buka folder database → migrations → 2014_10_12_000000_create_users_table.php. Lalu ubahlah isi dari **public function up()** dengan script yang ada di bawah ini

```
.env X
.env
1 APP_NAME=Laravel
2 APP_ENV=local
3 APP_KEY=base64:MtMfX3Txj8NzB6E8QNoM97mZp4zulIDaEME1oJR7GjI=
4 APP_DEBUG=true
5 APP_URL=http://localhost
6
7 LOG_CHANNEL=stack
8
9 DB_CONNECTION=mysql
10 DB_HOST=127.0.0.1
11 DB_PORT=3306
12 DB_DATABASE=eo
13 DB_USERNAME=root
14 DB_PASSWORD=
```

```
14 public function up()
15 {
16     Schema::create('users', function (Blueprint $table) {
17         $table->id();
18         $table->string("first_name")->nullable();
19         $table->string("last_name")->nullable();
20         $table->string("full_name")->nullable();
21         $table->string("email")->unique();
22         $table->string("password");
23         $table->string("phone")->nullable();
24         $table->timestamps();
25     });
26 }
```

9. Kemudian save, buka cmd lalu masuk ke direktori proyek dan jalankan perintah berikut ini **php artisan migrate** perintah ini digunakan untuk memigrasi atau membuat tabel baru di dalam database.

```
PS C:\xampp\htdocs\uaspbf> php artisan migrate
Migration table created successfully.
Migrating: 2014_10_12_000000_create_users_table
Migrated: 2014_10_12_000000_create_users_table (66.82ms)
Migrating: 2014_10_12_100000_create_password_resets_table
Migrated: 2014_10_12_100000_create_password_resets_table (52.44ms)
Migrating: 2019_08_19_000000_create_failed_jobs_table
Migrated: 2019_08_19_000000_create_failed_jobs_table (51.80ms)
PS C:\xampp\htdocs\uaspbf>
```

Membuat Autentifikasi Login

10. jalankan perintah berikut ini **php artisan ui vue --auth** lalu jalankan lagi perintah berikut ini **npm install** .Dan terakhir, jalankan lagi perintah berikut ini **npm run dev**

```
PS C:\xampp\htdocs\eventorganizer> php artisan ui vue --auth
Vue scaffolding installed successfully.
Please run "npm install && npm run dev" to compile your fresh scaffolding.
Authentication scaffolding generated successfully.
PS C:\xampp\htdocs\eventorganizer>
```

```
PS C:\xampp\htdocs\eventorganizer> npm install
npm WARN deprecated popper.js@1.16.1: You can find the new Popper v2 at @popperjs/core, this package is dedicated to the legacy v1
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\watchpack\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\sass\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.13 (node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

added 1132 packages from 498 contributors and audited 1139 packages in 116.659s

59 packages are looking for funding
  run `npm fund` for details

found 42 vulnerabilities (38 moderate, 4 high)
  run `npm audit fix` to fix them, or `npm audit` for details
PS C:\xampp\htdocs\eventorganizer>
```

```
PS C:\xampp\htdocs\eventorganizer> npm run dev
> @ dev C:\xampp\htdocs\eventorganizer
> npm run development

> @ development C:\xampp\htdocs\eventorganizer
> cross-env NODE_ENV=development node_modules\webpack\bin\webpack.js --progress --hide-modules --config=node_modules/laravel-mix/setup/webpack.config.js

13% building 25/26 modules 1 active ...\xampp\htdocs\eventorganizer\node_modules\sass-loader\dist\cjs.js?ref--5-51C:\xampp\htdocs\eventorganizer\resources\sass\app.scss
D
DEPRECATION WARNING: Using / for division is deprecated and will be removed in Dart Sass 2.0.0.

Recommendation: math.div($spacer, 2)

More info and automated migrator: https://sass-lang.com/d/slash-div

302 | $headings-margin-bottom:          $spacer / 2 $default;
    |                                ~~~~~
    |                                |
node_modules\bootstrap\scss\variables.scss 302:31 @import
node_modules\bootstrap\scss\bootstrap.scss 9:9 @import
stdin 8:9 root stylesheet


DEPRECATION WARNING: Using / for division is deprecated and will be removed in Dart Sass 2.0.0.

Recommendation: math.div($input-padding-y, 2)

More info and automated migrator: https://sass-lang.com/d/slash-div

498 | $input-height-inner-quarter:      add($input-line-height * .25em, $input-padding-y / 2) $default;
    |                                ~~~~~
    |                                |
node_modules\bootstrap\scss\variables.scss 498:73 @import
```

11. Silahkan jalankan project dengan mengetikkan perintah **php artisan**. Hasilnya akan tampil 2 menu di pojok kanan atas layar, yaitu menu login dan register. Berikut ini adalah halaman register laravel.



Membuat Middleware dan Setting Middleware

12. Jalankan perintah berikut ini untuk membuat middleware checkrole. **php artisan make:middleware CheckRole**

```
PS C:\xampp\htdocs\eventorganizer> php artisan make:middleware CheckRole
Middleware created successfully.
PS C:\xampp\htdocs\eventorganizer>
```

Maka sebuah middleware baru dengan nama **CheckRole.php** akan otomatis dibuat. Buka **app** → **Http** → **Middelware** → **CheckRole.php**. Lalu edit **public function handle()** dengan script di bawah ini

```
7 class CheckRole
8 {
9     /**
10      * Handle an incoming request.
11      *
12      * @param \Illuminate\Http\Request $request
13      * @param \Closure $next
14      * @return mixed
15      */
16
17     public function handle($request, Closure $next)
18     {
19         //jika akun yang login sesuai dengan role
20         //maka silahkan akses
21         //jika tidak sesuai akan diarahkan ke home
22
23         $roles = array_slice(func_get_args(), 2);
24
25         foreach ($roles as $role) {
26             $user = \Auth::user()->role;
27             if ($user == $role) {
28                 return $next($request);
29             }
30         }
31
32         return redirect('/');
33     }
34 }
35
```

13. Kemudian, masuk ke folder **app** → **Http** → **Kernel.php** lalu tambahkan script di bawah ini di dalam bagian **protected \$routeMiddleware = [..]**

```
54 protected $routeMiddleware = [
55     'auth' => \App\Http\Middleware\Authenticate::class,
56     'auth.basic' => \Illuminate\Auth\Middleware\AuthenticateWithBasicAuth::class,
57     'bindings' => \Illuminate\Routing\Middleware\SubstituteBindings::class,
58     'cache.headers' => \Illuminate\Http\Middleware\SetCacheHeaders::class,
59     'can' => \Illuminate\Auth\Middleware\Authorize::class,
60     'guest' => \App\Http\Middleware\RedirectIfAuthenticated::class,
61     'password.confirm' => \Illuminate\Auth\Middleware\RequirePassword::class,
62     'signed' => \Illuminate\Routing\Middleware\ValidateSignature::class,
63     'throttle' => \Illuminate\Routing\Middleware\ThrottleRequests::class,
64     'verified' => \Illuminate\Auth\Middleware\EnsureEmailIsVerified::class,
65     'checkRole' => \App\Http\Middleware\CheckRole::class,
66 ];
67 }
68
```

Create Database dan Migration Table

14.	<p>Masih di direktori project, ketik command berikut untuk membuat Model Article dan Migration-nya:</p> <p><i>php artisan make:model Booking --migration</i></p> <pre>PS C:\xampp\htdocs\eventorganizer> php artisan make:model Booking --migration Model created successfully. Created Migration: 2021_06_15_033511_create_bookings_table PS C:\xampp\htdocs\eventorganizer> █</pre>
15.	<p>Sekarang buka file Booking.php yang ada di dalam direktori app/Booking.php dan modifikasi:</p> <pre>1 <?php 2 3 namespace App; 4 5 use Illuminate\Database\Eloquent\Model; 6 7 class Booking extends Model 8 { 9 protected \$table = "booking"; 10 protected \$fillable = ['namalengkap', 'alamat', 'telepon', 'email', 'namaacara', 'pilihpaket', 'tambahanlain', 'tanggalacara']; 11 } 12</pre>
16.	<p>Kemudian, buka file *****create_booking_table.php yang tersimpan di direktori database/migrations dan modifikasi seperti kode di bawah ini:</p> <pre>1 <?php 2 3 use Illuminate\Database\Migrations\Migration; 4 use Illuminate\Database\Schema\Blueprint; 5 use Illuminate\Support\Facades\Schema; 6 7 class CreateBookingsTable extends Migration 8 { 9 /** 10 * Run the migrations. 11 * 12 * @return void 13 */ 14 public function up() 15 { 16 Schema::create('bookings', function (Blueprint \$table) { 17 \$table->bigIncrements('id'); 18 \$table->string('namalengkap'); 19 \$table->string('alamat'); 20 \$table->integer('telepon'); 21 \$table->string('email'); 22 \$table->string('namaacara'); 23 \$table->string('pilihpaket'); 24 \$table->string('tambahanlain'); 25 \$table->date_format('tanggalacara'); 26 \$table->timestamps(); 27 }); 28 } 29 }</pre>

17. Kemudian jalankan command berikut ini agar table yang kita buat migrate ke database:

php artisan migrate

```
PS C:\xampp\htdocs\eventorganizer> php artisan migrate
Migrating: 2021_06_15_033511_create_bookings_table
Migrated: 2021_06_15_033511_create_bookings_table (0.08 seconds)
PS C:\xampp\htdocs\eventorganizer>
```

Jika berhasil dengan baik, maka di database eo akan muncul table seperti gambar di bawah ini:

#	Nama	Jenis	Penyortiran	Atribut	Kosong	Bawaan	Ekstra	Tindakan
<input type="checkbox"/> 1	id	bigint(20)		UNSIGNED	Tidak	Tidak ada	AUTO_INCREMENT	Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 2	namalengkap	varchar(191)			Tidak	Tidak ada		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 3	alamat	varchar(191)			Tidak	Tidak ada		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 4	telepon	int(11)			Tidak	Tidak ada		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 5	email	varchar(191)			Tidak	Tidak ada		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 6	namaacara	varchar(191)			Tidak	Tidak ada		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 7	pilihpaket	varchar(191)			Tidak	Tidak ada		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 8	tambahanlain	varchar(191)			Tidak	Tidak ada		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 9	tanggalacara	date			Tidak	Tidak ada		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 10	created_at	timestamp			Ya	NULL		Ubah Hapus Kunci Utama Unik Lainnya
<input type="checkbox"/> 11	updated_at	timestamp			Ya	NULL		Ubah Hapus Kunci Utama Unik Lainnya

Setting Route Web dan Api

18. Buka file **routes/web.php** dan silahkan modifikasi:

```
47
48 Route::view('/booking', 'booking');
49 Route::view('/booking/edit/{id}', 'booking');
50 Route::view('/booking/{id}', 'booking');
51 Route::view('/{path}', 'booking');
52
```

19. Kemudian buka file **routes/api.php** dan modifikasi menjadi:

```
20
21 Route::get('/booking', 'BookingController@index');
22 Route::post('/booking/store', 'BookingController@store');
23 Route::get('/booking/edit/{id}', 'BookingController@getBooking');
24 Route::get('/booking/{id}', 'BookingController@getBooking');
25 Route::put('/booking/{id}', 'BookingController@update');
26 Route::delete('/booking/delete/{id}', 'BookingController@delete');
27
```

Buat Controller Booking

20.	<p>Ketik command di bawah ini untuk membuat controller baru bernama BookingController</p> <p><i>php artisan make:controller BookingController</i></p> <pre>PS C:\xampp\htdocs\eventorganizer> php artisan make:controller BookingController Controller created successfully. PS C:\xampp\htdocs\eventorganizer> </pre>
21.	<p>Sekarang buka file BookingController.php yang terdapat di app/Http/Controllers.</p> <p>Kemudian ketik kode berikut ini:</p> <pre>1 <?php 2 3 namespace App\Http\Controllers; 4 5 use Illuminate\Http\Request; 6 7 class BookingController extends Controller 8 { 9 public function index() 10 { 11 \$booking = \App\Booking::all(); 12 13 return \$booking->toJson(); 14 } 15 16 public function store(Request \$request) 17 { 18 \$validatedData = \$request->validate([19 'namalengkap' => 'required', 20 'alamat' => 'required', 21 'telepon' => 'required', 22 'email' => 'required', 23 'namaacara' => 'required', 24 'pilihpaket' => 'required', 25 'tambahanlain' => 'required', 26 'tanggalacara' => 'required', 27]); 28 29 \$project = \App\Booking::create([30 'namalengkap' => \$validatedData['namalengkap'], 31 'alamat' => \$validatedData['alamat'], 32 'telepon' => \$validatedData['telepon'], 33 'email' => \$validatedData['email'], 34 'namaacara' => \$validatedData['namaacara'], 35 'pilihpaket' => \$validatedData['pilihpaket'], 36 'tambahanlain' => \$validatedData['tambahanlain'], 37 'tanggalacara' => \$validatedData['tanggalacara'],</pre>

```

38     });
39
40     $msg = [
41         'success' => true,
42         'message' => 'Booking created successfully!'
43     ];
44
45     return response()->json($msg);
46 }
47
48 public function getBooking($id) // for edit and show
49 {
50     $booking = \App\Booking::find($id);
51
52     return $booking->toJson();
53 }
54
55 public function update(Request $request, $id)
56 {
57     $validatedData = $request->validate([
58         'namalengkap' => 'required',
59         'alamat' => 'required',
60         'telepon' => 'required',
61         'email' => 'required',
62         'namaacara' => 'required',
63         'pilihpaket' => 'required',
64         'tambahanlain' => 'required',
65         'tanggalacara' => 'required',
66     ]);
67
68     $booking = \App\Booking::find($id);
69     $booking->namalengkap = $validatedData['namalengkap'];
70     $booking->alamat = $validatedData['alamat'];
71     $booking->telepon = $validatedData['telepon'];
72     $booking->email = $validatedData['email'];
73     $booking->namaacara = $validatedData['namaacara'];
74     $booking->pilihpaket = $validatedData['pilihpaket'];
75     $booking->tambahanlain = $validatedData['tambahanlain'];
76     $booking->tanggalacara = $validatedData['tanggalacara'];
77     $booking->save();
78
79     $msg = [
80         'success' => true,
81         'message' => 'Booking updated successfully'
82     ];
83
84     return response()->json($msg);
85 }
86
87 public function delete($id)
88 {
89     $booking = \App\Booking::find($id);
90     if (empty($booking)) {
91         $booking->delete();
92         $msg = [
93             'success' => true,
94             'message' => 'Booking deleted successfully!'
95         ];
96         return response()->json($msg);
97     } else {
98         $msg = [
99             'success' => false,
100             'message' => 'Booking deleted failed!'
101         ];
102         return response()->json($msg);
103     }
104 }
105 }
106

```

Manejement CRUD React Js di Laravel 7

22. Buat file baru bernama **App.js** dan simpan di direktori **resources/js/components**.

```
1 import React, { Component } from "react";
2 import ReactDOM from "react-dom";
3 import { BrowserRouter, Route, Switch } from "react-router-dom";
4 import Header from "./Header";
5 import ArticleIndex from "./BookingIndex";
6 import ArticleCreate from "./BookingCreate";
7 import ArticleShow from "./BookingShow";
8 import ArticleEdit from "./BookingEdit";
9
10 class App extends Component {
11   render() {
12     return (
13       <BrowserRouter>
14         <div>
15           <Header />
16           <Switch>
17             <Route exact path="/" component={ArticleIndex} />
18             <Route exact path="/create" component={ArticleCreate} />
19             <Route
20               path="/booking/edit/:id"
21               component={ArticleEdit}
22             />
23             <Route path="/booking/:id" component={ArticleShow} />
24           </Switch>
25         </div>
26       </BrowserRouter>
27     );
28   }
29 }
30
31 ReactDOM.render(<App />, document.getElementById("app"));
32
```

23. Buat lagi file baru bernama **BookingIndex.js** dan simpan di direktori **resources/js/components**.

Ketik kode berikut ini:

```
1 import axios from "axios";
2 import React, { Component } from "react";
3 import { Link } from "react-router-dom";
4 import SweetAlert from "react-bootstrap-sweetalert";
5
6 class BookingIndex extends Component {
7   constructor() {
8     super();
9     this.state = {
10       booking: [],
11       msg: null,
12       type: null,
13       flash: false,
14       alert: null
15     };
16   }
17
18   hideAlert() {
19     this.setState({
20       alert: null
21     });
22   }
23
24   componentDidMount() {
25     axios.get("/api/booking").then(response => {
26       this.setState({
27         articles: response.data
28       });
29     });
30   }
31
32   confirmDelete(id) {
33     const getAlert = () => (
34       <SweetAlert
35         warning
36         showCancel
37         confirmBtnText="Hapus"
38       />
39     );
40   }
41 }
```

```

38         cancelBtnText="Tidak Jadi"
39         confirmBtnBsStyle="default"
40         cancelBtnBsStyle="danger"
41         title="Tunggu ..."
42         onConfirm={() => this.deleteItem(id)}
43         onCancel={() => this.hideAlert()}
44         focusCancelBtn
45     >
46     Kalau sudah dihapus, nggak bakal balik lagi.
47 </SweetAlert>
48 );
49 this.setState({
50     alert: getAlert()
51 });
52 }
53
54 deleteItem(id) {
55     axios.delete(`/api/booking/delete/${id}`).then(response => {
56         var msg = response.data.success;
57         if (msg == true) {
58             this.hideAlert();
59             this.goToHome();
60         }
61     });
62 }
63
64 goToHome() {
65     const getAlert = () => (
66         <SweetAlert
67             success
68             title="Success!"
69             onConfirm={() => this.onSuccess()}
70             onCancel={this.hideAlert()}
71             timeout={2000}
72             confirmBtnText="Oke Siap"
73         >
74         Deleted booking successfully
75     </SweetAlert>
76 );
77 this.setState({
78     alert: getAlert()
79 });
80 }
81
82 onSuccess() {
83     this.componentDidMount();
84     this.hideAlert();
85 }
86
87 render() {
88     const { booking } = this.state;
89     return (
90         <div className="container py-4">
91             <div className="row justify-content-center">
92                 <div className="col-md-8">
93                     <div className="card">
94                         <div className="card-header">All Booking</div>
95                         <div className="card-body">
96                             <Link
97                                 className="btn btn-primary btn-sm mb-3"
98                                 to="/create"
99                             >
100                                 Create new booking
101                             </Link>
102                             <div className="table-responsive">
103                                 <table className="table table-bordered table-hover">
104                                     <thead>
105                                         <tr>
106                                             <th
107                                                 width="50"
108                                                 className="text-center"
109                                             >
110                                                 No
111                                         </th>

```

```

111     </th>
112     <th>Nama Lengkap</th>
113     <th>Alamat</th>
114     <th>Telepon</th>
115     <th>Email</th>
116     <th>Nama Acara</th>
117     <th>Pilih Paket</th>
118     <th>Tambahan Lain</th>
119     <th>Tanggal Acara</th>
120     <th>
121       width="200"
122       className="text-center"
123     >
124       Action
125     </th>
126   </tr>
127 </thead>
128 <tbody>
129   {booking.map((booking, i) => (
130     <tr key={i}>
131       <td>
132         width="50"
133         className="text-center"
134       >
135         {i + 1}
136       </td>
137       <td>{booking.booking}</td>
138       <td>
139         width="200"
140         className="text-center"
141       >
142         <div className="btn-group">
143           <Link
144             className="btn btn-primary"
145             to={` /booking/${booking.id}`}
146           >
147             Detail
148           </Link>
149           <Link
150             className="btn btn-success"
151             to={` /booking/edit/${booking.id}`}
152           >
153             Edit
154           </Link>
155           <button
156             className="btn btn-danger"
157             onClick={() =>
158               this.confirmDelete(
159                 booking.id
160               )
161             }
162           >
163             Delete
164           </button>
165         </div>
166       </td>
167     </tr>
168   )})
169 </tbody>
170 </table>
171 {this.state.alert}
172 </div>
173 </div>
174 </div>
175 </div>
176 </div>
177 </div>
178 );
179 }
180 }
181
182 export default BookingIndex;
183

```

24. Buat lagi file baru bernama **BookingCreate.js** dan simpan di direktori **resources/js/components**.

```
1  import axios from "axios";
2  import React, { Component } from "react";
3  import { Link } from "react-router-dom";
4  import SweetAlert from "react-bootstrap-sweetalert";
5
6  class BookingCreate extends Component {
7    constructor(props) {
8      super(props);
9      this.state = {
10        title: "",
11        content: "",
12        alert: null,
13        errors: []
14      };
15      this.handleFieldChange = this.handleFieldChange.bind(this);
16      this.handleCreateNewBooking = this.handleCreateNewBooking.bind(this);
17      this.hasErrorFor = this.hasErrorFor.bind(this);
18      this.renderErrorFor = this.renderErrorFor.bind(this);
19    }
20
21    handleFieldChange(event) {
22      this.setState({
23        [event.target.name]: event.target.value
24      });
25    }
26
27    goToHome() {
28      const getAlert = () => (
29        <SweetAlert
30          success
31          title="Success!"
32          onConfirm={() => this.onSuccess()}
33          onCancel={this.hideAlert()}
34          timeout={2000}
35          confirmBtnText="Oke Siap"
36        >
37          Created booking successfully
38        </SweetAlert>
39      );
40      this.setState({
41        alert: getAlert()
42      });
43    }
44
45    onSuccess() {
46      this.props.history.push("/");
47    }
48
49    hideAlert() {
50      this.setState({
51        alert: null
52      });
53    }
54
55    handleCreateNewBooking(event) {
56      event.preventDefault();
57      const booking = {
58        title: this.state.title,
59        content: this.state.content
60      };
61      axios.post("/api/booking/store", booking).then(response => {
62        var msg = response.data.success;
63        if (msg == true) {
64          return this.goToHome();
65        }
66      });
67    }
68
69    hasErrorFor(field) {
70      return !!this.state.errors[field];
71    }
72
73    renderErrorFor(field) {
74      if (this.hasErrorFor(field)) {
```



```

149         this.hasErrorFor("email")
150         ? "is-invalid"
151         : ""
152     }}
153     name="email"
154     rows="10"
155     value={this.state.email}
156     onChange={this.handleFieldChange}
157   />
158   {this.renderErrorFor("email")}
159 </div>
160 <div className="form-group">
161   <label htmlFor="namaacara">
162     Nama Acara
163   </label>
164   <textarea
165     id="namaacara"
166     className={`form-control ${
167       this.hasErrorFor("namaacara")
168       ? "is-invalid"
169       : ""
170     }}`
171     name="namaacara"
172     rows="10"
173     value={this.state.namaacara}
174     onChange={this.handleFieldChange}
175   />
176   {this.renderErrorFor("namaacara")}
177 </div>
178 <div className="form-group">
179   <label htmlFor="pilihpaket">
180     Pilih Paket
181   </label>
182   <textarea
183     id="pilihpaket"
184     className={`form-control ${
185       this.hasErrorFor("pilihpaket")
186       ? "is-invalid"
187       : ""
188     }}`
189     name="pilihpaket"
190     rows="10"
191     value={this.state.pilihpaket}
192     onChange={this.handleFieldChange}
193   />
194   {this.renderErrorFor("pilihpaket")}
195 </div>
196 <div className="form-group">
197   <label htmlFor="tambahanlain">
198     Tambahan Lain
199   </label>
200   <textarea
201     id="tambahanlain"
202     className={`form-control ${
203       this.hasErrorFor("tambahanlain")
204       ? "is-invalid"
205       : ""
206     }}`
207     name="tambahanlain"
208     rows="10"
209     value={this.state.tambahanlain}
210     onChange={this.handleFieldChange}
211   />
212   {this.renderErrorFor("tambahanlain")}
213 </div>
214 <div className="form-group">
215   <label htmlFor="tanggal">
216     Tanggal Acara
217   </label>
218   <textarea
219     id="tanggal"
220     className={`form-control ${
221       this.hasErrorFor("tanggal")
222       ? "is-invalid"

```

```

223         : ""
224     }
225     name="tanggal"
226     rows="10"
227     value={this.state.tanggal}
228     onChange={this.handleFieldChange}
229     />
230     {this.renderErrorFor("tanggal")}
231 </div>
232 <Link
233     className="btn btn-secondary"
234     to={"/"}
235 >
236     Back
237 </Link>
238 <button className="btn btn-primary">
239     Create
240 </button>
241 {this.state.alert}
242 </form>
243 </div>
244 </div>
245 </div>
246 </div>
247 </div>
248 );
249 }
250 }
251 export default BookingCreate;
252

```

25. Buat lagi file baru bernama **BookingEdit.js** dan simpan di direktori **resources/js/components**.

Ketik kode berikut ini:

```

1  import axios from "axios";
2  import React, { Component } from "react";
3  import { Link } from "react-router-dom";
4  import SweetAlert from "react-bootstrap-sweetalert";
5
6  class BookingEdit extends Component {
7      constructor(props) {
8          super(props);
9          this.state = {
10             namalengkap: "",
11             alamat: "",
12             telepon: "",
13             email: "",
14             namaacara: "",
15             pilihpaket: "",
16             tambahanlain: "",
17             tanggalacarat: "",
18             alert: null,
19             message: "",
20             errors: []
21         };
22         this.handleFieldChange = this.handleFieldChange.bind(this);
23         this.handleUpdateBooking = this.handleUpdateBooking.bind(this);
24         this.hasErrorFor = this.hasErrorFor.bind(this);
25         this.renderErrorFor = this.renderErrorFor.bind(this);
26     }
27
28     handleFieldChange(event) {
29         this.setState({
30             [event.target.name]: event.target.value
31         });
32     }
33
34     componentDidMount() {
35         const bookingId = this.props.match.params.id;
36
37         axios.get(`/api/booking/edit/${bookingId}`).then(response => {

```

```

38         this.setState({
39             title: response.data.title,
40             content: response.data.content
41         });
42     });
43 }
44
45 goToHome() {
46     const getAlert = () => (
47         <SweetAlert
48             success
49             title="Success!"
50             onConfirm={() => this.onSuccess()}
51             onCancel={this.hideAlert()}
52             timeout={2000}
53             confirmBtnText="Oke Siap"
54         >
55             {this.state.message}
56         </SweetAlert>
57     );
58     this.setState({
59         alert: getAlert()
60     });
61 }
62
63 onSuccess() {
64     this.props.history.push("/");
65 }
66
67 hideAlert() {
68     this.setState({
69         alert: null
70     });
71 }
72
73 handleUpdateBooking(event) {
74     event.preventDefault();
75
76     const booking = {
77         namalengkap: this.state.namalengkap,
78         alamat: this.state.alamat,
79         telepon: this.state.telepon,
80         email: this.state.email,
81         namaacara: this.state.namaacara,
82         pilihpaket: this.state.pilihpaket,
83         tambhanlain: this.state.tambahanlain,
84         tanggalacara: this.state.tanggalacara
85     };
86
87     const bookingId = this.props.match.params.id;
88
89     axios.put(`/api/booking/${bookingId}`, booking).then(response => {
90         // redirect to the homepage
91         var msg = response.data.success;
92         if (msg == true) {
93             this.setState({
94                 message: response.data.message
95             });
96             return this.goToHome();
97         }
98     });
99 }
100
101 hasErrorFor(field) {
102     return !!this.state.errors[field];
103 }
104
105 renderErrorFor(field) {
106     if (this.hasErrorFor(field)) {
107         return (
108             <span className="invalid-feedback">
109                 <strong>{this.state.errors[field][0]}</strong>
110             </span>
111         );

```



```

186     }}
187     name="email"
188     value={this.state.email}
189     onChange={this.handleFieldChange}
190   />
191   {this.renderErrorFor("email")}
192 </div>
193 <div className="form-group">
194   <label htmlFor="namaacara">
195     Nama Acara
196   </label>
197   <input
198     id="namaacara"
199     type="text"
200     className={`form-control ${
201       this.hasErrorFor("namaacara")
202         ? "is-invalid"
203         : ""
204     }`}
205     name="namaacara"
206     value={this.state.namaacara}
207     onChange={this.handleFieldChange}
208   />
209   {this.renderErrorFor("namaacara")}
210 </div>
211 <div className="form-group">
212   <label htmlFor="pilihpaket">
213     Pilih Paket
214   </label>
215   <input
216     id="pilihpaket"
217     type="text"
218     className={`form-control ${
219       this.hasErrorFor("pilihpaket")
220         ? "is-invalid"
221         : ""
222     }`}

```

```

223     name="pilihpaket"
224     value={this.state.pilihpaket}
225     onChange={this.handleFieldChange}
226   />
227   {this.renderErrorFor("pilihpaket")}
228 </div>
229 <div className="form-group">
230   <label htmlFor="tambahanlain">
231     Tambahan Lain
232   </label>
233   <input
234     id="tambahanlain"
235     type="text"
236     className={`form-control ${
237       this.hasErrorFor("tambahanlain")
238         ? "is-invalid"
239         : ""
240     }`}
241     name="tambahanlain"
242     value={this.state.tambahanlain}
243     onChange={this.handleFieldChange}
244   />
245   {this.renderErrorFor("tambahanlain")}
246 </div>
247 <div className="form-group">
248   <label htmlFor="tanggalacara">
249     Tanggal Booking
250   </label>
251   <input
252     id="tanggalacara"
253     type="date"
254     className={`form-control ${
255       this.hasErrorFor("tanggalacara")
256         ? "is-invalid"
257         : ""
258     }`}
259     name="tanggalacara"

```

```

260         value={this.state.tanggalacara}
261         onChange={this.handleFieldChange}
262       />
263       {this.renderErrorFor("tanggalacara")}
264     </div>
265     <Link
266       className="btn btn-secondary"
267       to={'/' }
268     >
269       Back
270     </Link>
271     <button className="btn btn-primary">
272       Update
273     </button>
274     {this.state.alert}
275   </form>
276 </div>
277 </div>
278 </div>
279 </div>
280 </div>
281   );
282 }
283 }
284 export default BookingEdit;
285

```

26. Buat lagi file baru bernama **BookingShow.js** dan simpan di direktori **resources/js/components**.

Ketik kode berikut ini:

```

1  import axios from "axios";
2  import React, { Component } from "react";
3  import { Link } from "react-router-dom";
4
5  class BookingShow extends Component {
6    constructor(props) {
7      super(props);
8      this.state = {
9        booking: {}
10      };
11    }
12
13    componentDidMount() {
14      const bookingId = this.props.match.params.id;
15
16      axios.get(`/api/booking/${bookingId}`).then(response => {
17        this.setState({
18          booking: response.data
19        });
20      });
21    }
22
23    render() {
24      const { booking } = this.state;
25
26      return (
27        <div className="container py-4">
28          <div className="row justify-content-center">
29            <div className="col-md-8">
30              <div className="card">
31                <div className="card-header">
32                  Nama Lengkap: {booking.namalengkap}
33                </div>
34                <div className="card-body">
35                  <p>{article.content}</p>
36                  <Link className="btn btn-primary" to={'/' }>
37                    Back
38                  </Link>
39                </div>
40              </div>
41            </div>
42          </div>
43        </div>
44      );
45    }
46  }
47
48  export default BookingShow;
49

```

Buat Halaman View

27. Buat file baru bernama **app.blade.php** dan simpan di direktori **resource/views**.

Sekarang ketik kode berikut:

```
1 <!DOCTYPE html>
2 <html lang="{{ app()->getLocale() }}">
3
4 <head>
5     <meta charset="utf-8">
6     <meta http-equiv="X-UA-Compatible" content="IE=edge">
7     <meta name="viewport" content="width=device-width, initial-scale=1">
8
9     <!-- CSRF Token -->
10    <meta name="csrf-token" content="{{ csrf_token() }}">
11
12    <title>Event Organizer</title>
13
14    <!-- Styles -->
15    <link href="{{ asset('css/app.css') }}" rel="stylesheet">
16</head>
17
18<body>
19    <div id="app"></div>
20
21    <script src="{{ asset('js/app.js') }}"></script>
22</body>
23
24</html>
```

Edit app.js

28. Silahkan buka file **resources/js/app.js** kemudian cari kode berikut:

```
require('./components/Example');
```

Ubah menjadi kode berikut:

```
require('./components/App');
```

```
resources > js > JS app.js
1  /**
2   * First we will load all of this project's JavaScript dependencies which
3   * includes React and other helpers. It's a great starting point while
4   * building robust, powerful web applications using React + Laravel.
5   */
6
7  require("./bootstrap");
8
9  /**
10   * Next, we will create a fresh React component instance and attach it to
11   * the page. Then, you may begin adding components to this application
12   * or customize the JavaScript scaffolding to fit your unique needs.
13   */
14
15  require("./components/App");
16  |
```

Tambahan View Lainnya :

29. Views/welcome.blade.php

```
resources > views > welcome.blade.php > @div.flex-center position-ref.full-height > @div.content
1
2 @extends('layouts.welcome')
3
4 @section('content')
5 <div class="flex-center position-ref full-height">
6 <div class="content">
7 <div class="jumbotron jumbotron">
8 <div class="container text-center"> <br><br>
9 <br><br>
10 <h1 class="display-4"><b>Welcome to Our</b></h1>
11 <div class="title m-b-md">
12 EVENT ORGANIZER
13 </div>
14 <p class="lead">Decoration of engagement, aqiqoh, birthday party, akad, photo booth </p>
15 <p class="lead">| cake topper | table set |</p>
16 </div>
17 </div>
18
19 </div>
20 </div>
21 </div>
22 @endsection
```

Views/layouts/welcome.blade.php

```
1 <!doctype html>
2 <html lang="{{ str_replace('_', '-', app()->getLocale()) }}">
3
4 <head>
5 <meta charset="utf-8">
6 <meta name="viewport" content="width=device-width, initial-scale=1">
7
8 <!-- CSRF Token -->
9 <meta name="csrf-token" content="{{ csrf_token() }}">
10
11 <title>{{ config('Eventorganizer.name', 'Event Organizer') }}</title>
12
13 <!-- Scripts -->
14 <script src="{{ asset('js/') }}" defer></script>
15
16 <!-- Fonts -->
17 <link rel="dns-prefetch" href="//fonts.gstatic.com">
18 <link href="https://fonts.googleapis.com/css?family=Munito" rel="stylesheet">
19
20 <!-- Styles -->
21 <link href="{{ asset('css/app.css') }}" rel="stylesheet">
22
23 <!-- Styles -->
24 <style>
25 html,
26 body {
27 background-color: #fff;
28 color: #636b6f;
29 font-family: 'Munito', sans-serif;
30 font-weight: 200;
31 height: 100vh;
32 margin: 0;
33 }
34
35 .full-height {
36 height: 100vh;
37 }
38
39 .flex-center {
40 align-items: center;
41 display: flex;
42 justify-content: center;
43 }
44
45 .position-ref {
46 position: relative;
47 }
48
49 .top-right {
50 position: absolute;
51 right: 10px;
52 top: 18px;
53 }
54
55 .content {
56 text-align: center;
57 }
58
59 .title {
60 font-size: 84px;
61 }
62
63 .links>a {
64 color: #636b6f;
65 padding: 0 25px;
66 font-size: 13px;
67 font-weight: 600;
68 letter-spacing: .1rem;
69 text-decoration: none;
70 text-transform: uppercase;
71 }
72
73 .m-b-md {
74 margin-bottom: 30px;
```



```

75     }
76
77     .jumbotron {
78         background-size: cover;
79         text-align: center;
80
81     }
82
83     .jumbotron .display-4 {
84         color: black;
85     }
86
87     .jumbotron p {
88         color: black;
89     }
90
91     footer {
92         display: block;
93     }
94 </style>
95 </head>
96
97 <body>
98     <div id="app">
99         <nav class="navbar navbar-expand-md navbar-light bg-white shadow-sm">
100             <div class="container">
101                 <a class="navbar-brand" href="{{ url('/') }}">
102                     
103                 </a>
104                 <a class="navbar-brand" href="{{ url('/') }}">
105                     {{ config('app.Home', 'Home') }}
106                 </a>
107                 <a class="navbar-brand" href="{{ url('/Produk') }}">
108                     {{ config('app.Produk', 'Produk') }}
109                 </a>
110                 <a class="navbar-brand" href="{{ url('/booking') }}">
111                     {{ config('app.Booking', 'Booking') }}
112             </div>
113             <a class="navbar-brand" href="{{ url('/Galery') }}">
114                 {{ config('app.Contact', 'Contact') }}
115             </a>
116             <button class="navbar-toggler" type="button" data-toggle="collapse" data-target="#navbarSupportedContent" aria-cont
117                 <span class="navbar-toggler-icon"></span>
118             </button>
119
120             <div class="collapse navbar-collapse" id="navbarSupportedContent">
121                 <!-- Left Side Of Navbar -->
122                 <ul class="navbar-nav mr-auto">
123
124                 </ul>
125
126                 <!-- Right Side Of Navbar -->
127                 <ul class="navbar-nav ml-auto">
128                     <!-- Authentication links -->
129                     @guest
130                     <li class="nav-item">
131                         <a class="nav-link" href="{{ route('login') }}">{{ __('Login') }}</a>
132                     </li>
133                     @if (Route::has('register'))
134                     <li class="nav-item">
135                         <a class="nav-link" href="{{ route('register') }}">{{ __('Register') }}</a>
136                     </li>
137                     @endif
138                     @else
139                     <li class="nav-item dropdown">
140                         <a id="navbarDropdown" class="nav-link dropdown-toggle" href="#" role="button" data-toggle="dropdown" a
141                             {{ Auth::user()->name }} <span class="caret"></span>
142                         </a>
143
144                         <div class="dropdown-menu dropdown-menu-right" aria-labelledby="navbarDropdown">
145                             <a class="dropdown-item" href="{{ route('logout') }}" onclick="event.preventDefault();
146                                 document.getElementById('logout-form').submit();">
147                                 {{ __('Logout') }}
148                             </a>
149
150                             <form id="logout-form" action="{{ route('logout') }}" method="POST" style="display: none;">
151                                 @csrf
152                             </form>
153                         </div>
154                     </li>
155                     @endguest
156                 </ul>
157             </div>
158         </nav>
159
160
161
162         <main class="py-4">
163             @yield('content')
164         </main>
165     </div>
166 </body>
167 </html>

```

Views/produk.blade.php

```
1  @extends('layouts.produk')
2
3  @section('content')
4  <div class="container">
5      <div class="content">
6          <div class="jumbotron jumbotron">
7              <div class="container text-center">
8                  <br><br>
9                  <div class="title m-b-md">
10                     EVENT ORGANIZER
11                 </div>
12                 <p class="lead">Decoration of engagement, aqiqoh, birthday party, akad, photo booth </p>
13                 <p class="lead">| cake topper | table set |</p>
14             </div>
15         </div>
16
17
18
19     </div>
20     <div class="row">
21         <div class="col text-center">
22             <h1>NGGAEGAME</h1>
23         </div>
24     </div>
25
26     <div class="row" style="background-image: url(img/bacdrop/bg2.png)">
27         <div class="col-md">
28             <div class="card" style="width: 18rem;">
29                 <a href="{{ url('backdrop') }}"></a>
30                 <center>
31                     <div class="card-body">
32                         <p class="card-text"><b>BACKDROP</b></p>
33                     </div>
34                 </center>
35             </div>
36         </div>
37
38         <div class="col-md">
39             <div class="card" style="width: 18rem;">
40                 <a href="{{ url('birthday') }}"></a>
41                 <center>
42                     <div class="card-body">
43                         <p class="card-text"><b>BIRTHDAY</b></p>
44                     </div>
45                 </center>
46             </div>
47         </div>
48
49         <div class="col-md">
50             <div class="card" style="width: 18rem;">
51                 <a href="{{ url('engagement') }}"></a>
52                 <center>
53                     <div class="card-body">
54                         <p class="card-text"><b>ENGAGEMENT</b></p>
55                     </div>
56                 </center>
57             </div>
58         </div>
59     </div>
60 </div>
61 </div>
62 @endsection
```

App/Http/Controllers/ProdukController.php

```
1  <?php
2
3  namespace App\Http\Controllers;
4
5  use Illuminate\Http\Request;
6
7  class ProdukController extends Controller
8  {
9      /**
10       * Create a new controller instance.
11       *
12       * @return void
13       */
14     public function __construct()
15     {
16     }
17
18     /**
19      * Show the application dashboard.
20      *
21      * @return \Illuminate\Contracts\Support\Renderable
22      */
23     public function index()
24     {
25         return view('produk');
26     }
27 }
28
```

Views/backdrop.blade.php

```
1 @extends('layouts.backdrop')
2
3 @section('content')
4 <div class="container div-gallery-feed">
5     <div class="row">
6         <div class="col-md-12">
7             <h3 class="title-gallery-feed">OUR BACKDROP</h3>
8         </div>
9     </div>
10    <div class="row gallery-feed">
11        <div class="col-md-4 col-sm-6 col-xs-6">
12            
13        </div>
14        <div class="col-md-4 col-sm-6 col-xs-6">
15            
16        </div>
17        <div class="col-md-4 col-sm-6 col-xs-6">
18            
19        </div>
20        <div class="col-md-4 col-sm-6 col-xs-6">
21            
22        </div>
23        <div class="col-md-4 col-sm-6 col-xs-6">
24            
25        </div>
26        <div class="col-md-4 col-sm-6 col-xs-6">
27            
28        </div>
29        <div class="col-md-4 col-sm-6 col-xs-6">
30            
31        </div>
32        <div class="col-md-4 col-sm-6 col-xs-6">
33            
34        </div>
35        <div class="col-md-4 col-sm-6 col-xs-6">
36            
37        </div>
38        <div class="col-md-4 col-sm-6 col-xs-6">
39            
40        </div>
41        <div class="col-md-4 col-sm-6 col-xs-6">
42            
43        </div>
44        <div class="col-md-4 col-sm-6 col-xs-6">
45            
46        </div>
47    </div>
48
49    <a href="{{ url('/produk') }}" class="more-gallery-feed">Previous</a>
50    <br>
51
52    <div class="center">
53        <a href="https://www.instagram.com/nggaegawe/" class="more-gallery-feed">CHECK OUR INSTAGRAM</a>
54    </div>
55
56 </div>
57 @endsection
```

App/Http/Controllers/BackdropController.php

```
1 <?php
2
3 namespace App\Http\Controllers;
4
5 use Illuminate\Http\Request;
6
7 class BackdropController extends Controller
8 {
9     /**
10      * Create a new controller instance.
11      *
12      * @return void
13      */
14     public function __construct()
15     {
16     }
17
18     /**
19      * Show the application dashboard.
20      *
21      * @return \Illuminate\Contracts\Support\Renderable
22      */
23     public function index()
24     {
25         return view('backdrop');
26     }
27 }
28
```

Views/birthday.blade.php

```
1  @extends('layouts.birthday')
2
3  @section('content')
4  <div class="container div-gallery-feed">
5      <div class="row">
6          <div class="col-md-12">
7              <h3 class="title-gallery-feed">OUR BIRTHDAY</h3>
8          </div>
9      </div>
10     <div class="row gallery-feed">
11         <div class="col-md-4 col-sm-6 col-xs-6">
12             
13         </div>
14         <div class="col-md-4 col-sm-6 col-xs-6">
15             
16         </div>
17         <div class="col-md-4 col-sm-6 col-xs-6">
18             
19         </div>
20         <div class="col-md-4 col-sm-6 col-xs-6">
21             
22         </div>
23         <div class="col-md-4 col-sm-6 col-xs-6">
24             
25         </div>
26         <div class="col-md-4 col-sm-6 col-xs-6">
27             
28         </div>
29         <div class="col-md-4 col-sm-6 col-xs-6">
30             
31         </div>
32         <div class="col-md-4 col-sm-6 col-xs-6">
33             
34         </div>
35     </div>
36
37     <a href="{{ url('/produk') }}" class="more-gallery-feed">Previous</a>
38     <br>
39
40     <div class="center">
41         <a href="https://www.instagram.com/nggaegawe/" class="more-gallery-feed">CHECK OUR INSTAGRAM</a>
42     </div>
43 </div>
44 @endsection
```

App/Http/Controllers/BirthdayController.php

```
1  <?php
2
3  namespace App\Http\Controllers;
4
5  use Illuminate\Http\Request;
6
7  class BirthdayController extends Controller
8  {
9      /**
10       * Create a new controller instance.
11       *
12       * @return void
13       */
14     public function __construct()
15     {
16     }
17
18     /**
19      * Show the application dashboard.
20      *
21      * @return \Illuminate\Contracts\Support\Renderable
22      */
23     public function index()
24     {
25         return view('birthday');
26     }
27 }
28
```

Views/engagement.blade.php

```
1 @extends('layouts.engagement')
2
3 @section('content')
4 <div class="container div-gallery-feed">
5     <div class="row">
6         <div class="col-md-12">
7             <h3 class="title-gallery-feed">OUR ENGAGEMENT</h3>
8         </div>
9     </div>
10    <div class="row gallery-feed">
11        <div class="col-md-4 col-sm-6 col-xs-6">
12            
13        </div>
14        <div class="col-md-4 col-sm-6 col-xs-6">
15            
16        </div>
17        <div class="col-md-4 col-sm-6 col-xs-6">
18            
19        </div>
20        <div class="col-md-4 col-sm-6 col-xs-6">
21            
22        </div>
23        <div class="col-md-4 col-sm-6 col-xs-6">
24            
25        </div>
26        <div class="col-md-4 col-sm-6 col-xs-6">
27            
28        </div>
29        <div class="col-md-4 col-sm-6 col-xs-6">
30            
31        </div>
32        <div class="col-md-4 col-sm-6 col-xs-6">
33            
34        </div>
35        <div class="col-md-4 col-sm-6 col-xs-6">
36            
37        </div>
38        <div class="col-md-4 col-sm-6 col-xs-6">
39            
40        </div>
41        <div class="col-md-4 col-sm-6 col-xs-6">
42            
43        </div>
44        <div class="col-md-4 col-sm-6 col-xs-6">
45            
46        </div>
47    </div>
48    <a href="{{ url('/produk') }}" class="more-gallery-feed">Previous</a>
49    <br>
50
51    <div class="center">
52        <a href="https://www.instagram.com/nggaegawe/" class="more-gallery-feed">CHECK OUR INSTAGRAM</a>
53    </div>
54 </div>
55 @endsection
```

App/Http/Controllers/EngagementController.php

```
1 <?php
2
3 namespace App\Http\Controllers;
4
5 use Illuminate\Http\Request;
6
7 class EngagementController extends Controller
8 {
9     /**
10      * Create a new controller instance.
11      *
12      * @return void
13      */
14     public function __construct()
15     {
16     }
17
18     /**
19      * Show the application dashboard.
20      *
21      * @return \Illuminate\Contracts\Support\Renderable
22      */
23     public function index()
24     {
25         return view('engagement');
26     }
27 }
28
```

30. Routes/web.php

```
routes > web.php > ...
1  <?php
2
3  use Illuminate\Support\Facades\Route;
4
5  /*
6  |-----
7  | Web Routes
8  |-----
9  |
10 | Here is where you can register web routes for your application. These
11 | routes are loaded by the RouteServiceProvider within a group which
12 | contains the "web" middleware group. Now create something great!
13 |
14 */
15
16 Route::get('/', function () {
17     return view('welcome');
18 });
19
20 Route::get('Produk', function () {
21     return view('produk');
22 });
23
24 Route::get('Backdrop', function () {
25     return view('backdrop');
26 });
27
28 Route::get('Birthday', function () {
29     return view('birthday');
30 });
31
32 Route::get('Engagement', function () {
33     return view('engagement');
34 });
35
36
37 Auth::routes();
38
39 Route::get('/welcome', 'HomeController@index')->name('welcome');
40
41 Route::get('/produk', 'ProdukController@index')->name('produk');
42
43 Route::get('/backdrop', 'BackdropController@index')->name('backdrop');
44
45 Route::get('/birthday', 'BirthdayController@index')->name('birthday');
46
47 Route::get('/engagement', 'EngagementController@index')->name('engagement');
48
49 Route::get('admin', function () {
50     return view('admin');
51 })->middleware('checkRole:admin');
52 Route::get('customer', function () {
53     return view('welcome');
54 })->middleware(['checkRole:customer,admin']);
55
56 Route::view('/bookings', 'app');
57 Route::view('/booking/edit/{id}', 'app');
58 Route::view('/booking/{id}', 'app');
59 Route::view('/{path}', 'app');
60
```

Hasil :

31. Ketik command berikut untuk menginstall perubahan yang terjadi:

npm run dev

```
PS C:\xampp\htdocs\eventorganizer> npm run dev
> @ dev C:\xampp\htdocs\eventorganizer
> npm run development

> development C:\xampp\htdocs\eventorganizer
> cross-env NODE_ENV=development node_modules/webpack/bin/webpack.js --progress --hide-modules --config=node_modules/laravel-mix/setup/webpack.config.js

Additional dependencies must be installed. This will only take a moment.

Running: npm install vue-template-compiler --save-dev --production=false

npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\sass\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.13 (node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\watchpack\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

Okay, done. The following packages have been installed and saved to your package.json dependencies list:

- vue-template-compiler

98% after emitting SizeLimitsPlugin
DONE compiled successfully in 3975ms

Asset      Size  Chunks             Chunk Names
/css/app.css 0 bytes  /js/app [emitted]  /js/app
/js/app.js 596 KiB  /js/app [emitted]  /js/app
PS C:\xampp\htdocs\eventorganizer>
```


Kemudian ketik *php artisan serve*





```
PS C:\xampp\htdocs\eventorganizer> php artisan serve
Laravel development server started: http://127.0.0.1:8000
[Wed Jun 16 06:51:12 2021] 127.0.0.1:8128 [200]: /css/app.css
[Wed Jun 16 06:51:12 2021] 127.0.0.1:14733 [200]: /js/app.js
```





URL Halaman Index:

localhost:8000

Hasilnya :







Create new booking

Nama Lengkap

Alamat

Telepon

Email

Nama Acara

Pilih Paket

Tambahkan Lain

Create new booking

Nama Lengkap

Livia Yurike

Alamat

Jl Piranha Atas

Email

kliviayurike@gmail.com

Nama Acara

Birthday Party

Pilih Paket

Paket A

Tambahan Lain

Birthday Kids

Tanggal Booking

03/07/2021

Back Create

	id	nama lengkap	alamat	telepon	email	nama acara	pilih paket	tambahan lain	tanggal acara
	1	Livia Yurike	Jl Piranha Atas	822287732	kliviayurike@gmail.com	Birthday Party	Paket A	Birthday Kids	2021-07-03

Link Github :

<https://github.com/liviayurike/Pemrograman-Berbasis-Framework/tree/master/Pertemuan%20UAS>

Link Video Youtube :

<https://youtu.be/Q61rYZNwkfw>