

The following example demonstrates several requests for getting app acquisition data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/appacquisitions?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2015&endDate=2/1/2015&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/appacquisitions?
applicationId=9NBLGGGZ5QDR&startDate=8/1/2015&endDate=8/31/2015&skip=0&filter=market eq 'US' and gender eq 'm'
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate acquisition data for the app. For more information about the data in each object, see the acquisition values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of acquisition data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Acquisition values

Elements in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the acquisition data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.

Value	Type	Description
applicationId	string	The Store ID of the app for which you are retrieving acquisition data.
applicationName	string	The display name of the app.
deviceType	string	One of the following strings that specifies the type of device on which the acquisition occurred: • PC • Phone • Console-Xbox One • Console-Xbox Series X • IoT • Holographic • Unknown
orderName	string	The name of the order.
storeClient	string	One of the following strings that indicates the version of the Store where the acquisition occurred: • Windows Phone Store (client) • Microsoft Store (client) (or Windows Store (client) if querying for data before March 23, 2018) • Microsoft Store (web) (or Windows Store (web) if querying for data before March 23, 2018) • Volume purchase by organizations • Other
osVersion	string	One of the following strings that specifies the OS version on which the acquisition occurred: • Windows Phone 7.5 • Windows Phone 8 • Windows Phone 8.1 • Windows Phone 10 • Windows 8 • Windows 8.1 • Windows 10 • Windows 11 • Unknown
market	string	The ISO 3166 country code of the market where the acquisition occurred.

Value	Type	Description
gender	string	One of the following strings that specifies the gender of the user who made the acquisition: • m • f • Unknown
ageGroup	string	One of the following strings that specifies the age group of the user who made the acquisition: • less than 13 • 13-17 • 18-24 • 25-34 • 35-44 • 44-55 • greater than 55 • Unknown
acquisitionType	string	One of the following strings that indicates the type of acquisition: • Free • Trial • Paid • Promotional code • lap • Subscription lap • Private Audience • Pre Order • Xbox Game Pass (or Game Pass if querying for data before March 23, 2018) • Disk • Prepaid Code
acquisitionQuantity	number	The number of acquisitions that occurred during the specified aggregation level.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

```
syntax
```

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/appacquisitions?
applicationId=9NBLGGGZ5QDR HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "applicationId": "9NBLGGGZ5QDR",
      "date": "2022-07-29",
      "acquisitionQuantity": 7,
      "purchasePriceUSDAmount": 0.0,
      "purchasePriceLocalAmount": 0.0,
      "purchaseTaxUSDAmount": 0.0,
      "purchaseTaxLocalAmount": 0.0
    },
  ],
  "TotalCount": 1,
  "DataFreshnessTimestamp": "2022-07-29T08:42:00"
}
```

Sample Request

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/appacquisitions?
applicationId=9NBLGGGZ5QDR&startDate=8/1/2021&endDate=12/21/2021&skip=0&filter=market&groupby=date,applicationName,acquisitionType,ageGroup,storeClient,gender,market,osVersion,deviceType HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "acquisitionType": "Free",

```

```

        "storeClient": "Microsoft Store (client)",
        "gender": "f",
        "market": "TW",
        "osVersion": "Windows 10",
        "deviceType": "PC",
        "date": "2021-08-01",
        "acquisitionQuantity": 1,
        "purchasePriceUSDAmount": 0.0,
        "purchasePriceLocalAmount": 0.0,
        "purchaseTaxUSDAmount": 0.0,
        "purchaseTaxLocalAmount": 0.0
    },
    {
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "acquisitionType": "Free",
        "storeClient": "Microsoft Store (client)",
        "gender": "Unknown",
        "market": "BR",
        "osVersion": "Windows 10",
        "deviceType": "PC",
        "date": "2021-08-01",
        "acquisitionQuantity": 1,
        "purchasePriceUSDAmount": 0.0,
        "purchasePriceLocalAmount": 0.0,
        "purchaseTaxUSDAmount": 0.0,
        "purchaseTaxLocalAmount": 0.0
    },
],
"TotalCount": 2,
"DataFreshnessTimestamp": "2022-07-29T08:42:00"
}

```

Related topics

- [Acquisitions report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get app acquisition funnel data](#)
- [Get app conversions by channel](#)
- [Get add-on acquisitions](#)

Get app installs

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get aggregate install data in JSON format for an application during a given date range and other optional filters. This information is also available in the [Acquisitions report](#) in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/installs</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve install data.	Yes

Parameter	Type	Description	Required
startDate	date	The start date in the date range of install data to retrieve. The default is the current date.	No
endDate	date	The end date in the date range of install data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or. String values must be surrounded by single quotes in the <i>filter</i> parameter. You can specify the following fields from the response body: • market • osVersion • deviceType • packageVersion	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day , week , or month . If unspecified, the default is day .	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values for each install. The syntax is <i>orderby=field [order],field [order],...</i>. The <i>field</i> parameter can be one of the following fields from the response body: • applicationName • date • deviceType • market • osVersion • packageVersion • successfulInstallCount The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields from the response body: • applicationName • date • deviceType • market • osVersion • packageVersion The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • date • applicationId • successfulInstallCount The <i>groupby</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupby=ageGroup,market&aggregationLevel=week</i>	No

Request example

The following example demonstrates several requests for getting app install data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/installs?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2015&endDate=2/1/2015&top=10&skip=0
HTTP/1.1
```

Authorization: Bearer <your access token>

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/installs?
applicationId=9NBLGGGZ5QDR&startDate=8/1/2015&endDate=8/31/2015&skip=0&filter=market eq 'US' and deviceType eq 'PC' HTTP/1.1
```

Authorization: Bearer <your access token>

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate install data. For more information about the data in each object, see the following table.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of install data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Elements in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the install data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
applicationId	string	The Store ID of the app for which you are retrieving install data.
applicationName	string	The display name of the app.

Value	Type	Description
deviceType	string	One of the following strings that specifies the type of device that completed the install: - PC - Phone - Console-Xbox One - Console-Xbox Series X - IoT - Holographic - Unknown
packageVersion	string	The version of the package that was installed.
osVersion	string	One of the following strings that specifies the OS version on which the install occurred: - Windows Phone 7.5 - Windows Phone 8 - Windows Phone 8.1 - Windows Phone 10 - Windows 8 - Windows 8.1 - Windows 10 - Windows 11 - Unknown
market	string	The ISO 3166 country code of the market where the install occurred.
successfulInstallCount	number	The number of successful installs that occurred during the specified aggregation level.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/installs?
applicationId=9WZDNCRFJB4P
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "successfulInstallCount": 100053
    }
  ],
  "TotalCount": 1
}
```

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/installs?
applicationId=9NBLGGGZ5QDR&aggregationLevel=day&startDate=06/19/2022&endDate
=07/21/2022&top=10&skip=0&groupby=applicationName,date,deviceType,market,osV
ersion,packageVersion&orderby=date desc
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-07-22",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "packageVersion": "2013.1206.10.2936",
      "deviceType": "PC",
      "market": "AR",
      "osVersion": "Windows 10",
      "successfulInstallCount": 1
    },
    {
      "date": "2022-07-22",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",

```

```
    "packageVersion": "2013.1206.10.2936",
    "deviceType": "PC",
    "market": "AU",
    "osVersion": "Windows 10",
    "successfulInstallCount": 1
  },
  {
    "date": "2022-07-22",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "packageVersion": "2013.1206.10.2936",
    "deviceType": "PC",
    "market": "BD",
    "osVersion": "Windows 10",
    "successfulInstallCount": 1
  },
  {
    "date": "2022-07-22",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "packageVersion": "2013.1206.10.2936",
    "deviceType": "PC",
    "market": "BG",
    "osVersion": "Windows 11",
    "successfulInstallCount": 1
  },
  {
    "date": "2022-07-22",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "packageVersion": "2013.1206.10.2936",
    "deviceType": "PC",
    "market": "BO",
    "osVersion": "Windows 10",
    "successfulInstallCount": 1
  },
  {
    "date": "2022-07-22",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "packageVersion": "2013.1206.10.2936",
    "deviceType": "PC",
    "market": "BR",
    "osVersion": "Windows 10",
    "successfulInstallCount": 6
  },
  {
    "date": "2022-07-22",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "packageVersion": "2013.1206.10.2936",
    "deviceType": "PC",
    "market": "BR",
    "osVersion": "Windows 11",
    "successfulInstallCount": 3
  }
}
```

```

    },
    {
      "date": "2022-07-22",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "packageVersion": "2013.1206.10.2936",
      "deviceType": "PC",
      "market": "CA",
      "osVersion": "Windows 11",
      "successfulInstallCount": 1
    },
    {
      "date": "2022-07-22",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "packageVersion": "2013.1206.10.2936",
      "deviceType": "PC",
      "market": "CN",
      "osVersion": "Windows 11",
      "successfulInstallCount": 1
    },
    {
      "date": "2022-07-22",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "packageVersion": "2013.1206.10.2936",
      "deviceType": "PC",
      "market": "MX",
      "osVersion": "Windows 10",
      "successfulInstallCount": 1
    }
  ],
  "TotalCount": 10
}

```

Related topics

- [Installs report](#)
- [Access analytics data using Microsoft Store services](#)

Get app acquisition funnel data

Article • 03/16/2023

Use this method in the Microsoft Store analytics API to get acquisition funnel data for an application during a given date range and other optional filters. This information is also available in the [Acquisitions report](#) in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method.
After you obtain an access token, you have 60 minutes to use it before it expires.
After the token expires, you can obtain a new one.

Request

Request syntax

 Expand table

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/funnel</code>

Request header

 Expand table

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

 Expand table

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve acquisition funnel data. An example Store ID is 9WZDNCRFJ3Q8.	Yes
startDate	date	The start date in the date range of acquisition funnel data to retrieve. The default is the current date.	No
endDate	date	The end date in the date range of acquisition funnel data to retrieve. The default is the current date.	No
filter	string	One or more statements that filter the rows in the response. For more information, see the filter fields section below.	No

Filter fields

The *filter* parameter of the request contains one or more statements that filter the rows in the response. Each statement contains a field and value that are associated with the **eq** or **ne** operators, and statements can be combined using **and** or **or**.

The following filter fields are supported. String values must be surrounded by single quotes in the *filter* parameter.

 Expand table

Fields	Description
campaignId	The ID string for a custom app promotion campaign that is associated with the acquisition.
market	A string that contains the ISO 3166 country code of the market where the acquisition occurred.
deviceType	One of the following strings that specifies the device type on which the acquisition occurred: - PC - Phone - Console-Xbox One - Console-Xbox Series X - IoT - Holographic - Unknown

Fields	Description
ageGroup	One of the following strings that specifies the age group of the user who completed the acquisition: • 0 – 17 • 18 – 24 • 25 – 34 • 35 – 49 • 50 or over • Unknown
gender	One of the following strings that specifies the gender of the user who completed the acquisition: • M • F • Unknown

Request example

The following example demonstrates several requests for getting acquisition funnel data for an app. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/funnel?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2017&endDate=2/1/2017 HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/funnel?
applicationId=9NBLGGGZ5QDR&startDate=8/1/2016&endDate=8/31/2016&filter=marke
t eq 'US' and gender eq 'm' HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

 Expand table

Value	Type	Description
Value	array	An array of objects that contain acquisition funnel data for the app. For more information about the data in each object, see the funnel values section

Value	Type	Description
		below.
TotalCount	int	The total number of objects in the <i>Value</i> array.

Funnel values

Objects in the *Value* array contain the following values.

 Expand table

Value	Type	Description
MetricType	string	One of the following strings that specifies the type of funnel data that is included in this object: • PageView • Acquisition • Install • Usage
UserCount	string	The number of users who performed the funnel step specified by the <i>MetricType</i> value.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/funnel?
applicationId=9NBLGGGZ5QDR
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```

{
  "Value": [
    {
      "MetricType": "PageView",
      "UserCount": 6214
    },
    {
      "MetricType": "Acquisition",
      "UserCount": 1502
    },
    {
      "MetricType": "Usage",
      "UserCount": 606
    },
    {
      "MetricType": "Install",
      "UserCount": 977
    }
  ],
  "TotalCount": 4
}

```

Sample Request

syntax

```

GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/funnel?
applicationId=9NBLGGGZ5QDR&startDate=12/19/2021&endDate=12/21/2021&filter=ma
rket eq 'US' and gender eq 'm'
HTTP/1.1
Authorization: Bearer <your access token>

```

Sample Response

JSON

```

{
  "Value": [
    {
      "MetricType": "PageView",
      "UserCount": 10
    },
    {
      "MetricType": "Acquisition",
      "UserCount": 8
    },
    {
      "MetricType": "Usage",
      "UserCount": 5
    }
  ]
}

```

```
    },  
    {  
      "MetricType": "Install",  
      "UserCount": 3  
    }  
  ],  
  "TotalCount": 4  
}
```

Related topics

- [Acquisitions report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get app acquisitions](#)

Feedback

Was this page helpful?

 Yes

 No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

Get app conversions by channel

Article • 03/16/2023

Use this method in the Microsoft Store analytics API to get aggregate conversions by channel for an application during a given date range and other optional filters.

- A *conversion* means that a customer (signed in with a Microsoft account) has newly obtained a license to your app (whether you charged money or you've offered it for free).
- The *channel* is the method in which a customer arrived at your app's listing page (for example, via the Store or a [custom app promotion campaign](#)).

This information is also available in the [Acquisitions report](#) in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/appchannelconversions</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve conversion data. An example Store ID is 9WZDNCRFJ3Q8.	Yes
startDate	date	The start date in the date range of conversion data to retrieve. The default is 1/1/2016.	No
endDate	date	The end date in the date range of conversion data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the response body. Each statement can use the eq or ne operators, and statements can be combined using and or or. You can specify the following strings in the filter statements. For descriptions, see the conversion values section in this article. • applicationName • appType • customCampaignId • referrerUriDomain • channelType • storeClient • deviceType • market Here is an example <i>filter</i> parameter: <i>filter=deviceType eq 'PC'</i>.	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day , week , or month . If unspecified, the default is day .	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values for each conversion. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following strings: • date • applicationName • appType • customCampaignId • referrerUriDomain • channelType • storeClient • deviceType • market The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: • date • applicationName • appType • customCampaignId • referrerUriDomain • channelType • storeClient • deviceType • market The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • date • applicationId • conversionCount • clickCount The <i>groupby</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>groupby=ageGroup,market&aggregationLevel=week</i>	No

Request example

The following example demonstrates several requests for getting app conversion data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/appchannelconversions?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2017&endDate=2/1/2017&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/appchannelconversions?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2017&endDate=4/31/2017&skip=0&filter=market eq 'US'
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate conversion data for the app. For more information about the data in each object, see the conversion values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10 but there are more than 10 rows of conversion data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Conversion values

Objects in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the conversion data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.

Value	Type	Description
applicationId	string	The Store ID of the app for which you are retrieving conversion data.
applicationName	string	The display name of the app for which you are retrieving conversion data.
appType	string	The type of the product for which you are retrieving conversion data. For this method, the only supported value is App .
customCampaignId	string	The ID string for a custom app promotion campaign that is associated with the app.
referrerUriDomain	string	Specifies the domain where the app listing with the custom app promotion campaign ID was activated.
channelType	string	One of the following strings that specifies the channel for the conversion: • CustomCampaignId • Store Traffic • Other
storeClient	string	The version of the Store where the conversion occurred. Currently, the only supported value is SFC .
deviceType	string	One of the following strings: • PC • Phone • Console-Xbox One • Console-Xbox Series X • IoT • Holographic • Unknown
market	string	The ISO 3166 country code of the market where the conversion occurred.
clickCount	number	The number of customer clicks on your app listing link.
conversionCount	number	The number of customer conversions.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/appchannelconversions?
applicationId=9NBLGGGZ5QDR&startDate=06/23/2022&endDate=07/21/2022&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "applicationId": "9NBLGGGZ5QDR",
      "clickCount": 3089,
      "conversionCount": 14
    }
  ],
  "@nextLink": "",
  "TotalCount": 1
}
```

Sample Request

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/appchannelconversions?
applicationId=9NBLGGGZ5QDR&startDate=06/19/2022&endDate=07/21/2022&skip=0&groupby=date,applicationName,customCampaignId,referrerUriDomain,channelType,storeClient,deviceType,market&filter=market eq 'US'
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-06-19",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "customCampaignId": "",
      "referrerUriDomain": "Universal Client Store",
      "channelType": "Store Traffic",
      "storeClient": "SFC",
      "deviceType": "PC",
      "market": "US",
      "clickCount": 13,
      "conversionCount": 0
    },
    {
      "date": "2022-06-20",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "customCampaignId": "",
      "referrerUriDomain": "Universal Client Store",
      "channelType": "Store Traffic",
      "storeClient": "SFC",
      "deviceType": "PC",
      "market": "US",
      "clickCount": 6,
      "conversionCount": 0
    },
    {
      "date": "2022-06-21",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "customCampaignId": "",
      "referrerUriDomain": "Universal Client Store",
      "channelType": "Store Traffic",
      "storeClient": "SFC",
      "deviceType": "PC",
      "market": "US",
      "clickCount": 4,
      "conversionCount": 0
    },
    {
      "date": "2022-06-22",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "customCampaignId": "",
      "referrerUriDomain": "Universal Client Store",
      "channelType": "Store Traffic",
      "storeClient": "SFC",
      "deviceType": "PC",
      "market": "US",
      "clickCount": 4,
      "conversionCount": 0
    }
  ],
}
```

```
],  
  "@nextLink": "",  
  "TotalCount": 4  
}
```

Related topics

- [Acquisitions report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get app acquisitions](#)

Get add-on acquisitions

Article • 01/04/2023

Use this method in the Microsoft Store analytics API to get aggregate acquisition data for add-ons for your app in JSON format during a given date range and other optional filters. This information is also available in the [Add-on acquisitions report](#) in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappacquisitions</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

The *applicationId* or *inAppProductId* parameter is required. To retrieve acquisition data for all add-ons registered to the app, specify the *applicationId* parameter. To retrieve acquisition data for a single add-on, specify the *inAppProductId* parameter. If you specify both, the *applicationId* parameter is ignored.

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve add-on acquisition data.	Yes
inAppProductId	string	The Store ID of the add-on for which you want to retrieve acquisition data.	Yes
startDate	date	The start date in the date range of add-on acquisition data to retrieve. The default is the current date.	No
endDate	date	The end date in the date range of add-on acquisition data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. For more information, see the filter fields section below.	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day , week , or month . If unspecified, the default is day .	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values for each add-on acquisition. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following strings: • date • acquisitionType • ageGroup • storeClient • gender • market • osVersion • deviceType • orderName The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: • date • applicationName • inAppProductName • acquisitionType • ageGroup • storeClient • gender • market • osVersion • deviceType • orderName The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • date • applicationId • inAppProductId • acquisitionQuantity The <i>groupby</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupby=ageGroup,market&aggregationLevel=week</i>	No

Filter fields

The *filter* parameter of the request contains one or more statements that filter the rows in the response. Each statement contains a field and value that are associated with the **eq** or **ne** operators, and statements can be combined using **and** or **or**. Here are some example *filter* parameters:

- *filter=market eq 'US' and gender eq 'm'*
- *filter=(market ne 'US') and (gender ne 'Unknown') and (gender ne 'm') and (market ne 'NO') and (ageGroup ne 'greater than 55' or ageGroup ne 'less than 13')*

For a list of the supported fields, see the following table. String values must be surrounded by single quotes in the *filter* parameter.

Fields	Description
acquisitionType	One of the following strings: • free • trial • paid • promotional code • iap
ageGroup	One of the following strings: • less than 13 • 13-17 • 18-24 • 25-34 • 35-44 • 44-55 • greater than 55 • Unknown
storeClient	One of the following strings: • Windows Phone Store (client) • Microsoft Store (client) • Microsoft Store (web) • Volume purchase by organizations • Other
gender	One of the following strings: • m • f • Unknown

Fields	Description
market	A string that contains the ISO 3166 country code of the market where the acquisition occurred.
osVersion	One of the following strings: • Windows Phone 7.5 • Windows Phone 8 • Windows Phone 8.1 • Windows Phone 10 • Windows 8 • Windows 8.1 • Windows 10 • Windows 11 • Unknown
deviceType	One of the following strings: • PC • Phone • Console-Xbox One • Console-Xbox Series X • IoT • Holographic • Unknown
orderName	A string that specifies the name of the order for the promotional code that was used to acquire the add-on (this only applies if the user acquired the add-on by redeeming a promotional code).

Request example

The following examples demonstrates several requests for getting add-on acquisition data. Replace the *inAppProductId* and *applicationId* values with the appropriate Store ID for your add-on or app.

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappacquisitions?
inAppProductId=9NBLGGGZ5QDR&startDate=1/1/2015&endDate=2/1/2015&top=10&skip=
0 HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappacquisitions?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2015&endDate=2/1/2015&top=10&skip=0
HTTP/1.1
```


Authorization: Bearer <your access token>

GET

https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappacquisitions?
inAppProductId=9NBLGGGZ5QDR&startDate=1/1/2015&endDate=7/3/2015&top=100&skip
=0&filter=market ne 'US' and gender ne 'Unknown' and gender ne 'm' and
market ne 'NO' and ageGroup ne '>55' HTTP/1.1

Authorization: Bearer <your access token>

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate add-on acquisition data. For more information about the data in each object, see the add-on acquisition values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of add-on acquisition data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Add-on acquisition values

Elements in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the acquisition data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
inAppProductId	string	The Store ID of the add-on for which you are retrieving acquisition data.
inAppProductName	string	The display name of the add-on. This value only appears in the response data if the <i>aggregationLevel</i> parameter is set to day , unless you specify the inAppProductName field in the <i>groupby</i> parameter.

Value	Type	Description
applicationId	string	The Store ID of the app for which you want to retrieve add-on acquisition data.
applicationName	string	The display name of the app.
deviceType	string	The type of device that completed the acquisition. For a list of the supported strings, see the filter fields section above.
orderId	string	The name of the order.
storeClient	string	The version of the Store where the acquisition occurred. For a list of the supported strings, see the filter fields section above.
osVersion	string	The OS version on which the acquisition occurred. For a list of the supported strings, see the filter fields section above.
market	string	The ISO 3166 country code of the market where the acquisition occurred.
gender	string	The gender of the user who made the acquisition. For a list of the supported strings, see the filter fields section above.
ageGroup	string	The age group of the user who made the acquisition. For a list of the supported strings, see the filter fields section above.
acquisitionType	string	The type of acquisition (free, paid, and so on). For a list of the supported strings, see the filter fields section above.
acquisitionQuantity	integer	The number of acquisitions that occurred.

Request and Response example

The following code snippet demonstrates an example request and JSON response body for those request.

Sample Request

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappacquisitions?
applicationId=9NBLGGGZ5QDR
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "applicationId": "9NBLGGGZ5QDR",
      "inAppProductName": "Deluxe Collector's Edition",
      "addonProductId": "9NBLGGAAGZDQ",
      "date": "2022-07-29",
      "acquisitionQuantity": 1,
      "purchasePriceUSDAmount": 18.12,
      "purchasePriceLocalAmount": 18.12,
      "purchaseTaxUSDAmount": 1.13,
      "purchaseTaxLocalAmount": 1.13
    },
    {
      "applicationId": "9NBLGGGZ5QDR",
      "inAppProductName": "Episode 4",
      "addonProductId": "9NAAAAAAAAAAQ",
      "date": "2017-01-07",
      "acquisitionQuantity": 1,
      "purchasePriceUSDAmount": 4.147206,
      "purchasePriceLocalAmount": 3.99,
      "purchaseTaxUSDAmount": 0.686004,
      "purchaseTaxLocalAmount": 0.66
    },
    {
      "applicationId": "9NBLGGGZ5QDR",
      "inAppProductName": "Deluxe Collector's Edition",
      "addonProductId": "9NALGGGZ5QDQ",
      "date": "2018-04-01",
      "acquisitionQuantity": 1,
      "purchasePriceUSDAmount": 1.99,
      "purchasePriceLocalAmount": 1.99,
      "purchaseTaxUSDAmount": 0.0,
      "purchaseTaxLocalAmount": 0.0
    },
    {
      "applicationId": "9NBLGGGZ5QDR",
      "inAppProductName": "Strategy Guide Episode 4",
      "addonProductId": "9NBLGGGZ5QDQ",
      "date": "2021-11-25",
      "acquisitionQuantity": 1,
      "purchasePriceUSDAmount": 1.31902922876179,
      "purchasePriceLocalAmount": 150.0,
      "purchaseTaxUSDAmount": 0.114315866492689,
      "purchaseTaxLocalAmount": 13.0
    }
  ],
  "TotalCount": 4,
  "DataFreshnessTimestamp": "2022-07-29T05:54:00"
}
```

Related topics

- [Add-on acquisitions report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get add-on conversions by channel](#)
- [Get app acquisitions](#)
- [Get app acquisition funnel data](#)
- [Get app conversions by channel](#)

Get subscription add-on acquisitions

Article • 01/04/2023

Use this method in the Microsoft Store analytics API to get aggregate acquisition data for add-on subscriptions for your app during a given date range and other optional filters.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/subscriptions</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve subscription add-on acquisition data.	Yes

Parameter	Type	Description	Required
subscriptionProductId	string	The Store ID of the subscription add-on for which you want to retrieve acquisition data. If you do not specify this value, this method returns acquisition data for all subscription add-ons for the specified app.	No
startDate	date	The start date in the date range of subscription add-on acquisition data to retrieve. The default is the current date.	No
endDate	date	The end date in the date range of subscription add-on acquisition data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 100. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=100 and skip=0 retrieves the first 100 rows of data, top=100 and skip=100 retrieves the next 100 rows of data, and so on.	No
filter	string	One or more statements that filter the response body. Each statement can use the eq or ne operators, and statements can be combined using and or or. You can specify the following strings in the filter statements (these correspond to values in the response body): • date • subscriptionProductName • applicationName • skuld • market • deviceType Here is an example <i>filter</i> parameter: <i>filter=date eq '2017-07-08'</i>.	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day , week , or month . If unspecified, the default is day .	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values for each subscription add-on acquisition. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following strings: • date • subscriptionProductName • applicationName • skuld • market • deviceType The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: • date • subscriptionProductName • applicationName • skuld • market • deviceType The <i>groupby</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>groupby=market&aggregationLevel=week</i>	No

Request example

The following examples demonstrates how to get subscription add-on acquisition data. Replace the *applicationId* value with the appropriate Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/subscriptions?
applicationId=9NBLGGGZ5QDR&startDate=2017-07-07&endDate=2017-07-08 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate subscription add-on acquisition data. For more information about the data in each object, see the subscription acquisition values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 100 but there are more than 100 rows of subscription add-on acquisition data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Subscription acquisition values

Elements in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the acquisition data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
subscriptionProductId	string	The Store ID of the subscription add-on for which you are retrieving acquisition data.
subscriptionProductName	string	The display name of the subscription add-on.
applicationId	string	The Store ID of the app for which you are retrieving subscription add-on acquisition data.
applicationName	string	The display name of the app.
skuId	string	The ID of the SKU of the subscription add-on for which you are retrieving acquisition data.
deviceType	string	One of the following strings that specifies the type of device that completed the acquisition: • PC • Phone • Console-Xbox One • Console-Xbox Series X • IoT • Holographic • Unknown

Value	Type	Description
market	string	The ISO 3166 country code of the market where the acquisition occurred.
currencyCode	string	The currency code in ISO 4217 format for gross sales before taxes.
grossSalesBeforeTax	integer	The gross sales in the local currency specified by the <i>currencyCode</i> value.
totalActiveCount	integer	The number of total active subscriptions during the specified time period. This is equivalent to the sum of the <i>goodStandingActiveCount</i> , <i>pendingGraceActiveCount</i> , <i>graceActiveCount</i> , and <i>lockedActiveCount</i> values.
totalChurnCount	integer	The total count of subscriptions that were deactivated during the specified time period. This is equivalent to the sum of the <i>billingChurnCount</i> , <i>nonRenewalChurnCount</i> , <i>refundChurnCount</i> , <i>chargebackChurnCount</i> , <i>earlyChurnCount</i> , and <i>otherChurnCount</i> values.
newCount	integer	The number of new subscription acquisitions during the specified time period, including trials.
renewCount	integer	The number of subscription renewals during the specified time period, including user-initiated renewals and automatic renewals.
goodStandingActiveCount	integer	The number of subscriptions that were active during the specified time period and where the expiration date is $\geq$ the <i>endDate</i> value for the query.
pendingGraceActiveCount	integer	The number of subscriptions that were active during the specified time period but had a billing failure, and where the subscription expiration date is $\geq$ the <i>endDate</i> value for the query.
graceActiveCount	integer	The number of subscriptions that were active during the specified time period but had a billing failure, and where: - The subscription expiration date is $<$ the <i>endDate</i> value for the query. - The end of the grace period is $\geq$ the <i>endDate</i> value.

Value	Type	Description
lockedActiveCount	integer	The number of subscriptions that were in <i>dunning</i> (that is, the subscription is nearing expiration and Microsoft is trying to acquire funds to automatically renew the subscription) during the specified time period, and where: - The subscription expiration date is < the <i>endDate</i> value for the query. - The end of the grace period is <= the <i>endDate</i> value.
billingChurnCount	integer	The number of subscriptions that were deactivated during the specified time period because of a failure to process a billing charge and where the subscriptions were previously in dunning.
nonRenewalChurnCount	integer	The number of subscriptions that were deactivated during the specified time period because they were not renewed.
refundChurnCount	integer	The number of subscriptions that were deactivated during the specified time period because they were refunded.
chargebackChurnCount	integer	The number of subscriptions that were deactivated during the specified time period because of a chargeback.
earlyChurnCount	integer	The number of subscriptions that were deactivated during the specified time period while they were in good standing.
otherChurnCount	integer	The number of subscriptions that were deactivated during the specified time period for other reasons.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/subscriptions?
applicationId=9NBLGGGZ5QDR
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-04-18",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Windows and Doors",
      "grossSalesBeforeTax": 3460656.260391250,
      "totalActiveCount": 20211321,
      "totalChurnCount": 5605,
      "newCount": 3810366,
      "renewCount": 12102044,
      "goodStandingActiveCount": 17893664,
      "pendingGraceActiveCount": 2255792,
      "graceActiveCount": 61833,
      "lockedActiveCount": 32,
      "billingChurnCount": 4,
      "nonRenewalChurnCount": 0,
      "refundChurnCount": 0,
      "chargebackChurnCount": 0,
      "earlyChurnCount": 2717,
      "otherChurnCount": 2884
    },
    {
      "date": "2022-04-18",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Unknown",
      "grossSalesBeforeTax": 2342.580615228,
      "totalActiveCount": 50550,
      "totalChurnCount": 7,
      "newCount": 8312,
      "renewCount": 31446,
      "goodStandingActiveCount": 44047,
      "pendingGraceActiveCount": 6503,
      "graceActiveCount": 0,
      "lockedActiveCount": 0,
      "billingChurnCount": 0,
      "nonRenewalChurnCount": 0,
      "refundChurnCount": 0,
      "chargebackChurnCount": 0,
      "earlyChurnCount": 5,
      "otherChurnCount": 2
    }
  ],
  "TotalCount": 2
}
```

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/subscriptions?
applicationId=9NBLGGGZ5QDR&startDate=12/19/2021&endDate=04/20/2022&top=10&sk
ip=0&orderby=date&groupby=date,subscriptionProductName,applicationName,skuId
,market,deviceType&aggregationLevel=week
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-04-18",
      "subscriptionProductName":
"realms.subscription.monthly.10player.01",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Windows and Doors",
      "skuId": "0100",
      "market": "IT",
      "deviceType": "Console-Xbox One",
      "grossSalesBeforeTax": 0.0,
      "totalActiveCount": 0,
      "totalChurnCount": 0,
      "newCount": 2,
      "renewCount": 0,
      "goodStandingActiveCount": 0,
      "pendingGraceActiveCount": 0,
      "graceActiveCount": 0,
      "lockedActiveCount": 0,
      "billingChurnCount": 0,
      "nonRenewalChurnCount": 0,
      "refundChurnCount": 0,
      "chargebackChurnCount": 0,
      "earlyChurnCount": 0,
      "otherChurnCount": 0
    },
    {
      "date": "2022-04-18",
      "subscriptionProductName":
"realms.subscription.monthly.10player.01",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Windows and Doors",
      "skuId": "0100",
      "market": "NO",
      "deviceType": "Unknown",
      "grossSalesBeforeTax": 0.0,
      "totalActiveCount": 0,
      "totalChurnCount": 0,
      "newCount": 0,
    }
  ]
}
```

```

        "renewCount": 13,
        "goodStandingActiveCount": 0,
        "pendingGraceActiveCount": 0,
        "graceActiveCount": 0,
        "lockedActiveCount": 0,
        "billingChurnCount": 0,
        "nonRenewalChurnCount": 0,
        "refundChurnCount": 0,
        "chargebackChurnCount": 0,
        "earlyChurnCount": 0,
        "otherChurnCount": 0
    },
    {
        "date": "2022-04-18",
        "subscriptionProductName":
"realms.subscription.monthly.10player.02",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Windows and Doors",
        "skuId": "0100",
        "market": "CA",
        "deviceType": "Unknown",
        "grossSalesBeforeTax": 0.0,
        "totalActiveCount": 152,
        "totalChurnCount": 0,
        "newCount": 0,
        "renewCount": 270,
        "goodStandingActiveCount": 133,
        "pendingGraceActiveCount": 19,
        "graceActiveCount": 0,
        "lockedActiveCount": 0,
        "billingChurnCount": 0,
        "nonRenewalChurnCount": 0,
        "refundChurnCount": 0,
        "chargebackChurnCount": 0,
        "earlyChurnCount": 0,
        "otherChurnCount": 0
    }
],
    "TotalCount": 3
}

```

Related topics

- [Add-on acquisitions report](#)
- [Access analytics data using Microsoft Store services](#)

Get add-on conversions by channel

Article • 03/16/2023

Use this method in the Microsoft Store analytics API to get aggregate conversions by channel for an add-on during a given date range and other optional filters.

- A *conversion* means that a customer (signed in with a Microsoft account) has newly obtained a license to your add-on (whether you charged money or you've offered it for free).
- The *channel* is the method in which a customer arrived at your app's listing page (for example, via the Store or a [custom app promotion campaign](#)).

This information is also available in the [Add-on acquisitions report](#) in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappchannelconversions</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve add-on conversion data. An example Store ID is 9WZDNCRFJ3Q8.	Yes
inAppProductId	string	The Store ID of the add-on for which you want to retrieve conversion data.	Yes
startDate	date	The start date in the date range of conversion data to retrieve. The default is 1/1/2016.	No
endDate	date	The end date in the date range of conversion data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the response body. Each statement can use the eq or ne operators, and statements can be combined using and or or. You can specify the following strings in the filter statements. For descriptions, see the conversion values section in this article. • applicationName • appType • customCampaignId • referrerUriDomain • channelType • storeClient • deviceType • market Here is an example <i>filter</i> parameter: <i>filter=deviceType eq 'PC'</i>.	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day , week , or month . If unspecified, the default is day .	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values for each conversion. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following strings: • date • applicationName • inAppProductName • appType • customCampaignId • referrerUriDomain • channelType • storeClient • deviceType • market The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: • date • applicationName • inAppProductName • appType • customCampaignId • referrerUriDomain • channelType • storeClient • deviceType • market The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • date • applicationId • inAppProductId • inAppProductName • conversionCount • clickCount The <i>groupby</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>groupby=ageGroup,market&aggregationLevel=week</i>	No

Request example

The following example demonstrates several requests for getting app conversion data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappchannelconversions?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2017&endDate=2/1/2017&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappchannelconversions?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2017&endDate=4/31/2017&skip=0&filter=market eq 'US'
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate conversion data for the add-on. For more information about the data in each object, see the conversion values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10 but there are more than 10 rows of conversion data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Conversion values

Objects in the *Value* array contain the following values.

Value	Type	Description
-------	------	-------------

Value	Type	Description
date	string	The first date in the date range for the conversion data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
inAppProductId	string	The Store ID of the add-on for which you are retrieving conversion data.
inAppProductName	string	The display name of the add-on for which you are retrieving conversion data.
applicationId	string	The Store ID of the app for which you are retrieving conversion data.
applicationName	string	The display name of the app for which you are retrieving conversion data.
appType	string	The type of the product for which you are retrieving conversion data. For this method, the only supported value is Add-On .
customCampaignId	string	The ID string for a custom app promotion campaign that is associated with the app.
referrerUriDomain	string	Specifies the domain where the app listing with the custom app promotion campaign ID was activated.
channelType	string	One of the following strings that specifies the channel for the conversion: • CustomCampaignId • Store Traffic • Other
storeClient	string	The version of the Store where the conversion occurred. Currently, the only supported value is SFC .
deviceType	string	One of the following strings: • PC • Phone • Console-Xbox One • Console-Xbox Series X • IoT • Holographic • Unknown
market	string	The ISO 3166 country code of the market where the conversion occurred.
clickCount	number	The number of customer clicks on your app listing link.

Value	Type	Description
conversionCount	number	The number of customer conversions.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappchannelconversions?
applicationId=9NBLGGGZ5QDR&startDate=12/19/2019&endDate=12/20/2021&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "inAppProductId": "9NN2HW33ZB2G",
      "applicationId": "9NBLGGGZ5QDR",
      "clickCount": 220636,
      "conversionCount": 154
    },
    {
      "inAppProductId": "9PN07J0WC18B",
      "applicationId": "9NBLGGGZ5QDR",
      "clickCount": 277061,
      "conversionCount": 187
    }
  ],
  "@nextLink": "",
  "TotalCount": 2
}
```

Sample Request

syntax

GET

`https://manage.devcenter.microsoft.com/v1.0/my/analytics/inappchannelconversions?`

`applicationId=9NBLGGGZ5QDR&startDate=12/19/2021&endDate=12/20/2021&top=10&skip=0&groupby=date,applicationName,inAppProductName,appType,customCampaignId,referrerUriDomain,channelType,storeClient,deviceType,market`

HTTP/1.1

Authorization: Bearer <your access token>

Sample Response

JSON

```
{
  "Value": [
    {
      "inAppProductId": "9WZDNCRCWW61",
      "inAppProductName": "SeasonPass0",
      "appType": "Add-On",
      "date": "2022-06-21",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "customCampaignId": "mcg_mahjong_othersgames",
      "channelType": "CustomCampaignId",
      "storeClient": "SFW",
      "deviceType": "Unknown",
      "market": "BR",
      "clickCount": 1,
      "conversionCount": 1
    },
    {
      "inAppProductId": "9WZDNCRCWW5H",
      "inAppProductName": "OEMFreePurchase",
      "appType": "Add-On",
      "date": "2022-07-06",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "customCampaignId": "mcg_solitaire_othersgames",
      "channelType": "CustomCampaignId",
      "storeClient": "SFW",
      "deviceType": "Unknown",
      "market": "AT",
      "clickCount": 1,
      "conversionCount": 1
    },
    {
      "inAppProductId": "9WZDNCRCWW5Z",
      "inAppProductName": "Episode1Combo",
      "appType": "Add-On",
      "date": "2022-07-09",
```

```

        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "customCampaignId": "vungle",
        "channelType": "CustomCampaignId",
        "storeClient": "SFW",
        "deviceType": "Unknown",
        "market": "CZ",
        "clickCount": 1,
        "conversionCount": 1
    },
    {
        "inAppProductId": "9WZDNCRCWW5H",
        "inAppProductName": "OEMFreePurchase",
        "appType": "Add-On",
        "date": "2022-07-09",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "customCampaignId": "vungle",
        "channelType": "CustomCampaignId",
        "storeClient": "SFW",
        "deviceType": "Unknown",
        "market": "CZ",
        "clickCount": 1,
        "conversionCount": 1
    },
    {
        "inAppProductId": "9WZDNCRCWW4Z",
        "inAppProductName": "Episode1Grandfathered",
        "appType": "Add-On",
        "date": "2022-07-11",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "customCampaignId": "|autosuggest",
        "channelType": "CustomCampaignId",
        "storeClient": "SFW",
        "deviceType": "Unknown",
        "market": "ES",
        "clickCount": 1,
        "conversionCount": 1
    },
    {
        "inAppProductId": "9WZDNCRCWW5W",
        "inAppProductName": "Episode2Combo",
        "appType": "Add-On",
        "date": "2022-07-11",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "customCampaignId": "vungle",
        "channelType": "CustomCampaignId",
        "storeClient": "SFW",
        "deviceType": "Unknown",
        "market": "CZ",
        "clickCount": 1,
        "conversionCount": 1
    },

```

```

{
  "inAppProductId": "9WZDNCRCWW4P",
  "inAppProductName": "SeasonPass24",
  "appType": "Add-On",
  "date": "2022-07-12",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "customCampaignId": "vungle",
  "channelType": "CustomCampaignId",
  "storeClient": "SFW",
  "deviceType": "Unknown",
  "market": "CZ",
  "clickCount": 1,
  "conversionCount": 1
},
{
  "inAppProductId": "9WZDNCRCWW5H",
  "inAppProductName": "OEMFreePurchase",
  "appType": "Add-On",
  "date": "2022-07-13",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "customCampaignId": "9wzdnrcrfjbd8",
  "channelType": "CustomCampaignId",
  "storeClient": "SFW",
  "deviceType": "Unknown",
  "market": "CA",
  "clickCount": 1,
  "conversionCount": 1
},
{
  "inAppProductId": "9WZDNCRCWW61",
  "inAppProductName": "SeasonPass0",
  "appType": "Add-On",
  "date": "2022-07-17",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "customCampaignId": "scom-web-store",
  "channelType": "CustomCampaignId",
  "storeClient": "SFW",
  "deviceType": "Unknown",
  "market": "US",
  "clickCount": 1,
  "conversionCount": 1
}
],
"@nextLink": "",
"TotalCount": 9
}

```

Related topics

- [Add-on acquisitions report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get add-on acquisitions](#)

Get insights data

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get insights data related to acquisitions, health, and usage metrics for an app during a given date range and other optional filters. This information is also available in the [Insights report](#) in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/insights</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve insights data. If you do not specify this parameter, the response body will contain insights data for all apps registered to your account.	No

Parameter	Type	Description	Required
startDate	date	The start date in the date range of insights data to retrieve. The default is 30 days before the current date.	No
endDate	date	The end date in the date range of insights data to retrieve. The default is the current date.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or. String values must be surrounded by single quotes in the <i>filter</i> parameter. For example, <i>filter=dataType eq 'acquisition'</i>. You can specify the following filter fields: • acquisition • health • usage	Yes

Request example

The following example demonstrates a request for getting insights data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/insights?
applicationId=9NBLGGGZ5QDR&startDate=6/1/2018&endDate=6/15/2018&filter=dataT
ype eq 'acquisition' or dataType eq 'health' HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain insights data for the app. For more information about the data in each object, see the Insight values section below.
TotalCount	int	The total number of rows in the data result for the query.

Insight values

Elements in the *Value* array contain the following values.

Value	Type	Description
applicationId	string	The Store ID of the app for which you are retrieving insights data.
insightDate	string	The date on which we identified the change in a specific metric. This date represents the end of the week in which we detected a significant increase or decrease in a metric compared to the week before that.
dataType	string	One of the following strings that specifies the general analytics area that this insight describes: • acquisition • health • usage
insightDetail	array	One or more InsightDetail values that represent the details for current insight.

InsightDetail values

Value	Type	Description
FactName	string	One of the following values that indicates the metric that the current insight or current dimension describes, based on the dataType value. • For health, this value is always HitCount. • For acquisition, this value is always AcquisitionQuantity. • For usage, this value can be one of the following strings: ◦ DailyActiveUsers ◦ EngagementDurationMinutes ◦ DailyActiveDevices ◦ DailyNewUsers ◦ DailySessionCount
SubDimensions	array	One or more objects that describe a single metric for the insight.
PercentChange	string	The percentage that the metric changed across your entire customer base.
DimensionName	string	The name of the metric described in the current dimension. Examples include EventType , Market , DeviceType , PackageVersion , AcquisitionType , AgeGroup and Gender .

Value	Type	Description
DimensionValue	string	The value of the metric that is described in the current dimension. For example, if DimensionName is EventType , DimensionValue might be crash or hang .
FactValue	string	The absolute value of the metric on the date the insight was detected.
Direction	string	The direction of the change (Positive or Negative).
Date	string	The date on which we identified the change related to the current insight or the current dimension.

ⓘ Note

The Insights changes retrieved will be only for the last 30 days of acquisitions, health, and/or usage data.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/insights?
applicationId=9NBLGGGZ5QDR&startDate=7/12/2022&endDate=7/29/2022&filter=data
Type eq 'acquisition' or dataType eq 'health'
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "id":
        "8cdb672c7893bd33a3dec48ededdc676602a1361f3209ab4f3e0982672fc198f",
      "applicationId": "9NBLGGGZ5QDR",
      "insightDate": "2022-07-27T00:00:00",
      "dataType": "acquisition",
```

```

    "insightDetail": [
      {
        "DimensionName": "AcquisitionType",
        "DimensionValue": "Free",
        "Date": "2022-07-27 00:00:00",
        "FactName": "AcquisitionQuantity",
        "SubDimensions": [
          {
            "DimensionName": "DeviceType",
            "DimensionValue": "Tablet",
            "Date": "2022-07-27 00:00:00",
            "Direction": "Positive",
            "PercentChange": 16.091954022988507,
            "FactName": "AcquisitionQuantity",
            "FactQuantity": 28.0
          }
        ]
      }
    ]
  },
  {
    "id":
"6b8849ecb043c6e5ecdd1c20040c0a371e9ab176eff77f7312b0489e19379225",
    "applicationId": "9NBLGGGZ5QDR",
    "insightDate": "2022-07-26T00:00:00",
    "dataType": "acquisition",
    "insightDetail": [
      {
        "DimensionName": "AcquisitionType",
        "DimensionValue": "Free",
        "Date": "2022-07-26 00:00:00",
        "FactName": "AcquisitionQuantity",
        "SubDimensions": [
          {
            "DimensionName": "DeviceType",
            "DimensionValue": "Tablet",
            "Date": "2022-07-26 00:00:00",
            "Direction": "Positive",
            "PercentChange": 28.048780487804876,
            "FactName": "AcquisitionQuantity",
            "FactQuantity": 30.0
          }
        ]
      }
    ]
  },
  {
    "id":
"93115e855fec507385bab17251f49c33bcbc1b62c603e5c7863e327ba94bf160",
    "applicationId": "9NBLGGGZ5QDR",
    "insightDate": "2022-07-20T00:00:00",
    "dataType": "acquisition",
    "insightDetail": [
      {
        "DimensionName": "AcquisitionType",

```

```

        "DimensionValue": "Free",
        "Date": "2022-07-20 00:00:00",
        "FactName": "AcquisitionQuantity",
        "SubDimensions": [
            {
                "DimensionName": "Market",
                "DimensionValue": "GB",
                "Date": "2022-07-20 00:00:00",
                "Direction": "Negative",
                "PercentChange": 3.3035714285714284,
                "FactName": "AcquisitionQuantity",
                "FactQuantity": 158.0
            }
        ]
    },
    {
        "id":
"4814abe710042a2798b453d8821909c246c389dde814e6678da7189211410604",
        "applicationId": "9NBLGGGZ5QDR",
        "insightDate": "2022-07-24T00:00:00",
        "dataType": "acquisition",
        "insightDetail": [
            {
                "DimensionName": "AcquisitionType",
                "DimensionValue": "Free",
                "Date": "2022-07-24 00:00:00",
                "FactName": "AcquisitionQuantity",
                "SubDimensions": [
                    {
                        "DimensionName": "Market",
                        "DimensionValue": "DO",
                        "Date": "2022-07-24 00:00:00",
                        "Direction": "Negative",
                        "PercentChange": 13.533834586466165,
                        "FactName": "AcquisitionQuantity",
                        "FactQuantity": 8.0
                    }
                ]
            }
        ]
    },
    {
        "id":
"7941070bb17904f3ef4e19de9659110cb52e18ecfb637ad724e2da749445a860",
        "applicationId": "9NBLGGGZ5QDR",
        "insightDate": "2022-07-21T00:00:00",
        "dataType": "acquisition",
        "insightDetail": [
            {
                "DimensionName": "AcquisitionType",
                "DimensionValue": "Free",
                "Date": "2022-07-21 00:00:00",
                "FactName": "AcquisitionQuantity",

```