

```

        "SubDimensions": [
            {
                "DimensionName": "Market",
                "DimensionValue": "AT",
                "Date": "2022-07-21 00:00:00",
                "Direction": "Positive",
                "PercentChange": 0.0,
                "FactName": "AcquisitionQuantity",
                "FactQuantity": 17.0
            }
        ]
    },
    {
        "DimensionName": "AcquisitionType",
        "DimensionValue": "Free",
        "Date": "2022-07-21 00:00:00",
        "FactName": "AcquisitionQuantity",
        "SubDimensions": [
            {
                "DimensionName": "Market",
                "DimensionValue": "SE",
                "Date": "2022-07-21 00:00:00",
                "Direction": "Negative",
                "PercentChange": 21.686746987951807,
                "FactName": "AcquisitionQuantity",
                "FactQuantity": 5.0
            }
        ]
    }
]
},
{
    "id":
"55905f5458617b65669eb115cc28ebd7296841bd2ff3f8e2546ade1d5e93f68d",
    "applicationId": "9NBLGGGZ5QDR",
    "insightDate": "2022-07-13T00:00:00",
    "dataType": "acquisition",
    "insightDetail": [
        {
            "DimensionName": "AcquisitionType",
            "DimensionValue": "Free",
            "Date": "2022-07-13 00:00:00",
            "FactName": "AcquisitionQuantity",
            "SubDimensions": [
                {
                    "DimensionName": "Market",
                    "DimensionValue": "LK",
                    "Date": "2022-07-13 00:00:00",
                    "Direction": "Negative",
                    "PercentChange": 11.111111111111111,
                    "FactName": "AcquisitionQuantity",
                    "FactQuantity": 9.0
                }
            ]
        }
    ]
}

```

```

    ]
  },
  {
    "id":
"9ce9317bf4d0f903de51a49d00a07cf4b4a8ac4457fd1e2886493bd38ceac0b7",
    "applicationId": "9NBLGGGZ5QDR",
    "insightDate": "2022-07-19T00:00:00",
    "dataType": "acquisition",
    "insightDetail": [
      {
        "DimensionName": "Acquisition",
        "DimensionValue": "Free",
        "Date": "2022-07-19 00:00:00",
        "Direction": "Negative",
        "PercentChange": 12.188725230475788,
        "FactName": "AcquisitionQuantity",
        "FactQuantity": 2470,
        "SubDimensions": []
      }
    ]
  }
],
"TotalCount": 7
}

```

Related topics

- [Insights report](#)
- [Access analytics data using Microsoft Store services](#)

Get app ratings

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get aggregate ratings data in JSON format for a given date range and other optional filters. This information is also available in the [Reviews report](#) in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/ratings</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve ratings data.	Yes

Parameter	Type	Description	Required
startDate	date	The start date in the date range of ratings data to retrieve. The default is the current date.	No
endDate	date	The end date in the date range of ratings data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. For more information, see the filter fields section below.	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day , week , or month . If unspecified, the default is day .	No
orderby	string	A statement that orders the result data values for each rating. The syntax is <i>orderby=field [order],field [order],...</i>. The <i>field</i> parameter can be one of the following strings: • date • osVersion • market • deviceType • isRevised The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No

Parameter	Type	Description	Required
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: • date • applicationName • market • osVersion • deviceType • isRevised The returned data rows will contain the fields specified in the <i>groupBy</i> parameter as well as the following: • date • applicationId • fiveStars • fourStars • threeStars • twoStars • oneStar The <i>groupBy</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupBy=osVersion,market&aggregationLevel=week</i>	No

Filter fields

The *filter* parameter of the request contains one or more statements that filter the rows in the response. Each statement contains a field and value that are associated with the **eq** or **ne** operators, and statements can be combined using **and** or **or**.

Here is an example *filter* string: *filter=market eq 'US' and deviceType eq 'phone' and isRevised eq true*

For a list of the supported fields, see the following table. String values must be surrounded by single quotes in the *filter* parameter.

Fields	Description
market	A string that contains the ISO 3166 country code of the market where your app was rated.

Fields	Description
osVersion	One of the following strings: - Windows Phone 7.5 - Windows Phone 8 - Windows Phone 8.1 - Windows Phone 10 - Windows 8 - Windows 8.1 - Windows 10 - Windows 11 - Unknown
deviceType	One of the following strings: - PC - Phone - Console-Xbox One - Console-Xbox Series X - IoT - Holographic - Unknown
isRevised	Specify true to filter for ratings that have been revised; otherwise false .

Request example

The following examples demonstrate several requests for getting ratings data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/ratings?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2015&endDate=2/1/2015&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>

GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/ratings?
applicationId=9NBLGGGZ5QDR&startDate=8/1/2015&endDate=8/31/2015&skip=0&filter=market eq 'US' and deviceType eq 'phone'
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate ratings data. For more information about the data in each object, see the rating values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of ratings data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Rating values

Elements in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the ratings data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
applicationId	string	The Store ID of the app for which you are retrieving ratings data.
applicationName	string	The display name of the app.
market	string	The ISO 3166 country code of the market where the rating was submitted.
osVersion	string	The OS version on which the rating was submitted. For a list of the supported strings, see the filter fields section above.
deviceType	string	The type of device on which the rating was submitted. For a list of the supported strings, see the filter fields section above.
isRevised	Boolean	The value true indicates that the rating was revised; otherwise false .
oneStar	number	The number of one-star ratings.
twoStars	number	The number of two-star ratings.
threeStars	number	The number of three-star ratings.
fourStars	number	The number of four-star ratings.
fiveStars	number	The number of five-star ratings.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/ratings?
applicationId=9NBLGGGZ5QDR
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2012-09-01",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "oneStar": 1,
      "twoStars": 0,
      "threeStars": 0,
      "fourStars": 1,
      "fiveStars": 3
    },
    {
      "date": "2012-09-02",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "oneStar": 3,
      "twoStars": 0,
      "threeStars": 1,
      "fourStars": 2,
      "fiveStars": 17
    },
    {
      "date": "2012-09-03",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "oneStar": 1,
      "twoStars": 1,
      "threeStars": 1,
      "fourStars": 5,

```

```
        "fiveStars": 17
    },
],
    "totalCount": 3
}
```

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/ratings?
applicationId=9NBLGGGZ5QDR&startDate=06/19/2022&endDate=07/20/2022&top=10&skip=0&groupby=date,applicationName,market,osVersion,deviceType,isRevised
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-06-22",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "market": "CL",
      "osVersion": "Windows 11",
      "deviceType": "PC",
      "isRevised": "false",
      "oneStar": 0,
      "twoStars": 0,
      "threeStars": 0,
      "fourStars": 0,
      "fiveStars": 1
    },
    {
      "date": "2022-06-22",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "market": "TR",
      "osVersion": "Windows 11",
      "deviceType": "PC",
      "isRevised": "false",
      "oneStar": 0,
      "twoStars": 0,
      "threeStars": 0,
      "fourStars": 0,
      "fiveStars": 1
    }
  ]
}
```

```
},
{
  "date": "2022-06-29",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "market": "FR",
  "osVersion": "Windows 10",
  "deviceType": "PC",
  "isRevised": "false",
  "oneStar": 0,
  "twoStars": 0,
  "threeStars": 0,
  "fourStars": 1,
  "fiveStars": 0
},
{
  "date": "2022-07-01",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "market": "BR",
  "osVersion": "Windows 10",
  "deviceType": "PC",
  "isRevised": "false",
  "oneStar": 0,
  "twoStars": 0,
  "threeStars": 0,
  "fourStars": 0,
  "fiveStars": 1
},
{
  "date": "2022-07-04",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "market": "ES",
  "osVersion": "Windows 10",
  "deviceType": "PC",
  "isRevised": "false",
  "oneStar": 0,
  "twoStars": 0,
  "threeStars": 0,
  "fourStars": 0,
  "fiveStars": 1
},
{
  "date": "2022-07-06",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "market": "ES",
  "osVersion": "Windows 10",
  "deviceType": "PC",
  "isRevised": "false",
  "oneStar": 0,
  "twoStars": 0,
  "threeStars": 0,
  "fourStars": 0,
```

```
        "fiveStars": 1
    },
    {
        "date": "2022-07-07",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "market": "AE",
        "osVersion": "Windows 10",
        "deviceType": "PC",
        "isRevised": "true",
        "oneStar": 1,
        "twoStars": 0,
        "threeStars": 0,
        "fourStars": 0,
        "fiveStars": 0
    },
    {
        "date": "2022-07-10",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "market": "BR",
        "osVersion": "Windows 10",
        "deviceType": "PC",
        "isRevised": "true",
        "oneStar": 0,
        "twoStars": 0,
        "threeStars": 0,
        "fourStars": 0,
        "fiveStars": 1
    },
    {
        "date": "2022-07-13",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "market": "EG",
        "osVersion": "Windows 10",
        "deviceType": "PC",
        "isRevised": "false",
        "oneStar": 0,
        "twoStars": 0,
        "threeStars": 0,
        "fourStars": 0,
        "fiveStars": 1
    },
    {
        "date": "2022-07-14",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "market": "BR",
        "osVersion": "Windows 10",
        "deviceType": "PC",
        "isRevised": "true",
        "oneStar": 0,
        "twoStars": 0,
        "threeStars": 0,
```

```
        "fourStars": 1,  
        "fiveStars": 0  
    }  
],  
    "TotalCount": 10  
}
```

Related topics

- [Ratings report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get app acquisitions](#)
- [Get add-on acquisitions](#)
- [Get error reporting data](#)
- [Get app reviews](#)

Get app reviews

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get review data in JSON format for a given date range and other optional filters. This information is also available in the [Reviews report](#) in Partner Center.

After you retrieve reviews, you can use the [get response info for app reviews](#) and [submit responses to app reviews](#) methods in the Microsoft Store reviews API to programmatically respond to reviews.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/reviews</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Parameter	Type	Description	Required
-----------	------	-------------	----------

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve review data.	Yes
startDate	date	The start date in the date range of review data to retrieve. The default is the current date.	No
endDate	date	The end date in the date range of review data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. For more information, see the filter fields section below.	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values. The syntax is <i>orderby=field [order],field [order],...</i>. The <i>field</i> parameter can be one of the following strings: • date • osVersion • market • deviceType • isRevised • packageVersion • deviceModel • productFamily • deviceScreenResolution • isTouchEnabled • reviewerName • reviewTitle • reviewText • helpfulCount • notHelpfulCount • responseDate • responseText • deviceRAM • deviceStorageCapacity • rating The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No

Filter fields

The *filter* parameter of the request contains one or more statements that filter the rows in the response. Each statement contains a field and value that are associated with the **eq** or **ne** operators, and some fields also support the **contains**, **gt**, **lt**, **ge**, and **le** operators. Statements can be combined using **and** or **or**.

Here is an example *filter* string: *filter=contains(reviewText,'great') and contains(reviewText,'ads') and deviceRAM lt 2048 and market eq 'US'*

For a list of the supported fields and support operators for each field, see the following table. String values must be surrounded by single quotes in the *filter* parameter.

Fields	Supported operators	Description
market	eq, ne	A string that contains the ISO 3166 country code of the device market.
osVersion	eq, ne	One of the following strings: • Windows Phone 7.5 • Windows Phone 8 • Windows Phone 8.1 • Windows Phone 10 • Windows 8 • Windows 8.1 • Windows 10 • Windows 11 • Unknown
deviceType	eq, ne	One of the following strings: • PC • Phone • Console-Xbox One • Console-Xbox Series X • IoT • Holographic • Unknown
isRevised	eq, ne	Specify true to filter for reviews that have been revised; otherwise false .
packageVersion	eq, ne	The version of the app package that was reviewed.
deviceModel	eq, ne	The type of device on which the app was reviewed.
productFamily	eq, ne	One of the following strings: • PC • Tablet • Phone • Wearable • Server • Collaborative • Other
deviceRAM	eq, ne, gt, lt, ge, le	The physical RAM, in MB.
deviceScreenResolution	eq, ne	The device screen resolution in the format " <i>width x height</i> ".

Fields	Supported operators	Description
deviceStorageCapacity	eq, ne, gt, lt, ge, le	The capacity of the primary storage disk, in GB.
isTouchEnabled	eq, ne	Specify true to filter for touch-enabled devices; otherwise false .
reviewerName	eq, ne	The reviewer name.
rating	eq, ne, gt, lt, ge, le	The app rating, in stars.
reviewTitle	eq, ne, contains	The title of the review.
reviewText	eq, ne, contains	The text contents of the review.
helpfulCount	eq, ne	The number of times the review was marked helpful.
notHelpfulCount	eq, ne	The number of times the review was marked not helpful.
responseDate	eq, ne	The date that the response was submitted.
responseText	eq, ne, contains	The text contents of the response.
id	eq, ne	The ID of the review (this is a GUID).

Request example

The following examples demonstrate several requests for getting review data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/reviews?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2015&endDate=2/1/2015&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/reviews?
applicationId=9NBLGGGZ5QDR&startDate=8/1/2015&endDate=8/31/2015&skip=0&filter=contains(reviewText,'great') and contains(reviewText,'ads') and deviceRAM
lt 2048 and market eq 'US' HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain review data. For more information about the data in each object, see the review values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of reviews data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Review values

Elements in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the review data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
applicationId	string	The Store ID of the app for which you are retrieving review data.
applicationName	string	The display name of the app.
market	string	The ISO 3166 country code of the market where the review was submitted.
osVersion	string	The OS version on which the review was submitted. For a list of the supported strings, see the filter fields section above.
deviceType	string	The type of device on which the review was submitted. For a list of the supported strings, see the filter fields section above.
isRevised	Boolean	The value true indicates that the review was revised; otherwise false .
packageVersion	string	The version of the app package that was reviewed.
deviceModel	string	The type of device on which the app was reviewed.

Value	Type	Description
productFamily	string	The device family name. For a list of the supported strings, see the filter fields section above.
deviceRAM	number	The physical RAM, in MB.
deviceScreenResolution	string	The device screen resolution in the format " <i>width x height</i> ".
deviceStorageCapacity	number	The capacity of the primary storage disk, in GB.
isTouchEnabled	Boolean	The value true indicates that touch is enabled; otherwise false .
reviewerName	string	The reviewer name.
rating	number	The app rating, in stars.
reviewTitle	string	The title of the review.
reviewText	string	The text contents of the review.
helpfulCount	number	The number of times the review was marked helpful.
notHelpfulCount	number	The number of times the review was marked not helpful.
responseDate	string	The date a response was submitted.
responseText	string	The text contents of the response.
id	string	The ID of the review (this is a GUID). You can use this ID in the get response info for app reviews and submit responses to app reviews methods.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/reviews?
applicationId=9WZDNCRFJB4P&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "3/5/2021 12:48:33 PM",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "market": "ES",
      "osVersion": "Windows 10",
      "deviceType": "PC",
      "isRevised": false,
      "packageVersion": "2.5.2.34894",
      "reviewerName": "Jose Antonio",
      "rating": 5,
      "reviewTitle": "Contoso Demo",
      "reviewText": "Un juego fantastico",
      "helpfulCount": 3,
      "notHelpfulCount": 0,
      "id": "b5e27de9-2334-4849-d17d-4eae3e1e7aa9"
    },
    {
      "date": "1/6/2021 8:41:42 AM",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "market": "TR",
      "osVersion": "Windows 10",
      "deviceType": "PC",
      "isRevised": false,
      "packageVersion": "2.5.2.34894",
      "reviewerName": "fef",
      "rating": 5,
      "helpfulCount": 0,
      "notHelpfulCount": 0,
      "id": "f5d2510a-9796-45ee-01e5-6d5cc4550b09"
    }
  ],
  "TotalCount": 2
}
```

Related topics

- [Reviews report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get response info for app reviews](#)
- [Submit responses to app reviews](#)
- [Get app acquisitions](#)

- [Get add-on acquisitions](#)
- [Get error reporting data](#)
- [Get app ratings](#)

Get daily app usage

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get aggregate usage data (not including Xbox multiplayer) in JSON format for an application during a given date range (last 90 days only) and other optional filters. This information is also available in the [Usage report](#) in Partner Center.

Telemetry for Anaheim based PWA apps is collected at Device level. So metrics related to users will not be available for such products. Please refer to the below Usage values section for more details on the validity of fields.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method.
After you obtain an access token, you have 60 minutes to use it before it expires.
After the token expires, you can obtain a new one.

Request

Request syntax

 Expand table

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/usagedaily</code>

Request header

 Expand table

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

 Expand table

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve review data.	Yes
startDate	date	The start date in the date range of review data to retrieve. The default is the current date.	No
endDate	date	The end date in the date range of review data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or. String values must be surrounded by single quotes in the filter parameter. You can specify the following fields from the response body: • market • deviceType • packageVersion	No
orderby	string	A statement that orders the result data values. The syntax is <i>orderby=field [order],field [order],...</i> . The <i>field</i> parameter can be one of the following strings: • date • applicationId • applicationName • market • packageVersion • deviceType • subscriptionName • dailySessionCount • engagementDurationMinutes	No

Parameter	Type	Description	Required
		• <code>dailyActiveUsers</code> • <code>dailyActiveDevices</code> • <code>dailyNewUsers</code> • <code>monthlyActiveUsers</code> • <code>monthlyActiveDevices</code> • <code>monthlyNewUsers</code> • <code>dailyNewDevices</code> • <code>monthlyNewDevices</code> The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	
<code>groupby</code>	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields from the response body: • <code>applicationName</code> • <code>subscriptionName</code> • <code>deviceType</code> • <code>packageVersion</code> • <code>market</code> • <code>date</code> The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • <code>applicationId</code> • <code>subscriptionName</code> • <code>dailySessionCount</code> • <code>engagementDurationMinutes</code> • <code>dailyActiveUsers</code> • <code>dailyActiveDevices</code> • <code>dailyNewUsers</code> • <code>monthlyActiveUsers</code> • <code>monthlyActiveDevices</code> • <code>monthlyNewUsers</code> • <code>dailyNewDevices</code> • <code>monthlyNewDevices</code> The <i>groupby</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupBy=ageGroup,market&aggregationLevel=week</i>	No

Request example

The following example demonstrates a request for getting daily app usage data. Replace the *applicationId* value with the Store ID for your app.

HTTP

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/usagedaily?
applicationId=XXXXXXXXXXXX&startDate=2018-08-10&endDate=2018-08-14 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

[Expand table](#)

Value	Type	Description
Value	array	An array of objects that contain aggregate usage data. For more information about the data in each object, see the following table.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of reviews data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Usage values

Elements in the *Value* array contain the following values.

[Expand table](#)

Value	Type	Description	UWP Availability	Anaheim based PWA Availability	Xbox Availability
date	string	The first date in the date range for the usage data. If the request specified a single	Yes	Yes	Yes

Value	Type	Description	UWP Availability	Anaheim based PWA Availability	Xbox Availability
		day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.			
applicationId	string	The Store ID of the app for which you are retrieving usage data.	Yes	Yes	Yes
applicationName	string	The display name of the app.	Yes	Yes	Yes
deviceType	string	One of the following strings that specifies the type of device where usage occurred: • PC • Phone • Console-Xbox One • Console-Xbox Series X • Tablet • IoT • Server • Holographic • Unknown	Yes	Yes	Yes
packageVersion	string	The version of the package where usage occurred.	Yes	Yes	No
market	string	The ISO 3166 country code of the market where	Yes	Yes	Yes

Value	Type	Description	UWP Availability	Anaheim based PWA Availability	Xbox Availability
		the customer used your app.			
subscriptionName	string	Indicates if usage was through Xbox Game Pass.	Yes	No	No
dailySessionCount	long	The number of user sessions on that day.	Yes	Yes	Yes
engagementDurationMinutes	double	The minutes where users are actively using your app measured by a distinct period of time, starting when the app launches (process start) and ending when it terminates (process end) or after a period of inactivity.	Yes	Yes	Yes
dailyActiveUsers	long	The number of customers using the app that day.	Yes	No	Yes
dailyActiveDevices	long	The number of daily devices used to interact with your app by all users.	Yes	Yes	Yes
dailyNewUsers	long	The number of customers who used your app for the first time that day.	Yes	No	Yes
monthlyActiveUsers	long	The number of customers using the app that month.	Yes	No	Yes

Value	Type	Description	UWP Availability	Anaheim based PWA Availability	Xbox Availability
monthlyActiveDevices	long	The number of devices running your app for a distinct period of time, starting when the app launches (process start) and ending when it terminates (process end) or after a period of inactivity.	Yes	Yes	Yes
monthlyNewUsers	long	The number of customers who used your app for the first time that month.	Yes	No	Yes
dailyNewDevices	long	The number of devices which used the app for the first time that day.	No	Yes	No
monthlyNewDevices	long	The number of devices which used the app for the first time in last 30 days.	No	Yes	No

ⓘ Note

If a field is not valid for a specific product, then the value to those fields will be sent as 0 or null in the response. Computation of new users and new devices is done with the rolling window of 3 years, i.e., if a user/device doesn't use the application for 3 years and above, they will be treated as new user/device after 3 years.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/usagedaily?
applicationId=9NBLGGGZ5QDR
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "deviceType": "All",
      "packageVersion": "All",
      "market": "All",
      "dailySessionCount": 6102,
      "engagementDurationMinutes": 75801.0,
      "dailyActiveUsers": 3866,
      "dailyActiveDevices": 3855,
      "dailyNewUsers": 2041,
      "monthlyActiveUsers": 85206,
      "monthlyActiveDevices": 88995,
      "monthlyNewUsers": 63184,
      "dailyNewDevices": 0,
      "monthlyNewDevices": 0
    }
  ],
  "TotalCount": 1
}
```

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/usagedaily?
applicationId=9NBLGGGZ5QDR&startDate=06/19/2022&endDate=07/20/2022&top=10&sk
ip=0&groupby=applicationName,subscriptionName,deviceType,packageVersion,mark
et,date
```

HTTP/1.1

Authorization: Bearer <your access token>

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-07-11",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "subscriptionName": "null",
      "deviceType": "PC",
      "packageVersion": "1.4.0.17837",
      "market": "BR",
      "dailySessionCount": 1,
      "engagementDurationMinutes": 35.2,
      "dailyActiveUsers": 1,
      "dailyActiveDevices": 1,
      "dailyNewUsers": 0,
      "monthlyActiveUsers": 1,
      "monthlyActiveDevices": 1,
      "monthlyNewUsers": 0,
      "dailyNewDevices": 0,
      "monthlyNewDevices": 0
    },
    {
      "date": "2022-07-04",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "subscriptionName": "null",
      "deviceType": "PC",
      "packageVersion": "2.5.2.34894",
      "market": "AD",
      "dailySessionCount": 1,
      "engagementDurationMinutes": 2.7,
      "dailyActiveUsers": 1,
      "dailyActiveDevices": 1,
      "dailyNewUsers": 0,
      "monthlyActiveUsers": 1,
      "monthlyActiveDevices": 1,
      "monthlyNewUsers": 0,
      "dailyNewDevices": 0,
      "monthlyNewDevices": 0
    },
    {
      "date": "2022-06-24",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
```

```
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "2.5.2.34894",
    "market": "AE",
    "dailySessionCount": 2,
    "engagementDurationMinutes": 2.9,
    "dailyActiveUsers": 1,
    "dailyActiveDevices": 1,
    "dailyNewUsers": 0,
    "monthlyActiveUsers": 2,
    "monthlyActiveDevices": 2,
    "monthlyNewUsers": 0,
    "dailyNewDevices": 0,
    "monthlyNewDevices": 0
  },
  {
    "date": "2022-07-08",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "2.5.2.34894",
    "market": "AE",
    "dailySessionCount": 1,
    "engagementDurationMinutes": 0.5,
    "dailyActiveUsers": 1,
    "dailyActiveDevices": 1,
    "dailyNewUsers": 0,
    "monthlyActiveUsers": 2,
    "monthlyActiveDevices": 2,
    "monthlyNewUsers": 0,
    "dailyNewDevices": 0,
    "monthlyNewDevices": 0
  },
  {
    "date": "2022-06-26",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "2.5.2.34894",
    "market": "A0",
    "dailySessionCount": 1,
    "engagementDurationMinutes": 1.2,
    "dailyActiveUsers": 1,
    "dailyActiveDevices": 1,
    "dailyNewUsers": 0,
    "monthlyActiveUsers": 1,
    "monthlyActiveDevices": 1,
    "monthlyNewUsers": 0,
    "dailyNewDevices": 0,
    "monthlyNewDevices": 0
  },
  {
    "date": "2022-06-19",
```

```
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "2.5.2.34894",
    "market": "AR",
    "dailySessionCount": 1,
    "engagementDurationMinutes": 1.0,
    "dailyActiveUsers": 1,
    "dailyActiveDevices": 1,
    "dailyNewUsers": 0,
    "monthlyActiveUsers": 40,
    "monthlyActiveDevices": 40,
    "monthlyNewUsers": 0,
    "dailyNewDevices": 0,
    "monthlyNewDevices": 0
  },
  {
    "date": "2022-06-20",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "2.5.2.34894",
    "market": "AR",
    "dailySessionCount": 2,
    "engagementDurationMinutes": 10.9,
    "dailyActiveUsers": 2,
    "dailyActiveDevices": 2,
    "dailyNewUsers": 0,
    "monthlyActiveUsers": 42,
    "monthlyActiveDevices": 42,
    "monthlyNewUsers": 0,
    "dailyNewDevices": 0,
    "monthlyNewDevices": 0
  },
  {
    "date": "2022-06-21",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "2.5.2.34894",
    "market": "AR",
    "dailySessionCount": 6,
    "engagementDurationMinutes": 32.8,
    "dailyActiveUsers": 3,
    "dailyActiveDevices": 3,
    "dailyNewUsers": 0,
    "monthlyActiveUsers": 44,
    "monthlyActiveDevices": 43,
    "monthlyNewUsers": 0,
    "dailyNewDevices": 0,
    "monthlyNewDevices": 0
  },
}
```

```

{
  "date": "2022-06-22",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "subscriptionName": "null",
  "deviceType": "PC",
  "packageVersion": "2.5.2.34894",
  "market": "AR",
  "dailySessionCount": 1,
  "engagementDurationMinutes": 0.1,
  "dailyActiveUsers": 1,
  "dailyActiveDevices": 1,
  "dailyNewUsers": 0,
  "monthlyActiveUsers": 43,
  "monthlyActiveDevices": 42,
  "monthlyNewUsers": 0,
  "dailyNewDevices": 0,
  "monthlyNewDevices": 0
},
{
  "date": "2022-06-23",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "subscriptionName": "null",
  "deviceType": "PC",
  "packageVersion": "2.5.2.34894",
  "market": "AR",
  "dailySessionCount": 2,
  "engagementDurationMinutes": 0.3,
  "dailyActiveUsers": 2,
  "dailyActiveDevices": 2,
  "dailyNewUsers": 0,
  "monthlyActiveUsers": 42,
  "monthlyActiveDevices": 42,
  "monthlyNewUsers": 0,
  "dailyNewDevices": 0,
  "monthlyNewDevices": 0
}
],
"@nextLink": "usagedaily?
applicationId=9NBLGGGZ5QDR&startDate=2022/06/19&endDate=2022/07/21&groupby=a
pplicationName,subscriptionName,deviceType,packageVersion,market,date&top=10
&skip=10",
"TotalCount": 765
}

```

Related topics

- [Access analytics data using Microsoft Store services](#)
- [Get monthly app usage](#)
- [Get app acquisitions](#)

- [Get add-on acquisitions](#)
- [Get error reporting data](#)

Feedback

Was this page helpful?



Yes



No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

Get monthly app usage

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get aggregate usage data (not including Xbox multiplayer) in JSON format for an application during a given date range (last 90 days only) and other optional filters. This information is also available in the [Usage report](#) in Partner Center.

Telemetry for Anaheim based PWA apps is collected at Device level. So metrics related to users will not be available for such products. Please refer to the below Usage values section for more details on the validity of fields.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method.
After you obtain an access token, you have 60 minutes to use it before it expires.
After the token expires, you can obtain a new one.

Request

Request syntax

 Expand table

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/usagemonthly</code>

Request header

 Expand table

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

 Expand table

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve review data.	Yes
startDate	date	The start date in the date range of review data to retrieve. The default is the current date.	No
endDate	date	The end date in the date range of review data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or. String values must be surrounded by single quotes in the filter parameter. You can specify the following fields from the response body: • market • deviceType • packageVersion	No
orderby	string	A statement that orders the result data values. The syntax is <i>orderby=field [order],field [order],...</i> . The <i>field</i> parameter can be one of the following strings: • date • applicationId • applicationName • market • packageVersion • deviceType • subscriptionName • monthlySessionCount • engagementDurationMinutes	No

Parameter	Type	Description	Required
		- monthlyActiveUsers - monthlyActiveDevices - monthlyNewUsers - averageDailyActiveUsers - averageDailyActiveDevices - monthlyNewDevices The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderBy</i> string: <i>orderBy=date,market</i>	
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields from the response body: - applicationName - subscriptionName - deviceType - packageVersion - market - date The returned data rows will contain the fields specified in the <i>groupBy</i> parameter as well as the following: - applicationId - subscriptionName - monthlySessionCount - engagementDurationMinutes - monthlyActiveUsers - monthlyActiveDevices - monthlyNewUsers - averageDailyActiveUsers - averageDailyActiveDevices - monthlyNewDevices The <i>groupBy</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupBy=ageGroup,market&aggregationLevel=week</i>	No

Request example

The following example demonstrates a request for getting monthly app usage data. Replace the *applicationId* value with the Store ID for your app.

HTTP

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/usagemonthly?
applicationId=XXXXXXXXXXXX&startDate=2018-06-01&endDate=2018-07-01 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

 Expand table

Value	Type	Description
Value	array	An array of objects that contain aggregate usage data. For more information about the data in each object, see the following table.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of reviews data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Usage values

Elements in the *Value* array contain the following values.

 Expand table

Value	Type	Description	UWP Availability	Anaheim based PWA Availability	Xbox Availability
date	string	The first date in the date range for the usage data. If the request specified a single day, this value is that date. If the request specified a week, month, or	Yes	Yes	Yes

Value	Type	Description	UWP Availability	Anaheim based PWA Availability	Xbox Availability
		other date range, this value is the first date in that date range.			
applicationId	string	The Store ID of the app for which you are retrieving usage data.	Yes	Yes	Yes
applicationName	string	The display name of the app.	Yes	Yes	Yes
market	string	The ISO 3166 country code of the market where the customer used your app.	Yes	Yes	Yes
packageVersion	string	The version of the package where usage occurred.	Yes	Yes	No
deviceType	string	One of the following strings that specifies the type of device where usage occurred: • PC • Phone • Console-Xbox One • Console-Xbox Series X • Tablet • IoT • Server • Holographic • Unknown	Yes	Yes	Yes
subscriptionName	string	Indicates if usage was through Xbox Game Pass.	Yes	No	No

Value	Type	Description	UWP Availability	Anaheim based PWA Availability	Xbox Availability
monthlySessionCount	long	The number of user sessions during that month.	Yes	Yes	Yes
engagementDurationMinutes	double	The minutes where users are actively using your app measured by a distinct period of time, starting when the app launches (process start) and ending when it terminates (process end) or after a period of inactivity.	Yes	Yes	Yes
monthlyActiveUsers	long	The number of customers using the app that month.	Yes	No	Yes
monthlyActiveDevices	long	The number of devices running your app for a distinct period of time, starting when the app launches (process start) and ending when it terminates (process end) or after a period of inactivity.	Yes	Yes	Yes
monthlyNewUsers	long	The number of customers who used your app for the first time that month.	Yes	No	Yes
averageDailyActiveUsers	double	The average number of	Yes	No	Yes

Value	Type	Description	UWP Availability	Anaheim based PWA Availability	Xbox Availability
		customers using the app on a daily basis.			
averageDailyActiveDevices	double	The average number of devices used to interact with your app by all users on a daily basis.	Yes	Yes	Yes
monthlyNewDevices	long	The number of devices which used the app for the first time in that month.	No	Yes	No

ⓘ Note

If a field is not valid for a specific product, then the value to those fields will be sent as 0 or null in the response. Computation of new users and new devices is done with the rolling window of 3 years, i.e., if a user/device doesn't use the application for 3 years and above, they will be treated as new user/device after 3 years.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/usagemonthly?
applicationId=9NBLGGGZ5QDR
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "deviceType": "All",
      "packageVersion": "All",
      "market": "All",
      "engagementDurationMinutes": 2828568.3,
      "monthlyActiveUsers": 165249,
      "monthlyActiveDevices": 165753,
      "monthlyNewUsers": 95787,
      "monthlySessionCount": 314263,
      "averageDailyActiveUsers": 192.506111111111,
      "averageDailyActiveDevices": 191.199722222222,
      "monthlyNewDevices": 0
    }
  ],
  "TotalCount": 1
}
```

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/usagemonthly?
applicationId=9NBLGGGZ5QDR&startDate=2022-06-01&endDate=2022-07-
01&groupby=applicationName,subscriptionName,deviceType,packageVersion,market
,date&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-06-01",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "subscriptionName": "null",
      "deviceType": "PC",
      "packageVersion": "1.0.0.4957",
      "market": "JP",
      "engagementDurationMinutes": 0.3,

```

```
    "monthlyActiveUsers": 1,
    "monthlyActiveDevices": 1,
    "monthlyNewUsers": 0,
    "monthlySessionCount": 1,
    "averageDailyActiveUsers": 0.03,
    "averageDailyActiveDevices": 0.03,
    "monthlyNewDevices": 0
  },
  {
    "date": "2022-06-01",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "1.0.0.4957",
    "market": "MX",
    "engagementDurationMinutes": 2.7,
    "monthlyActiveUsers": 1,
    "monthlyActiveDevices": 1,
    "monthlyNewUsers": 0,
    "monthlySessionCount": 1,
    "averageDailyActiveUsers": 0.03,
    "averageDailyActiveDevices": 0.03,
    "monthlyNewDevices": 0
  },
  {
    "date": "2022-06-01",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "1.0.0.4957",
    "market": "Unknown",
    "engagementDurationMinutes": 0.1,
    "monthlyActiveUsers": 1,
    "monthlyActiveDevices": 1,
    "monthlyNewUsers": 0,
    "monthlySessionCount": 1,
    "averageDailyActiveUsers": 0.03,
    "averageDailyActiveDevices": 0.03,
    "monthlyNewDevices": 0
  },
  {
    "date": "2022-06-01",
    "applicationId": "9NBLGGGZ5QDR",
    "applicationName": "Contoso Demo",
    "subscriptionName": "null",
    "deviceType": "PC",
    "packageVersion": "1.0.0.4957",
    "market": "US",
    "engagementDurationMinutes": 0.2,
    "monthlyActiveUsers": 1,
    "monthlyActiveDevices": 1,
    "monthlyNewUsers": 0,
    "monthlySessionCount": 1,
```

```
    "averageDailyActiveUsers": 0.03,  
    "averageDailyActiveDevices": 0.03,  
    "monthlyNewDevices": 0  
  },  
  {  
    "date": "2022-06-01",  
    "applicationId": "9NBLGGGZ5QDR",  
    "applicationName": "Contoso Demo",  
    "subscriptionName": "null",  
    "deviceType": "PC",  
    "packageVersion": "2.5.2.34894",  
    "market": "AE",  
    "engagementDurationMinutes": 3.2,  
    "monthlyActiveUsers": 2,  
    "monthlyActiveDevices": 2,  
    "monthlyNewUsers": 0,  
    "monthlySessionCount": 3,  
    "averageDailyActiveUsers": 0.07,  
    "averageDailyActiveDevices": 0.07,  
    "monthlyNewDevices": 0  
  },  
  {  
    "date": "2022-06-01",  
    "applicationId": "9NBLGGGZ5QDR",  
    "applicationName": "Contoso Demo",  
    "subscriptionName": "null",  
    "deviceType": "PC",  
    "packageVersion": "2.5.2.34894",  
    "market": "AO",  
    "engagementDurationMinutes": 1.2,  
    "monthlyActiveUsers": 1,  
    "monthlyActiveDevices": 1,  
    "monthlyNewUsers": 0,  
    "monthlySessionCount": 1,  
    "averageDailyActiveUsers": 0.03,  
    "averageDailyActiveDevices": 0.03,  
    "monthlyNewDevices": 0  
  },  
  {  
    "date": "2022-06-01",  
    "applicationId": "9NBLGGGZ5QDR",  
    "applicationName": "Contoso Demo",  
    "subscriptionName": "null",  
    "deviceType": "PC",  
    "packageVersion": "2.5.2.34894",  
    "market": "AR",  
    "engagementDurationMinutes": 574.7,  
    "monthlyActiveUsers": 39,  
    "monthlyActiveDevices": 39,  
    "monthlyNewUsers": 0,  
    "monthlySessionCount": 53,  
    "averageDailyActiveUsers": 1.43,  
    "averageDailyActiveDevices": 1.43,  
    "monthlyNewDevices": 0  
  },  
}
```

```

{
  "date": "2022-06-01",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "subscriptionName": "null",
  "deviceType": "PC",
  "packageVersion": "2.5.2.34894",
  "market": "AT",
  "engagementDurationMinutes": 5.3,
  "monthlyActiveUsers": 4,
  "monthlyActiveDevices": 4,
  "monthlyNewUsers": 0,
  "monthlySessionCount": 9,
  "averageDailyActiveUsers": 0.17,
  "averageDailyActiveDevices": 0.17,
  "monthlyNewDevices": 0
},
{
  "date": "2022-06-01",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "subscriptionName": "null",
  "deviceType": "PC",
  "packageVersion": "2.5.2.34894",
  "market": "AU",
  "engagementDurationMinutes": 434.7,
  "monthlyActiveUsers": 22,
  "monthlyActiveDevices": 22,
  "monthlyNewUsers": 0,
  "monthlySessionCount": 36,
  "averageDailyActiveUsers": 0.9,
  "averageDailyActiveDevices": 0.9,
  "monthlyNewDevices": 0
},
{
  "date": "2022-06-01",
  "applicationId": "9NBLGGGZ5QDR",
  "applicationName": "Contoso Demo",
  "subscriptionName": "null",
  "deviceType": "PC",
  "packageVersion": "2.5.2.34894",
  "market": "AZ",
  "engagementDurationMinutes": 13.5,
  "monthlyActiveUsers": 1,
  "monthlyActiveDevices": 1,
  "monthlyNewUsers": 0,
  "monthlySessionCount": 1,
  "averageDailyActiveUsers": 0.03,
  "averageDailyActiveDevices": 0.03,
  "monthlyNewDevices": 0
}
],
"TotalCount": 10
}

```

Related topics

- [Access analytics data using Microsoft Store services](#)
 - [Get daily app usage](#)
 - [Get app acquisitions](#)
 - [Get add-on acquisitions](#)
 - [Get error reporting data](#)
-

Feedback

Was this page helpful?

 Yes

 No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

Get error reporting data for your app

Article • 12/12/2024

Use this method in the Microsoft Store analytics API to get aggregate error reporting data for your app in JSON format for a given date range and other optional filters. This method can only retrieve errors that occurred in the last 30 days. This information is also available in the **Failures** section of the [Health report](#) in Partner Center.

You can retrieve additional error information by using the [get error details](#), [get stack trace](#), and [download CAB file](#) methods.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

 Expand table

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/failurehits</code>

Request header

 Expand table

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

 Expand table

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve error reporting data. The Store ID is available on the App identity page in Partner Center. An example Store ID is 9WZDNCRFJ3Q8.	Yes
startDate	date	The start date in the date range of error reporting data to retrieve. The default is the current date. If <i>aggregationLevel</i> is day, week, or month, this parameter should specify a date in the format <code>mm/dd/yyyy</code>. If <i>aggregationLevel</i> is hour, this parameter can specify a date in the format <code>mm/dd/yyyy</code> or a date and time in the format <code>yyyy-mm-dd hh:mm:ss</code>. Note: This method can only retrieve errors that occurred in the last 30 days.	No
endDate	date	The end date in the date range of error reporting data to retrieve. The default is the current date. If <i>aggregationLevel</i> is day, week, or month, this parameter should specify a date in the format <code>mm/dd/yyyy</code>. If <i>aggregationLevel</i> is hour, this parameter can specify a date in the format <code>mm/dd/yyyy</code> or a date and time in the format <code>yyyy-mm-dd hh:mm:ss</code>.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, <code>top=10000</code> and <code>skip=0</code> retrieves the first 10000 rows of data, <code>top=10000</code> and <code>skip=10000</code> retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or . String values must be surrounded by single quotes in the <i>filter</i> parameter. You can specify the following fields from the response body:	No

Parameter	Type	Description	Required
		• <code>applicationName</code> • <code>failureName</code> • <code>failureHash</code> • <code>symbol</code> • <code>osVersion</code> • <code>osRelease</code> • <code>eventType</code> • <code>market</code> • <code>deviceType</code> • <code>packageName</code> • <code>packageVersion</code> • <code>date</code>	
<code>aggregationLevel</code>	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: hour, day, week, or month. If unspecified, the default is day. If you specify week or month, the <i>failureName</i> and <i>failureHash</i> values are limited to 1000 buckets. Note: If you specify hour, you can retrieve error data only from the previous 72 hours. To retrieve error data older than 72 hours, specify day or one of the other aggregation levels.	No
<code>orderby</code>	string	A statement that orders the result data values. The syntax is <code>*orderby=field [order]</code>. The <i>field</i> parameter can be one (and only one) of the following strings: • <code>applicationName</code> • <code>failureName</code> • <code>failureHash</code> • <code>symbol</code> • <code>osVersion</code> • <code>osRelease</code> • <code>eventType</code> • <code>market</code> • <code>deviceType</code> • <code>packageName</code> • <code>packageVersion</code> • <code>date</code> The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <code>orderby=date</code>	No

Parameter	Type	Description	Required
Note: Any parameter must be from the list supported by <i>groupby</i> .			
groupBy	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: - failureName - failureHash - symbol - osVersion - eventType - market - deviceType - packageName - packageVersion The returned data rows will contain the fields specified in the <i>groupBy</i> parameter as well as the following: - date - applicationId - applicationName - deviceCount - eventCount The <i>groupBy</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupBy=failureName,market&aggregationLevel=week</i> Note: The parameters may not contain duplicates.	No

Request example

The following examples demonstrate several requests for getting error reporting data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/failurehits?
applicationId=9NBLGGGZ5QDR&startDate=1/1/2015&endDate=2/1/2015&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/failurehits?
applicationId=9NBLGGGZ5QDR&startDate=8/1/2015&endDate=8/31/2015&skip=0&filter=market eq 'US' and deviceType eq 'phone'
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

 Expand table

Value	Type	Description
Value	array	An array of objects that contain aggregate error reporting data. For more information about the data in each object, see the error values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of errors for the query.
TotalCount	integer	The total number of rows in the data result for the query.

Error values

Elements in the *Value* array contain the following values.

 Expand table

Value	Type	Description
date	string	The first date in the date range for the error data, in the format <code>yyyy-mm-dd</code> . If the request specifies a single day, this value is that date. If the request specifies a longer date range, this value is the first date in that date range. For requests that specify an <i>aggregationLevel</i> value of hour , this value also includes a time value in the format <code>hh:mm:ss</code> .
applicationId	string	The Store ID of the app for which you want to retrieve error data.
applicationName	string	The display name of the app.
failureName	string	The name of the failure, which is made up of four parts: one or more problem classes, an exception/bug check code, the name of the image where the failure occurred, and the associated function name.
failureHash	string	The unique identifier for the error.
symbol	string	The symbol assigned to this error.

Value	Type	Description
osVersion	string	One of the following strings that specifies the OS version on which the error occurred: • Windows Phone 7.5 • Windows Phone 8 • Windows Phone 8.1 • Windows Phone 10 • Windows 8 • Windows 8.1 • Windows 10 • Windows 11 • Unknown
osRelease	string	One of the following strings that specifies the OS release or flighting ring (as a subpopulation within OS version) on which the error occurred. For Windows 11: Version 2110 For Windows 10: • Version 1507 • Version 1511 • Version 1607 • Version 1703 • Version 1709 • Version 1803 • Release Preview • Insider Fast • Insider Slow For Windows Server 1709: • RTM For Windows Server 2016: • Version 1607 For Windows 8.1: • Update 1 For Windows 7: • Service Pack 1 If the OS release or flighting ring is unknown, this field has the value Unknown.

Value	Type	Description
eventType	string	One of the following strings: • crash • hang • memory • jse
market	string	The ISO 3166 country code of the device market.
deviceType	string	One of the following strings that indicates the type of device on which the error occurred: • PC • Phone • Console-Xbox One • Console-Xbox Series X • IoT • Holographic • Unknown
packageName	string	The unique name of the app package that is associated with this error.
packageVersion	string	The version of the app package that is associated with this error.
deviceCount	number	The number of unique devices that correspond to this error for the specified aggregation level.
eventCount	number	The number of events that are attributed to this error for the specified aggregation level.

ⓘ Note

This method can only retrieve errors that occurred in the last 30 days.

Request and Response example

The following code snippet demonstrates an example request and JSON response body for those request.

Sample Request

```
syntax
```

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/failurehits?
applicationId=9NBLGGGZ5QDR&startDate=07/02/2022&endDate=07/20/2022&top=10&sk
ip=0&filter=market eq
'US'&groupby=failureName,failureHash,symbol,osVersion,eventType,market,devic
eType,packageName,packageVersion,osRelease&orderby=date
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-07-21",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "failureName":
"APPLICATION_HANG_BlockedOn_FileIO_Microsoft.Contoso
Demo!CEServices.InternalLiveTileUpdaterRuntime_dfffffff_Microsoft.Contoso
Demo!unknown_error_in_application",
      "failureHash": "c21da75f-ea4d-538b-cfec-73654ef810b9",
      "symbol": "Microsoft.Contoso Demo!unknown_error_in_application",
      "osVersion": "6.3.9600",
      "osRelease": "RTM",
      "osArchitecture": null,
      "eventType": "hang",
      "market": "US",
      "deviceType": "PC",
      "praid": null,
      "packageName": "microsoft.Contoso
Demo_2.5.2.34894_x86__8wekyb3d8bbwe",
      "packageVersion": "2.5.2.34894",
      "ram": null,
      "massStorage": null,
      "cpu": null,
      "cpuManufacturer": null,
      "cpuFamilyName": null,
      "sandboxId": null,
      "deviceCount": 6.0,
      "eventCount": 1.05263157894737
    },
    {
      "date": "2022-07-21",
      "applicationId": "9NBLGGGZ5QDR",
      "applicationName": "Contoso Demo",
      "failureName":
"APPLICATION_HANG_BlockedOn_FileIO_Microsoft.Contoso
Demo!CEServices.InternalLiveTileUpdaterRuntime_dfffffff_Microsoft.Contoso
Demo!unknown_error_in_application",
```

```

        "failureHash": "c21da75f-ea4d-538b-cfec-73654ef810b9",
        "symbol": "Microsoft.Contoso Demo!unknown_error_in_application",
        "osVersion": "6.3.9600",
        "osRelease": "RTM",
        "osArchitecture": null,
        "eventType": "hang",
        "market": "US",
        "deviceType": "Unknown",
        "praid": null,
        "packageName": "microsoft.Contoso
Demo_2.5.2.34894_x86__8wekyb3d8bbwe",
        "packageVersion": "2.5.2.34894",
        "ram": null,
        "massStorage": null,
        "cpu": null,
        "cpuManufacturer": null,
        "cpuFamilyName": null,
        "sandboxId": null,
        "deviceCount": 7.14285714285714,
        "eventCount": 1.05263157894737
    },
    {
        "date": "2022-07-21",
        "applicationId": "9NBLGGGZ5QDR",
        "applicationName": "Contoso Demo",
        "failureName": "APPLICATION_HANG_Microsoft.Contoso
Demo!CEServices.InternalLiveTileUpdaterRuntime_dfffffff_twinapi.appcore.dll!
WaitCoalesced",
        "failureHash": "233e04bb-7a3d-eb28-c316-1120aa9defc0",
        "symbol": "twinapi.appcore.dll!WaitCoalesced",
        "osVersion": "6.3.9600",
        "osRelease": "RTM",
        "osArchitecture": null,
        "eventType": "hang",
        "market": "US",
        "deviceType": "PC",
        "praid": null,
        "packageName": "microsoft.Contoso
Demo_2.5.2.34894_x86__8wekyb3d8bbwe",
        "packageVersion": "2.5.2.34894",
        "ram": null,
        "massStorage": null,
        "cpu": null,
        "cpuManufacturer": null,
        "cpuFamilyName": null,
        "sandboxId": null,
        "deviceCount": 6.0,
        "eventCount": 8.94736842105263
    }
],
    "@nextLink": "failurehits?
applicationId=9NBLGGGZ5QDR&aggregationLevel=day&startDate=2022/07/02&endDate
=2022/07/21&top=10&skip=10&groupby=failureName,failureHash,symbol,osVersion,
eventType,market,deviceType,packageName,packageVersion,osRelease&filter=mark
et eq 'US'&orderby=date",

```

```
"TotalCount": 443  
}
```

Related topics

- [Health report](#)
- [Get details for an error in your app](#)
- [Get the stack trace for an error in your app](#)
- [Download the CAB file for an error in your app](#)
- [Access analytics data using Microsoft Store services](#)
- [Get app acquisitions](#)
- [Get add-on acquisitions](#)
- [Get app ratings](#)
- [Get app reviews](#)

Feedback

Was this page helpful?

 Yes

 No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

Get details for an error in your app

Article • 01/04/2023

Use this method in the Microsoft Store analytics API to get detailed data for a specific error for your app in JSON format. This method can only retrieve details for errors that occurred in the last 30 days. Detailed error data is also available in the **Failures** section of the [Health report](#) in Partner Center.

Before you can use this method, you must first use the [get error reporting data](#) method to retrieve the ID of the error for which you want to get detailed info.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Get the ID of the error for which you want to get detailed info. To get this ID, use the [get error reporting data](#) method and use the **failureHash** value in the response body of that method.

Request

Request syntax

 Expand table

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/failedetails</code>

Request header

 Expand table

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

 Expand table

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve detailed error data. The Store ID is available on the App identity page in Partner Center. An example Store ID is 9WZDNCRFJ3Q8.	Yes
failureHash	string	The unique ID of the error for which you want to get detailed info. To get this value for the error you are interested in, use the get error reporting data method and use the failureHash value in the response body of that method.	Yes
startDate	date	The start date in the date range of detailed error data to retrieve. The default is 30 days before the current date. Note: This method can only retrieve details for errors that occurred in the last 30 days.	No
endDate	date	The end date in the date range of detailed error data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10 and skip=0 retrieves the first 10 rows of data, top=10 and skip=10 retrieves the next 10 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or . String values must be surrounded by single quotes in the <i>filter</i> parameter. You can specify the following fields from the response body: market date	No

Parameter	Type	Description	Required
		• cabId • cabExpirationTime • deviceType • deviceModel • osVersion • osRelease • packageVersion • osBuild	
orderby	string	A statement that orders the result data values. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following strings: • market • date • cabId • cabExpirationTime • deviceType • deviceModel • osVersion • osRelease • packageVersion • osBuild The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No

Request example

The following examples demonstrate several requests for getting detailed error data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/failedetails?
applicationId=9NBLGGGZ5QDR&failureHash=00001111-aaaa-2222-bbbb-
3333cccc4444&startDate=2016-11-05&endDate=2016-11-06&top=10&skip=0 HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/failedetails?
applicationId=9NBLGGGZ5QDR&failureHash=00001111-aaaa-2222-bbbb-
3333cccc4444&startDate=2016-11-05&endDate=2016-11-
06&top=10&skip=0&filter=market eq 'US' and deviceType eq 'Windows.Desktop'
```

HTTP/1.1

Authorization: Bearer <your access token>

Response

Response body

 Expand table

Value	Type	Description
Value	array	An array of objects that contain detailed error data. For more information about the data in each object, see the error detail values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10 but there are more than 10 rows of errors for the query.
TotalCount	integer	The total number of rows in the data result for the query.

Error detail values

Elements in the *Value* array contain the following values.

 Expand table

Value	Type	Description
applicationId	string	The Store ID of the app for which you retrieved detailed error data.
failureHash	string	The unique identifier for the error.
failureName	string	The name of the failure, which is made up of four parts: one or more problem classes, an exception/bug check code, the name of the image where the failure occurred, and the associated function name.
date	string	The first date in the date range for the error data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
cabId	string	The unique ID of the CAB file that is associated with this error.

Value	Type	Description
cabExpirationTime	string	The date and time when the CAB file is expired and can no longer be downloaded, in ISO 8601 format.
market	string	The ISO 3166 country code of the device market.
osBuild	string	The build number of the OS on which the error occurred.
packageVersion	string	The version of the app package that is associated with this error.
deviceModel	string	A string that specifies the model of the device on which the app was running when the error occurred.
osVersion	string	One of the following strings that indicates the OS version on which the error occurred: • Windows Phone 7.5 • Windows Phone 8 • Windows Phone 8.1 • Windows Phone 10 • Windows 8 • Windows 8.1 • Windows 10 • Windows 11 • Unknown
osRelease	string	One of the following strings that specifies the OS release or flighting ring (as a subpopulation within OS version) on which the error occurred. For Windows 11: Version 21H0 For Windows 10: • Version 1507 • Version 1511 • Version 1607 • Version 1703 • Version 1709 • Version 1803 • Release Preview • Insider Fast • Insider Slow For Windows Server 1709: • RTM For Windows Server 2016: • Version 1607