

Value	Type	Description
		For Windows 8.1: • Update 1 For Windows 7: • Service Pack 1 If the OS release or flighting ring is unknown, this field has the value Unknown.
deviceType	string	One of the following strings that specifies the type of the device on which the app was running when the error occurred: • PC • Phone • Console-Xbox One • Console-Xbox Series X • IoT • Holographic • Unknown
cabDownloadable	Boolean	Indicates whether the CAB file is downloadable for this user.

ⓘ Note

This method can only retrieve details for errors that occurred in the last 30 days.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/failedetails?
applicationId=9NBLGGGZ5QDR&failureHash=012345-5dbc9-b12f-c124-
9d9810f05d8b&startDate=2022-06-30&endDate=2022-07-28&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "date": "2022-07-12 00:00:00",
      "cabExpirationTime": "2022-08-16 01:37:00",
      "cabDownloadable": false,
      "applicationId": "9NBLGGGZ5QDR",
      "failureHash": "012345-5dbc9-b12f-c124-9d9810f05d8b",
      "failureName":
"MOAPPLICATION_HANG_cfffffff_Microsoft.Contoso!HANG QUIESCE",
      "cabId": "1180087848576586304",
      "market": "MX",
      "osBuild": "10.0.19043",
      "packageVersion": "2.5.2.34894",
      "deviceModel": "Dell Inc.-Inspiron 15-3567",
      "osVersion": "Windows 10",
      "osRelease": "Version 21H1",
      "osArchitecture": "x64",
      "deviceType": "PC",
      "cpuManufacturer": "Intel",
      "cpuFamilyName": "Core i5",
      "cpuName": "Intel Core i5-7200U CPU @ 2.50GHz",
      "praid": "app",
      "flightRing": "",
      "sandboxId": "retail"
    },
    {
      "date": "2022-07-13 00:00:00",
      "cabExpirationTime": "2022-08-17 13:35:53",
      "cabDownloadable": true,
      "applicationId": "9NBLGGGZ5QDR",
      "failureHash": "012345-5dbc9-b12f-c124-9d9810f05d8b",
      "failureName":
"MOAPPLICATION_HANG_cfffffff_Microsoft.Contoso!HANG QUIESCE",
      "cabId": "2058585545558157474",
      "market": "RO",
      "osBuild": "10.0.22622",
      "packageVersion": "2.5.2.34894",
      "deviceModel": "Dell Inc.-Vostro 5502",
      "osVersion": "Windows 11",
      "osRelease": "External",
      "osArchitecture": "x64",
      "deviceType": "PC",
      "cpuManufacturer": "Intel",
      "cpuFamilyName": "Core i5",
      "cpuName": "11th Gen Intel Core i5-1135G7 @ 2.40GHz",
      "praid": "app",
      "flightRing": "external",
      "sandboxId": "retail"
    },
    {
      "date": "2022-07-14 00:00:00",
```

```

        "cabExpirationTime": "2022-08-18 07:27:06",
        "cabDownloadable": false,
        "applicationId": "9NBLGGGZ5QDR",
        "failureHash": "012345-5dbc9-b12f-c124-9d9810f05d8b",
        "failureName":
"MOAPPLICATION_HANG_cffffffff_Microsoft.Contoso!HANG QUIESCE",
        "cabId": "1940204079766793391",
        "market": "IN",
        "osBuild": "10.0.19044",
        "packageVersion": "2.5.2.34894",
        "deviceModel": "Generic Desktop",
        "osVersion": "Windows 10",
        "osRelease": "Version 21H2",
        "osArchitecture": "x64",
        "deviceType": "PC",
        "cpuManufacturer": "Intel",
        "cpuFamilyName": "Pentium",
        "cpuName": "Intel Pentium CPU G630 @ 2.70GHz",
        "praid": "app",
        "flightRing": "",
        "sandboxId": "retail"
    },
    {
        "date": "2022-07-17 00:00:00",
        "cabExpirationTime": "2022-08-21 10:04:16",
        "cabDownloadable": true,
        "applicationId": "9NBLGGGZ5QDR",
        "failureHash": "012345-5dbc9-b12f-c124-9d9810f05d8b",
        "failureName":
"MOAPPLICATION_HANG_cffffffff_Microsoft.Contoso!HANG QUIESCE",
        "cabId": "1197051093472061859",
        "market": "ES",
        "osBuild": "10.0.22621",
        "packageVersion": "2.5.2.34894",
        "deviceModel": "Microsoft Corporation-Surface Pro 3",
        "osVersion": "Windows 11",
        "osRelease": "External",
        "osArchitecture": "x64",
        "deviceType": "PC",
        "cpuManufacturer": "Intel",
        "cpuFamilyName": "Core i7",
        "cpuName": "Intel Core i7-4650U CPU @ 1.70GHz",
        "praid": "app",
        "flightRing": "external",
        "sandboxId": "retail"
    },
    {
        "date": "2022-07-20 00:00:00",
        "cabExpirationTime": "2022-08-24 12:40:05",
        "cabDownloadable": false,
        "applicationId": "9NBLGGGZ5QDR",
        "failureHash": "012345-5dbc9-b12f-c124-9d9810f05d8b",
        "failureName":
"MOAPPLICATION_HANG_cffffffff_Microsoft.Contoso!HANG QUIESCE",
        "cabId": "1332886311327579782",

```

```
        "market": "RU",
        "osBuild": "6.3.9600",
        "packageVersion": "2.5.2.34894",
        "deviceModel": "ASUSTeK COMPUTER INC.-K75VJ",
        "osVersion": "Windows 8.1",
        "osRelease": "RTM",
        "osArchitecture": "x64",
        "deviceType": "PC",
        "cpuManufacturer": "Intel",
        "cpuFamilyName": "Core i7",
        "cpuName": "Intel Core i7-3630QM CPU @ 2.40GHz",
        "praid": "app",
        "flightRing": "",
        "sandboxId": ""
    }
},
    "TotalCount": 5
}
```

Related topics

- [Health report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get error reporting data](#)
- [Get the stack trace for an error in your app](#)
- [Download the CAB file for an error in your app](#)

Feedback

Was this page helpful?

 Yes

 No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

Get the stack trace for an error in your app

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get the stack trace for an error in your app. This method can only download the stack trace for an app error that occurred in the last 30 days. Stack traces are also available in the **Failures** section of the [Health report](#) in Partner Center.

Before you can use this method, you must first use the [get details for an error in your app](#) method to retrieve the ID of the CAB file that is associated with the error for which you want to retrieve the stack trace.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Get the ID of the CAB file that is associated with the error for which you want to retrieve the stack trace. To get this ID, use the [get details for an error in your app](#) method to retrieve details for a specific error in your app, and use the **cabId** value in the response body of that method.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/stacktrace</code>

Request header

Header	Type	Description
--------	------	-------------

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to get the stack trace. The Store ID is available on the App identity page in Partner Center. An example Store ID is 9WZDNCRFJ3Q8.	Yes
cabId	string	The unique ID of the CAB file that is associated with the error for which you want to retrieve the stack trace. To get this ID, use the get details for an error in your app method to retrieve details for a specific error in your app, and use the cabId value in the response body of that method.	Yes

Request example

The following example demonstrates how to get a stack trace using this method. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/stacktrace?
applicationId=9NBLGGGZ5QDR&cabId=1336373323853 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that each contain one frame of stack trace data. For more information about the data in each object, see the stack trace values section below.

Value	Type	Description
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10 but there are more than 10 rows of errors for the query.
TotalCount	integer	The total number of rows in the data result for the query.

Stack trace values

Elements in the *Value* array contain the following values.

Value	Type	Description
level	string	The frame number that this element represents in the call stack.
image	string	The name of the executable or library image that contains the function that is called in this stack frame.
function	string	The name of the function that is called in this stack frame. This is available only if your app includes symbols for the executable or library.
offset	string	The byte offset of the current instruction relative to the start of the function.

Note

This method can only download the stack trace for an app error that occurred in the last 30 days.

Request and Response example

The following code snippets demonstrates some example request and JSON response body for those request.

Sample Request

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/stacktrace?
applicationId=9NBLGGGZ5QDR&cabId=1234567890123456789
HTTP/1.1
Authorization: Bearer <your access token>
```

Sample Response

JSON

```
{
  "Value": [
    {
      "level": "0",
      "image": "Microsoft.Contoso",
      "function": "HANG_QUIESCE",
      "offset": "0x0000000000000000",
      "isBlamedFrame": true
    },
    {
      "level": "1",
      "image": "unknown.dll",
      "function": "[.ecx]",
      "offset": "0x0000000000000000",
      "isBlamedFrame": false
    },
    {
      "level": "2",
      "image": "ntdll.dll",
      "function": "RtlpHpSegFree",
      "offset": "0x0000000000000000",
      "isBlamedFrame": false
    },
    {
      "level": "3",
      "image": "ntdll.dll",
      "function": "RtlpHpFreeHeap",
      "offset": "0x0000000000000000",
      "isBlamedFrame": false
    },
    {
      "level": "4",
      "image": "ntdll.dll",
      "function": "RtlpFreeHeapInternal",
      "offset": "0x0000000000000000",
      "isBlamedFrame": false
    }
  ],
  "TotalCount": 5
}
```

Related topics

- [Health report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get error reporting data](#)

- [Get details for an error in your app](#)
- [Download the CAB file for an error in your app](#)

Download the CAB file for an error in your app

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to download the CAB file that is associated with a particular error in your app that has been reported to Partner Center. This method can only download the CAB file for an app error that occurred in the last 30 days. CAB file downloads are also available in the **Failures** section of the [Health report](#) in Partner Center.

Before you can use this method, you must first use the [get details for an error in your app](#) method to retrieve the ID of the CAB file you want to download.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Get the ID of the CAB file you want to download. To get this ID, use the [get details for an error in your app](#) method to retrieve details for a specific error in your app, and use the **cabId** value in the response body of that method.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/cabdownload</code>

Request header

Header	Type	Description
--------	------	-------------

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to download a CAB file. The Store ID is available on the App identity page of Partner Center. An example Store ID is 9WZDNCRFJ3Q8.	Yes
cabId	string	The unique ID of the CAB file you want to download. To get this ID, use the get details for an error in your app method to retrieve details for a specific error in your app, and use the cabId value in the response body of that method.	Yes

Request example

The following example demonstrates how to download a CAB file using this method. Replace the *applicationId* and *cabId* parameters with the appropriate values for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/cabdownload?
applicationId=9NBLGGGZ5QDR&cabId=1336373323853 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

This method returns a 302 (redirect) response code, and the **Location** header in the response is assigned to the shared access signature (SAS) URI of the CAB file. The caller is redirected to this URI to automatically download the CAB file.

Related topics

- [Health report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get error reporting data](#)

- [Get details for an error in your app](#)
- [Get the stack trace for an error in your app](#)

Get ad performance data

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get aggregate ad performance data for your applications during a given date range and other optional filters. This method returns the data in JSON format.

This method returns the same data that is provided by the [Advertising performance report](#) in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

For more information, see [Access analytics data using Microsoft Store services](#).

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/adsperformance</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

To retrieve ad performance data for a specific app, use the *applicationId* parameter. To retrieve ad performance data for all apps that are associated with your developer account, omit the *applicationId* parameter.

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve ad performance data.	No
startDate	date	The start date in the date range of ad performance data to retrieve, in the format YYYY/MM/DD. The default is the current date minus 30 days.	No
endDate	date	The end date in the date range of ad performance data to retrieve, in the format YYYY/MM/DD. The default is the current date minus one day.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. For more information, see the filter fields section below.	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day , week , or month . If unspecified, the default is day .	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following strings: • date • market • deviceType • adUnitId The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: • applicationId • applicationName • date • accountCurrencyCode • market • deviceType • adUnitName • adUnitId • pubCenterAppName • adProvider The <i>groupBy</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupBy=applicationId&aggregationLevel=week</i>	No

Filter fields

The *filter* parameter of the request body contains one or more statements that filter the rows in the response. Each statement contains a field and value that are associated with the **eq** or **ne** operators, and statements can be combined using **and** or **or**. Here is an example *filter* parameter:

- *filter=market eq 'US' and deviceType eq 'phone'*

For a list of the supported fields, see the following table. String values must be surrounded by single quotes in the *filter* parameter.

Field	Description
-------	-------------

Field	Description
market	A string that contains the ISO 3166 country code of the market where the ads were served.
deviceType	One of the following strings: PC/Tablet or Phone .
adUnitId	A string that specifies an ad unit ID to apply to the filter.
pubCenterAppName	A string that specifies the pubCenter name for the current app to apply to the filter.
adProvider	A string that specifies an ad provider name to apply to the filter.
date	A string that specifies a date in YYYY/MM/DD format to apply to the filter.

Request example

The following example demonstrates several requests for getting ad performance data. Replace the *applicationId* value with the Store ID for your app.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/adsperformance?
applicationId=9NBLGGH4R315&startDate=1/1/2015&endDate=2/1/2015&top=10&skip=0
HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/adsperformance?
applicationId=9NBLGGH4R315&startDate=8/1/2015&endDate=8/31/2015&skip=0&$filter=market eq 'US' and deviceType eq 'phone' eq 'US'; and gender eq 'm'
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate ad performance data. For more information about the data in each object, see the ad performance values section below.

Value	Type	Description
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 5 but there are more than 5 items of data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Ad performance values

Elements in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the ad performance data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
applicationId	string	The Store ID of the app for which you are retrieving ad performance data.
applicationName	string	The display name of the app.
adUnitId	string	The ID of the ad unit.
adUnitName	string	The name of the ad unit, as specified by the developer in Partner Center.
adProvider	string	The name of the ad provider
deviceType	string	The type of device on which the ads were served. For a list of the supported strings, see the filter fields section above.
market	string	The ISO 3166 country code of the market where the ads were served.
accountCurrencyCode	string	The currency code for the account.
pubCenterAppName	string	The name of the pubCenter app that is associated with the app in Partner Center.
adProviderRequests	int	The number of ad requests for the specified ad provider.
impressions	int	The number of ad impressions.
clicks	int	The number of ad clicks.

Value	Type	Description
revenueInAccountCurrency	number	The revenue, in the currency for the country/region of the account.
requests	int	The number of ad requests.

Response example

The following example demonstrates an example JSON response body for this request.

JSON

```
{
  "Value": [
    {
      "date": "2015-03-09",
      "applicationId": "9NBLGGH4R315",
      "applicationName": "Contoso Demo",
      "market": "US",
      "deviceType": "phone",
      "adUnitId": "10765920",
      "adUnitName": "TestAdUnit",
      "revenueInAccountCurrency": 10.0,
      "impressions": 1000,
      "requests": 10000,
      "clicks": 1,
      "accountCurrencyCode": "USD"
    },
    {
      "date": "2015-03-09",
      "applicationId": "9NBLGGH4R315",
      "applicationName": "Contoso Demo",
      "market": "US",
      "deviceType": "phone",
      "adUnitId": "10795110",
      "adUnitName": "TestAdUnit2",
      "revenueInAccountCurrency": 20.0,
      "impressions": 2000,
      "requests": 20000,
      "clicks": 3,
      "accountCurrencyCode": "USD"
    }
  ],
  "@nextLink": "adsperformance?applicationId=9NBLGGH4R315&aggregationLevel=week&startDate=2015/03/01&endDate=2016/02/01&top=2&skip=2",
  "TotalCount": 191753
}
```

Related topics

- [Advertising performance report](#)
- [Access analytics data using Microsoft Store services](#)

Get ad campaign performance data

Article • 03/16/2023

Use this method in the Microsoft Store analytics API to get an aggregate summary of promotional ad campaign performance data for your applications during a given date range and other optional filters. This method returns the data in JSON format.

This method returns the same data that is provided by the [Ad campaign report](#) in Partner Center. For more information about ad campaigns, see [Create an ad campaign for your app](#).

To create, update, or retrieve details for ad campaigns, you can use the [Manage ad campaigns](#) methods in the [Microsoft Store promotions API](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/promotion</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

To retrieve ad campaign performance data for a specific app, use the *applicationId* parameter. To retrieve ad performance data for all apps that are associated with your developer account, omit the *applicationId* parameter.

Parameter	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve ad campaign performance data.	No
startDate	date	The start date in the date range of ad campaign performance data to retrieve, in the format YYYY/MM/DD. The default is the current date minus 30 days.	No
endDate	date	The end date in the date range of ad campaign performance data to retrieve, in the format YYYY/MM/DD. The default is the current date minus one day.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. The only supported filter is campaignId . Each statement can use the eq or ne operators, and statements can be combined using and or or . Here is an example <i>filter</i> parameter: <code>filter=campaignId eq '100023'</code> .	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day , week , or month . If unspecified, the default is day .	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values for the ad campaign performance data. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following strings: • date • campaignId The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,campaignId</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: • campaignId • applicationId • date • currencyCode The <i>groupby</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupby=applicationId&aggregationLevel=week</i>	No

Request example

The following example demonstrates several requests for getting ad campaign performance data.

syntax

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/promotion?
aggregationLevel=week&groupby=applicationId,campaignId,date HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET https://manage.devcenter.microsoft.com/v1.0/my/analytics/promotion?
applicationId=9NBLGGH0XK8Z&startDate=2015/1/20&endDate=2016/8/31&skip=0&filter=campaignId eq '31007388' HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate ad campaign performance data. For more information about the data in each object, see the campaign performance object section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 5 but there are more than 5 items of data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Campaign performance object

Elements in the *Value* array contain the following values.

Value	Type	Description
date	string	The first date in the date range for the ad campaign performance data. If the request specified a single day, this value is that date. If the request specified a week, month, or other date range, this value is the first date in that date range.
applicationId	string	The Store ID of the app for which you are retrieving ad campaign performance data.
campaignId	string	The ID of the ad campaign.
lineId	string	The ID of the ad campaign delivery line that generated this performance data.
currencyCode	string	The currency code of the campaign budget.
spend	string	The budget amount that has been spent for the ad campaign.
impressions	long	The number of ad impressions for the campaign.
installs	long	The number of app installs related to the campaign.
clicks	long	The number of ad clicks for the campaign.
iapInstalls	long	The number of add-on (also called in-app purchase or IAP) installs related to the campaign.
activeUsers	long	The number of users who have clicked an ad that is part of the campaign and returned to the app.

Response example

The following example demonstrates an example JSON response body for this request.

JSON

```
{
  "Value": [
    {
      "date": "2015-04-12",
      "applicationId": "9WZDNCRFJ31Q",
      "campaignId": "4568",
      "lineId": "0001",
      "currencyCode": "USD",
      "spend": 700.6,
      "impressions": 200,
      "installs": 30,
      "clicks": 8,
      "iapInstalls": 0,
      "activeUsers": 0
    },
    {
      "date": "2015-05-12",
      "applicationId": "9WZDNCRFJ31Q",
      "campaignId": "1234",
      "lineId": "0002",
      "currencyCode": "USD",
      "spend": 325.3,
      "impressions": 20,
      "installs": 2,
      "clicks": 5,
      "iapInstalls": 0,
      "activeUsers": 0
    }
  ],
  "@nextLink": "promotion?applicationId=9NBLGGGZ5QDR&aggregationLevel=day&startDate=2015/1/20&endDate=2016/8/31&top=2&skip=2",
  "TotalCount": 1917
}
```

Related topics

- [Create an ad campaign for your app](#)
- [Run ad campaigns using Microsoft Store services](#)
- [Access analytics data using Microsoft Store services](#)

Get desktop application installs

Article • 03/07/2024

Use this REST URI to get aggregate install data in JSON format for a desktop application that you have added to the [Windows Desktop Application program](#). This URI enables you to get install data during a given date range and other optional filters. This information is also available in the [Installs report](#) for desktop applications in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method.
After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

 Expand table

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/installbasedaily</code>

Request header

 Expand table

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Parameter	Type	Description	Required
applicationId	string	The product ID of the desktop application for which you want to retrieve install data. To get the product ID of a desktop application, open any analytics report for your desktop application in Partner Center (such as the Installs report) and retrieve the product ID from the URL by hovering your mouse over the link to reveal the details.	Yes
startDate	date	The start date in the date range of install data to retrieve. The default is 90 days prior to the current date.	No
endDate	date	The end date in the date range of install data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or . String values must be surrounded by single quotes in the <i>filter</i> parameter. You can specify the following fields from the response body: • applicationVersion • deviceType • market • osVersion • osRelease	No
orderby	string	A statement that orders the result data values for each install. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following fields from the response body: • productName • date • applicationVersion • deviceType	No

Parameter	Type	Description	Required
		• market • osVersion • osRelease • installBase The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields from the response body: • applicationVersion • deviceType • market • osVersion • osRelease The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • applicationId • date • productName • installBase	No

Request example

The following example demonstrates several requests for getting desktop application install data. Replace the *applicationId* value with the Product ID for your desktop application.

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/installbase
daily?applicationId=1234567890&startDate=2018-01-01&endDate=2018-02-
01&top=10&skip=0 HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/installbase
daily?applicationId=1234567890&startDate=2018-01-01&endDate=2018-02-
```

```
01&filter=market eq 'US' and deviceType eq 'PC' HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

[Expand table](#)

Value	Type	Description
Value	array	An array of objects that contain aggregate install data. For more information about the data in each object, see the following table.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of install data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Elements in the *Value* array contain the following values.

[Expand table](#)

Value	Type	Description
date	string	The date associated with the install base value.
applicationId	string	The product ID of the desktop application for which you retrieved install data.
productName	string	The display name of the desktop application as derived from the metadata of its associated executable(s).
applicationVersion	string	The version of the application executable that was installed.
deviceType	string	One of the following strings that specifies the type of device on which the desktop application is installed: • PC • Server • Tablet • Unknown

Value	Type	Description
market	string	The ISO 3166 country code of the market in which the desktop application is installed.
osVersion	string	One of the following strings that specifies the OS version on which the desktop application is installed: • Windows 7 • Windows 8.1 • Windows 10 • Windows 11 • Windows Server 2016 • Windows Server 1709 • Unknown
osRelease	string	One of the following strings that specifies the OS release or flighting ring (as a subpopulation within OS version) on which the desktop application is installed. For Windows 11: Version 21H0 For Windows 10: • Version 1507 • Version 1511 • Version 1607 • Version 1703 • Version 1709 • Release Preview • Insider Fast • Insider Slow For Windows Server 1709: • RTM For Windows Server 2016: • Version 1607 For Windows 8.1: • Update 1 For Windows 7: • Service Pack 1 If the OS release or flighting ring is unknown, this field has the value Unknown.

Value	Type	Description
installBase	number	The number of distinct devices that had the product installed at the specified aggregation level.

Response example

The following example demonstrates an example JSON response body for this request.

JSON

```
{
  "Value": [
    {
      "date": "2018-01-24",
      "applicationId": "123456789",
      "productName": "Contoso Demo",
      "applicationVersion": "1.0.0.0",
      "deviceType": "PC",
      "market": "All",
      "osVersion": "Windows 10",
      "osRelease": "Version 1709",
      "installBase": 348218.0
    }
  ],
  "@nextLink": "desktop/installbasedaily?applicationId=123456789&startDate=2018-01-01&endDate=2018-02-01&top=10000&skip=10000&groupby=applicationVersion,deviceType,osVersion,osRelease",
  "TotalCount": 23012
}
```

Related topics

- [Windows Desktop Application program](#)

Feedback

Was this page helpful?

 Yes

 No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

Get insights data for your desktop application

Article • 10/20/2022

Use this method in the Microsoft Store analytics API to get insights data related to health metrics for a desktop application that you have added to the [Windows Desktop Application program](#). This data is also available in the [Health report](#) for desktop applications in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/insights</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Parameter	Type	Description	Required
-----------	------	-------------	----------

Parameter	Type	Description	Required
applicationId	string	The product ID of the desktop application for which you want to get insights data. To get the product ID of a desktop application, open any analytics report for your desktop application in Partner Center (such as the Health report) and retrieve the product ID from the URL. If you do not specify this parameter, the response body will contain insights data for all apps registered to your account.	No
startDate	date	The start date in the date range of insights data to retrieve. The default is 30 days before the current date.	No
endDate	date	The end date in the date range of insights data to retrieve. The default is the current date.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or . String values must be surrounded by single quotes in the <i>filter</i> parameter. For example, <i>filter=dataType eq 'acquisition'</i> . Currently this method only supports the filter health .	No

Request example

The following example demonstrates a request for getting insights data. Replace the *applicationId* value with the appropriate value for your desktop application.

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/insights?
applicationId=10238467886765136388&startDate=6/1/2018&endDate=6/15/2018&filter=dataType eq 'health' HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
-------	------	-------------

Value	Type	Description
Value	array	An array of objects that contain insights data for the app. For more information about the data in each object, see the Insight values section below.
TotalCount	int	The total number of rows in the data result for the query.

Insight values

Elements in the *Value* array contain the following values.

Value	Type	Description
applicationId	string	The product ID of the desktop application for which you retrieved insights data.
insightDate	string	The date on which we identified the change in a specific metric. This date represents the end of the week in which we detected a significant increase or decrease in a metric compared to the week before that.
dataType	string	A string that specifies the general analytics area that this insight informs. Currently, this method only supports health .
insightDetail	array	One or more InsightDetail values that represent the details for current insight.

InsightDetail values

Value	Type	Description
FactName	string	A string that indicates the metric that the current insight or current dimension describes. Currently, this method only supports the value HitCount .
SubDimensions	array	One or more objects that describe a single metric for the insight.
PercentChange	string	The percentage that the metric changed across your entire customer base.
DimensionName	string	The name of the metric described in the current dimension. Examples include EventType , Market , DeviceType , and PackageVersion .
DimensionValue	string	The value of the metric that is described in the current dimension. For example, if DimensionName is EventType , DimensionValue might be crash or hang .
FactValue	string	The absolute value of the metric on the date the insight was detected.

Value	Type	Description
Direction	string	The direction of the change (Positive or Negative).
Date	string	The date on which we identified the change related to the current insight or the current dimension.

Response example

The following example demonstrates an example JSON response body for this request.

JSON

```
{
  "Value": [
    {
      "applicationId": "9NBLGGGZ5QDR",
      "insightDate": "2018-06-03T00:00:00",
      "dataType": "health",
      "insightDetail": [
        {
          "FactName": "HitCount",
          "SubDimensions": [
            {
              "FactName": "HitCount",
              "PercentChange": "21",
              "DimensionValue": "DE",
              "FactValue": "109",
              "Direction": "Positive",
              "Date": "6/3/2018 12:00:00 AM",
              "DimensionName": "Market"
            }
          ],
          "DimensionValue": "crash",
          "Date": "6/3/2018 12:00:00 AM",
          "DimensionName": "EventType"
        },
        {
          "FactName": "HitCount",
          "SubDimensions": [
            {
              "FactName": "HitCount",
              "PercentChange": "71",
              "DimensionValue": "JP",
              "FactValue": "112",
              "Direction": "Positive",
              "Date": "6/3/2018 12:00:00 AM",
              "DimensionName": "Market"
            }
          ],
          "DimensionValue": "hang",
          "Date": "6/3/2018 12:00:00 AM",

```

```
        "DimensionName": "EventType"
      },
    ],
    "insightId": "9CY0F3VBT1AS942AFQaey00k2zUKfy0hr0Hc0036Iwc="
  }
],
"@nextLink": null,
"TotalCount": 2
}
```

Related topics

- [Windows Desktop Application program](#)
- [Health report](#)
- [Access analytics data using Microsoft Store services](#)

Get upgrade blocks for your desktop application

Article • 10/20/2022

Use this REST URI to get info about Windows 10 and Windows 11 devices on which your desktop application is blocking a Windows 10 or Windows 11 upgrade from running. You can use this URI only for desktop applications that you have added to the [Windows Desktop Application program](#). This information is also available in the [Application blocks report](#) for desktop applications in Partner Center.

To get details about device blocks for a specific executable in your desktop application, see [Get upgrade block details for your desktop application](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/blockhits</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
applicationId	string	The product ID of the desktop application for which you want to retrieve block data. To get the product ID of a desktop application, open any analytics report for your desktop application in Partner Center (such as the Blocks report) and retrieve the product ID from the URL.	Yes
startDate	date	The start date in the date range of block data to retrieve. The default is 90 days prior to the current date.	No
endDate	date	The end date in the date range of block data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or. String values must be surrounded by single quotes in the <i>filter</i> parameter. You can specify the following fields from the response body: • applicationVersion • architecture • blockType • deviceType • fileName • market • osRelease • osVersion • productName • targetOs	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values for each block. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following fields from the response body: • applicationVersion • architecture • blockType • date • deviceType • fileName • market • osRelease • osVersion • productName • targetOs • deviceCount The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields from the response body: • applicationVersion • architecture • blockType • deviceType • fileName • market • osRelease • osVersion • targetOs The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • applicationId • date • productName • deviceCount	No

Request example

The following example demonstrates several requests for getting desktop application block data. Replace the *applicationId* value with the Product ID for your desktop application.

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/blockhits?
applicationId=5126873772241846776&startDate=2018-05-01&endDate=2018-06-
07&skip=0 HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/blockhits?
applicationId=5126873772241846776&startDate=2018-05-01&endDate=2018-06-
07&filter=market eq 'US' and deviceType eq 'PC' HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate block data. For more information about the data in each object, see the following table.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of block data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Elements in the *Value* array contain the following values.

Value	Type	Description
applicationId	string	The product ID of the desktop application for which you retrieved block data.
date	string	The date associated with the block hits value.
productName	string	The display name of the desktop application as derived from the metadata of its associated executable(s).
fileName	string	The executable that was blocked.

Value	Type	Description
applicationVersion	string	The version of the application executable that was blocked.
osVersion	string	One of the following strings that specifies the OS version on which the desktop application is currently running: • Windows 7 • Windows 8.1 • Windows 10 • Windows 11 • Windows Server 2016 • Windows Server 1709 • Unknown
osRelease	string	One of the following strings that specifies the OS release or flighting ring (as a subpopulation within OS version) on which the desktop application is currently running. For Windows 11: Version 21H0 For Windows 10: • Version 1507 • Version 1511 • Version 1607 • Version 1703 • Version 1709 • Release Preview • Insider Fast • Insider Slow For Windows Server 1709: • RTM For Windows Server 2016: • Version 1607 For Windows 8.1: • Update 1 For Windows 7: • Service Pack 1 If the OS release or flighting ring is unknown, this field has the value Unknown.

Value	Type	Description
market	string	The ISO 3166 country code of the market in which the desktop application is blocked.
deviceType	string	One of the following strings that specifies the type of device on which the desktop application is blocked: • PC • Server • Tablet • Unknown
blockType	string	One of the following strings that specifies the type of block found on the device: • Potential Sediment • Temporary Sediment • Runtime Notification For more information about these block types and what they mean to developers and users, see the description of the Application blocks report.
architecture	string	The architecture of the device on which the block exists: • ARM64 • X86
targetOs	string	One of the following strings that specifies the Windows 10 or Windows 11 OS release on which the desktop application is blocked from running: • Version 1709 • Version 1803
deviceCount	number	The number of distinct devices that have blocks at the specified aggregation level.

Response example

The following example demonstrates an example JSON response body for this request.

JSON

```
{
  "Value": [
    {
```

```
"applicationId": "10238467886765136388",
"date": "2018-06-03",
"productName": "Contoso Demo",
"fileName": "contosodemo.exe",
"applicationVersion": "2.2.2.0",
"osVersion": "Windows 8.1",
"osRelease": "Update 1",
"market": "ZA",
"deviceType": "All",
"blockType": "Runtime Notification",
"architecture": "X86",
"targetOs": "RS4",
"deviceCount": 120
}
],
"@nextLink": "desktop/blockhits?applicationId=123456789&startDate=2018-01-01&endDate=2018-02-01&top=10000&skip=10000&groupby=applicationVersion,deviceType,osVersion,osRelease",
"TotalCount": 23012
}
```

Related topics

- [Windows Desktop Application program](#)
- [Get upgrade block details for your desktop application](#)

Get upgrade block details for your desktop application

Article • 10/20/2022

Use this REST URI to get details for Windows 10 and Windows 11 devices on which a specific executable in your desktop application is blocking a Windows 10 or Windows 11 upgrade from running. You can use this URI only for desktop applications that you have added to the [Windows Desktop Application program](#). This information is also available in the [Application blocks report](#) for desktop applications in Partner Center.

This URI is similar to [Get upgrade blocks for your desktop application](#), but it returns device block info for a specific executable in your desktop application.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/blockdetails</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Parameter	Type	Description	Required
applicationId	string	The product ID of the desktop application for which you want to retrieve block data. To get the product ID of a desktop application, open any analytics report for your desktop application in Partner Center (such as the Blocks report) and retrieve the product ID from the URL.	Yes
fileName	string	The name of the blocked executable	
startDate	date	The start date in the date range of block data to retrieve. The default is 90 days prior to the current date.	No
endDate	date	The end date in the date range of block data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10000 and skip=0 retrieves the first 10000 rows of data, top=10000 and skip=10000 retrieves the next 10000 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or. String values must be surrounded by single quotes in the <i>filter</i> parameter. You can specify the following fields from the response body: • applicationVersion • architecture • blockType • deviceType • market • osRelease • osVersion • productName • targetOs	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values for each block. The syntax is <i>orderby=field [order],field [order],....</i> The <i>field</i> parameter can be one of the following fields from the response body: • applicationVersion • architecture • blockType • date • deviceType • market • osRelease • osVersion • productName • targetOs • deviceCount The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields from the response body: • applicationVersion • architecture • blockType • deviceType • market • osRelease • osVersion • targetOs The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • applicationId • date • productName • deviceCount	No

Request example

The following example demonstrates several requests for getting desktop application block data. Replace the *applicationId* value with the Product ID for your desktop application.

HTTP

GET

`https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/blockdetails?applicationId=10238467886765136388&fileName=contoso.exe&startDate=2018-05-01&endDate=2018-06-07&skip=0` HTTP/1.1

Authorization: Bearer <your access token>

GET

`https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/blockdetails?applicationId=10238467886765136388&fileName=contoso.exe&startDate=2018-05-01&endDate=2018-06-07&filter=market eq 'US' and deviceType eq 'PC'` HTTP/1.1

Authorization: Bearer <your access token>

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate block data. For more information about the data in each object, see the following table.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of block data for the query.
TotalCount	int	The total number of rows in the data result for the query.

Elements in the *Value* array contain the following values.

Value	Type	Description
applicationId	string	The product ID of the desktop application for which you retrieved block data.
date	string	The date associated with the block hits value.
productName	string	The display name of the desktop application as derived from the metadata of its associated executable(s).
fileName	string	The executable that was blocked.

Value	Type	Description
applicationVersion	string	The version of the application executable that was blocked.
osVersion	string	One of the following strings that specifies the OS version on which the desktop application is currently running: • Windows 7 • Windows 8.1 • Windows 10 • Windows 11 • Windows Server 2016 • Windows Server 1709 • Unknown
osRelease	string	One of the following strings that specifies the OS release or flighting ring (as a subpopulation within OS version) on which the desktop application is currently running. For Windows 11: Version 21H0 For Windows 10: • Version 1507 • Version 1511 • Version 1607 • Version 1703 • Version 1709 • Release Preview • Insider Fast • Insider Slow For Windows Server 1709: • RTM For Windows Server 2016: • Version 1607 For Windows 8.1: • Update 1 For Windows 7: • Service Pack 1 If the OS release or flighting ring is unknown, this field has the value Unknown.

Value	Type	Description
market	string	The ISO 3166 country code of the market in which the desktop application is blocked.
deviceType	string	One of the following strings that specifies the type of device on which the desktop application is blocked: • PC • Server • Tablet • Unknown
blockType	string	One of the following strings that specifies the type of block found on the device: • Potential Sediment • Temporary Sediment • Runtime Notification For more information about these block types and what they mean to developers and users, see the description of the Application blocks report.
architecture	string	The architecture of the device on which the block exists: • ARM64 • X86
targetOs	string	One of the following strings that specifies the Windows 10 or Windows 11 OS release on which the desktop application is blocked from running: • Version 1709 • Version 1803
deviceCount	number	The number of distinct devices that have blocks at the specified aggregation level.

Response example

The following example demonstrates an example JSON response body for this request.

JSON

```
{
  "Value": [
    {
```

```
"applicationId": "10238467886765136388",
"date": "2018-06-03",
"productName": "Contoso Demo",
"fileName": "contosodemo.exe",
"applicationVersion": "2.2.2.0",
"osVersion": "Windows 8.1",
"osRelease": "Update 1",
"market": "ZA",
"deviceType": "All",
"blockType": "Runtime Notification",
"architecture": "X86",
"targetOs": "RS4",
"deviceCount": 120
}
],
"@nextLink": "desktop/blockdetails?applicationId=123456789&startDate=2018-01-01&endDate=2018-02-01&top=10000&skip=10000&groupby=applicationVersion,deviceType,osVersion,osRelease",
"TotalCount": 23012
}
```

Related topics

- [Windows Desktop Application program](#)
- [Get upgrade blocks for your desktop application](#)

Get error reporting data for your desktop application

Article • 11/01/2022

Use this method in the Microsoft Store analytics API to get aggregate error reporting data for a desktop application that you have added to the [Windows Desktop Application program](#). This method can only retrieve errors that occurred in the last 30 days. This information is also available in the [Health report](#) for desktop applications in Partner Center.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

Request syntax

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/failurehits</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Parameter	Type	Description	Required
-----------	------	-------------	----------

Parameter	Type	Description	Required
applicationId	string	The product ID of the desktop application for which you want to retrieve error reporting data. To get the product ID of a desktop application, open any analytics report for your desktop application in Partner Center (such as the Health report) and retrieve the product ID from the URL.	Yes
startDate	date	The start date in the date range of error reporting data to retrieve, in the format <code>mm/dd/yyyy</code>. The default is the current date. Note: This method can only retrieve errors that occurred in the last 30 days.	No
endDate	date	The end date in the date range of error reporting data to retrieve, in the format <code>mm/dd/yyyy</code> . The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, <code>top=10000</code> and <code>skip=0</code> retrieves the first 10000 rows of data, <code>top=10000</code> and <code>skip=10000</code> retrieves the next 10000 rows of data, and so on.	No

Parameter	Type	Description	Required
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or. String values must be surrounded by single quotes in the <i>filter</i> parameter. You can specify the following fields from the response body: • fileName • applicationVersion • failureName • failureHash • symbol • osVersion • osBuild • osRelease • eventType • market • deviceType • productName • date	No
aggregationLevel	string	Specifies the time range for which to retrieve aggregate data. Can be one of the following strings: day, week, or month. If unspecified, the default is day. If you specify week or month, the <i>failureName</i> and <i>failureHash</i> values are limited to 1000 buckets.	No

Parameter	Type	Description	Required
orderby	string	A statement that orders the result data values. The syntax is <i>orderby=field [order],field [order],....</i>. The <i>field</i> parameter can be one of the following strings: • fileName • applicationVersion • failureName • failureHash • symbol • osVersion • osBuild • osRelease • eventType • market • deviceType • productName • date The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No
groupby	string	A statement that applies data aggregation only to the specified fields. You can specify the following fields: • failureName • failureHash • symbol • osVersion • eventType • market • deviceType The returned data rows will contain the fields specified in the <i>groupby</i> parameter as well as the following: • date • applicationId • applicationName • eventCount The <i>groupby</i> parameter can be used with the <i>aggregationLevel</i> parameter. For example: <i>&groupby=failureName,market&aggregationLevel=week</i>	No

Request example

The following examples demonstrate several requests for getting error reporting data. Replace the *applicationId* value with the product ID for your desktop application.

syntax

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/failurehits
?
applicationId=10238467886765136388&startDate=1/1/2018&endDate=2/1/2018&top=1
0&skip=0 HTTP/1.1
Authorization: Bearer <your access token>
```

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/failurehits
?
applicationId=10238467886765136388&startDate=8/1/2017&endDate=8/31/2017&skip
=0&filter=market eq 'US' and deviceType eq 'PC' HTTP/1.1
Authorization: Bearer <your access token>
```

Response

Response body

Value	Type	Description
Value	array	An array of objects that contain aggregate error reporting data. For more information about the data in each object, see the error values section below.
@nextLink	string	If there are additional pages of data, this string contains a URI that you can use to request the next page of data. For example, this value is returned if the top parameter of the request is set to 10000 but there are more than 10000 rows of errors for the query.
TotalCount	integer	The total number of rows in the data result for the query.

Error values

Elements in the *Value* array contain the following values.

Value	Type	Description
-------	------	-------------

Value	Type	Description
date	string	The first date in the date range for the error data, in the format <code>yyyy-mm-dd</code> . If the request specifies a single day, this value is that date. If the request specifies a longer date range, this value is the first date in that date range. For requests that specify an <i>aggregationLevel</i> value of hour , this value also includes a time value in the format <code>hh:mm:ss</code> .
applicationId	string	The product ID of the desktop application for which you retrieved error data.
productName	string	The display name of the desktop application as derived from the metadata of its associated executable(s).
appName	string	TBD
fileName	string	The name of the executable file for the desktop application.
failureName	string	The name of the failure, which is made up of four parts: one or more problem classes, an exception/bug check code, the name of the image where the failure occurred, and the associated function name.
failureHash	string	The unique identifier for the error.
symbol	string	The symbol assigned to this error.
osBuild	string	The four-part build number of the OS on which the error occurred.
osVersion	string	One of the following strings that specifies the OS version on which the desktop application is installed: • Windows 7 • Windows 8.1 • Windows 10 • Windows 11 • Windows Server 2016 • Windows Server 1709 • Unknown

Value	Type	Description
osRelease	string	One of the following strings that specifies the OS release or flighting ring (as a subpopulation within OS version) on which the error occurred. For Windows 11: Version 2110 For Windows 10: • Version 1507 • Version 1511 • Version 1607 • Version 1703 • Version 1709 • Version 1803 • Release Preview • Insider Fast • Insider Slow For Windows Server 1709: • RTM For Windows Server 2016: • Version 1607 For Windows 8.1: • Update 1 For Windows 7: • Service Pack 1 If the OS release or flighting ring is unknown, this field has the value Unknown.
eventType	string	One of the following strings that indicates the type of error event: • crash • hang • memory • jse
market	string	The ISO 3166 country code of the device market.

Value	Type	Description
deviceType	string	One of the following strings that specifies the type of device on which the error occurred: • PC • Server • Tablet • Unknown
applicationVersion	string	The version of the application executable in which the error occurred.
eventCount	number	The number of events that are attributed to this error for the specified aggregation level.

Response example

The following example demonstrates an example JSON response body for this request.

JSON

```
{
  "Value": [
    {
      "date": "2018-02-01",
      "applicationId": "10238467886765136388",
      "productName": "Contoso Demo",
      "appName": "Contoso Demo",
      "fileName": "contosodemo.exe",
      "failureName":
"SVCHOSTGROUP_localservice_IN_PAGE_ERROR_c0000006_hardware_disk!Unknown",
      "failureHash": "11242ef3-ebd8-d525-838d-b5497b225695",
      "symbol": "hardware_disk!Unknown",
      "osBuild": "10.0.15063.850",
      "osVersion": "Windows 10",
      "osRelease": "Version 1703",
      "eventType": "crash",
      "market": "US",
      "deviceType": "PC",
      "applicationVersion": "2.2.2.0",
      "eventCount": 0.0012422360248447205
    }
  ],
  "@nextLink": "desktop/failurehits?
applicationId=10238467886765136388&aggregationLevel=week&startDate=2018/02/0
1&endDate2018/02/08&top=1&skip=1",
  "TotalCount": 21
}
```

Related topics

- [Health report](#)
- [Access analytics data using Microsoft Store services](#)
- [Get details for an error in your desktop application](#)
- [Get the stack trace for an error in your desktop application](#)
- [Download the CAB file for an error in your desktop application](#)

Get details for an error in your desktop application

Article • 01/04/2023

Use this method in the Microsoft Store analytics API to get detailed data for a specific error for your app in JSON format. This method can only retrieve details for errors that occurred in the last 30 days. Detailed error data is also available in the [Health report](#) for desktop applications in Partner Center.

Before you can use this method, you must first use the [get error reporting data](#) method to retrieve the ID of the error for which you want to get detailed info.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store analytics API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Get the ID of the error for which you want to get detailed info. To get this ID, use the [get error reporting data](#) method and use the **failureHash** value in the response body of that method.

Request

Request syntax

 Expand table

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/failedetails</code>

Request header

 Expand table

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

 Expand table

Parameter	Type	Description	Required
applicationId	string	The product ID of the desktop application for which you want to retrieve error details. To get the product ID of a desktop application, open any analytics report for your desktop application in Partner Center (such as the Health report) and retrieve the product ID from the URL.	Yes
failureHash	string	The unique ID of the error for which you want to get detailed info. To get this value for the error you are interested in, use the get error reporting data method and use the failureHash value in the response body of that method.	Yes
startDate	date	The start date in the date range of detailed error data to retrieve. The default is 30 days before the current date. Note: This method can only retrieve details for errors that occurred in the last 30 days.	No
endDate	date	The end date in the date range of detailed error data to retrieve. The default is the current date.	No
top	int	The number of rows of data to return in the request. The maximum value and the default value if not specified is 10000. If there are more rows in the query, the response body includes a next link that you can use to request the next page of data.	No
skip	int	The number of rows to skip in the query. Use this parameter to page through large data sets. For example, top=10 and skip=0 retrieves the first 10 rows of data, top=10 and skip=10 retrieves the next 10 rows of data, and so on.	No
filter	string	One or more statements that filter the rows in the response. Each statement contains a field name from the response body and value that are associated with the eq or ne operators, and statements can be combined using and or or . String values must be surrounded by single quotes in the <i>filter</i> parameter. You can specify the following fields from the response body: market	No

Parameter	Type	Description	Required
		• date • cabIdHash • cabExpirationTime • deviceType • deviceModel • osVersion • osRelease • applicationVersion • osBuild • fileName	
orderby	string	A statement that orders the result data values. The syntax is <i>orderby=field [order],field [order],...</i>. The <i>field</i> parameter can be one of the following strings: • market • date • cabIdHash • cabExpirationTime • deviceType • deviceModel • osVersion • osRelease • applicationVersion • osBuild • fileName The <i>order</i> parameter is optional, and can be asc or desc to specify ascending or descending order for each field. The default is asc. Here is an example <i>orderby</i> string: <i>orderby=date,market</i>	No

Request example

The following examples demonstrate several requests for getting detailed error data. Replace the *applicationId* value with the product ID for your desktop application.

syntax

GET

```
https://manage.devcenter.microsoft.com/v1.0/my/analytics/desktop/failedetails?applicationId=10238467886765136388&failureHash=00001111-aaaa-2222-bbbb-3333cccc4444&startDate=2016-11-05&endDate=2016-11-06&top=10&skip=0 HTTP/1.1
Authorization: Bearer <your access token>
```

GET