

⚠ Note

This API currently does not support a PUT method.

Header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .
Tracking ID	GUID	Optional. An ID that tracks the call flow.

Request body

The POST method requires a JSON request body with the required fields of a [Creative](#) object.

Request examples

The following example demonstrates how to call the POST method to create a creative. In this example, the *content* value has been shortened for brevity.

JSON

```
POST https://manage.devcenter.microsoft.com/v1.0/my/promotion/creative HTTP/1.1
Authorization: Bearer <your access token>

{
  "name": "Contoso App Campaign - Creative 1",
  "content":
    "...other base64
    data shortened for brevity...",
  "height": 80,
  "width": 480,
  "imageAttributes":
  {
    "imageExtension": "PNG"
  }
}
```

The following example demonstrates how to call the GET method to retrieve a creative.

JSON

```
GET https://manage.devcenter.microsoft.com/v1.0/my/promotion/creative/106851
HTTP/1.1
```

Authorization: Bearer <your access token>

Response

These methods return a JSON response body with a [Creative](#) object that contains information about the creative that was created or retrieved. The following example demonstrates a response body for these methods. In this example, the *content* value has been shortened for brevity.

JSON

```
{
  "Data": {
    "id": 106126,
    "name": "Contoso App Campaign - Creative 2",
    "content":
      "...other base64
      data shortened for brevity...",
    "height": 50,
    "width": 300,
    "format": "Banner",
    "imageAttributes":
      {
        "imageExtension": "PNG"
      },
    "storeProductId": "9nblggh42cfd"
  }
}
```

Creative object

The request and response bodies for these methods contain the following fields. This table shows which fields are read-only (meaning that they cannot be changed in the PUT method) and which fields are required in the request body for the POST method.

Field	Type	Description	Read only	Default	Required for POST
id	integer	The ID of the creative.	Yes		No
name	string	The name of the creative.	No		Yes

Field	Type	Description	Read only	Default	Required for POST
content	string	The content of the creative image, in Base64-encoded format. Note The maximum allowed size for your creative is 40 KB. If you submit a creative file larger than this, this API will not return an error, but the campaign will not successfully be created.	No		Yes
height	integer	The height of the creative.	No		Yes
width	integer	The width of the creative.	No		Yes
landingUrl	string	If you are using a campaign tracking service such as AppsFlyer, Kochava, Tune, or Vungle to measure install analytics for your app, assign your tracking URL in this field when you call the POST method (if specified, this value must be a valid URI). If you are not using a campaign tracking service, omit this value when you call the POST method (in this case, this URL will be created automatically).	No		Yes
format	string	The ad format. Currently, the only supported value is Banner .	No	Banner	No
imageAttributes	ImageAttributes	Provides attributes for the creative.	No		Yes
storeProductId	string	The Store ID for the app that this ad campaign is associated with. An example Store ID for a product is 9nblggh42cfd.	No		No

ImageAttributes object

Field	Type	Description	Read-only	Default value	Required for POST
-------	------	-------------	-----------	---------------	-------------------

Field	Type	Description	Read-only	Default value	Required for POST
imageExtension	string	One of the following values: PNG or JPG.	No		Yes

Related topics

- [Run ad campaigns using Microsoft Store Services](#)
- [Manage ad campaigns](#)
- [Manage delivery lines for ad campaigns](#)
- [Manage targeting profiles for ad campaigns](#)
- [Get ad campaign performance data](#)

Create and manage submissions

Article • 07/22/2024

Use the *Microsoft Store submission API* to programmatically query and create submissions for apps, add-ons and package flights for your or your organization's Partner Center account. This API is useful if your account manages many apps or add-ons, and you want to automate and optimize the submission process for these assets. This API uses Azure Active Directory (Azure AD) to authenticate the calls from your app or service.

The following steps describe the end-to-end process of using the Microsoft Store submission API:

1. Make sure that you have completed all the [prerequisites](#).
2. Before you call a method in the Microsoft Store submission API, [obtain an Azure AD access token](#). After you obtain a token, you have 60 minutes to use this token in calls to the Microsoft Store submission API before the token expires. After the token expires, you can generate a new token.
3. [Call the Microsoft Store submission API](#).

Important

If you use this API to create a submission for an app, package flight, or add-on, be sure to make further changes to the submission only by using the API, rather than in Partner Center. If you use Partner Center to change a submission that you originally created by using the API, you will no longer be able to change or commit that submission by using the API. In some cases, the submission could be left in an error state where it cannot proceed in the submission process. If this occurs, you must delete the submission and create a new submission.

Important

You cannot use this API to publish submissions for [volume purchases through the Microsoft Store for Business and Microsoft Store for Education](#) or to publish submissions for [LOB apps](#) directly to enterprises. For both of these scenarios, you must use publish the submission in Partner Center.

Note

This API cannot be used with apps or add-ons that use mandatory app updates and Store-managed consumable add-ons. If you use the Microsoft Store submission API with an app or add-on that uses one of these features, the API will return a 409 error code. In this case, you must use Partner Center to manage the submissions for the app or add-on.

ⓘ Note

You can't use this API with apps or add-ons that are on Pricing Version 2. A product is on Pricing Version 2 if there's a **Review price per market** button in the **Pricing** section of the **Pricing and availability** page. If you use the Microsoft Store submission API with an app or add-on that's on Pricing Version 2, then the API will return an unknown tier for the pricing part. You can continue using this API to update modules other than **Pricing and availability**.

Step 1: Complete prerequisites for using the Microsoft Store submission API

Before you start writing code to call the Microsoft Store submission API, make sure that you have completed the following prerequisites.

- You (or your organization) must have an Azure AD directory and you must have [Global administrator](#) permission for the directory. If you already use Microsoft 365 or other business services from Microsoft, you already have Azure AD directory. Otherwise, you can [create a new Azure AD in Partner Center](#) for no additional charge.
- You must [associate an Azure AD application with your Partner Center account](#) and obtain your tenant ID, client ID and key. You need these values to obtain an Azure AD access token, which you will use in calls to the Microsoft Store submission API.
- Prepare your app for use with the Microsoft Store submission API:
 - If your app does not yet exist in Partner Center, you must [create your app by reserving its name in Partner Center](#). You cannot use the Microsoft Store submission API to create an app in Partner Center; you must work in Partner Center to create it, and then after that you can use the API to access the app and programmatically create submissions for it. However, you can use the API to programmatically create add-ons and package flights before you create submissions for them.

- Before you can create a submission for a given app using this API, you must first [create one submission for the app in Partner Center](#), including answering the [age ratings](#) questionnaire. After you do this, you will be able to programmatically create new submissions for this app using the API. You do not need to create an add-on submission or package flight submission before using the API for those types of submissions.
- If you are creating or updating an app submission and you need to include an app package, [prepare the app package](#).
- If you are creating or updating an app submission and you need to include screenshots or images for the Store listing, [prepare the app screenshots and images](#).
- If you are creating or updating an add-on submission and you need to include an icon, [prepare the icon](#).

How to associate an Azure AD application with your Partner Center account

Before you can use the Microsoft Store submission API, you must associate an Azure AD application with your Partner Center account, retrieve the tenant ID and client ID for the application and generate a key. The Azure AD application represents the app or service from which you want to call the Microsoft Store submission API. You need the tenant ID, client ID and key to obtain an Azure AD access token that you pass to the API.

ⓘ Note

You only need to perform this task one time. After you have the tenant ID, client ID and key, you can reuse them any time you need to create a new Azure AD access token.

1. In Partner Center, [associate your organization's Partner Center account with your organization's Azure AD directory](#).
2. Next, from the **Users** page in the **Account settings** section of Partner Center, [add the Azure AD application](#) that represents the app or service that you will use to access submissions for your Partner Center account. Make sure you assign this application the **Manager** role. If the application doesn't exist yet in your Azure AD directory, you can [create a new Azure AD application in Partner Center](#).

3. Return to the **Users** page, click the name of your Azure AD application to go to the application settings, and copy down the **Tenant ID** and **Client ID** values.
4. Click **Add new key**. On the following screen, copy down the **Key** value. You won't be able to access this info again after you leave this page. For more information, see [Manage keys for an Azure AD application](#).

Step 2: Obtain an Azure AD access token

Before you call any of the methods in the Microsoft Store submission API, you must first obtain an Azure AD access token that you pass to the **Authorization** header of each method in the API. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can refresh the token so you can continue to use it in further calls to the API.

To obtain the access token, follow the instructions in [Service to Service Calls Using Client Credentials](#) to send an HTTP POST to the

`https://login.microsoftonline.com/<tenant_id>/oauth2/token` endpoint. Here is a sample request.

JSON

```
POST https://login.microsoftonline.com/<tenant_id>/oauth2/token HTTP/1.1
Host: login.microsoftonline.com
Content-Type: application/x-www-form-urlencoded; charset=utf-8

grant_type=client_credentials
&client_id=<your_client_id>
&client_secret=<your_client_secret>
&resource=https://manage.devcenter.microsoft.com
```

For the *tenant_id* value in the POST URI and the *client_id* and *client_secret* parameters, specify the tenant ID, client ID and the key for your application that you retrieved from Partner Center in the previous section. For the *resource* parameter, you must specify `https://manage.devcenter.microsoft.com`.

After your access token expires, you can fetch a new one by making the same HTTP call again.

For examples that demonstrate how to obtain an access token by using C#, Java, or Python code, see the Microsoft Store submission API [code examples](#).

Step 3: Use the Microsoft Store submission API

After you have an Azure AD access token, you can call methods in the Microsoft Store submission API. The API includes many methods that are grouped into scenarios for apps, add-ons, and package flights. To create or update submissions, you typically call multiple methods in the Microsoft Store submission API in a specific order. For information about each scenario and the syntax of each method, see the articles in the following table.

ⓘ Note

After you obtain an access token, you have 60 minutes to call methods in the Microsoft Store submission API before the token expires.

 Expand table

Scenario	Description
Apps	Retrieve data for all the apps that are registered to your Partner Center account and create submissions for apps. For more information about these methods, see the following articles: • Get app data • Manage app submissions
Add-ons	Get, create, or delete add-ons for your apps, and then get, create, or delete submissions for the add-ons. For more information about these methods, see the following articles: • Manage add-ons • Manage add-on submissions
Package flights	Get, create, or delete package flights for your apps, and then get, create, or delete submissions for the package flights. For more information about these methods, see the following articles: • Manage package flights • Manage package flight submissions

Code examples

The following articles provide detailed code examples that demonstrate how to use the Microsoft Store submission API in several different programming languages:

- [C# sample: submissions for apps, add-ons, and flights](#)
- [C# sample: app submission with game options and trailers](#)
- [Java sample: submissions for apps, add-ons, and flights](#)

- [Java sample: app submission with game options and trailers](#)
- [Python sample: submissions for apps, add-ons, and flights](#)
- [Python sample: app submission with game options and trailers](#)

StoreBroker PowerShell module

As an alternative to calling the Microsoft Store submission API directly, we also provide an open-source PowerShell module which implements a command-line interface on top of the API. This module is called [StoreBroker](#). You can use this module to manage your app, flight, and add-on submissions from the command line instead of calling the Microsoft Store submission API directly, or you can simply browse the source to see more examples for how to call this API. The StoreBroker module is actively used within Microsoft as the primary way that many first-party applications are submitted to the Store.

For more information, see our [StoreBroker page on GitHub](#).

Troubleshooting

 Expand table

Issue	Resolution
After calling the Microsoft Store submission API from PowerShell, the response data for the API is corrupted if you convert it from JSON format to a PowerShell object using the ConvertFrom-Json cmdlet and then back to JSON format using the ConvertTo-Json cmdlet.	By default, the <i>-Depth</i> parameter for the ConvertTo-Json cmdlet is set to 2 levels of objects, which is too shallow for most of the JSON objects that are returned by the Microsoft Store submission API. When you call the ConvertTo-Json cmdlet, set the <i>-Depth</i> parameter to a larger number, such as 20.

Additional help

If you have questions about the Microsoft Store submission API or need assistance managing your submissions with this API, use the following resources:

- Ask your questions on our [forums](#).
- Visit our [support page](#) and request one of the assisted support options for Partner Center. If you are prompted to choose a problem type and category, choose **App submission and certification** and **Submitting an app**, respectively.

Related topics

- [Get app data](#)
 - [Manage app submissions](#)
 - [Manage add-ons](#)
 - [Manage add-on submissions](#)
 - [Manage package flights](#)
 - [Manage package flight submissions](#)
-

Feedback

Was this page helpful?



Yes



No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

Get app data

Article • 01/04/2023

Use the following methods in the Microsoft Store submission API to get data for existing apps in your Partner Center account. For an introduction to the Microsoft Store submission API, including prerequisites for using the API, see [Create and manage submissions using Microsoft Store services](#).

Before you can use these methods, the app must already exist in your Partner Center account. To create or manage submissions for apps, see the methods in [Manage app submissions](#).

Method	URI	Description
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications</code>	Get data for all your apps
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}</code>	Get data for a specific app
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/listinappproducts</code>	Get add-ons for an app
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/listflights</code>	Get package flights for an app

Prerequisites

If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API before trying to use any of these methods.

Data resources

The Microsoft Store submission API methods for getting app data use the following JSON data resources.

Application resource

This resource represents an app that is registered to your account.

JSON

```
{
  "id": "9NBLGGH4R315",
  "primaryName": "ApiTestApp",
  "packageFamilyName": "30481DevCenterAPITester.ApiTestAppForDevbox_ng6try80pwt52",
  "packageIdentityName": "30481DevCenterAPITester.ApiTestAppForDevbox",
  "publisherName": "CN=...",
  "firstPublishedDate": "1601-01-01T00:00:00Z",
  "lastPublishedApplicationSubmission": {
```

```

    "id": "1152921504621086517",
    "resourceLocation": "applications/9NBLGGH4R315/submissions/1152921504621086517"
  },
  "pendingApplicationSubmission": {
    "id": "1152921504621243487",
    "resourceLocation": "applications/9NBLGGH4R315/submissions/1152921504621243487"
  },
  "hasAdvancedListingPermission": true
}

```

This resource has the following values.

Value	Type	Description
id	string	The Store ID of the app. For more information about the Store ID, see View app identity details .
primaryName	string	The primary name of the app.
packageFamilyName	string	The package family name of the app.
packageIdentityName	string	The package identity name of the app.
publisherName	string	The Windows publisher ID that is associated with the app. This corresponds to the Package/Identity/Publisher value that appears on the App identity page for the app in Partner Center.
firstPublishedDate	string	The date the app was first published, in ISO 8601 format.
lastPublishedApplicationSubmission	object	A submission resource that provides information about the last published submission for the app.
pendingApplicationSubmission	object	A submission resource that provides information about the current pending submission for the app.
hasAdvancedListingPermission	boolean	Indicates whether you can configure the gamingOptions or trailers for submissions for the app. This value is true for submissions created after May 2017.

Add-on resource

This resource provides information about an add-on.

JSON

```

{
  "inAppProductId": "9WZDNCRD7DLK"
}

```

This resource has the following values.

Value	Type	Description
inAppProductId	string	The Store ID of the add-on. This value is supplied by the Store. An example Store ID is 9NBLGGH4TNMP.

Flight resource

This resource provides information about a package flight for an app.

JSON

```
{
  "flightId": "7bfc11d5-f710-47c5-8a98-e04bb5aad310",
  "friendlyName": "myflight",
  "lastPublishedFlightSubmission": {
    "id": "1152921504621086517",
    "resourceLocation": "flights/7bfc11d5-f710-47c5-8a98-e04bb5aad310/submissions/1152921504621086517"
  },
  "pendingFlightSubmission": {
    "id": "1152921504621215786",
    "resourceLocation": "flights/7bfc11d5-f710-47c5-8a98-e04bb5aad310/submissions/1152921504621215786"
  },
  "groupIds": [
    "1152921504606962205"
  ],
  "rankHigherThan": "Non-flighted submission"
}
```

This resource has the following values.

Value	Type	Description
flightId	string	The ID for the package flight. This value is supplied by Partner Center.
friendlyName	string	The name of the package flight, as specified by the developer.
lastPublishedFlightSubmission	object	A submission resource that provides information about the last published submission for the package flight.
pendingFlightSubmission	object	A submission resource that provides information about the current pending submission for the package flight.
groupIds	array	An array of strings that contain the IDs of the flight groups that are associated with the package flight. For more information about flight groups, see Package flights .
rankHigherThan	string	The friendly name of the package flight that is ranked immediately lower than the current package flight. For more information about ranking flight groups, see Package flights .

Submission resource

This resource provides information about a submission. The following example demonstrates the format of this resource.

JSON

```
{
  "pendingApplicationSubmission": {
    "id": "1152921504621243487",
    "resourceLocation": "applications/9WZDNCRD9MMD/submissions/1152921504621243487"
  }
}
```

```
}  
}
```

This resource has the following values.

Value	Type	Description
id	string	The ID of the submission.
resourceLocation	string	A relative path that you can append to the base <code>https://manage.devcenter.microsoft.com/v1.0/my/</code> request URI to retrieve the complete data for the submission.

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Manage app submissions using the Microsoft Store submission API](#)
- [Get all apps](#)
- [Get an app](#)
- [Get add-ons for an app](#)
- [Get package flights for an app](#)

Get all apps

Article • 10/20/2022

Use this method in the Microsoft Store submission API to retrieve data for the apps that are registered to your Partner Center account.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

All request parameters are optional for this method. If you call this method without parameters, the response contains data for the first 10 apps that are registered to your account.

Parameter	Type	Description	Required
-----------	------	-------------	----------

Parameter	Type	Description	Required
top	int	The number of items to return in the request (that is, the number of apps to return). If your account has more apps than the value you specify in the query, the response body includes a relative URI path that you can append to the method URI to request the next page of data.	No
skip	int	The number of items to bypass in the query before returning the remaining items. Use this parameter to page through data sets. For example, top=10 and skip=0 retrieves items 1 through 10, top=10 and skip=10 retrieves items 11 through 20, and so on.	No

Request body

Do not provide a request body for this method.

Request examples

The following example demonstrates how to retrieve the first 10 apps that are registered to your account.

HTTP

```
GET https://manage.devcenter.microsoft.com/v1.0/my/applications HTTP/1.1
Authorization: Bearer <your access token>
```

The following example demonstrates how to retrieve information about all the apps that are registered to your account. First, get the top 10 apps:

HTTP

```
GET https://manage.devcenter.microsoft.com/v1.0/my/applications?top=10
HTTP/1.1
Authorization: Bearer <your access token>
```

Then recursively call `GET https://manage.devcenter.microsoft.com/v1.0/my/{@nextLink}` until `{@nextlink}` is null or doesn't exist in the response. For example:

HTTP

```
GET https://manage.devcenter.microsoft.com/v1.0/my/applications?
skip=10&top=10 HTTP/1.1
Authorization: Bearer <your access token>
```

HTTP

```
GET https://manage.devcenter.microsoft.com/v1.0/my/applications?
skip=20&top=10 HTTP/1.1
Authorization: Bearer <your access token>
```

HTTP

```
GET https://manage.devcenter.microsoft.com/v1.0/my/applications?
skip=30&top=10 HTTP/1.1
Authorization: Bearer <your access token>
```

If you already know the total number of apps you have in your account, you can simply pass that number in the **top** parameter to get information about all your apps.

HTTP

```
GET https://manage.devcenter.microsoft.com/v1.0/my/applications?top=23
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body returned by a successful request for the first 10 apps that are registered to a developer account with 21 total apps. For brevity, this example only shows the data for the first two apps returned by the request. For more details about the values in the response body, see the following section.

JSON

```
{
  "@nextLink": "applications?skip=10&top=10",
  "value": [
    {
      "id": "9NBLGGH4R315",
      "primaryName": "Contoso sample app",
      "packageFamilyName":
"5224ContosoDeveloper.ContosoSampleApp_ng6try80pwt52",
      "packageIdentityName": "5224ContosoDeveloper.ContosoSampleApp",
      "publisherName": "CN=...",
      "firstPublishedDate": "2016-03-11T01:32:11.0747851Z",
      "pendingApplicationSubmission": {
        "id": "1152921504621134883",
        "resourceLocation":
```

```

"applications/9NBLGGH4R315/submissions/1152921504621134883"
    }
  },
  {
    "id": "9NBLGGH29DM8",
    "primaryName": "Contoso sample app 2",
    "packageFamilyName":
"5224ContosoDeveloper.ContosoSampleApp2_ng6try80pwt52",
    "packageIdentityName": "5224ContosoDeveloper.ContosoSampleApp2",
    "publisherName": "CN=...",
    "firstPublishedDate": "2016-03-12T01:49:11.0747851Z",
    "lastPublishedApplicationSubmission": {
      "id": "1152921504621225621",
      "resourceLocation":
"applications/9NBLGGH29DM8/submissions/1152921504621225621"
    }
    // Next 8 apps are omitted for brevity ...
  }
],
"totalCount": 21
}

```

Response body

Value	Type	Description
value	array	An array of objects that contain information about each app that is registered to your account. For more information about the data in each object, see Application resource .
@nextLink	string	If there are additional pages of data, this string contains a relative path that you can append to the base https://manage.devcenter.microsoft.com/v1.0/my/ request URI to request the next page of data. For example, if the <i>top</i> parameter of the initial request body is set to 10 but there are 20 apps registered to your account, the response body will include a @nextLink value of <code>applications?skip=10&top=10</code> , which indicates that you can call https://manage.devcenter.microsoft.com/v1.0/my/applications?skip=10&top=10 to request the next 10 apps.
totalCount	int	The total number of rows in the data result for the query (that is, the total number of apps that are registered to your account).

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	No apps were found.
409	The apps use Partner Center features that are currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get an app](#)
- [Get package flights for an app](#)
- [Get add-ons for an app](#)

Get an app

Article • 11/01/2022

Use this method in the Microsoft Store submission API to retrieve information about a specific app that is registered to your Partner Center account.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app to retrieve. For more information about the Store ID, see View app identity details .

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to retrieve information about an app with the Store ID value 9NBLGGH4R315.

JSON

```
GET https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method. For more details about the values in the response body, see [Application resource](#).

JSON

```
{
  "id": "9NBLGGH4R315",
  "primaryName": "ApiTestApp",
  "packageFamilyName":
    "30481DevCenterAPITester.ApiTestAppForDevbox_ng6try80pwt52",
  "packageIdentityName": "30481DevCenterAPITester.ApiTestAppForDevbox",
  "publisherName": "CN=...",
  "firstPublishedDate": "1601-01-01T00:00:00Z",
  "lastPublishedApplicationSubmission": {
    "id": "1152921504621086517",
    "resourceLocation":
      "applications/9NBLGGH4R315/submissions/1152921504621086517"
  },
  "pendingApplicationSubmission": {
    "id": "1152921504621243487",
    "resourceLocation":
      "applications/9NBLGGH4R315/submissions/1152921504621243487"
  },
  "hasAdvancedListingPermission": false
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The specified app could not be found.
409	The app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get all apps](#)
- [Get package flights for an app](#)
- [Get add-ons for an app](#)

Get add-ons for an app

Article • 11/01/2022

Use this method in the Microsoft Store submission API to list the add-ons for an app that is registered to your Partner Center account.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/listinappproducts</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve the add-ons. For more information about the Store ID, see View app identity details .	Yes
top	int	The number of items to return in the request (that is, the number of add-ons to return). If the app has more add-ons than the value you specify in the query, the response body includes a relative URI path that you can append to the method URI to request the next page of data.	No
skip	int	The number of items to bypass in the query before returning the remaining items. Use this parameter to page through data sets. For example, top=10 and skip=0 retrieves items 1 through 10, top=10 and skip=10 retrieves items 11 through 20, and so on.	No

Request body

Do not provide a request body for this method.

Request examples

The following example demonstrates how to list all the add-ons for an app.

JSON

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/listinappproducts HTTP/1.1
Authorization: Bearer <your access token>
```

The following example demonstrates how to list the first 10 add-ons for an app.

JSON

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/listinappproducts?top=10 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body returned by a successful request for the first 10 add-ons for an app with 53 total add-ons. For brevity, this example only shows the data for the first three add-ons returned by the request. For more details about the values in the response body, see the following section.

JSON

```
{
  "@nextLink": "applications/9NBLGGH4R315/listinappproducts/?skip=10&top=10",
  "value": [
    {
      "inAppProductId": "9NBLGGH4TNMP"
    },
    {
      "inAppProductId": "9NBLGGH4TNMN"
    },
    {
      "inAppProductId": "9NBLGGH4TNNR"
    },
    // Next 7 add-ons are omitted for brevity ...
  ],
  "totalCount": 53
}
```

Response body

Value	Type	Description
@nextLink	string	If there are additional pages of data, this string contains a relative path that you can append to the base <code>https://manage.devcenter.microsoft.com/v1.0/my/</code> request URI to request the next page of data. For example, if the <i>top</i> parameter of the initial request body is set to 10 but there are 50 add-ons for the app, the response body will include a @nextLink value of <code>applications/{applicationid}/listinappproducts/?skip=10&top=10</code> , which indicates that you can call <code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationid}/listinappproducts/?skip=10&top=10</code> to request the next 10 add-ons.
value	array	An array of objects that list the Store ID of each add-on for the specified app. For more information about the data in each object, see add-on resource .
totalCount	int	The total number of rows in the data result for the query (that is, the total number of add-ons for the specified app).

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	No add-ons were found.
409	The add-ons use Partner Center features that are currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get all apps](#)
- [Get an app](#)
- [Get package flights for an app](#)

Get package flights for an app

Article • 11/01/2022

Use this method in the Microsoft Store submission API to list the package flights for an app that is registered to your Partner Center account. For more information about package flights, see [Package flights](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/listflights</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Name	Type	Description	Required
applicationId	string	The Store ID of the app for which you want to retrieve the package flights. For more information about the Store ID, see View app identity details .	Yes
top	int	The number of items to return in the request (that is, the number of package flights to return). If your account has more package flights than the value you specify in the query, the response body includes a relative URI path that you can append to the method URI to request the next page of data.	No

Name	Type	Description	Required
skip	int	The number of items to bypass in the query before returning the remaining items. Use this parameter to page through data sets. For example, top=10 and skip=0 retrieves items 1 through 10, top=10 and skip=10 retrieves items 11 through 20, and so on.	No

Request body

Do not provide a request body for this method.

Request examples

The following example demonstrates how to list all the package flights for an app.

JSON

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/listflights
HTTP/1.1
Authorization: Bearer <your access token>
```

The following example demonstrates how to list the first package flight for an app.

JSON

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/listflights
?top=1 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body returned by a successful request for the first package flight for an app with three total package flights. For more details about the values in the response body, see the following section.

JSON

```
{
  "value": [
    {
      "flightId": "7bfc11d5-f710-47c5-8a98-e04bb5aad310",
      "friendlyName": "myflight",
      "lastPublishedFlightSubmission": {
        "id": "1152921504621086517",
        "resourceLocation": "flights/7bfc11d5-f710-47c5-8a98-e04bb5aad310/submissions/1152921504621086517"
      }
    },
  ],
}
```

```
"pendingFlightSubmission": {
  "id": "1152921504621215786",
  "resourceLocation": "flights/7bfc11d5-f710-47c5-8a98-e04bb5aad310/submissions/1152921504621215786"
},
"groupIds": [
  "1152921504606962205"
],
"rankHigherThan": "Non-flighted submission"
},
],
"totalCount": 3
}
```

Response body

Value	Type	Description
@nextLink	string	If there are additional pages of data, this string contains a relative path that you can append to the base <code>https://manage.devcenter.microsoft.com/v1.0/my/</code> request URI to request the next page of data. For example, if the <i>top</i> parameter of the initial request body is set to 2 but there are 4 package flights for the app, the response body will include a @nextLink value of <code>applications/{applicationid}/listflights/?skip=2&top=2</code> , which indicates that you can call <code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationid}/listflights/?skip=2&top=2</code> to request the next 2 package flights.
value	array	An array of objects that provide information about package flights for the specified app. For more information about the data in each object, see Flight resource .
totalCount	int	The total number of rows in the data result for the query (that is, the total number of package flights for the specified app).

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	No package flights were found.
409	The app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get all apps](#)
- [Get an app](#)

- [Get add-ons for an app](#)

Manage app submissions

Article • 03/16/2023

The Microsoft Store submission API provides methods you can use to manage submissions for your apps, including gradual package rollouts. For an introduction to the Microsoft Store submission API, including prerequisites for using the API, see [Create and manage submissions using Microsoft Store services](#).

❗ Important

If you use the Microsoft Store submission API to create a submission for an app, be sure to make further changes to the submission only by using the API, rather than Partner Center. If you use Partner Center to change a submission that you originally created by using the API, you will no longer be able to change or commit that submission by using the API. In some cases, the submission could be left in an error state where it cannot proceed in the submission process. If this occurs, you must delete the submission and create a new submission.

❗ Important

You cannot use this API to publish submissions for **volume purchases through the Microsoft Store for Business and Microsoft Store for Education** or to publish submissions for **LOB apps** directly to enterprises. For both of these scenarios, you must use Partner Center to publish the submission.

Methods for managing app submissions

Use the following methods to get, create, update, commit, or delete an app submission. Before you can use these methods, the app must already exist in your Partner Center account and you must first create one submission for the app in Partner Center. For more information, see the [prerequisites](#).

Method	URI	Description
GET	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}	Get an existing app submission
GET	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/status	Get the status of an existing app submission
POST	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions	Create a new app submission
PUT	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}	Update an existing app submission
POST	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/commit	Commit a new or updated app submission
DELETE	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}	Delete an app submission

Create an app submission

To create a submission for an app, follow this process.

1. If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.

📌 Note

Make sure the app already has at least one completed submission with the **age ratings** information completed.

2. [Obtain an Azure AD access token](#). You must pass this access token to the methods in the Microsoft Store submission API. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
3. [Create an app submission](#) by executing the following method in the Microsoft Store submission API. This method creates a new in-progress submission, which is a copy of your last published submission.

JSON

```
POST https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions
```

The response body contains an [app submission](#) resource that includes the ID of the new submission, the shared access signature (SAS) URI for uploading any related files for the submission to Azure Blob Storage (such as app packages, listing images, and trailer files), and all of the data for the new submission (such as the listings and pricing information).

Note

A SAS URI provides access to a secure resource in Azure storage without requiring account keys. For background information about SAS URIs and their use with Azure Blob Storage, see [Shared Access Signatures, Part 1: Understanding the SAS model](#) and [Shared Access Signatures, Part 2: Create and use a SAS with Blob storage](#).

- If you are adding new packages, listing images, or trailer files for the submission, [prepare the app packages](#) and [prepare the app screenshots, images, and trailers](#). Add all of these files to a ZIP archive.
- Revise the [app submission](#) data with any required changes for the new submission, and execute the following method to [update the app submission](#).

JSON

```
PUT https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}
```

Note

If you are adding new files for the submission, make sure you update the submission data to refer to the name and relative path of these files in the ZIP archive.

- If you are adding new packages, listing images, or trailer files for the submission, upload the ZIP archive to [Azure Blob Storage](#) using the SAS URI that was provided in the response body of the POST method you called earlier. There are different Azure libraries you can use to do this on a variety of platforms, including:

- [Azure Storage Client Library for .NET](#)
- [Azure Storage SDK for Java](#)
- [Azure Storage SDK for Python](#)

The following C# code example demonstrates how to upload a ZIP archive to Azure Blob Storage using the [CloudBlockBlob](#) class in the Azure Storage Client Library for .NET. This example assumes that the ZIP archive has already been written to a stream object.

C#

```
string sasUrl = "https://productingestionbin1.blob.core.windows.net/ingestion/26920f66-b592-4439-9a9d-fb0f014902ec?sv=2014-02-14&sr=b&sig=usAN0kNFNnYE2tGQBI%2BARQWejX1Guiz7hdFtRhyk%2Bog%3D&se=2016-06-17T20:45:51Z&sp=rw1";
Microsoft.WindowsAzure.Storage.Blob.CloudBlockBlob blockBob =
    new Microsoft.WindowsAzure.Storage.Blob.CloudBlockBlob(new System.Uri(sasUrl));
await blockBob.UploadFromStreamAsync(stream);
```

- [Commit the app submission](#) by executing the following method. This will alert Partner Center that you are done with your submission and that your updates should now be applied to your account.

JSON

```
POST https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/commit
```

- Check on the commit status by executing the following method to [get the status of the app submission](#).

JSON

```
GET https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/status
```

To confirm the submission status, review the *status* value in the response body. This value should change from **CommitStarted** to either **PreProcessing** if the request succeeds or to **CommitFailed** if there are errors in the request. If there are errors, the *statusDetails* field contains further details about the error.

9. After the commit has successfully completed, the submission is sent to the Store for ingestion. You can continue to monitor the submission progress by using the previous method, or by visiting Partner Center.

Methods for managing a gradual package rollout

You can gradually roll out the updated packages in an app submission to a percentage of your app's customers on Windows 10 and Windows 11. This allows you to monitor feedback and analytic data for the specific packages to make sure you're confident about the update before rolling it out more broadly. You can change the rollout percentage (or halt the update) for a published submission without having to create a new submission. For more details, including instructions for how to enable and manage a gradual package rollout in Partner Center, see [this article](#).

To programmatically enable a gradual package rollout for an app submission, follow this process using methods in the Microsoft Store submission API:

1. [Create an app submission](#) or [get an existing app submission](#).
2. In the response data, locate the [packageRollout](#) resource, set the *isPackageRollout* field to **true**, and set the *packageRolloutPercentage* field to the percentage of your app's customers who should get the updated packages.
3. Pass the updated app submission data to the [update an app submission](#) method.

After a gradual package rollout is enabled for an app submission, you can use the following methods to programmatically get, update, halt, or finalize the gradual rollout.

Method	URI	Description
GET	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/packagerollout	Get the gradual rollout info for an app submission
POST	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/updatepackagerolloutpercentage	Update the gradual rollout percentage for an app submission
POST	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/haltpackagerollout	Halt the gradual rollout for an app submission
POST	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/finalizepackagerollout	Finalize the gradual rollout for an app submission

Code examples for managing app submissions

The following articles provide detailed code examples that demonstrate how to create an app submission in several different programming languages:

- [C# sample: submissions for apps, add-ons, and flights](#)
- [C# sample: app submission with game options and trailers](#)
- [Java sample: submissions for apps, add-ons, and flights](#)
- [Java sample: app submission with game options and trailers](#)
- [Python sample: submissions for apps, add-ons, and flights](#)
- [Python sample: app submission with game options and trailers](#)

StoreBroker PowerShell module

As an alternative to calling the Microsoft Store submission API directly, we also provide an open-source PowerShell module which implements a command-line interface on top of the API. This module is called [StoreBroker](#). You can use this module to manage your app, flight, and add-on submissions from the command line instead of calling the Microsoft Store submission API directly, or you can simply

browse the source to see more examples for how to call this API. The StoreBroker module is actively used within Microsoft as the primary way that many first-party applications are submitted to the Store.

For more information, see our [StoreBroker page on GitHub](#).

Data resources

The Microsoft Store submission API methods for managing app submissions use the following JSON data resources.

App submission resource

This resource describes an app submission.

JSON

```
{
  "id": "1152921504621243540",
  "applicationCategory": "BooksAndReference_EReader",
  "pricing": {
    "trialPeriod": "FifteenDays",
    "marketSpecificPricings": {},
    "sales": [],
    "priceId": "Tier2",
    "isAdvancedPricingModel": true
  },
  "visibility": "Public",
  "targetPublishMode": "Manual",
  "targetPublishDate": "1601-01-01T00:00:00Z",
  "listings": {
    "en-us": {
      "baseListing": {
        "copyrightAndTrademarkInfo": "",
        "keywords": [
          "epub"
        ],
        "licenseTerms": "",
        "privacyPolicy": "",
        "supportContact": "",
        "websiteUrl": "",
        "description": "Description",
        "features": [
          "Free ebook reader"
        ],
        "releaseNotes": "",
        "images": [
          {
            "fileName": "contoso.png",
            "fileStatus": "Uploaded",
            "id": "1152921504672272757",
            "description": "Main page",
            "imageType": "Screenshot"
          }
        ],
        "recommendedHardware": [],
        "title": "Contoso ebook reader"
      },
      "platformOverrides": {
        "Windows81": {
          "description": "Ebook reader for Windows 8.1"
        }
      }
    }
  },
  "hardwarePreferences": [
    "Touch"
  ],
  "automaticBackupEnabled": false,
  "canInstallOnRemovableMedia": true,
  "isGameDvrEnabled": false,
  "gamingOptions": [],
  "hasExternalInAppProducts": false,
  "meetAccessibilityGuidelines": true,
  "notesForCertification": "",
  "status": "PendingCommit",
  "statusDetails": {
    "errors": [],
    "warnings": [],
    "certificationReports": []
  }
}
```

```

},
"fileUploadUrl": "https://productingestionbin1.blob.core.windows.net/ingestion/387a9ea8-a412-43a9-8fb3-a38d03eb483d?sv=2014-02-14&sr=b&sig=sdd12JmoaT6BhVC%2BZUrwRwEA%2Fkvj%2BEBCY09C2SZZowg%3D&se=2016-06-17T18:32:26Z&sp=rwl",
"applicationPackages": [
  {
    "fileName": "contoso_app.appx",
    "fileStatus": "Uploaded",
    "id": "1152921504620138797",
    "version": "1.0.0.0",
    "architecture": "ARM",
    "languages": [
      "en-US"
    ],
    "capabilities": [
      "ID_RESOLUTION_HD720P",
      "ID_RESOLUTION_WVGA",
      "ID_RESOLUTION_WXGA"
    ],
    "minimumDirectXVersion": "None",
    "minimumSystemRam": "None",
    "targetDeviceFamilies": [
      "Windows.Mobile min version 10.0.10240.0"
    ]
  }
],
"packageDeliveryOptions": {
  "packageRollout": {
    "isPackageRollout": false,
    "packageRolloutPercentage": 0.0,
    "packageRolloutStatus": "PackageRolloutNotStarted",
    "fallbackSubmissionId": "0"
  },
  "isMandatoryUpdate": false,
  "mandatoryUpdateEffectiveDate": "1601-01-01T00:00:00.0000000Z"
},
"enterpriseLicensing": "Online",
"allowMicrosoftDecideAppAvailabilityToFutureDeviceFamilies": true,
"allowTargetFutureDeviceFamilies": {
  "Desktop": false,
  "Mobile": true,
  "Holographic": true,
  "Xbox": false,
  "Team": true
},
"friendlyName": "Submission 2",
"trailers": []
}

```

This resource has the following values.

Value	Type	Description
id	string	The ID of the submission. This ID is available in the response data for requests to create an app submission , get all apps , and get an app . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.
applicationCategory	string	A string that specifies the category and/or subcategory for your app. Categories and subcategories are combined into a single string with the underscore '_' character, such as BooksAndReference_EReader .
pricing	object	A pricing resource that contains pricing info for the app.
visibility	string	The visibility of the app. This can be one of the following values: - Hidden - Public - Private - NotSet
targetPublishMode	string	The publish mode for the submission. This can be one of the following values: - Immediate - Manual - SpecificDate
targetPublishDate	string	The publish date for the submission in ISO 8601 format, if the <i>targetPublishMode</i> is set to SpecificDate.

Value	Type	Description
listings	object	A dictionary of key and value pairs, where each key is a country code and each value is a listing resource that contains listing info for the app.
hardwarePreferences	array	An array of strings that define the hardware preferences for your app. This can be one of the following values: • Touch • Keyboard • Mouse • Camera • NfcHce • Nfc • BluetoothLE • Telephony
automaticBackupEnabled	boolean	Indicates whether Windows can include your app's data in automatic backups to OneDrive. For more information, see App declarations .
canInstallOnRemovableMedia	boolean	Indicates whether customers can install your app to removable storage. For more information, see App declarations .
isGameDvrEnabled	boolean	Indicates whether game DVR is enabled for the app.
gamingOptions	array	An array that contains one gaming options resource that defines game-related settings for the app.
hasExternalInAppProducts	boolean	Indicates whether your app allows users to make purchase outside the Microsoft Store commerce system. For more information, see App declarations .
meetAccessibilityGuidelines	boolean	Indicates whether your app has been tested to meet accessibility guidelines. For more information, see App declarations .
notesForCertification	string	Contains notes for certification for your app.
status	string	The status of the submission. This can be one of the following values: • None • Canceled • PendingCommit • CommitStarted • CommitFailed • PendingPublication • Publishing • Published • PublishFailed • PreProcessing • PreProcessingFailed • Certification • CertificationFailed • Release • ReleaseFailed
statusDetails	object	A status details resource that contains additional details about the status of the submission, including information about any errors.
fileUploadUrl	string	The shared access signature (SAS) URI for uploading any packages for the submission. If you are adding new packages, listing images, or trailer files for the submission, upload the ZIP archive that contains the packages and images to this URI. For more information, see Create an app submission .
applicationPackages	array	An array of application package resources that provide details about each package in the submission.
packageDeliveryOptions	object	A package delivery options resource that contains gradual package rollout and mandatory update settings for the submission.
enterpriseLicensing	string	One of the enterprise licensing values values that indicate the enterprise licensing behavior for the app.
allowMicrosoftDecideAppAvailabilityToFutureDeviceFamilies	boolean	Indicates whether Microsoft is allowed to make the app available to future Windows 10 and Windows 11 device families .
allowTargetFutureDeviceFamilies	object	A dictionary of key and value pairs, where each key is a Windows 10 and Windows 11 device family and each value is a boolean that indicates whether your app is allowed to target the specified device family.

Value	Type	Description
friendlyName	string	The friendly name of the submission, as shown in Partner Center. This value is generated for you when you create the submission.
trailers	array	An array that contains up to 15 trailer resources that represent video trailers for the app listing.

Pricing resource

This resource contains pricing info for the app. This resource has the following values.

Value	Type	Description
trialPeriod	string	A string that specifies the trial period for the app. This can be one of the following values: - NoFreeTrial - OneDay - TrialNeverExpires - SevenDays - FifteenDays - ThirtyDays
marketSpecificPricings	object	A dictionary of key and value pairs, where each key is a two-letter ISO 3166-1 alpha-2 country code and each value is a price tier . These items represent the custom prices for your app in specific markets . Any items in this dictionary override the base price specified by the <i>priceId</i> value for the specified market.
sales	array	Deprecated. An array of sale resources that contain sales information for the app.
priceId	string	A price tier that specifies the base price for the app.
isAdvancedPricingModel	boolean	If true , your developer account has access to the expanded set of price tiers from .99 USD to 1999.99 USD. If false , your developer account has access to the original set of price tiers from .99 USD to 999.99 USD. For more information about the different tiers, see price tiers . Note This field is read-only.

Sale resource

This resources contains sale info for an app.

Important

The **Sale** resource is no longer supported, and currently you cannot get or modify the sale data for an app submission using the Microsoft Store submission API. In the future, we will update the Microsoft Store submission API to introduce a new way to programmatically access sales information for app submissions.

- After calling the [GET method to get an app submission](#), the *sales* value will be empty. You can continue to use Partner Center to get the sale data for your app submission.
- When calling the [PUT method to update an app submission](#), the information in the *sales* value is ignored. You can continue to use Partner Center to change the sale data for your app submission.

This resource has the following values.

Value	Type	Description
name	string	The name of the sale.
basePriceId	string	The price tier to use for the base price of the sale.
startDate	string	The start date for the sale in ISO 8601 format.
endDate	string	The end date for the sale in ISO 8601 format.
marketSpecificPricings	object	A dictionary of key and value pairs, where each key is a two-letter ISO 3166-1 alpha-2 country code and each value is a price tier . These items represent the custom prices for your app in specific markets . Any items in this dictionary override the base price specified by the <i>basePriceId</i> value for the specified market.

Listing resource

This resource contains listing info for an app. This resource has the following values.

Value	Type	Description
baseListing	object	The base listing info for the app, which defines the default listing info for all platforms.
platformOverrides	object	A dictionary of key and value pairs, where each key is string that identifies a platform for which to override the listing info, and each value is a base listing resource (containing only the values from description to title) that specifies the listing info to override for the specified platform. The keys can have the following values: - Unknown - Windows80 - Windows81 - WindowsPhone71 - WindowsPhone80 - WindowsPhone81

Base listing resource

This resource contains base listing info for an app. This resource has the following values.

Value	Type	Description
copyrightAndTrademarkInfo	string	Optional copyright and/or trademark info .
keywords	array	An array of keyword to help your app appear in search results.
licenseTerms	string	The optional license terms for your app.
privacyPolicy	string	This value is obsolete. To set or change the privacy policy URL for your app, you must do this on the Properties page in Partner Center. You can omit this value from your calls to the submission API. If you set this value, it will be ignored.
supportContact	string	This value is obsolete. To set or change the support contact URL or email address for your app, you must do this on the Properties page in Partner Center. You can omit this value from your calls to the submission API. If you set this value, it will be ignored.
websiteUrl	string	This value is obsolete. To set or change the URL of the web page for your app, you must do this on the Properties page in Partner Center. You can omit this value from your calls to the submission API. If you set this value, it will be ignored.
description	string	The description for the app listing.
features	array	An array of up to 20 strings that list the features for your app.
releaseNotes	string	The release notes for your app.
images	array	An array of image and icon resources for the app listing.
recommendedHardware	array	An array of up to 11 strings that list the recommended hardware configurations for your app.
minimumHardware	string	An array of up to 11 strings that list the minimum hardware configurations for your app.
title	string	The title for the app listing.
shortDescription	string	Only used for games. This description appears in the Information section of the Game Hub on Xbox One, and helps customers understand more about your game.
shortTitle	string	A shorter version of your product's name. If provided, this shorter name may appear in various places on Xbox One (during installation, in Achievements, etc.) in place of the full title of your product.
sortTitle	string	If your product could be alphabetized in different ways, you can enter another version here. This may help customers find the product more quickly when searching.
voiceTitle	string	An alternate name for your product that, if provided, may be used in the audio experience on Xbox One when using Kinect or a headset.
devStudio	string	Specify this value if you want to include a Developed by field in the listing. (The Published by field will list the publisher display name associated with your account, whether or not you provide a <i>devStudio</i> value.)

Image resource

This resource contains image and icon data for an app listing. For more information about images and icons for an app listing, see [App screenshots and images](#). This resource has the following values.

Value	Type	Description
fileName	string	The name of the image file in the ZIP archive that you uploaded for the submission.
fileStatus	string	The status of the image file. This can be one of the following values: - None - PendingUpload - Uploaded - PendingDelete
id	string	The ID for the image. This value is supplied by Partner Center.
description	string	The description for the image.
imageType	string	Indicates the type of the image. The following strings are currently supported. Screenshot images : - Screenshot (use this value for the desktop screenshot) - MobileScreenshot - XboxScreenshot - SurfaceHubScreenshot - HoloLensScreenshot Store logos : - StoreLogo9x16 - StoreLogoSquare - Icon (use this value for the 1:1 300 x 300 pixels logo) Promotional images : - PromotionalArt16x9 - PromotionalArtwork2400X1200 Xbox images : - XboxBrandedKeyArt - XboxTitledHeroArt - XboxFeaturedPromotionalArt Optional promotional images : - SquareIcon358X358 - BackgroundImage1000X800 - PromotionalArtwork414X180

Gaming options resource

This resource contains game-related settings for the app. The values in this resource correspond to the [game settings](#) for submissions in Partner Center.

JSON

```
{
  "gamingOptions": [
    {
      "genres": [
        "Games_ActionAndAdventure",
        "Games_Casino"
      ],
      "isLocalMultiplayer": true,
      "isLocalCooperative": true,
      "isOnlineMultiplayer": false,
      "isOnlineCooperative": false,
      "localMultiplayerMinPlayers": 2,
      "localMultiplayerMaxPlayers": 12,
      "localCooperativeMinPlayers": 2,
      "localCooperativeMaxPlayers": 12,
      "isBroadcastingPrivilegeGranted": true,
      "isCrossPlayEnabled": false,
      "kinectDataForExternal": "Enabled"
    }
  ]
}
```

```
  },  
}
```

This resource has the following values.

Value	Type	Description
genres	array	An array of one or more of the following strings that describe the genres of the game: - Games_ActionAndAdventure - Games_CardAndBoard - Games_Casino - Games_Educational - Games_FamilyAndKids - Games_Fighting - Games_Music - Games_Platformer - Games_PuzzleAndTrivia - Games_RacingAndFlying - Games_RolePlaying - Games_Shooter - Games_Simulation - Games_Sports - Games_Strategy - Games_Word
isLocalMultiplayer	boolean	Indicates whether the game supports local multiplayer.
isLocalCooperative	boolean	Indicates whether the game supports local co-op.
isOnlineMultiplayer	boolean	Indicates whether the game supports online multiplayer.
isOnlineCooperative	boolean	Indicates whether the game supports online co-op.
localMultiplayerMinPlayers	int	Specifies the minimum number of players the game supports for local multiplayer.
localMultiplayerMaxPlayers	int	Specifies the maximum number of players the game supports for local multiplayer.
localCooperativeMinPlayers	int	Specifies the minimum number of players the game supports for local co-op.
localCooperativeMaxPlayers	int	Specifies the maximum number of players the game supports for local co-op.
isBroadcastingPrivilegeGranted	boolean	Indicates whether the game supports broadcasting.
isCrossPlayEnabled	boolean	Indicates whether the game supports multiplayer sessions between players on Windows 10 and Windows 11 PCs and Xbox.
kinectDataForExternal	string	One of the following string values that indicates whether the game can collect Kinect data and send it to external services: - NotSet - Unknown - Enabled - Disabled

Note

The *gamingOptions* resource was added in May 2017, after the Microsoft Store submission API was first released to developers. If you created a submission for an app via the submission API before this resource was introduced and this submission is still in progress, this resource will be null for submissions for the app until you successfully commit the submission or you delete it. If the *gamingOptions* resource is not available for submissions for an app, the *hasAdvancedListingPermission* field of the **Application** resource returned by the **get an app** method is false.

Status details resource

This resource contains additional details about the status of a submission. This resource has the following values.

Value	Type	Description
errors	object	An array of status detail resources that contain error details for the submission.
warnings	object	An array of status detail resources that contain warning details for the submission.

Value	Type	Description
certificationReports	object	An array of certification report resources that provide access to the certification report data for the submission. You can examine these reports for more information if the certification fails.

Status detail resource

This resource contains additional information about any related errors or warnings for a submission. This resource has the following values.

Value	Type	Description
code	string	A submission status code that describes the type of error or warning.
details	string	A message with more details about the issue.

Application package resource

This resource contains details about an app package for the submission.

```
JSON

{
  "applicationPackages": [
    {
      "fileName": "contoso_app.appx",
      "fileStatus": "Uploaded",
      "id": "1152921504620138797",
      "version": "1.0.0.0",
      "architecture": "ARM",
      "languages": [
        "en-US"
      ],
      "capabilities": [
        "ID_RESOLUTION_HD720P",
        "ID_RESOLUTION_WVGA",
        "ID_RESOLUTION_WXGA"
      ],
      "minimumDirectXVersion": "None",
      "minimumSystemRam": "None",
      "targetDeviceFamilies": [
        "Windows.Mobile min version 10.0.10240.0"
      ]
    }
  ],
}
```

This resource has the following values.

 **Note**

When calling the `update an app submission` method, only the `fileName`, `fileStatus`, `minimumDirectXVersion`, and `minimumSystemRam` values of this object are required in the request body. The other values are populated by Partner Center.

Value	Type	Description
fileName	string	The name of the package.
fileStatus	string	The status of the package. This can be one of the following values: - None - PendingUpload - Uploaded - PendingDelete
id	string	An ID that uniquely identifies the package. This value is provided by Partner Center.
version	string	The version of the app package. For more information, see Package version numbering .
architecture	string	The architecture of the package (for example, ARM).
languages	array	An array of language codes for the languages the app supports. For more information, see Supported languages .

Value	Type	Description
capabilities	array	An array of capabilities required by the package. For more information about capabilities, see App capability declarations .
minimumDirectXVersion	string	The minimum DirectX version that is supported by the app package. This can be set only for apps that target Windows 8.x. For apps that target other OS versions, this value must be present when calling the update an app submission method but the value you specify is ignored. This can be one of the following values: - None - DirectX93 - DirectX100
minimumSystemRam	string	The minimum RAM that is required by the app package. This can be set only for apps that target Windows 8.x. For apps that target other OS versions, this value must be present when calling the update an app submission method but the value you specify is ignored. This can be one of the following values: - None - Memory2GB
targetDeviceFamilies	array	An array of strings that represent the device families that the package targets. This value is used only for packages that target Windows 10; for packages that target earlier releases, this value has the value None . The following device family strings are currently supported for Windows 10 and Windows 11 packages, where <i>{0}</i> is a Windows 10 or Windows 11 version string such as 10.0.10240.0, 10.0.10586.0 or 10.0.14393.0: - Windows.Universal min version <i>{0}</i> - Windows.Desktop min version <i>{0}</i> - Windows.Mobile min version <i>{0}</i> - Windows.Xbox min version <i>{0}</i> - Windows.Holographic min version <i>{0}</i>

id="certification-report-resource"

Certification report resource

This resource provides access to the certification report data for a submission. This resource has the following values.

Value	Type	Description
date	string	The date and time the report was generated, in ISO 8601 format.
reportUrl	string	The URL at which you can access the report.

Package delivery options resource

This resource contains gradual package rollout and mandatory update settings for the submission.

JSON
<pre>{ "packageDeliveryOptions": { "packageRollout": { "isPackageRollout": false, "packageRolloutPercentage": 0, "packageRolloutStatus": "PackageRolloutNotStarted", "fallbackSubmissionId": "0" }, "isMandatoryUpdate": false, "mandatoryUpdateEffectiveDate": "1601-01-01T00:00:00.0000000Z" }, }</pre>

This resource has the following values.

Value	Type	Description
packageRollout	object	A package rollout resource that contains gradual package rollout settings for the submission.
isMandatoryUpdate	boolean	Indicates whether you want to treat the packages in this submission as mandatory for self-installing app updates. For more information about mandatory packages for self-installing app updates, see Download and install package updates for your app .

Value	Type	Description
mandatoryUpdateEffectiveDate	date	The date and time when the packages in this submission become mandatory, in ISO 8601 format and UTC time zone.

Package rollout resource

This resource contains gradual [package rollout settings](#) for the submission. This resource has the following values.

Value	Type	Description
isPackageRollout	boolean	Indicates whether gradual package rollout is enabled for the submission.
packageRolloutPercentage	float	The percentage of users who will receive the packages in the gradual rollout.
packageRolloutStatus	string	One of the following strings that indicates the status of the gradual package rollout: - PackageRolloutNotStarted - PackageRolloutInProgress - PackageRolloutComplete - PackageRolloutStopped
fallbackSubmissionId	string	The ID of the submission that will be received by customers who do not get the gradual rollout packages.

Note

The *packageRolloutStatus* and *fallbackSubmissionId* values are assigned by Partner Center, and are not intended to be set by the developer. If you include these values in a request body, these values will be ignored.

Trailers resource

This resource represents a video trailer for the app listing. The values in this resource correspond to the [trailers](#) options for submissions in Partner Center.

You can add up to 15 trailer resources to the *trailers* array in an [app submission resource](#). To upload trailer video files and thumbnail images for a submission, add these files to the same ZIP archive that contains the packages and listing images for the submission, and then upload this ZIP archive to the shared access signature (SAS) URI for the submission. For more information uploading the ZIP archive to the SAS URI, see [Create an app submission](#).

JSON

```
{
  "trailers": [
    {
      "id": "1158943556954955699",
      "videoFileName": "Trailers\\ContosoGameTrailer.mp4",
      "videoFileId": "1159761554639123258",
      "trailerAssets": {
        "en-us": {
          "title": "Contoso Game",
          "imageList": [
            {
              "fileName": "Images\\ContosoGame-Thumbnail.png",
              "id": "1155546904097346923",
              "description": "This is a still image from the video."
            }
          ]
        }
      }
    }
  ]
}
```

This resource has the following values.

Value	Type	Description
id	string	The ID for the trailer. This value is provided by Partner Center.
videoFileName	string	The name of the trailer video file in the ZIP archive that contains files for the submission.

Value	Type	Description
videoFileId	string	The ID for the trailer video file. This value is provided by Partner Center.
trailerAssets	object	A dictionary of key and value pairs, where each key is a language code and each value is a trailer assets resource that contains additional locale-specific assets for the trailer. For more information about the supported language codes, see Supported languages .

Note

The *trailers* resource was added in May 2017, after the Microsoft Store submission API was first released to developers. If you created a submission for an app via the submission API before this resource was introduced and this submission is still in progress, this resource will be null for submissions for the app until you successfully commit the submission or you delete it. If the *trailers* resource is not available for submissions for an app, the *hasAdvancedListingPermission* field of the **Application** resource returned by the **get an app** method is false.

Trailer assets resource

This resource contains additional locale-specific assets for a trailer that is defined in a [trailer resource](#). This resource has the following values.

Value	Type	Description
title	string	The localized title of the trailer. The title is displayed when the user plays the trailer in full screen mode.
imageList	array	An array that contains one image resource that provides the thumbnail image for the trailer. You can only include one image resource in this array.

Image resource (for a trailer)

This resource describes the thumbnail image for a trailer. This resource has the following values.

Value	Type	Description
fileName	string	The name of the thumbnail image file in the ZIP archive that you uploaded for the submission.
id	string	The ID for the thumbnail image. This value is provided by Partner Center.
description	string	The description for the thumbnail image. This value is metadata only, and is not displayed to users.

Enums

These methods use the following enums.

Price tiers

The following values represent available price tiers in the [pricing resource](#) resource for an app submission.

Value	Description
Base	The price tier is not set; use the base price for the app.
NotAvailable	The app is not available in the specified region.
Free	The app is free.
Tierxxx	A string that specifies the price tier for the app, in the format Tierxxxx. Currently, the following ranges of price tiers are supported: - If the <i>isAdvancedPricingModel</i> value of the pricing resource is true, the available price tier values for your account are Tier1012 - Tier1424. - If the <i>isAdvancedPricingModel</i> value of the pricing resource is false, the available price tier values for your account are Tier2 - Tier96. To see the complete table of price tiers that are available for your developer account, including the market-specific prices that are associated with each tier, go to the Pricing and availability page for any of your app submissions in Partner Center and click the view table link in the Markets and custom prices section (for some developer accounts, this link is in the Pricing section).

Enterprise licensing values

The following values represent the organizational licensing behavior for the app. For more information about these options, see [Organizational licensing options](#).

Note

Although you can configure the organizational licensing options for an app submission via the submission API, you cannot use this API to publish submissions for **volume purchases through the Microsoft Store for Business and Microsoft Store for Education**. To publish submissions to the Microsoft Store for Business and Microsoft Store for Education, you must use Partner Center.

Value	Description
None	Do not make your app available to enterprises with Store-managed (online) volume licensing.
Online	Make your app available to enterprises with Store-managed (online) volume licensing.
OnlineAndOffline	Make your app available to enterprises with Store-managed (online) volume licensing, and make your app available to enterprises via disconnected (offline) licensing.

Submission status code

The following values represent the status code of a submission.

Value	Description
None	No code was specified.
InvalidArchive	The ZIP archive containing the package is invalid or has an unrecognized archive format.
MissingFiles	The ZIP archive does not have all files which were listed in your submission data, or they are in the wrong location in the archive.
PackageValidationFailed	One or more packages in your submission failed to validate.
InvalidParameterValue	One of the parameters in the request body is invalid.
InvalidOperation	The operation you attempted is invalid.
InvalidState	The operation you attempted is not valid for the current state of the package flight.
ResourceNotFound	The specified package flight could not be found.
ServiceError	An internal service error prevented the request from succeeding. Try the request again.
ListingOptOutWarning	The developer removed a listing from a previous submission, or did not include listing information that is supported by the package.
ListingOptInWarning	The developer added a listing.
UpdateOnlyWarning	The developer is trying to insert something that only has update support.
Other	The submission is in an unrecognized or uncategorized state.
PackageValidationWarning	The package validation process resulted in a warning.

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get app data using the Microsoft Store submission API](#)
- [App submissions in Partner Center](#)

Get an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to get data for an existing app submission. For more information about the process of creating an app submission by using the Microsoft Store submission API, see [Manage app submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create a submission for one of your apps. You can do this in Partner Center, or you can do this by using the [create an app submission](#) method.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app with the submission you want to get. For more information about the Store ID, see View app identity details .
submissionId	string	Required. The ID of the submission to get. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to get an app submission.

JSON

GET

`https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/1152921504621243680 HTTP/1.1`

Authorization: Bearer <your access token>

Response

The following example demonstrates the JSON response body for a successful call to this method.

The response body contains information about the specified submission. For more details about the values in the response body, see [App submission resource](#).

JSON

```
{
  "id": "1152921504621243540",
  "applicationCategory": "BooksAndReference_EReader",
  "pricing": {
    "trialPeriod": "FifteenDays",
    "marketSpecificPricings": {},
    "sales": [],
    "priceId": "Tier2",
    "isAdvancedPricingModel": true
  },
  "visibility": "Public",
  "targetPublishMode": "Manual",
  "targetPublishDate": "1601-01-01T00:00:00Z",
  "listings": {
    "en-us": {
      "baseListing": {
        "copyrightAndTrademarkInfo": "",
        "keywords": [
          "epub"
        ],
        "licenseTerms": "",
        "privacyPolicy": "",
        "supportContact": "",
        "websiteUrl": "",
        "description": "Description",
        "features": [
          "Free ebook reader"
        ],
        "releaseNotes": "",
        "images": [
          {
            "fileName": "contoso.png",
```

```

        "fileStatus": "Uploaded",
        "id": "1152921504672272757",
        "imageType": "Screenshot"
    }
],
"recommendedHardware": [],
"title": "Contoso ebook reader"
},
"platformOverrides": {
    "Windows81": {
        "description": "Ebook reader for Windows 8.1"
    }
}
},
"hardwarePreferences": [
    "Touch"
],
"automaticBackupEnabled": false,
"canInstallOnRemovableMedia": true,
"isGameDvrEnabled": false,
"gamingOptions": [],
"hasExternalInAppProducts": false,
"meetAccessibilityGuidelines": true,
"notesForCertification": "",
"status": "PendingCommit",
"statusDetails": {
    "errors": [],
    "warnings": [],
    "certificationReports": []
},
"fileUploadUrl":
"https://productingestionbin1.blob.core.windows.net/ingestion/387a9ea8-a412-43a9-8fb3-
a38d03eb483d?sv=2014-02-
14&sr=b&sig=sdd12JmoaT6BhVC%2BZUrwRweA%2Fkvj%2BEBCY09C2SZZowg%3D&se=2016-06-
17T18:32:26Z&sp=rwl",
"applicationPackages": [
    {
        "fileName": "contoso_app.appx",
        "fileStatus": "Uploaded",
        "id": "1152921504620138797",
        "version": "1.0.0.0",
        "architecture": "ARM",
        "languages": [
            "en-US"
        ],
        "capabilities": [
            "ID_RESOLUTION_HD720P",
            "ID_RESOLUTION_WVGA",
            "ID_RESOLUTION_WXGA"
        ],
        "minimumDirectXVersion": "None",
        "minimumSystemRam": "None",
        "targetDeviceFamilies": [
            "Windows.Mobile min version 10.0.10240.0"
        ]
    }
],
"packageDeliveryOptions": {
    "packageRollout": {
        "isPackageRollout": false,

```

```
    "packageRolloutPercentage": 0.0,
    "packageRolloutStatus": "PackageRolloutNotStarted",
    "fallbackSubmissionId": "0"
  },
  "isMandatoryUpdate": false,
  "mandatoryUpdateEffectiveDate": "1601-01-01T00:00:00.0000000Z"
},
"enterpriseLicensing": "Online",
"allowMicrosoftDecideAppAvailabilityToFutureDeviceFamilies": true,
"allowTargetFutureDeviceFamilies": {
  "Desktop": false,
  "Mobile": true,
  "Holographic": true,
  "Xbox": false,
  "Team": true
},
"friendlyName": "Submission 2",
"trailers": []
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The submission could not be found.
409	The submission does not belong to the specified app, or the app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Create an app submission](#)
- [Commit an app submission](#)
- [Update an app submission](#)
- [Delete an app submission](#)
- [Get the status of an app submission](#)

Get the status of an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to get the status of an app submission. For more information about the process of creating an app submission by using the Microsoft Store submission API, see [Manage app submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/status</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app that contains the submission for which you want to get the status. For more information about the Store ID, see View app identity details .
submissionId	string	Required. The ID of the submission for which you want to get the status. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to get the status of an app submission.

JSON

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/1152921504621243610/status HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method. The response body contains information about the specified submission. For more details about the values in the response body, see the following sections.

JSON

```
{
  "status": "PendingCommit",
  "statusDetails": {
    "errors": [],
    "warnings": [],
    "certificationReports": []
  },
}
```

Response body

Value	Type	Description
status	string	The status of the submission. This can be one of the following values: • None • Canceled • PendingCommit • CommitStarted • CommitFailed • PendingPublication • Publishing • Published • PublishFailed • PreProcessing • PreProcessingFailed • Certification • CertificationFailed • Release • ReleaseFailed
statusDetails	object	Contains additional details about the status of the submission, including information about any errors. For more information, see the Status details resource .

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The submission could not be found.
409	The app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get an app submission](#)
- [Create an app submission](#)
- [Commit an app submission](#)
- [Update an app submission](#)
- [Delete an app submission](#)

Create an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to create a new submission for an app that is registered to your Partner Center account. After you successfully create a new submission by using this method, [update the submission](#) to make any necessary changes to the submission data, and then [commit the submission](#) for ingestion and publishing.

For more information about how this method fits into the process of creating an app submission by using the Microsoft Store submission API, see [Manage app submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Make sure the app already has at least one submission with the [age ratings](#) information completed.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
POST	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app for which you want to create a submission. For more information about the Store ID, see View app identity details .

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to create a new submission for an app.

JSON

POST

`https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions HTTP/1.1`

`Authorization: Bearer <your access token>`

Response

The following example demonstrates the JSON response body for a successful call to this method. The response body contains information about the new submission. For more details about the values in the response body, see [App submission resource](#).

JSON

```
{
  "id": "1152921504621243540",
  "applicationCategory": "BooksAndReference_EReader",
  "pricing": {
    "trialPeriod": "FifteenDays",
    "marketSpecificPricings": {},
    "sales": [],
    "priceId": "Tier2",
    "isAdvancedPricingModel": true
  },
  "visibility": "Public",
  "targetPublishMode": "Manual",
  "targetPublishDate": "1601-01-01T00:00:00Z",
  "listings": {
    "en-us": {
```

```

"baseListing": {
  "copyrightAndTrademarkInfo": "",
  "keywords": [
    "epub"
  ],
  "licenseTerms": "",
  "privacyPolicy": "",
  "supportContact": "",
  "websiteUrl": "",
  "description": "Description",
  "features": [
    "Free ebook reader"
  ],
  "releaseNotes": "",
  "images": [
    {
      "fileName": "contoso.png",
      "fileStatus": "Uploaded",
      "id": "1152921504672272757",
      "imageType": "Screenshot"
    }
  ],
  "recommendedHardware": [],
  "title": "Contoso ebook reader"
},
"platformOverrides": {
  "Windows81": {
    "description": "Ebook reader for Windows 8.1"
  }
}
},
"hardwarePreferences": [
  "Touch"
],
"automaticBackupEnabled": false,
"canInstallOnRemovableMedia": true,
"isGameDvrEnabled": false,
"gamingOptions": [],
"hasExternalInAppProducts": false,
"meetAccessibilityGuidelines": true,
"notesForCertification": "",
"status": "PendingCommit",
"statusDetails": {
  "errors": [],
  "warnings": [],
  "certificationReports": []
},
"fileUploadUrl":
"https://productingestionbin1.blob.core.windows.net/ingestion/387a9ea8-a412-43a9-8fb3-a38d03eb483d?sv=2014-02-14&sr=b&sig=sdd12JmoaT6BhvC%2BZUrwRweA%2Fkvj%2BEBY09C2SZZowg%3D&se=2016-06-17T18:32:26Z&sp=rwl",
"applicationPackages": [
  {

```

```

    "fileName": "contoso_app.appx",
    "fileStatus": "Uploaded",
    "id": "1152921504620138797",
    "version": "1.0.0.0",
    "architecture": "ARM",
    "languages": [
        "en-US"
    ],
    "capabilities": [
        "ID_RESOLUTION_HD720P",
        "ID_RESOLUTION_WVGA",
        "ID_RESOLUTION_WXGA"
    ],
    "minimumDirectXVersion": "None",
    "minimumSystemRam": "None",
    "targetDeviceFamilies": [
        "Windows.Mobile min version 10.0.10240.0"
    ]
  },
  "packageDeliveryOptions": {
    "packageRollout": {
      "isPackageRollout": false,
      "packageRolloutPercentage": 0.0,
      "packageRolloutStatus": "PackageRolloutNotStarted",
      "fallbackSubmissionId": "0"
    },
    "isMandatoryUpdate": false,
    "mandatoryUpdateEffectiveDate": "1601-01-01T00:00:00.0000000Z"
  },
  "enterpriseLicensing": "Online",
  "allowMicrosoftDecideAppAvailabilityToFutureDeviceFamilies": true,
  "allowTargetFutureDeviceFamilies": {
    "Desktop": false,
    "Mobile": true,
    "Holographic": true,
    "Xbox": false,
    "Team": true
  },
  "friendlyName": "Submission 2",
  "trailers": []
}

```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
------------	-------------

Error code	Description
400	The submission could not be created because the request is invalid.
409	The submission could not be created because of the current state of the app, or the app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get an app submission](#)
- [Commit an app submission](#)
- [Update an app submission](#)
- [Delete an app submission](#)
- [Get the status of an app submission](#)

Commit an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to commit a new or updated app submission to Partner Center. The commit action alerts Partner Center that the submission data has been uploaded (including any related packages and images). In response, Partner Center commits the changes to the submission data for ingestion and publishing. After the commit operation succeeds, the changes to the submission are shown in Partner Center.

For more information about how the commit operation fits into the process of submitting an app by using the Microsoft Store submission API, see [Manage app submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- [Create an app submission](#) and then [update the submission](#) with any necessary changes to the submission data.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
POST	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/commit</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app that contains the submission you want to commit. For more information about the Store ID, see View app identity details .
submissionId	string	Required. The ID of the submission you want to commit. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to commit an app submission.

JSON

```
POST
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/1152921504621243610/commit HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method. For more details about the values in the response body, see the following sections.

JSON

```
{
  "status": "CommitStarted"
}
```

Response body

Value	Type	Description
status	string	The status of the submission. This can be one of the following values: - None - Canceled - PendingCommit - CommitStarted - CommitFailed - PendingPublication - Publishing - Published - PublishFailed - PreProcessing - PreProcessingFailed - Certification - CertificationFailed - Release - ReleaseFailed

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
400	The request parameters are invalid.
404	The specified submission could not be found.
409	The specified submission was found but it could not be committed in its current state, or the app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get an app submission](#)
- [Create an app submission](#)
- [Update an app submission](#)
- [Delete an app submission](#)
- [Get the status of an app submission](#)

Update an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to update an existing app submission. After you successfully update a submission by using this method, you must [commit the submission](#) for ingestion and publishing.

For more information about how this method fits into the process of creating an app submission by using the Microsoft Store submission API, see [Manage app submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create a submission for one of your apps. You can do this in Partner Center, or you can do this by using the [create an app submission](#) method.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
PUT	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app for which you want to update a submission. For more information about the Store ID, see View app identity details .