

Name	Type	Description
submissionId	string	Required. The ID of the submission to update. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

The request body has the following parameters.

Value	Type	Description
applicationCategory	string	A string that specifies the category and/or subcategory for your app. Categories and subcategories are combined into a single string with the underscore '_' character, such as BooksAndReference_EReader .
pricing	object	An object that contains pricing info for the app. For more information, see the Pricing resource section.
visibility	string	The visibility of the app. This can be one of the following values: • Hidden • Public • Private • NotSet
targetPublishMode	string	The publish mode for the submission. This can be one of the following values: • Immediate • Manual • SpecificDate
targetPublishDate	string	The publish date for the submission in ISO 8601 format, if the <i>targetPublishMode</i> is set to SpecificDate.
listings	object	A dictionary of key and value pairs, where each key is a country code and each value is a Listing resource object that contains listing info for the app.

Value	Type	Description
hardwarePreferences	array	An array of strings that define the hardware preferences for your app. This can be one of the following values: • Touch • Keyboard • Mouse • Camera • NfcHce • Nfc • BluetoothLE • Telephony
automaticBackupEnabled	boolean	Indicates whether Windows can include your app's data in automatic backups to OneDrive. For more information, see App declarations .
canInstallOnRemovableMedia	boolean	Indicates whether customers can install your app to removable storage. For more information, see App declarations .
isGameDvrEnabled	boolean	Indicates whether game DVR is enabled for the app.
gamingOptions	object	An array that contains one gaming options resource that defines game-related settings for the app.
hasExternallnAppProducts	boolean	Indicates whether your app allows users to make purchase outside the Microsoft Store commerce system. For more information, see App declarations .
meetAccessibilityGuidelines	boolean	Indicates whether your app has been tested to meet accessibility guidelines. For more information, see App declarations .
notesForCertification	string	Contains notes for certification for your app.
applicationPackages	array	Contains objects that provide details about each package in the submission. For more information, see the Application package section. When calling this method to update an app submission, only the <i>fileName</i>, <i>fileStatus</i>, <i>minimumDirectXVersion</i>, and <i>minimumSystemRam</i> values of these objects are required in the request body. The other values are populated by Partner Center.

Value	Type	Description
packageDeliveryOptions	object	Contains gradual package rollout and mandatory update settings for the submission. For more information, see Package delivery options object .
enterpriseLicensing	string	One of the enterprise licensing values that indicate the enterprise licensing behavior for the app.
allowMicrosoftDecideAppAvailabilityToFutureDeviceFamilies	boolean	Indicates whether Microsoft is allowed to make the app available to future Windows 10 and Windows 11 device families .
allowTargetFutureDeviceFamilies	boolean	Indicates whether your app is allowed to target future Windows 10 and Windows 11 device families .
trailers	array	An array that contains up to trailer resources that represent video trailers for the app listing.

Request example

The following example demonstrates how to update an app submission.

JSON

```
PUT
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/1152921504621230023 HTTP/1.1
Authorization: Bearer <your access token>
Content-Type: application/json
{
  "applicationCategory": "BooksAndReference_EReader",
  "pricing": {
    "trialPeriod": "FifteenDays",
    "marketSpecificPricings": {},
    "sales": [],
    "priceId": "Tier2"
  },
  "visibility": "Public",
  "targetPublishMode": "Manual",
  "targetPublishDate": "1601-01-01T00:00:00Z",
  "listings": {
    "en-us": {
      "baseListing": {
        "copyrightAndTrademarkInfo": "",
        "keywords": [
          "epub"
        ],
        "licenseTerms": "",
        "privacyPolicy": "",
        "supportContact": "",
        "websiteUrl": ""
      }
    }
  }
}
```

```

        "description": "Description",
        "features": [
            "Free ebook reader"
        ],
        "releaseNotes": "",
        "images": [
            {
                "fileName": "contoso.png",
                "fileStatus": "Uploaded",
                "id": "1152921504672272757",
                "imageType": "Screenshot"
            }
        ],
        "recommendedHardware": [],
        "title": "Contoso ebook reader"
    },
    "platformOverrides": {
        "Windows81": {
            "description": "Ebook reader for Windows 8.1"
        }
    }
},
"hardwarePreferences": [
    "Touch"
],
"automaticBackupEnabled": false,
"canInstallOnRemovableMedia": true,
"isGameDvrEnabled": false,
"gamingOptions": [],
"hasExternalInAppProducts": false,
"meetAccessibilityGuidelines": true,
"notesForCertification": "",
"applicationPackages": [
    {
        "fileName": "contoso_app.appx",
        "fileStatus": "PendingUpload",
        "minimumDirectXVersion": "None",
        "minimumSystemRam": "None"
    }
],
"packageDeliveryOptions": {
    "packageRollout": {
        "isPackageRollout": false,
        "packageRolloutPercentage": 0.0,
        "packageRolloutStatus": "PackageRolloutNotStarted",
        "fallbackSubmissionId": "0"
    },
    "isMandatoryUpdate": false,
    "mandatoryUpdateEffectiveDate": "1601-01-01T00:00:00.0000000Z"
},
"enterpriseLicensing": "Online",
"allowMicrosoftDecideAppAvailabilityToFutureDeviceFamilies": true,
"allowTargetFutureDeviceFamilies": {
    "Desktop": false,
    "Mobile": true,
    "Holographic": true,
    "Xbox": false,
    "Team": true
},

```

```
"trailers": []  
}
```

Response

The following example demonstrates the JSON response body for a successful call to this method. The response body contains information about the updated submission. For more details about the values in the response body, see [App submission resource](#).

JSON

```
{  
  "id": "1152921504621243540",  
  "applicationCategory": "BooksAndReference_EReader",  
  "pricing": {  
    "trialPeriod": "FifteenDays",  
    "marketSpecificPricings": {},  
    "sales": [],  
    "priceId": "Tier2"  
  },  
  "visibility": "Public",  
  "targetPublishMode": "Manual",  
  "targetPublishDate": "1601-01-01T00:00:00Z",  
  "listings": {  
    "en-us": {  
      "baseListing": {  
        "copyrightAndTrademarkInfo": "",  
        "keywords": [  
          "epub"  
        ],  
        "licenseTerms": "",  
        "privacyPolicy": "",  
        "supportContact": "",  
        "websiteUrl": "",  
        "description": "Description",  
        "features": [  
          "Free ebook reader"  
        ],  
        "releaseNotes": "",  
        "images": [  
          {  
            "fileName": "contoso.png",  
            "fileStatus": "Uploaded",  
            "id": "1152921504672272757",  
            "imageType": "Screenshot"  
          }  
        ],  
        "recommendedHardware": [],  
        "title": "Contoso ebook reader"  
      },  
      "platformOverrides": {  
        "Windows81": {  
          "description": "Ebook reader for Windows 8.1",  
        }  
      }  
    }  
  },  
}
```

```
"hardwarePreferences": [
  "Touch"
],
"automaticBackupEnabled": false,
"canInstallOnRemovableMedia": true,
"isGameDvrEnabled": false,
"gamingOptions": [],
"hasExternalInAppProducts": false,
"meetAccessibilityGuidelines": true,
"notesForCertification": "",
"status": "PendingCommit",
"statusDetails": {
  "errors": [],
  "warnings": [],
  "certificationReports": []
},
"fileUploadUrl":
"https://productingestionbin1.blob.core.windows.net/ingestion/387a9ea8-a412-43a9-8fb3-
a38d03eb483d?sv=2014-02-
14&sr=b&sig=sdd12JmoaT6BhVC%2BZUrwRweA%2Fkvj%2BEBCY09C2SZZowg%3D&se=2016-06-
17T18:32:26Z&sp=rwl",
"applicationPackages": [
  {
    "fileName": "contoso_app.appx",
    "fileStatus": "PendingUpload",
    "id": "1152921504620138797",
    "version": "1.0.0.0",
    "architecture": "ARM",
    "languages": [
      "en-US"
    ],
    "capabilities": [
      "ID_RESOLUTION_HD720P",
      "ID_RESOLUTION_WVGA",
      "ID_RESOLUTION_WXGA"
    ],
    "minimumDirectXVersion": "None",
    "minimumSystemRam": "None",
    "targetDeviceFamilies": [
      "Windows.Mobile min version 10.0.10240.0"
    ]
  }
],
"packageDeliveryOptions": {
  "packageRollout": {
    "isPackageRollout": false,
    "packageRolloutPercentage": 0.0,
    "packageRolloutStatus": "PackageRolloutNotStarted",
    "fallbackSubmissionId": "0"
  },
  "isMandatoryUpdate": false,
  "mandatoryUpdateEffectiveDate": "1601-01-01T00:00:00.0000000Z"
},
"enterpriseLicensing": "Online",
"allowMicrosoftDecideAppAvailabilityToFutureDeviceFamilies": true,
"allowTargetFutureDeviceFamilies": {
  "Desktop": false,
  "Mobile": true,
  "Holographic": true,
  "Xbox": false,
  "Team": true
}
```

```
},  
"friendlyName": "Submission 2",  
"trailers": []  
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
400	The submission could not be updated because the request is invalid.
409	The submission could not be updated because of the current state of the app, or the app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get an app submission](#)
- [Create an app submission](#)
- [Commit an app submission](#)
- [Delete an app submission](#)
- [Get the status of an app submission](#)

Delete an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to delete an existing app submission.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
DELETE	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app that contains the submission to delete. For more information about the Store ID, see View app identity details .
submissionId	string	Required. The ID of the submission to delete. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to delete an app submission.

JSON

```
DELETE
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/1152921504621243610 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

If successful, this method returns an empty response body.

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
400	The request parameters are invalid.
404	The specified submission could not be found.
409	The specified submission was found but it could not be deleted in its current state, or the app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get an app submission](#)
- [Create an app submission](#)
- [Commit an app submission](#)
- [Update an app submission](#)
- [Get the status of an app submission](#)

Get rollout info for an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to get [package rollout](#) info for a package flight submission. For more information about the process of creating an app submission by using the Microsoft Store submission API, see [Manage app submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create a submission for one of your apps. You can do this in Partner Center, or you can do this by using the [create an app submission](#) method.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request parameters.

Method	Request URI
GET	https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/packagerollout

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app that contains the submission with the package rollout info you want to get. For more information about the Store ID, see View app identity details .
submissionId	string	Required. The ID of the submission with the package rollout info you want to get. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to get the package rollout info for an app submission.

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/115292150462124
3649/package rollout HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method for an app submission with gradual package rollout enabled. For more details about the values in the response body, see [Package rollout resource](#).

JSON

```
{
  "isPackageRollout": true,
  "packageRolloutPercentage": 25.0,
  "packageRolloutStatus": "PackageRolloutInProgress",
  "fallbackSubmissionId": "1212922684621243058"
}
```

If the app submission does not have gradual package rollout enabled, the following response body will be returned.

JSON

```
{
  "isPackageRollout": false,
  "packageRolloutPercentage": 0.0,
  "packageRolloutStatus": "PackageRolloutNotStarted",
  "fallbackSubmissionId": "0"
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The submission could not be found.
409	The submission does not belong to the specified app, or the app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Gradual package rollout](#)
- [Manage app submissions using the Microsoft Store submission API](#)
- [Create and manage submissions using Microsoft Store services](#)

Update the rollout percentage for an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to [update the rollout percentage](#) for an app submission. For more information about the process of creating an app submission by using the Microsoft Store submission API, see [Manage app submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create a submission for one of your apps. You can do this in Partner Center, or you can do this by using the [create an app submission](#) method.
- Enable a gradual package rollout for the submission. You can do this in [Partner Center](#), or you can do this by [using the Microsoft Store submission API](#).

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request parameters.

 Expand table

Method	Request URI
POST	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/updatepackagerolloutpercentage</code>

Request header

 Expand table

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

 Expand table

Name	Type	Description
applicationId	string	Required. The Store ID of the app that contains the submission with the package rollout percentage you want to update. For more information about the Store ID, see View app identity details .
submissionId	string	Required. The ID of the submission with the package rollout percentage you want to update. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.
percentage	float	Required. The percentage of users who will receive the gradual rollout package.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to update the package rollout percentage for an app submission.

JSON

```
POST
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/1152921504621243680/updatepackage?percentage=25 HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method. For more details about the values in the response body, see [Package rollout resource](#).

JSON

```
{
  "isPackageRollout": true,
  "packageRolloutPercentage": 25.0,
  "packageRolloutStatus": "PackageRolloutInProgress",
  "fallbackSubmissionId": "1212922684621243058"
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

 Expand table

Error code	Description
404	The submission could not be found.
409	This code indicates one of the following errors: - The submission is not in a valid state for the gradual rollout operation (before calling this method, the submission must be published and the <code>packageRolloutStatus</code> value must be set to <code>PackageRolloutInProgress</code>). - The submission does not belong to the specified app. - The app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API.

Related topics

- [Gradual package rollout](#)
- [Manage app submissions using the Microsoft Store submission API](#)
- [Create and manage submissions using Microsoft Store services](#)

Feedback

Was this page helpful?

Yes

No

[Provide product feedback](#) | [Get help at Microsoft Q&A](#)

Halt the rollout for an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to [halt the package rollout](#) for an app submission. For more information about the process of creating an app submission by using the Microsoft Store submission API, see [Manage app submissions](#).

ⓘ Note

If you halt the rollout for an app submission and then **create a new app submission**, the new submission is a clone of the halted submission.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create a submission for one of your apps. You can do this in Partner Center, or you can do this by using the [create an app submission](#) method.
- Enable a gradual package rollout for the submission. You can do this [in Partner Center](#), or you can do this by [using the Microsoft Store submission API](#).

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request parameters.

Method	Request URI
POST	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/haltpackagerollout</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app that contains the submission with the package rollout you want to halt. For more information about the Store ID, see View app identity details .
submissionId	string	Required. The ID of the submission with the package rollout you want to halt. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to halt the package rollout for an app submission.

JSON

```
POST
https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/115292150462124368
0/haltpackagerollout HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method. For more details about the values in the response body, see [Package rollout resource](#).

JSON

```
{
  "isPackageRollout": true,
  "packageRolloutPercentage": 0.0,
  "packageRolloutStatus": "PackageRolloutStopped",
  "fallbackSubmissionId": "1212922684621243058"
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The submission could not be found.
409	This code indicates one of the following errors: • The submission is not in a valid state for the gradual rollout operation (before calling this method, the submission must be published and the packageRolloutStatus value must be set to PackageRolloutInProgress). • The submission does not belong to the specified app. • The app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API.

Related topics

- [Gradual package rollout](#)
- [Manage app submissions using the Microsoft Store submission API](#)
- [Create and manage submissions using Microsoft Store services](#)

Finalize the rollout for an app submission

Article • 11/01/2022

Use this method in the Microsoft Store submission API to [finalize the package rollout](#) for an app submission. For more information about the process of creating an app submission by using the Microsoft Store submission API, see [Manage app submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create a submission for an app in your Partner Center account. You can do this in Partner Center, or you can do this by using the [create an app submission](#) method.
- Enable a gradual package rollout for the submission. You can do this [in Partner Center](#), or you can do this by [using the Microsoft Store submission API](#).

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request parameters.

Method	Request URI
POST	<code>https://manage.devcenter.microsoft.com/v1.0/my/applications/{applicationId}/submissions/{submissionId}/finalizepackagerollout</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Name	Type	Description
applicationId	string	Required. The Store ID of the app that contains the submission with the package rollout you want to finalize. For more information about the Store ID, see View app identity details .
submissionId	string	Required. The ID of the submission with the package rollout you want to finalize. This ID is available in the response data for requests to create an app submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to finalize the package rollout for a package flight submission.

JSON

POST

https://manage.devcenter.microsoft.com/v1.0/my/applications/9NBLGGH4R315/submissions/1152921504621243680/finalizepackagerollout HTTP/1.1

Authorization: Bearer <your access token>

Response

The following example demonstrates the JSON response body for a successful call to this method. For more details about the values in the response body, see [Package rollout resource](#).

JSON

```
{
  "isPackageRollout": true,
  "packageRolloutPercentage": 100.0,
  "packageRolloutStatus": "PackageRolloutComplete",
  "fallbackSubmissionId": "1212922684621243058"
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The submission could not be found.
409	This code indicates one of the following errors: - The submission is not in a valid state for the gradual rollout operation (before calling this method, the submission must be published and the packageRolloutStatus value must be set to PackageRolloutInProgress). - The submission does not belong to the specified app. - The app uses a DevPartner Center feature that is currently not supported by the Microsoft Store submission API.

Related topics

- [Gradual package rollout](#)
- [Manage app submissions using the Microsoft Store submission API](#)
- [Create and manage submissions using Microsoft Store services](#)

Manage add-ons

Article • 03/13/2023

Use the following methods in the Microsoft Store submission API to manage add-ons for your apps. For an introduction to the Microsoft Store submission API, including prerequisites for using the API, see [Create and manage submissions using Microsoft Store services](#).

These methods can only be used to get, create, or delete add-ons. To create submissions for add-ons, see the methods in [Manage add-on submissions](#).

Method	URI	Description
GET	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts	Get all add-ons for your apps
GET	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}	Get a specific add-on
POST	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts	Create an add-on
DELETE	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}	Delete an add-on

Prerequisites

If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API before trying to use any of these methods.

Data resources

The Microsoft Store submission API methods for managing add-ons use the following JSON data resources.

Add-on resource

This resource describes an add-on.

JSON

```

{
  "applications": {
    "value": [
      {
        "id": "9NBLGGH4R315",
        "resourceLocation": "applications/9NBLGGH4R315"
      }
    ],
    "totalCount": 1
  },
  "id": "9NBLGGH4TNMP",
  "productId": "TestAddOn",
  "productType": "Durable",
  "pendingInAppProductSubmission": {
    "id": "1152921504621243619",
    "resourceLocation":
      "inappproducts/9NBLGGH4TNMP/submissions/1152921504621243619"
  },
  "lastPublishedInAppProductSubmission": {
    "id": "1152921504621243705",
    "resourceLocation":
      "inappproducts/9NBLGGH4TNMP/submissions/1152921504621243705"
  }
}

```

This resource has the following values.

Value	Type	Description
applications	array	An array that contains one application resource that represents the app that this add-on is associated with. Only one item is supported in this array.
id	string	The Store ID of the add-on. This value is supplied by the Store. An example Store ID is 9NBLGGH4TNMP.
productId	string	The product ID of the add-on. This is the ID that was provided by the developer when the add-on was created. For more information, see Set your product type and product ID .
productType	string	The product type of the add-on. The following values are supported: Durable and Consumable .
lastPublishedInAppProductSubmission	object	A submission resource that provides information about the last published submission for the add-on.

Value	Type	Description
pendingInAppProductSubmission	object	A submission resource that provides information about the current pending submission for the add-on.

Application resource

This resource describes the app that an add-on is associated with. The following example demonstrates the format of this resource.

JSON

```
{
  "applications": {
    "value": [
      {
        "id": "9NBLGGH4R315",
        "resourceLocation": "applications/9NBLGGH4R315"
      }
    ],
    "totalCount": 1
  },
}
```

This resource has the following values.

Value	Type	Description
value	object	An object that contains the following values: <i>id</i>. The Store ID of the app. For more information about the Store ID, see View app identity details. <i>resourceLocation</i>. A relative path that you can append to the base <code>https://manage.devcenter.microsoft.com/v1.0/my/</code> request URI to retrieve the complete data for the app.
totalCount	int	The number of app objects in the <i>applications</i> array of the response body.

Submission resource

This resource provides information about a submission for an add-on. The following example demonstrates the format of this resource.

JSON

```
{
  "pendingInAppProductSubmission": {
```

```
"id": "1152921504621243619",
"resourceLocation":
"inappproducts/9NBLGGH4TNMP/submissions/1152921504621243619"
},
}
```

This resource has the following values.

Value	Type	Description
id	string	The ID of the submission.
resourceLocation	string	A relative path that you can append to the base <code>https://manage.devcenter.microsoft.com/v1.0/my/</code> request URI to retrieve the complete data for the submission.

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Manage add-on submissions using the Microsoft Store submission API](#)
- [Get all add-ons](#)
- [Get an add-on](#)
- [Create an add-on](#)
- [Delete an add-on](#)

Get all add-ons

Article • 10/20/2022

Use this method in the Microsoft Store submission API to retrieve data for all add-ons for all the apps that are registered to your Partner Center account.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

All request parameters are optional for this method. If you call this method without parameters, the response contains data for all add-ons for all apps that are registered to your account.

Parameter	Type	Description	Required
-----------	------	-------------	----------

Parameter	Type	Description	Required
top	int	The number of items to return in the request (that is, the number of add-ons to return). If your account has more add-ons than the value you specify in the query, the response body includes a relative URI path that you can append to the method URI to request the next page of data.	No
skip	int	The number of items to bypass in the query before returning the remaining items. Use this parameter to page through data sets. For example, top=10 and skip=0 retrieves items 1 through 10, top=10 and skip=10 retrieves items 11 through 20, and so on.	No

Request body

Do not provide a request body for this method.

Request examples

The following example demonstrates how to retrieve all add-on data for all the apps that are registered to your account.

JSON

```
GET https://manage.devcenter.microsoft.com/v1.0/my/inappproducts HTTP/1.1
Authorization: Bearer <your access token>
```

The following example demonstrates how to retrieve the first 10 add-ons only.

JSON

```
GET https://manage.devcenter.microsoft.com/v1.0/my/inappproducts?top=10
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body returned by a successful request for the first 5 add-ons that are registered to a developer account with 1072 total add-ons. For brevity, this example only shows the data for the first two add-ons returned by the request. For more details about the values in the response body, see the following section.

JSON

```

{
  "@nextLink": "inappproducts/?skip=5&top=5",
  "value": [
    {
      "applications": {
        "value": [
          {
            "id": "9NBLGGH4R315",
            "resourceLocation": "applications/9NBLGGH4R315"
          }
        ],
        "totalCount": 1
      },
      "id": "9NBLGGH4TNMP",
      "productId": "a8b8310b-fa8d-4da0-aca0-577ef6dce4dd",
      "productType": "Consumable",
      "pendingInAppProductSubmission": {
        "id": "1152921504621243619",
        "resourceLocation":
          "inappproducts/9NBLGGH4TNMP/submissions/1152921504621243619"
      },
      "lastPublishedInAppProductSubmission": {
        "id": "1152921504621243705",
        "resourceLocation":
          "inappproducts/9NBLGGH4TNMP/submissions/1152921504621243705"
      }
    },
    {
      "applications": {
        "value": [
          {
            "id": "9NBLGGH4R315",
            "resourceLocation": "applications/9NBLGGH4R315"
          }
        ],
        "totalCount": 1
      },
      "id": "9NBLGGH4TNMN",
      "productId": "6a3c9788-a350-448a-bd32-16160a13018a",
      "productType": "Consumable",
      "pendingInAppProductSubmission": {
        "id": "1152921504621243538",
        "resourceLocation":
          "inappproducts/9NBLGGH4TNMN/submissions/1152921504621243538"
      },
      "lastPublishedInAppProductSubmission": {
        "id": "1152921504621243106",
        "resourceLocation":
          "inappproducts/9NBLGGH4TNMN/submissions/1152921504621243106"
      }
    }
  ],
}
```



```
// Other add-ons omitted for brevity...
],
"totalCount": 1072
}
```

Response body

Value	Type	Description
@nextLink	string	If there are additional pages of data, this string contains a relative path that you can append to the base <code>https://manage.devcenter.microsoft.com/v1.0/my/</code> request URI to request the next page of data. For example, if the <i>top</i> parameter of the initial request body is set to 10 but there are 100 add-ons registered to your account, the response body will include a @nextLink value of <code>inappproducts?skip=10&top=10</code> , which indicates that you can call <code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts?skip=10&top=10</code> to request the next 10 add-ons.
value	array	An array that contains objects that provide information about each add-on. For more information, see add-on resource .
totalCount	int	The number of app objects in the <i>value</i> array of the response body.

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	No add-ons were found.
409	The apps or add-ons use Partner Center features that are currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Manage add-on submissions](#)
- [Get an add-on](#)
- [Create an add-on](#)
- [Delete an add-on](#)

Get an add-on

Article • 10/20/2022

Use this method in the Microsoft Store submission API to retrieve information about an add-on (also known as in-app product or IAP) for an app that is registered to your Partner Center account.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description
id	string	Required. The Store ID of the add-on to retrieve. The Store ID is available in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to retrieve information about an add-on.

JSON

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/9NBLGGH4TNMP
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method. For more details about the values in the response body, see [add-on resource](#).

JSON

```
{
  "applications": {
    "value": [
      {
        "id": "9NBLGGH4R315",
        "resourceLocation": "applications/9NBLGGH4R315"
      }
    ],
    "totalCount": 1
  },
  "id": "9NBLGGH4TNMP",
  "productId": "Test-add-on",
  "productType": "Durable",
  "pendingInAppProductSubmission": {
    "id": "1152921504621243619",
    "resourceLocation":
      "inappproducts/9NBLGGH4TNMP/submissions/1152921504621243619"
  },
  "lastPublishedInAppProductSubmission": {
    "id": "1152921504621243705",
    "resourceLocation":
      "inappproducts/9NBLGGH4TNMP/submissions/1152921504621243705"
  }
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The specified add-on could not be found.
409	The add-on uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Manage add-on submissions](#)
- [Get all add-ons](#)
- [Create an add-on](#)
- [Delete an add-on](#)

Create an add-on

Article • 10/24/2022

Use this method in the Microsoft Store submission API to create an add-on (also known as in-app product or IAP) for an app that is registered to your Partner Center account.

ⓘ Note

This method creates an add-on without any submissions. To create a submission for an add-on, see the methods in [Manage add-on submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
POST	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request body

The request body has the following parameters.

Parameter	Type	Description	Required
applicationIds	array	An array that contains the Store ID of the app that this add-on is associated with. Only one item is supported in this array.	Yes
productId	string	The product ID of the add-on. This is an identifier that can use in code to refer to the add-on. For more information, see Set your product type and product ID .	Yes
productType	string	The product type of the add-on. The following values are supported: Durable and Consumable .	Yes

Request example

The following example demonstrates how to create a new consumable add-on for an app.

JSON

```
POST https://manage.devcenter.microsoft.com/v1.0/my/inappproducts HTTP/1.1
Authorization: Bearer eyJ0eXAiOiJKV1Q...
Content-Type: application/json
{
  "applicationIds": [ "9NBLGGH4R315" ],
  "productId": "my-new-add-on",
  "productType": "Consumable",
}
```

Response

The following example demonstrates the JSON response body for a successful call to this method. For more details about the values in the response body, see [add-on resource](#).

JSON

```
{
  "applications": {
    "value": [
      {
        "id": "9NBLGGH4R315",
        "resourceLocation": "applications/9NBLGGH4R315"
      }
    ],
    "totalCount": 1
  },
}
```

```
"id": "9NBLGGH4TNMP",  
"productId": "my-new-add-on",  
"productType": "Consumable",  
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
400	The request is invalid.
409	The add-on could not be created because of its current state, or the add-on uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Manage add-on submissions](#)
- [Get all add-ons](#)
- [Get an add-on](#)
- [Delete an add-on](#)

Delete an add-on

Article • 10/20/2022

Use this method in the Microsoft Store submission API to delete an add-on (also known as in-app product or IAP) for an app that is registered to your Partner Center account.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
DELETE	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description
id	string	Required. The Store ID of the add-on to delete. The Store ID is available in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to delete an add-on.

JSON

```
DELETE
https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/9NBLGGH4TNMP
HTTP/1.1
Authorization: Bearer <your access token>
```

Response

If successful, this method returns an empty response body.

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
400	The request is invalid.
404	The specified add-on could not be found.
409	The specified add-on was found but it could not be deleted in its current state, or the add-on uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get all add-ons](#)
- [Get an add-on](#)
- [Create an add-on](#)

Manage add-on submissions

Article • 01/04/2023

The Microsoft Store submission API provides methods you can use to manage add-on (also known as in-app product or IAP) submissions for your apps. For an introduction to the Microsoft Store submission API, including prerequisites for using the API, see [Create and manage submissions using Microsoft Store services](#).

Important

If you use the Microsoft Store submission API to create a submission for an add-on, be sure to make further changes to the submission only by using the API, rather than making changes in Partner Center. If you use Partner Center to change a submission that you originally created by using the API, you will no longer be able to change or commit that submission by using the API. In some cases, the submission could be left in an error state where it cannot proceed in the submission process. If this occurs, you must delete the submission and create a new submission.

Methods for managing add-on submissions

Use the following methods to get, create, update, commit, or delete an add-on submission. Before you can use these methods, the add-on must already exist in your Partner Center account. You can create an add-on in Partner Center by [defining its product type and product ID](#) or by using the Microsoft Store submission API methods in described in [Manage add-ons](#).

 Expand table

Method	URI	Description
GET	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions/{submissionId}	Get an existing add-on submission
GET	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions/{submissionId}/status	Get the status of an existing add-on submission
POST	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions	Create a new add-on submission
PUT	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions/{submissionId}	Update an existing add-on submission
POST	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions/{submissionId}/commit	Commit a new or updated add-on submission

Method	URI	Description
DELETE	https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions/{submissionId}	Delete an add-on submission

Create an add-on submission

To create a submission for an add-on, follow this process.

1. If you have not yet done so, complete the prerequisites described in [Create and manage submissions using Microsoft Store services](#), including associating an Azure AD application with your Partner Center account and obtaining your client ID and key. You only need to do this one time; after you have the client ID and key, you can reuse them any time you need to create a new Azure AD access token.
2. [Obtain an Azure AD access token](#). You must pass this access token to the methods in the Microsoft Store submission API. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
3. Execute the following method in the Microsoft Store submission API. This method creates a new in-progress submission, which is a copy of your last published submission. For more information, see [Create an add-on submission](#).

JSON

POST <https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions>

The response body contains an [add-on submission](#) resource that includes the ID of the new submission, the shared access signature (SAS) URI for uploading any add-on icons for the submission to Azure Blob Storage, and all of the data for the new submission (such as the listings and pricing information).

Note

A SAS URI provides access to a secure resource in Azure storage without requiring account keys. For background information about SAS URIs and their use with Azure Blob Storage, see [Shared Access Signatures, Part 1: Understanding the SAS model](#) and [Shared Access Signatures, Part 2: Create and use a SAS with Blob storage](#).

4. If you are adding new icons for the submission, [prepare the icons](#) and add them to a ZIP archive.
5. Update the [add-on submission](#) data with any required changes for the new submission, and execute the following method to update the submission. For more information, see [Update an add-on submission](#).

JSON

PUT <https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions/{submissionId}>

Note

If you are adding new icons for the submission, make sure you update the submission data to refer to the name and relative path of these files in the ZIP archive.

6. If you are adding new icons for the submission, upload the ZIP archive to [Azure Blob Storage](#) using the SAS URI that was provided in the response body of the POST method you called earlier. There are different Azure libraries you can use to do this on a variety of platforms, including:

- [Azure Storage Client Library for .NET](#)
- [Azure Storage SDK for Java](#)
- [Azure Storage SDK for Python](#)

The following C# code example demonstrates how to upload a ZIP archive to Azure Blob Storage using the [CloudBlockBlob](#) class in the Azure Storage Client Library for .NET. This example assumes that the ZIP archive has already been written to a stream object.

C#

```
string sasUrl = "https://productingestionbin1.blob.core.windows.net/ingestion/26920f66-b592-4439-9a9d-fb0f014902ec?sv=2014-02-14&sr=b&sig=usAN0kNFNnYE2tGQBI%2BARQWejX1Guiz7hdFtRhyK%2Bog%3D&se=2016-06-17T20:45:51Z&sp=rwl";
Microsoft.WindowsAzure.Storage.Blob.CloudBlockBlob blockBob =
    new Microsoft.WindowsAzure.Storage.Blob.CloudBlockBlob(new System.Uri(sasUrl));
await blockBob.UploadFromStreamAsync(stream);
```

7. Commit the submission by executing the following method. This will alert Partner Center that you are done with your submission and that your updates should now be applied to your account. For more information, see [Commit an add-on submission](#).

JSON

```
POST
https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions/{submissionId}/commit
```

8. Check on the commit status by executing the following method. For more information, see [Get the status of an add-on submission](#).

JSON

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{id}/submissions/{submissionId}/status
```

To confirm the submission status, review the *status* value in the response body. This value should change from **CommitStarted** to either **PreProcessing** if the request succeeds or to **CommitFailed** if there are errors in the request. If there are errors, the *statusDetails* field contains further details about the error.

9. After the commit has successfully completed, the submission is sent to the Store for ingestion. You can continue to monitor the submission progress by using the previous method, or by visiting Partner Center.

Code examples

The following articles provide detailed code examples that demonstrate how to create an add-on submission in several different programming languages:

- [C# code examples](#)
- [Java code examples](#)
- [Python code examples](#)

StoreBroker PowerShell module

As an alternative to calling the Microsoft Store submission API directly, we also provide an open-source PowerShell module which implements a command-line interface on top of the API. This module is called [StoreBroker](#). You can use this module to manage your app, flight, and add-on submissions from the command line instead of calling the Microsoft Store submission API directly, or you can simply browse the source to see more examples for how to call this API. The StoreBroker module is actively used within Microsoft as the primary way that many first-party applications are submitted to the Store.

For more information, see our [StoreBroker page on GitHub](#).

Data resources

The Microsoft Store submission API methods for managing add-on submissions use the following JSON data resources.

Add-on submission resource

This resource describes an add-on submission.

JSON

```
{
  "id": "1152921504621243680",
  "contentType": "EMagazine",
  "keywords": [
    "books"
  ],
  "lifetime": "FiveDays",
  "listings": {
    "en": {
      "description": "English add-on description",
      "icon": {
        "fileName": "add-on-en-us-listing2.png",
        "fileStatus": "Uploaded"
      },
      "title": "Add-on Title (English)"
    },
    "ru": {
      "description": "Russian add-on description",
      "icon": {
        "fileName": "add-on-ru-listing.png",
        "fileStatus": "Uploaded"
      },
      "title": "Add-on Title (Russian)"
    }
  },
  "pricing": {
    "marketSpecificPricings": {
      "RU": "Tier3",
```

```

    "US": "Tier4",
  },
  "sales": [],
  "priceId": "Free",
  "isAdvancedPricingModel": true
},
"targetPublishDate": "2016-03-15T05:10:58.047Z",
"targetPublishMode": "Immediate",
"tag": "SampleTag",
"visibility": "Public",
"status": "PendingCommit",
"statusDetails": {
  "errors": [
    {
      "code": "None",
      "details": "string"
    }
  ],
  "warnings": [
    {
      "code": "ListingOptOutWarning",
      "details": "You have removed listing language(s): []"
    }
  ],
  "certificationReports": [
    {
    }
  ]
},
"fileUploadUrl": "https://productingestionbin1.blob.core.windows.net/ingestion/26920f66-b592-4439-9a9d-fb0f014902ec?sv=2014-02-14&sr=b&sig=usAN0kNfNnYE2tGQBI%2BARQWejX1Guiz7hdFtRhyK%2Bog%3D&se=2016-06-17T20:45:51Z&sp=rw1",
"friendlyName": "Submission 2"
}

```

This resource has the following values.

[Expand table](#)

Value	Type	Description
id	string	The ID of the submission. This ID is available in the response data for requests to create an add-on submission , get all add-ons , and get an add-on . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.
contentType	string	The type of content that is provided in the add-on. This can be one of the following values: - NotSet - BookDownload - EMagazine - ENewspaper - MusicDownload - MusicStream - OnlineDataStorage - VideoDownload - VideoStream - Asp - OnlineDownload
keywords	array	An array of strings that contain up to 10 keywords for the add-on. Your app can query for add-ons using these keywords.
lifetime	string	The lifetime of the add-on. This can be one of the following values:

Value	Type	Description
		• Forever • OneDay • ThreeDays • FiveDays • OneWeek • TwoWeeks • OneMonth • TwoMonths • ThreeMonths • SixMonths • OneYear
listings	object	A dictionary of key and value pairs, where each key is a two-letter ISO 3166-1 alpha-2 country code and each value is a listing resource that contains listing info for the add-on.
pricing	object	A pricing resource that contains pricing info for the add-on.
targetPublishMode	string	The publish mode for the submission. This can be one of the following values: • Immediate • Manual • SpecificDate
targetPublishDate	string	The publish date for the submission in ISO 8601 format, if the <i>targetPublishMode</i> is set to SpecificDate.
tag	string	The custom developer data for the add-on (this information was previously called the <i>tag</i>).
visibility	string	The visibility of the add-on. This can be one of the following values: • Hidden • Public • Private • NotSet
status	string	The status of the submission. This can be one of the following values: • None • Canceled • PendingCommit • CommitStarted • CommitFailed • PendingPublication • Publishing • Published • PublishFailed • PreProcessing • PreProcessingFailed • Certification • CertificationFailed • Release • ReleaseFailed
statusDetails	object	A status details resource that contains additional details about the status of the submission, including information about any errors.
fileUploadUrl	string	The shared access signature (SAS) URI for uploading any packages for the submission. If you are adding new packages for the submission, upload the ZIP archive that contains the packages to this URI. For more information, see Create an add-on submission .
friendlyName	string	The friendly name of the submission, as shown in Partner Center. This value is generated for you when you create the submission.

Listing resource

This resource contains [listing info for an add-on](#). This resource has the following values.

 Expand table

Value	Type	Description
description	string	The description for the add-on listing.
icon	object	An icon resource that contains data for the icon for the add-on listing.
title	string	The title for the add-on listing.

Icon resource

This resource contains icon data for an add-on listing. This resource has the following values.

 Expand table

Value	Type	Description
fileName	string	The name of the icon file in the ZIP archive that you uploaded for the submission. The icon must be a .png file that measures exactly 300 x 300 pixels.
fileStatus	string	The status of the icon file. This can be one of the following values: • None • PendingUpload • Uploaded • PendingDelete

Pricing resource

This resource contains pricing info for the add-on. This resource has the following values.

 Expand table

Value	Type	Description
marketSpecificPricings	object	A dictionary of key and value pairs, where each key is a two-letter ISO 3166-1 alpha-2 country code and each value is a price tier . These items represent the custom prices for your add-on in specific markets . Any items in this dictionary override the base price specified by the <i>priced</i> value for the specified market.
sales	array	Deprecated. An array of sale resources that contain sales information for the add-on.
priced	string	A price tier that specifies the base price for the add-on.
isAdvancedPricingModel	boolean	If true , your developer account has access to the expanded set of price tiers from .99 USD to 1999.99 USD. If false , your developer account has access to the original set of price tiers from .99 USD to 999.99 USD. For more information about the different tiers, see price tiers . Note This field is read-only.

Sale resource

This resources contains sale info for an add-on.

Important

The **Sale** resource is no longer supported, and currently you cannot get or modify the sale data for an add-on submission using the Microsoft Store submission API. In the future, we will update the Microsoft Store submission API to introduce a new way to programmatically access sales information for add-on submissions.

- After calling the [GET method to get an add-on submission](#), the *sales* value will be empty. You can continue to use Partner Center to get the sale data for your add-on submission.
- When calling the [PUT method to update an add-on submission](#), the information in the *sales* value is ignored. You can continue to use Partner Center to change the sale data for your add-on submission.

This resource has the following values.

 Expand table

Value	Type	Description
name	string	The name of the sale.
basePriceId	string	The price tier to use for the base price of the sale.
startDate	string	The start date for the sale in ISO 8601 format.
endDate	string	The end date for the sale in ISO 8601 format.
marketSpecificPricings	object	A dictionary of key and value pairs, where each key is a two-letter ISO 3166-1 alpha-2 country code and each value is a price tier . These items represent the custom prices for your add-on in specific markets . Any items in this dictionary override the base price specified by the <i>basePriceId</i> value for the specified market.

Status details resource

This resource contains additional details about the status of a submission. This resource has the following values.

 Expand table

Value	Type	Description
errors	object	An array of status detail resources that contain error details for the submission.
warnings	object	An array of status detail resources that contain warning details for the submission.
certificationReports	object	An array of certification report resources that provide access to the certification report data for the submission. You can examine these reports for more information if the certification fails.

Status detail resource

This resource contains additional information about any related errors or warnings for a submission. This resource has the following values.

[Expand table](#)

Value	Type	Description
code	string	A submission status code that describes the type of error or warning.
details	string	A message with more details about the issue.

Certification report resource

This resource provides access to the certification report data for a submission. This resource has the following values.

[Expand table](#)

Value	Type	Description
date	string	The date and time the report was generated, in ISO 8601 format.
reportUrl	string	The URL at which you can access the report.

Enums

These methods use the following enums.

Price tiers

The following values represent available price tiers in the [pricing resource](#) resource for an add-on submission.

[Expand table](#)

Value	Description
Base	The price tier is not set; use the base price for the add-on.
NotAvailable	The add-on is not available in the specified region.
Free	The add-on is free.
Tierxxxx	A string that specifies the price tier for the add-on, in the format Tierxxxx. Currently, the following ranges of price tiers are supported: - If the <i>isAdvancedPricingModel</i> value of the pricing resource is true, the available price tier values for your account are Tier1012 - Tier1424. - If the <i>isAdvancedPricingModel</i> value of the pricing resource is false, the available price tier values for your account are Tier2 - Tier96. To see the complete table of price tiers that are available for your developer account, including the market-specific prices that are associated with each tier, go to the Pricing and availability page for any of your app submissions in Partner Center and click the view table link in the Markets and custom prices section (for some developer accounts, this link is in the Pricing section).

Submission status code

The following values represent the status code of a submission.

 Expand table

Value	Description
None	No code was specified.
InvalidArchive	The ZIP archive containing the package is invalid or has an unrecognized archive format.
MissingFiles	The ZIP archive does not have all files which were listed in your submission data, or they are in the wrong location in the archive.
PackageValidationFailed	One or more packages in your submission failed to validate.
InvalidParameterValue	One of the parameters in the request body is invalid.
InvalidOperation	The operation you attempted is invalid.
InvalidState	The operation you attempted is not valid for the current state of the package flight.
ResourceNotFound	The specified package flight could not be found.
ServiceError	An internal service error prevented the request from succeeding. Try the request again.
ListingOptOutWarning	The developer removed a listing from a previous submission, or did not include listing information that is supported by the package.
ListingOptInWarning	The developer added a listing.
UpdateOnlyWarning	The developer is trying to insert something that only has update support.
Other	The submission is in an unrecognized or uncategorized state.
PackageValidationWarning	The package validation process resulted in a warning.

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Manage add-ons using the Microsoft Store submission API](#)
- [Add-on submissions in Partner Center](#)

Get an add-on submission

Article • 10/20/2022

Use this method in the Microsoft Store submission API to get data for an existing add-on (also known as in-app product or IAP) submission. For more information about the process of creating an add-on submission by using the Microsoft Store submission API, see [Manage add-on submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create an add-on submission for one of your apps. You can do this in Partner Center, or you can do this by using the [Create an add-on submission](#) method.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}/submissions/{submissionId}</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token> .

Request parameters

Name	Type	Description
inAppProductId	string	Required. The Store ID of the add-on that contains the submission you want to get. The Store ID is available in Partner Center, and it is included in the response data for requests to Create an add-on or get add-on details .
submissionId	string	Required. The ID of the submission to get. This ID is available in the response data for requests to create an add-on submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to get an add-on submission.

JSON

GET

`https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/9NBLGGH4TNMP/submissions/1152921504621243680 HTTP/1.1`

Authorization: Bearer <your access token>

Response

The following example demonstrates the JSON response body for a successful call to this method. The response body contains information about the specified submission. For more details about the values in the response body, see [add-on submission resource](#).

JSON

```
{
  "id": "1152921504621243680",
  "contentType": "EMagazine",
  "keywords": [
    "books"
  ],
  "lifetime": "FiveDays",
  "listings": {
    "en": {
      "description": "English add-on description",
      "icon": {
        "fileName": "add-on-en-us-listing2.png",
        "fileStatus": "Uploaded"
      },
      "title": "Add-on Title (English)"
    },
    "ru": {
      "description": "Russian add-on description",
      "icon": {
        "fileName": "add-on-ru-listing.png",
        "fileStatus": "Uploaded"
      },
      "title": "Add-on Title (Russian)"
    }
  },
  "pricing": {
    "marketSpecificPricings": {
      "RU": "Tier3",
      "US": "Tier4"
    },
    "sales": [],
    "priceId": "Free",
    "isAdvancedPricingModel": true
  }
}
```

```

},
"targetPublishDate": "2016-03-15T05:10:58.047Z",
"targetPublishMode": "Immediate",
"tag": "SampleTag",
"visibility": "Public",
"status": "PendingCommit",
"statusDetails": {
  "errors": [
    {
      "code": "None",
      "details": "string"
    }
  ],
  "warnings": [
    {
      "code": "ListingOptOutWarning",
      "details": "You have removed listing language(s): []"
    }
  ],
  "certificationReports": [
    {
    }
  ]
},

"fileUploadUrl":
"https://productingestionbin1.blob.core.windows.net/ingestion/26920f66-b592-4439-9a9d-
fb0f014902ec?sv=2014-02-
14&sr=b&sig=usAN0kNFNnYE2tGQBI%2BARQWejX1Guiz7hdFtRhyK%2Bog%3D&se=2016-06-
17T20:45:51Z&sp=rwl",
"friendlyName": "Submission 2"
}

```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The submission could not be found.
409	The submission does not belong to the specified add-on, or the add-on uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Create an add-on submission](#)
- [Commit an add-on submission](#)
- [Update an add-on submission](#)
- [Delete an add-on submission](#)
- [Get the status of an add-on submission](#)

Get the status of an add-on submission

Article • 10/20/2022

Use this method in the Microsoft Store submission API to get the status of an add-on (also known as in-app product or IAP) submission. For more information about the process of creating an add-on submission by using the Microsoft Store submission API, see [Manage add-on submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create an add-on submission for one of your apps. You can do this in Partner Center, or you can do this by using the [Create an add-on submission](#) method.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
GET	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}/submissions/{submissionId}/status</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <i><token></i> .

Request parameters

Name	Type	Description
inAppProductId	string	Required. The Store ID of the add-on that contains the submission for which you want to get the status. The Store ID is available in Partner Center.
submissionId	string	Required. The ID of the submission for which you want to get the status. This ID is available in the response data for requests to create an add-on submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to get the status of an add-on submission.

JSON

```
GET
https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/9NBLGGH4TNMP/submissions/1152921504621243680/status HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method. The response body contains information about the specified submission. For more details about the values in the response body, see the following sections.

JSON

```
{
  "status": "PendingCommit",
  "statusDetails": {
    "errors": [],
    "warnings": [],
    "certificationReports": []
  },
}
```

Response body

Value	Type	Description
status	string	The status of the submission. This can be one of the following values: • None • Canceled • PendingCommit • CommitStarted • CommitFailed • PendingPublication • Publishing • Published • PublishFailed • PreProcessing • PreProcessingFailed • Certification • CertificationFailed • Release • ReleaseFailed
statusDetails	object	Contains additional details about the status of the submission, including information about any errors. For more information, see Status details resource .

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
404	The submission could not be found.
409	The add-on uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get an add-on submission](#)
- [Create an add-on submission](#)
- [Commit an add-on submission](#)
- [Update an add-on submission](#)
- [Delete an add-on submission](#)

Create an add-on submission

Article • 10/20/2022

Use this method in the Microsoft Store submission API to create a new add-on (also known as in-app product or IAP) submission for an app that is registered to your Partner Center account. After you successfully create a new submission by using this method, [update the submission](#) to make any necessary changes to the submission data, and then [commit the submission](#) for ingestion and publishing.

For more information about how this method fits into the process of creating an add-on submission by using the Microsoft Store submission API, see [Manage add-on submissions](#).

ⓘ Note

This method creates a submission for an existing add-on. To create an add-on, use the [Create an add-on](#) method.

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create an add-on for one of your apps. You can do this in Partner Center, or you can do this by using the [Create an add-on](#) method.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
POST	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}/submissions</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token>.

Request parameters

Name	Type	Description
inAppProductId	string	Required. The Store ID of the add-on for which you want to create a submission. The Store ID is available in Partner Center, and it is included in the response data for requests to Create an add-on or get add-on details .

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to create a new submission for an add-on.

JSON

POST

https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/9NBLGGH4TNMP/submissions HTTP/1.1

Authorization: Bearer <your access token>

Response

The following example demonstrates the JSON response body for a successful call to this method. The response body contains information about the new submission. For more details about the values in the response body, see [add-on submission resource](#).

JSON

```
{
  "id": "1152921504621243680",
  "contentType": "EMagazine",
  "keywords": [
    "books"
```

```
],
"lifetime": "FiveDays",
"listings": {
  "en": {
    "description": "English add-on description",
    "icon": {
      "fileName": "add-on-en-us-listing2.png",
      "fileStatus": "Uploaded"
    },
    "title": "Add-on Title (English)"
  },
  "ru": {
    "description": "Russian add-on description",
    "icon": {
      "fileName": "add-on-ru-listing.png",
      "fileStatus": "Uploaded"
    },
    "title": "Add-on Title (Russian)"
  }
},
"pricing": {
  "marketSpecificPricings": {
    "RU": "Tier3",
    "US": "Tier4",
  },
  "sales": [
    {
      "name": "Sale1",
      "basePriceId": "Free",
      "startDate": "2016-05-21T18:40:11.7369008Z",
      "endDate": "2016-05-22T18:40:11.7369008Z",
      "marketSpecificPricings": {
        "RU": "NotAvailable"
      }
    }
  ],
  "priceId": "Free",
  "isAdvancedPricingModel": true
},
"targetPublishDate": "2016-03-15T05:10:58.047Z",
"targetPublishMode": "Immediate",
"tag": "SampleTag",
"visibility": "Public",
"status": "PendingCommit",
"statusDetails": {
  "errors": [
    {
      "code": "None",
      "details": "string"
    }
  ],
  "warnings": [
    {
      "code": "ListingOptOutWarning",
      "details": "You have removed listing language(s): []"
```

```
    }
  ],
  "certificationReports": [
    {
    }
  ]
},
"fileUploadUrl":
"https://productingestionbin1.blob.core.windows.net/ingestion/26920f66-b592-4439-9a9d-fb0f014902ec?sv=2014-02-14&sr=b&sig=usAN0kNFNnYE2tGQBI%2BARQWejX1Guiz7hdFtRhyK%2Bog%3D&se=2016-06-17T20:45:51Z&sp=rwl",
"friendlyName": "Submission 2"
}
```

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
400	The submission could not be created because the request is invalid.
409	The submission could not be created because of the current state of the app, or the app uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Manage add-on submissions](#)
- [Get an add-on submission](#)
- [Commit an add-on submission](#)
- [Update an add-on submission](#)
- [Delete an add-on submission](#)
- [Get the status of an add-on submission](#)

Commit an add-on submission

Article • 10/20/2022

Use this method in the Microsoft Store submission API to commit a new or updated add-on (also known as in-app product or IAP) submission to Partner Center. The commit action alerts Partner Center that the submission data has been uploaded (including any related icons). In response, Partner Center commits the changes to the submission data for ingestion and publishing. After the commit operation succeeds, the changes to the submission are shown in Partner Center.

For more information about how the commit operation fits into the process of submitting an add-on by using the Microsoft Store submission API, see [Manage add-on submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- [Create an add-on submission](#) and then [update the submission](#) with any necessary changes to the submission data.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
POST	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}/submissions/{submissionId}/commit</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token> .

Request parameters

Name	Type	Description
inAppProductId	string	Required. The Store ID of the add-on that contains the submission you want to commit. The Store ID is available in Partner Center, and it is included in the response data for requests to Get all add-ons and Create an add-on .
submissionId	string	Required. The ID of the submission you want to commit. This ID is available in the response data for requests to create an add-on submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

Do not provide a request body for this method.

Request example

The following example demonstrates how to commit an add-on submission.

JSON

```
POST
https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/9NBLGGH4TNMP/submissions/1152921504621230023/commit HTTP/1.1
Authorization: Bearer <your access token>
```

Response

The following example demonstrates the JSON response body for a successful call to this method. For more details about the values in the response body, see the following sections.

JSON

```
{
  "status": "CommitStarted"
}
```

Response body

Value	Type	Description
status	string	The status of the submission. This can be one of the following values: - None - Canceled - PendingCommit - CommitStarted - CommitFailed - PendingPublication - Publishing - Published - PublishFailed - PreProcessing - PreProcessingFailed - Certification - CertificationFailed - Release - ReleaseFailed

Error codes

If the request cannot be successfully completed, the response will contain one of the following HTTP error codes.

Error code	Description
400	The request parameters are invalid.
404	The specified submission could not be found.
409	The specified submission was found but it could not be committed in its current state, or the add-on uses a Partner Center feature that is currently not supported by the Microsoft Store submission API .

Related topics

- [Create and manage submissions using Microsoft Store services](#)
- [Get an add-on submission](#)
- [Create an add-on submission](#)
- [Update an add-on submission](#)
- [Delete an add-on submission](#)
- [Get the status of an add-on submission](#)

Update an add-on submission

Article • 10/24/2022

Use this method in the Microsoft Store submission API to update an existing add-on (also known as in-app product or IAP) submission. After you successfully update a submission by using this method, you must [commit the submission](#) for ingestion and publishing.

For more information about how this method fits into the process of creating an add-on submission by using the Microsoft Store submission API, see [Manage add-on submissions](#).

Prerequisites

To use this method, you need to first do the following:

- If you have not done so already, complete all the [prerequisites](#) for the Microsoft Store submission API.
- [Obtain an Azure AD access token](#) to use in the request header for this method. After you obtain an access token, you have 60 minutes to use it before it expires. After the token expires, you can obtain a new one.
- Create an add-on submission for one of your apps. You can do this in Partner Center, or you can do this by using the [Create an add-on submission](#) method.

Request

This method has the following syntax. See the following sections for usage examples and descriptions of the header and request body.

Method	Request URI
PUT	<code>https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/{inAppProductId}/submissions/{submissionId}</code>

Request header

Header	Type	Description
Authorization	string	Required. The Azure AD access token in the form Bearer <token> .

Request parameters

Name	Type	Description
inAppProductId	string	Required. The Store ID of the add-on for which you want to update a submission. The Store ID is available in Partner Center, and it is included in the response data for requests to Create an add-on or get add-on details .

Name	Type	Description
submissionId	string	Required. The ID of the submission to update. This ID is available in the response data for requests to create an add-on submission . For a submission that was created in Partner Center, this ID is also available in the URL for the submission page in Partner Center.

Request body

The request body has the following parameters.

Value	Type	Description
contentType	string	The type of content that is provided in the add-on. This can be one of the following values: • NotSet • BookDownload • EMagazine • ENewspaper • MusicDownload • MusicStream • OnlineDataStorage • VideoDownload • VideoStream • Asp • OnlineDownload
keywords	array	An array of strings that contain up to 10 keywords for the add-on. Your app can query for add-ons using these keywords.
lifetime	string	The lifetime of the add-on. This can be one of the following values: • Forever • OneDay • ThreeDays • FiveDays • OneWeek • TwoWeeks • OneMonth • TwoMonths • ThreeMonths • SixMonths • OneYear
listings	object	An object that contains listing info for the add-on. For more information, see Listing resource .
pricing	object	An object that contains pricing info for the add-on. For more information, see Pricing resource .

Value	Type	Description
targetPublishMode	string	The publish mode for the submission. This can be one of the following values: • Immediate • Manual • SpecificDate
targetPublishDate	string	The publish date for the submission in ISO 8601 format, if the <i>targetPublishMode</i> is set to SpecificDate.
tag	string	The custom developer data for the add-on (this information was previously called the <i>tag</i>).
visibility	string	The visibility of the add-on. This can be one of the following values: • Hidden • Public • Private • NotSet

Request example

The following example demonstrates how to update an add-on submission.

JSON

```
PUT
https://manage.devcenter.microsoft.com/v1.0/my/inappproducts/9NBLGGH4TNMP/submissions/115
2921504621230023 HTTP/1.1
Authorization: Bearer <your access token>
Content-Type: application/json
{
  "contentType": "EMagazine",
  "keywords": [
    "books"
  ],
  "lifetime": "FiveDays",
  "listings": {
    "en": {
      "description": "English add-on description",
      "icon": {
        "fileName": "add-on-en-us-listing2.png",
        "fileStatus": "Uploaded"
      },
      "title": "Add-on Title (English)"
    },
    "ru": {
      "description": "Russian add-on description",
      "icon": {
        "fileName": "add-on-ru-listing.png",
        "fileStatus": "Uploaded"
      },
      "title": "Add-on Title (Russian)"
    }
  },
  "pricing": {
    "marketSpecificPricings": {
      "RU": "Tier3",
```

```

        "US": "Tier4",
    },
    "sales": [],
    "priceId": "Free"
},
"targetPublishDate": "2016-03-15T05:10:58.047Z",
"targetPublishMode": "Immediate",
"tag": "SampleTag",
"visibility": "Public",
}

```

Response

The following example demonstrates the JSON response body for a successful call to this method. The response body contains information about the updated submission. For more details about the values in the response body, see [Add-on submission resource](#).

JSON

```

{
  "id": "1152921504621243680",
  "contentType": "EMagazine",
  "keywords": [
    "books"
  ],
  "lifetime": "FiveDays",
  "listings": {
    "en": {
      "description": "English add-on description",
      "icon": {
        "fileName": "add-on-en-us-listing2.png",
        "fileStatus": "Uploaded"
      },
      "title": "Add-on Title (English)"
    },
    "ru": {
      "description": "Russian add-on description",
      "icon": {
        "fileName": "add-on-ru-listing.png",
        "fileStatus": "Uploaded"
      },
      "title": "Add-on Title (Russian)"
    }
  },
  "pricing": {
    "marketSpecificPricings": {
      "RU": "Tier3",
      "US": "Tier4",
    },
    "sales": [],
    "priceId": "Free"
  },
  "targetPublishDate": "2016-03-15T05:10:58.047Z",
  "targetPublishMode": "Immediate",
  "tag": "SampleTag",
  "visibility": "Public",
  "status": "PendingCommit",
  "statusDetails": {

```