




# CS 400

## Heap - Introduction



**ID: 10-01**

# Priority Queue




# Priority Queue Implementation

insert	removeMin
$O(1)^*$	$O(n)$
$O(1)$	$O(n)$
$O(n)$	$O(1)$
$O(n)$	$O(1)$




# Another possibly structure...




# (min)Heap

A complete binary tree  $T$  is a min-heap if:

- $T = \{\}$  or
- $T = \{r, T_L, T_R\}$ , where  $r$  is less than the roots of  $\{T_L, T_R\}$  and  $\{T_L, T_R\}$  are min-heaps.



# (min)Heap





4	5	6	15	9	7	20	16	25	14	12	11			
---	---	---	----	---	---	----	----	----	----	----	----	--	--	--

# CS 400

**Heap – Insert and removeMin**

**ID: 10-02**



# insert






# insert

```
1  template <class T>
2  void Heap<T>::_insert(const T & key) {
3      // Check to ensure there's space to insert an element
4      // ...if not, grow the array
5      if ( size_ == capacity_ ) { _growArray(); }
6
7      // Insert the new element at the end of the array
8      item_[++size] = key;
9
10     // Restore the heap property
11     _heapifyUp(size);
12 }
```



# growArray




# insert- heapifyUp

```
1  template <class T>
2  void Heap<T>::_insert(const T & key) {
3      // Check to ensure there's space to insert an element
4      // ...if not, grow the array
5      if ( size_ == capacity_ ) { _growArray(); }
6
7      // Insert the new element at the end of the array
8      item_[++size] = key;
9
10     // Restore the heap property
11     _heapifyUp(size);
12 }
```

```
1  template <class T>
2  void Heap<T>::_heapifyUp( int index _____ ) {
3      if ( index > 1 _____ ) {
4          if ( item_[index] < item_[ parent(index) ] ) {
5              std::swap( item_[index], item_[ parent(index) ] );
6              _heapifyUp( parent (index) _____ );
7          }
8      }
9  }
```



# removeMin



	4	5	6	15	9	7	20	16	25	14	12	11			
--	---	---	---	----	---	---	----	----	----	----	----	----	--	--	--

# removeMin

```
1  template <class T>
2  void Heap<T>::_removeMin() {
3      // Swap with the last value
4      T minValue = item_[1];
5      item_[1] = item_[size_];
6      size--;
7
8      // Restore the heap property
9      heapifyDown();
10
11     // Return the minimum value
12     return minValue;
13 }
```



# removeMin- heapifyDown

```
1 template <class T>
2 void Heap<T>::_removeMin() {
3     // Swap with the last value
4     T minValue = item_[1];
5     item_[1] = item_[size_];
6     size--;
7
8     // Restore the heap property
9     _heapifyDown();
10
11     // Return the minimum value
12     return minValue;
13 }
```

```
1 template <class T>
2 void Heap<T>::_heapifyDown(int index) {
3     if ( !_isLeaf(index) ) {
4         T minChildIndex = _minChild(index);
5         if ( item_[index] > item_[minChildIndex] ) {
6             std::swap( item_[index], item_[minChildIndex] );
7             _heapifyDown( minChildIndex );
8         }
9     }
10 }
```




# CS 400

**Heap – buildHeap**


**ID: 10-03**

# buildHeap







# buildHeap – sorted array



# buildHeap - heapifyUp



# buildHeap - heapifyDown



# buildHeap


1. Sort the array – it's a heap!

2.

```
1 template <class T>
2 void Heap<T>::buildHeap() {
3     for (unsigned i = 2; i <= size_; i++) {
4         heapifyUp(i);
5     }
6 }
```

3.

```
1 template <class T>
2 void Heap<T>::buildHeap() {
3     for (unsigned i = parent(size); i > 0; i--) {
4         heapifyDown(i);
5     }
6 }
```






# CS 400

## **Heap – Runtime Analysis**

**ID: 10-04**

# Heap Sort



1. *built heap*

2.  $n * \text{removeMin } O(\log(n))$

3. Swap elements to order list  
(ASC/DESC)



## Running Time?

$n * \log(n)$

## Why do we care about another sort?

it's often going to be very convenient to do this sort entirely in memory