


Participation Constraints

26

- Does every student have to take a course?
 - ▣ If so, this is a participation constraint: the participation of Students in Enrolled is said to be *total* (vs. *partial*).
 - ▣ Every *sid* value in Students table must appear in a row of the Enrolled table (with a non-null *sid* value!)
- Textbook notation: total participation represented by a thick (bolded) line originating from entity


Example: Many-One Relationship

27




Example: Many-One Relationship

28



Alternative (Textbook) Notation


29



Notation


30

- Be consistent with your chosen notation!



Key Constraints

31





- Many-many: “An employee can work in many depts, and a dept. can have many employees
- One-many: A dept has **at most one** manager, and employees can manage many departments

Participation Constraints

32

- Does every dept. have to have a manager?
 - ▣ If yes, then every dept. must appear in the manages relation: **total** participation (vs. **partial**)




Attributes on Relationships

33

- Sometimes it is useful to attach an attribute to a relationship.
- Think of this attribute as a property of tuples in the relationship set.

Example: Attribute on Relationship

34



Price is a function of both the bar and the beer,
not of one alone.
E.g., "The price of Miller beer at Joe's bar"


Equivalent Diagrams Without Attributes on Relationships

35

- Create an entity set representing values of the attribute.
- Make that entity set participate in the relationship.

Example: Removing an Attribute from a Relationship

36



Note convention: arrow from multiway relationship
= "all other entity sets
together determine a
unique one of these."

Roles


37

- Sometimes an entity set appears more than once in a relationship.
- Label the edges between the relationship and the entity set with names called *roles*.

Example: Roles

38


Relationship Set



Example: Roles

39

Relationship Set



Subclasses

40

- **Subclass** = special case = more properties.
- **Example:** Ales are a kind of beer.
 - ▣ Not every beer is an ale, but some are.
 - ▣ Let us suppose that in addition to all the **properties** (attributes and relationships) of beers, ales also have the attribute **color**.


Subclasses in E/R Diagrams

41

- **isa** triangles indicate the subclass relationship.
 - ▣ Point to the superclass.
- Reasons for using isa:
 - ▣ To add descriptive attributes specific to a subclass.
 - ▣ To identify entities that participate in a relationship.

Example: Subclasses


42



Assume subclasses form a tree.

ISA ('is a') Hierarchies

43



- As in C++, or other PLs, attributes are inherited.
- If we declare A **ISA** B, every A entity is also considered to be a B entity.

- Overlap constraints:** Can two sub-classes contain the same entity?
E.g., Can Joe be an Hourly_Emps as well as a Contract_Emps entity?
- Covering constraints:** Does every Employees entity have to be an Hourly_Emps or a Contract_Emps entity?

R. Ramakrishnan & J. Gehrke


Keys

44

- A **key** is a set of attributes for one entity set such that no two entities in this set agree on all the attributes of the key.
 - It is allowed for two entities to agree on some, but not all, of the key attributes.
- We must designate a key for every entity set.
- Underline the key attribute(s).

Example: a Multi-attribute Key

45




- Note that **hours** and **room** could also serve as a key, but we must select only one primary key.

Keys

46

In an Isa hierarchy, only the root entity set has a key, and it must serve as the key for all entities in the hierarchy.



Weak Entity Sets

47

- Occasionally, entities of an entity set need “help” to identify them uniquely.
- Entity set E is said to be *weak* if in order to identify entities of E uniquely, we need to follow one or more many-one relationships from E and include the key of the related entities from the connected entity sets.


Example: Weak Entity Set

48

- $name$ is almost a key for football players, but there might be two with the same name.
- $number$ is certainly not a key, since players on two teams could have the same number.
- But $number$, together with the team $name$ related to the player by *Plays-on* should be unique.

In E/R Diagrams

49



Note: must be rounded because each player needs a team to help with the key.

- Double diamond for *supporting* many-one relationship.
- Double rectangle for the weak entity set.

Weak Entity-Set Rules

50

- A weak entity set has one or more many-one relationships to other (supporting) entity sets.
 - ▣ Not every many-one relationship from a weak entity set need be supporting.
 - ▣ But supporting relationships must have a rounded arrow (entity at the “one” end is guaranteed).

Weak Entity-Set Rules – (2)

51

- The key for a weak entity set is its own underlined attributes and the keys from the supporting entity sets.
 - ▣ Eg., (player) number and (team) name is a key for Players in the previous example.

Design Techniques

52

1. Avoid redundancy.
2. Limit the use of weak entity sets.
3. Don't use an entity set when an attribute will do.


Avoiding Redundancy

53

- **Redundancy** = saying the same thing in two (or more) different ways.
- Wastes space and (more importantly) encourages inconsistency.
 - ▣ Two representations of the same fact become inconsistent if we change one and forget to change the other.

Example: Good


54



This design gives the address of each manufacturer exactly once.

Example: Bad


55



This design states the manufacturer of a beer twice: as an attribute and as a related entity.

Example: Bad

56



This design repeats the manufacturer's address once for each beer and loses the address if there are temporarily no beers for a manufacturer.


Entity Sets Versus Attributes

57

- An entity set should satisfy at least one of the following conditions:
 - ▣ It is more than the name of something; it has at least one non-key attribute. OR
 - ▣ It is the "many" in a many-one or many-many relationship.
- Depends on the application requirements:
 - If we have several addresses per employee, *address* must be an entity (since attributes cannot be set-valued).
 - If the structure (city, street, etc.) is important, e.g., we want to retrieve employees in a given city, *address* must be modeled as an entity (since attribute values are atomic).

Example: Good


58



- **Manfs** deserves to be an entity set because of the nonkey attribute **addr**.
- **Beers** deserves to be an entity set because it is the "many" of the many-one relationship **ManfBy**.

Example: Bad


59



Since the manufacturer is nothing but a name, and is not at the "many" end of any relationship, it need not be an entity set.

Example: Good

60



There is no need to make the manufacturer an entity set, because we record nothing about manufacturers besides their name.