Interface	Getting information of detailed operation state
Method	GET

URI parameter	type	overview	remarkss
operation_id	string	Operation ID	-

URI /v1/operations/{operation_id}

ssage	code	body	type	required	null	empty array	overview	remarks
uest	T-	-	-	-	_	-	-	-
		operation id	string	Υ	N	Υ	Operation ID	-
		occurred time	string	Υ	N		Occurrence time	format is "YYYYMMDD_hhmmss"
								When the status is in the completed state, the
		last_update_time	string	Υ	N		Last update time	completion time is stored.
		last_apaato_timo	oung		.,		Lust aparte time	format is "YYYYMMDD_hhmmss"
						_		"unexecuted": Unexecuted
								unexecuted : Onexecuted
								"executing": Running
		status	string	string Y N	N		status	"completed" : completed
								"failed":failed
						\		"canceled": System dependent execution cancellate
				N	N		sub status	As required, each function stores the detailed stat
		sub_status	string	IN	IN		sub_status	"executing".
		request	object	Υ	Υ		Request information	=
		uri	string	Y	N		Request URI	_
		un	String		11	$\overline{}$	request oru	"POST"
								"PUT"
		1 1		.,	N.		B	
		method	string	Y	N		Request method	"DELETE"
								※ Only operations that can be asynchronous can
						\		specified Onaracter string information of request body
		body	string	Υ	N		Request body part	information
			Ü				1 ' ''	* For double quotation marked from the original,
		response	object	N	Υ		Response information	Required when status is "completed" or "failed"
		response	ODJOOC		•	$\overline{}$	response information	Set the value with the same policy as REST respo
				V	N		Process result information	
		status_code	int	ī	IN		Process result information	code
								Example: 200 = OK
						Λ		created for each processing.
						1		Basically it assumes the json format, but for do
	200					\ \		quotes, it is assumed to be replaced by [¥"] and
	200					\ \		
						\ \		stored.
		body	string	Υ	N	\	Response body part	※ In the IF case where information is not placed
		1 200,	04.11.6			\	Tresponde Boay part	the body part, it is an empty string.
						\		
						\		The created object_id to be included in the respon
						\		of the POST request,
						\		The message corresponding to the processing fail
					.,	,		is also showed beaut
		target_clusters	object[]	N	Y	Y		
		cluster_id	string	Υ	N			
		request	object	Υ	N			
	1	uri	string	Υ	N			
	1	method	string	Υ	N			
	1	body	string	Υ	N			
	1	response		N	Y			
1	1	status code		N	Y			
	1	body		N	Y			
	1			N	Y	$\overline{}$		
	1	rollbacks		IN .		$\overline{}$		
	1	result	string	Y	N			
	1	occurred_time	string	Υ	N			
	1	target_clusters		N	Υ	Υ		
	1	cluster_id	string	Υ	N			
	1	request	object	Υ	N			
	1	uri	string	Υ	N			
	1	method	string	Y	N			
	1	body		N	Y			
	1					_		
	1	response		N	Y			
Refe	1	status_code		N	Υ			
		body	string	N	Υ			
	D (to the "Error response format"	" sheet for err	or respon	nse			

Body uses JSON format.