Interface nar	ne	Deleting CP										
Method		DELETE										
		turn.						-				
		URI parameter	type string string string				overview	remarks				
		slice_type					Slice type	"l2vpn" : L2 slice "l3vpn" : L3 slice				
		slice_id					Slice ID	-				
		cp_id					CP ID	-				
		<u></u>	•									
		Optional parameters	type required string Y			overview	remarks					
		notification_address				Operation completion notification address	Refer to "Asynchronous request format" for					
		notification_port	string	Υ			Operation completion notification destination port	specification of optional parameters to URI				
URI		/v1/slices/{slice_type}/	{slice_id}/cp:	s/{cp_id}								
message	code	body	type	required	Allow nu	Allow empty	overview	remarks				
request	-	-	-	-	-	-	-	-				
response	202	operation_id	string	Υ	N		ID for getting information on asynchronous operation	-				
	Refer	Refer to the "Error response format" sheet for error response										

Asynchronous response

The result of the asynchronous response is set by being set in "processing result information (status_code)" and "response body part (body)" of "000103 operation detail acquisition" IF.

message	code	body	type	required	Allow nul	Allow empty	overview	remarks			
response	204	_	-	-	_	_	-	-			
	Refer to the "Error response format" sheet for error response										

Body uses JSON format.