Interface name	Bypass traffic to switch
Method	PUT

URI parameter	type	overview	remarks
cluster_id	string	cluster ID	-
fabric_type	string	Device type	"spines" : Spine "leafs" : Leaf
node_id	string	Device ID	-

Optional parameter	type	required	overview	remarks
notification_address	string	×	Operation completion notification address	Refer to "Asynchronous request format" for
notification_port	string	×	Operation completion notification destination port	specification of optional parameters to URI

URI /v1/detour/clusters/{cluster_id}/nodes/{fabric_type}/{node_id}

message	code	body	type	required	Allow null	Allow empty array	overview	remarks	
	_	action	string	0	×		Control type	"update"	
request		update_option	object	×	0		Optional information	If action is "update", required	
		detoured	boolean	0	×		Bypass state	true: Bypass / false: Non-bypass	
response	202	operation_id	string	0	×		ID for getting information on asynchronous operation		
	Refer	Refer to the "Error response format" sheet for error response							

Body uses JSON format.

Asynchronous response

The result of the asynchronous response is set by being set in "processing result information (status_code)" and "response body part (body)" of "000103 operation detail acquisition" IF.

message	code body	type	required	Allow null	Allow empty array	overview	remarks
	200 -	_	_	_	_	-	-
response							