

The response code list returned to MSF host system is shown below.
For the sake of simplicity, 400, 404, 409 for the response code originating from the client, and 500 for the response code attributed to the server.
It may be possible that the library you are using returns code other than the above, but it is not stipulated here.

Class	Response code	Request operation type				Overview	Other codes to include in the response code
		POST	GET	PUT	DELETE		
Normal response	200 OK	○	○	○	—	Successful resource acquisition, or resource update or processing request by POST succeed	—
	201 Created	○	—	—	—	When resource creation succeeds	—
	202 Accepted	○	—	○	○	When acceptance of processing is successful by asynchronous processing	—
	204 No Contents	—	—	—	○	When the resource deletion is successful	—
Abnormal response	400 Bad Request	○	○	○	○	When the data format is incorrect	401 Unauthorized 402 Payment Required 403 Forbidden 405 Method Not Allowed 406 Not Acceptable 408 Request Timeout 412 Precondition Failed 413 Request Entity Too Large 414 Request-URI Too Large 415 Unsupported Media Type
	404 Not Found	○	○	○	○	When it is desired to hide that the operation target resource does not exist or exists	—
	409 Conflict	○	—	○	○	If there is already a resource you want to create or the operation target resource is locked	—
	500 Internal Server Error	○	○	○	○	Processing can not be continued due to server origin.	501 Not Implemented 503 Service Unavailable