

Interface name	Getting IF traffic information
Method	GET

URI parameter	type	overview	remarks
cluster_id	string	Switch cluster ID	Fixed below "l3vpn" : L3 slice
fabric_type	string	fabric type	"spines" : Spine "leafs" : Leaf
node_id	string	Slice ID	-
if_type	string	IF type	"physical-if" : Physical IF "lag-if" : LagIF "breakout-if" : breakoutIF
if_id	string	IF ID	-

URI	/v1/traffic/clusters/{cluster_id}/nodes/{fabric_type}/{node_id}/interfaces/{if_type}/{if_id}
-----	--

message	code	body	type	required	Allow null	Allow empty array	overview	remarks
response	-	-	-	-	-	-	Traffic information	-
response	200	if_traffic	object	Y	N	-	Slice ID	Traffic information collected from the target device
		fabric_type	string	Y	N	-	fabric type	"spines" : Spine "leafs" : Leaf
		node_id	string	Y	N	-	Device ID	-
		traffic_value	object	Y	N	-	-	-
		if_type	string	Y	N	-	-	A value obtained by converting the number of received packets into a traffic amount (Gbps)
		if_id	string	Y	N	-	-	A value obtained by converting the number of transmitted packets into the traffic volume (Gbps)
		receive_rate	double	Y	N	-	receive rate	A value obtained by converting the number of received packets into a traffic amount (Gbps)
		send_rate	double	Y	N	-	transmission rate	A value obtained by converting the number of transmitted packets into the traffic volume (Gbps)
		Refer to the "Error response format" sheet for error response						

Body uses JSON format.