



Incident report analysis using NIST CSF

Summary	The company experienced a security event when all network services suddenly stopped responding. After investigating the team found that it was an ICMP flood attack. The incident management team responded by blocking incoming ICMP packets, stopping all non-critical network services offline, and restoring critical network services.
Identify	We investigated the incident and found that a malicious actor had sent a flood of ICMP pings into the company's network through an unconfigured firewall. This vulnerability allowed the malicious attacker to overwhelm the company's network through a DoS attack. During the attack, the company's internal network could not access any network resources and network services were shut down for two hours.
Protect	We configured the firewall to limit incoming ICMP packets. An IDS/IPS system was set up to detect and filter out some suspicious traffic.
Detect	Network monitoring software was installed to detect abnormal traffic patterns. We also configured the firewall for source IP address verification to check for spoofed IP addresses on incoming traffic.
Respond	For such future events, the security team will isolate affected systems to avoid any access/damage to the unaffected data and then attempt to restore the affected systems and bring it back to normal as soon as possible.
Recover	To recover from an ICMP flood attack we need to follow these steps: 1. Stop all non-critical network services temporarily to reduce network traffic. 2. All steps to restore the critical network services should be taken. 3. When the incoming ICMP packets time-out and the system is restored

	the non-critical network services can be brought back online.
--	---