Meta-Programming and Hybrid Parallel Strategies for Solving PDEs: An FDM and PINN Comparison [1] [2]

Seminar Presentation III

LI YIHAI

Student ID: 23345919

Supervision: Michael Peardon

September 18, 2024

Trinity College Dublin

Coláiste na Tríonóide, Baile Átha Cliath

[1] full docs: `https://liyihai.com/html/index.html`

[2] repository: `https://github.com/liyihai-official/Final-Project`

Outline

1. Introduction
   - Related Work
   - Challenges & Objectives
2. Problem Setups
   - General Form
   - Thermal Conduction Systems
3. Methodology
   - N-Dimension Matrix
   - Parallelization of N-dimension Arrays
4. Implementations
   - PDE Solvers
   - PINN Model
5. Experiments
   - On Single Node
   - On Multi-node
   - On Different Dimensions
   - With PINN on accuracy
6. Discussion

Outline

1. Introduction
   - Related Work
   - Challenges & Objectives
2. Problem Setups
   - General Form
   - Thermal Conduction Systems
3. Methodology
   - N-Dimension Matrix
   - Parallelization of N-dimension Arrays
4. Implementations
   - PDE Solvers
   - PINN Model
5. Experiments
   - On Single Node
   - On Multi-node
   - On Different Dimensions
   - With PINN on accuracy
6. Discussion

Kolmogorov PDEs

Solving $u(x,T)$, for $\mathbb{R}^1 \ni T > 0$, $x \in \mathbb{R}^d$, $t \in [0,T]$, $u(t,x) = u \in \mathbb{R}^1$, $\mu(x) \in \mathbb{R}^d$, $\sigma(x) \in \mathbb{R}^{d\times d}$,

$$u_t = \frac{1}{2}\,\mathrm{Trace}_{\mathbb{R}^d}\left[\sigma(x)\,[\sigma(x)]^*\,\mathrm{Hess}_x u\right] + \langle \mu(x), \nabla_x u\rangle_{\mathbb{R}^d} \tag{1}$$



Figure: Deep Neural Network (DNN) Methodology of Solving Kolmogorov PDEs [**FIRST**]

General Form of PDEs

– $u(t,x)$ denotes with the target function, $x \in \mathbb{R}^d$.

– $\Gamma[\,\cdot\,;\lambda]$ is a non-linear operator parameterized by λ.

$$u_t(t,x) + \Gamma[u;\lambda] = 0 \tag{2}$$

Define $f(t,x)$ to be given by

$$f(t,x) = u_t(t,x) + \Gamma[u;\lambda] \tag{3}$$



Figure: PINN, with 3 fully connected hidden layers

Comparing With Finite Difference Time Domain Method (FDTD)

1. Deep Neural Network [**FIRST**]
   - Gives lower quality approximations.
   - Takes longer time to train.
   - Possible to solve high dimension PDEs
2. Physics Informed Neural Network
   - Gives higher quality approximations.
   - Takes longer time to train.
   - Has more flexible way to get results.
   - Possible to solve high dimension PDEs

Objectives

This project focused on following objectives:

1. Implement FDTD and PINN in `C++/C`.
2. Implement FDTD hybrid parallel version using `MPI/OpenMP`.
3. Implement PINN GPU parallel version using `Libtorch/CUDA`.
4. Evaluate the efficiency and accuracy of FDTDs and PINNs.

Challanges

However, there were many obstacles including:

1. Portability.
2. Overlapping Communication and Computation.
3. Unnecessary intra-node communication
4. Communication Overhead.
5. Scalability Issues.
6. Memory Management.

Outline

1. Introduction
   - Related Work
   - Challenges & Objectives
2. Problem Setups
   - General Form
   - Thermal Conduction Systems
3. Methodology
   - N-Dimension Matrix
   - Parallelization of N-dimension Arrays
4. Implementations
   - PDE Solvers
   - PINN Model
5. Experiments
   - On Single Node
   - On Multi-node
   - On Different Dimensions
   - With PINN on accuracy
6. Discussion

General Form of problem

The PDE parametrized by number λ and an operator $\mathscr{N}[\cdot;\lambda]$, and assume the variable x is a 2D or 3D spatio-vector which is written in

$$\begin{cases} \dfrac{\partial u}{\partial t}(t,\vec{x}) + \mathscr{N}[u;\lambda] = 0 \\ u(0,\vec{x}) = \varphi(\vec{x}) \end{cases} \tag{4}$$

where φ is the initial condition, and $\vec{x} \in \Omega, t \in [0,+\infty)$.

Boundary Conditions

The Dirichlet and Von Neurmann boundary conditions are formed as

$$\begin{cases} u(t,\vec{x}) = g(t,\vec{x}) \\ \dfrac{\partial u}{\partial \vec{n}} = g(t,\vec{x}) \end{cases} \tag{5}$$

where $\vec{n}$ is the normal vector on $\overline{\Omega}$ the boundary of domain Ω.

The function

$$u(t,x,y) = x + y - xy,\ \forall \alpha \in \mathbb{R}^1 \tag{6}$$

is the solution of 2D Heat Equation 7 below

$$\begin{aligned}
&\frac{\partial u}{\partial t} = \alpha \left(\frac{\partial u^2}{\partial^2 x} + \frac{\partial u^2}{\partial^2 y} \right) && (x,y) \in \Omega,\ t \in [0,+\infty) \\
&u(0,x,y) = \varphi(x,y) = 0 && (x,y) \in \Omega \\
&u(t,x,y) = g(x,y) = \begin{cases} y,\ x = 0, y \in (0,1) \\ 1,\ x = 1, y \in (0,1) \\ x,\ y = 0, x \in (0,1) \\ 1,\ y = 1, x \in (0,1) \end{cases} && t \in [0,+\infty)
\end{aligned} \tag{7}$$

The function

$$u(t,x,y,z) = x+y+z-2xy-2xz-2yz+4xyz,\ \forall \alpha \in \mathbb{R}^1 \tag{8}$$

is the solution of 3D Heat Equation 9 below

$$\begin{aligned}
&\frac{\partial u}{\partial t} = \alpha\left(\frac{\partial u^2}{\partial^2 x}+\frac{\partial u^2}{\partial^2 y}+\frac{\partial u^2}{\partial^2 z}\right) && (x,y,z)\in\Omega,\ t\in[0,+\infty)\\
&u(0,x,y,z) = \varphi(x,y,z) = 0 && (x,y,z)\in\Omega\\
&u(t,x,y,z) = g(x,y,z) = \begin{cases} y+z-2yz, & x=0,\\ 1-y-z+2yz, & x=1,\\ x+z-2xz, & y=0,\\ 1-x-z+2xz, & y=1,\\ x+y-2xy, & z=0,\\ 1-x-y+2xy, & z=1 \end{cases} && t\in[0,+\infty)
\end{aligned} \tag{9}$$

Outline

1. Introduction
   - Related Work
   - Challenges & Objectives
2. Problem Setups
   - General Form
   - Thermal Conduction Systems
3. Methodology
   - N-Dimension Matrix
   - Parallelization of N-dimension Arrays
4. Implementations
   - PDE Solvers
   - PINN Model
5. Experiments
   - On Single Node
   - On Multi-node
   - On Different Dimensions
   - With PINN on accuracy
6. Discussion

STL provides containers `std::array` and `std::vector` for creating one-dimension array.
There are two way for dealing with high-dimension data:

1. Nesting the one dimension arrays or vectors.
2. Hierarchy approach, designing derived classes of one-dimension array base class.



Figure: Derived Class calling members in Base class, timing is not predictable.

1. Nesting multi-dimension array has non-contiguous memory layout.
2. Derived class needs more time to access members in base class.
3. Poor cache utilization leads to poor performance.
4. MPI type create requires contiguous memory layout.



Figure: Using nested `std::array<T, N>` to store 2D array data.

N-dimension Matrix
Solution

- An external small `__multi_array_shape` object defines the routines for accessing the elements.
- Smart pointer, ensure memory's contiguous layout and safety.
- Separate into two detail and user interface objects adhering RAII rules.



Figure: The solution of N-dimension Matrix, using detail Class, user interface Class and a shape management structure.

The hybrid PDE solver requires the MPI supports multi-threads on each processes.

- High-level libraries like Boost.MPI
  1. have better MPI resource management and other basic communication features.
  2. only provide limited useful features for latter PDE solvers.
  3. lead to lower performance than low-level OpenMPI.

- I developed an environment class for MPI
  1. better resource management than raw MPI.
  2. provides basic features exclusively for this project.

Distributed N-dimension arrays are created based on MPI N-dimension Cartesian topology.

1. Ghost communication is required in overlapping of MPI communication and local computation.
2. Parallel I/O is needed for debugging and storing results.
3. Topology information will be frequently used in PDE solver.

1. An MPI Topology class defines the distribution details of N-dimension array.
2. Using `MPI_Type_create_subarray` for creating Ghost MPI datatype for communication.
3. Cartesian array has members Topology class and N-dimension array class, to ensure they are closely located on memory.
4. The external functions provide gather-based I/O and MPI I/O for handling different scenarios.
5. User interface class unified features for both topology and array classes.
6. Separate into two detail and user interface objects adhering RAII rules.

Outline

1. Introduction
   - Related Work
   - Challenges & Objectives
2. Problem Setups
   - General Form
   - Thermal Conduction Systems
3. Methodology
   - N-Dimension Matrix
   - Parallelization of N-dimension Arrays
4. Implementations
   - PDE Solvers
   - PINN Model
5. Experiments
   - On Single Node
   - On Multi-node
   - On Different Dimensions
   - With PINN on accuracy
6. Discussion

N-dimension Boundary and Initial Conditions
Challanges

1. Mathematical function needs be discretized and distributed as well.
2. Need to access the data.
3. Initial and Dirichlet boundary conditions only applies once.
4. Von Neumann boundary condition participates the evolving process in FDM.

N-dimension Boundary and Initial Conditions
Solution

1. Use lambda function to construct classes.
2. Creating external classes for each conditions as the friend classes of PDE solver classes.
3. Set Bool vectors help to determine the status of conditions and type of boundary conditions.

1. PDE solver of Heat Equations in different dimension space have similar parameters and features, type-field solution lead to code redundancy.
2. Applying MPI communications between local arrays, avoiding overhead.
3. Three type of strategies:
    1. Pure MPI parallel
    2. Master-only, no overlapping hybrid parallel.
    3. Master-only, communication/computation overlapping hybrid parallel.

1. Create an abstract Heat base class of Heat Equation, and overriding functions in derived class on every dimension.

2. MPI communications are implemented in blocking and non-blocking ways using `MPI_Sendrecv` and `MPI_Isend`/`MPI_Irecv`.

3. Three type of strategies
    1. Pure MPI parallel

3. Three type of strategies
    1. Master-only, no overlapping hybrid parallel.

3. Three type of strategies
    1. Master-only, communication/computation overlapping hybrid parallel.

Outline

1. Introduction
   - Related Work
   - Challenges & Objectives
2. Problem Setups
   - General Form
   - Thermal Conduction Systems
3. Methodology
   - N-Dimension Matrix
   - Parallelization of N-dimension Arrays
4. Implementations
   - PDE Solvers
   - PINN Model
5. Experiments
   - On Single Node
   - On Multi-node
   - On Different Dimensions
   - With PINN on accuracy
6. Discussion

Outline

1. Introduction
   - Related Work
   - Challenges & Objectives
2. Problem Setups
   - General Form
   - Thermal Conduction Systems
3. Methodology
   - N-Dimension Matrix
   - Parallelization of N-dimension Arrays
4. Implementations
   - PDE Solvers
   - PINN Model
5. Experiments
   - On Single Node
   - On Multi-node
   - On Different Dimensions
   - With PINN on accuracy
6. Discussion

Closing Remarks

Thank you for your attention!

Any questions?