Homepage Personalization at Spotify

Oguz Semerci Spotify oguz@spotify.com

Ben Lacker Spotify benl@spotify.com Alois Gruson Spotify agruson@spotify.com

Clay Gibson Spotify cgibson@spotify.com Catherinee Edwards
Spotify
catherinee@spotify.com

Vladan Radosavljevic Spotify vladanr@spotify.com

ABSTRACT

We aim to surface the best of Spotify for each user on the Home page by providing a personalized space where users can find recommendations of playlists, albums, artists, podcasts tailored to their individual preferences. Hundreds of millions of users listen to music on Spotify each month, with more than 50 million daily active users on the Homepage alone. The quality of the recommendations on Home depends on a multi-armed bandit framework that balances exploration and exploitation and allows us to adapt quickly to changes in user preferences. We employ counterfactual training and reasoning to evaluate new algorithms without having to always rely on A/B testing or randomized data collection experiments [3].

In this talk, we explain the methods and technologies used in the end-to-end process of homepage personalization and demonstrate a case study where we show improved user satisfaction over a popularity-based baseline. In addition, we present some of the challenges we faced in implementing such machine learning solutions in a production environment at scale and the approaches used to address them.

The first challenge stems from the fact that training and offline evaluation of machine learning methods from incomplete logged feedback data requires robust off-policy estimators that account for several forms of bias [1, 2]. The ability to quickly sanity check and gain confidence in the methods we use in the production system is a crucial foundation for developing and maintaining effective algorithms. We demonstrate how we used a single-feature model, optimized for impression-to-click rate, to validate, and improve if necessary, the methods we use for off-policy estimation and accounting for position bias.

Lastly, the business metrics we optimize for do not always reflect the expectations of all users of the Home page at a granular level. Consider a niche, daily podcast producing independent, fact-based news every morning. A small segment of Spotify customers might want to see that content on top of their Home page every morning. We present simple but informative metrics we developed to validate our model's ability to account for such habitual behaviors of our customers.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

RecSys 19, September 16–20, 2019, Copenhagen, Denmark 2019 Association for Computing Machinery. ACM ISBN 978-1-4503-6243-6/19/09...\$15.00 https://doi.org/10.1145/3298689.3346977

CCS CONCEPTS

• Information systems \rightarrow Personalization; Recommender systems; Learning to rank.

KEYWORDS

Recommender Systems; Counterfactual Reasoning; Learning-to-rank; Personalization; Spotify

ACM Reference Format:

Oguz Semerci, Alois Gruson, Catherinee Edwards, Ben Lacker, Clay Gibson, and Vladan Radosavljevic. 2019. Homepage Personalization at Spotify. In Thirteenth ACM Conference on Recommender Systems (RecSys '19), September 16–20, 2019, Copenhagen, Denmark. ACM, New York, NY, USA, 1 page. https://doi.org/10.1145/3298689.3346977

REFERENCES

- [1] Alexandre Gilotte, Clément Calauzènes, Thomas Nedelec, Alexandre Abraham, and Simon Dollé. 2018. Offline A/B Testing for Recommender Systems. In Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining (WSDM '18). ACM, New York, NY, USA, 198–206. https://doi.org/10.1145/3159652.3159687
- [2] Thorsten Joachims, Adith Swaminathan, and Tobias Schnabel. 2017. Unbiased Learning-to-Rank with Biased Feedback. In Proceedings of the Tenth ACM International Conference on Web Search and Data Mining (WSDM '17). ACM, New York, NY, USA, 781–789. https://doi.org/10.1145/3018661.3018699
- [3] James McInerney, Benjamin Lacker, Samantha Hansen, Karl Higley, Hugues Bouchard, Alois Gruson, and Rishabh Mehrotra. 2018. Explore, Exploit, and Explain: Personalizing Explainable Recommendations with Bandits. In Proceedings of the 12th ACM Conference on Recommender Systems (RecSys '18). ACM, New York, NY, USA, 31–39. https://doi.org/10.1145/3240323.3240354