Liz Dauster Analytics

# Designing Smarter Workflows Under Operational Uncertainty

*A Systems and Causal Framework*
*for Automation Strategy in Regulated Laboratories*

---

## Table of Contents


1. Introduction & Problem Framing ..... 2
    1.1 Decision-Maker ..... 2
    1.2 Goals, Constraints & Pressures ..... 2
    1.3 Gap Between Current & Desired State ..... 3
2. Systems Analysis & Synthesis ..... 3
    2.1 System Architecture ..... 3
    2.2 Gap Analysis ..... 4
    2.3 System Synthesis ..... 4
    2.4 Model Variables ..... 4
    2.5 KPI Framework ..... 5
    2.6 Markov Network ..... 6
3. Conceptual Bayesian Causal Model ..... 6
    3.1 Model Rationale ..... 7
4. Decision Analysis ..... 7
    4.1 Alternatives ..... 7
    4.2 Preferences & Utility Considerations ..... 7
    4.3 Reasoning ..... 7
    4.4 Conceptual Recommendation ..... 7
5. Conclusion ..... 8
    5.1 Limitations ..... 8
    5.2 Future Development ..... 8

# 1. Introduction & Problem Framing

Regulated Quality Control (QC) laboratories are experiencing rising sample volumes, increased scrutiny of data integrity, and tighter release timelines. To address these pressures, QC leadership must evaluate transitioning from fully manual sample handling and data transcription to a semi-automated workflow.

Currently, lab personnel manually transcribe instrument outputs into spreadsheets or reports, introducing delays and the risk of errors. While this manual workflow works under moderate workloads, it becomes fragile under sustained pressure, leading to longer cycle times and potential release bottlenecks.

The central question is whether the current workflow can sustain increased demand without compromising reliability or overburdening capacity. This brief evaluates the automation decision as a systems intervention, focusing on how workflow architecture affects workload, cycle time variability, instrument utilization, and overall QC performance stability.

## 1.1 Decision-Maker

The decision is whether to maintain the existing manual workflow or implement semi-automation to reduce transcription touchpoints and standardize documentation capture. The trade-off is clear: short-term validation effort versus long-term structural stability.

Decision authority resides with the Quality Assurance Manager, who is accountable for data integrity and compliance posture. Although QA holds authority, technical and operational stakeholders inform feasibility, validation scope, and implementation risk. The decision, therefore, balances compliance risk with measurable gains in throughput stability and capacity resilience.

## 1.2 Goals, Constraints & Pressures

The redesign must improve throughput stability and workload sustainability without increasing headcount or compromising inspection readiness.

Objectives are interdependent:

- Reduce manual transcription burden
- Stabilize cycle time variability
- Maintain utilization below saturation thresholds
- Improve effective runs per instrument-hour

Constraints are structural. GMP and ISO validation requirements slow system changes. IT/OT integrations require formal qualification. The budget and staffing are fixed. Implementation downtime is unacceptable because QC acts as a product release gate.

External pressures compound the issue. Smaller batch sizes and increased lot frequency raise sample volume. Lean manufacturing reduces operational slack. Heightened regulatory scrutiny increases sensitivity to documentation errors. As demand grows, manual processes amplify variability rather than absorb it, widening the gap between workload demand and processing stability.

### 1.3 Gap Between Current & Desired State

In the current state, manual documentation steps consume disproportionate analyst time. For example, duplicative data entry between instrument output and controlled records increases review burden and hands-on time per sample. As workload rises, effective throughput fails to scale proportionally.

A reinforcing dynamic emerges:
Higher sample volume → increased analyst workload → greater cycle time variability → rising instrument utilization → reduced scheduling flexibility → higher instability risk.

The desired state is not simply faster processing, but structural stability under load, characterized by:

- Reduced manual transcription
- Improved runs per instrument-hour
- Lower cycle time variability
- Utilization below saturation thresholds
- Sustainable analyst workload

The accompanying dashboard and modeling notebook quantify this gap using measurable indicators of throughput, cycle time, instrument utilization, manual entry reduction, and capacity saturation risk. The performance deficit is therefore structural and observable.

## 2. Systems Analysis & Synthesis

### 2.1 System Architecture

The QC workflow includes sample login, bench testing, result capture, documentation preparation, and layered review. While instruments are automated, data capture and downstream documentation often remain manual.

### People
Analysts balance testing, documentation, troubleshooting, audit preparation, and investigations. Under elevated demand, cognitive load increases and execution time variability widens.

### Structure
Partial system integration and legacy documentation practices create redundant steps. Analysts frequently reformat electronic outputs before review. Validation requirements slow structural change, reinforcing reliance on manual processes.

### Environment
Increased lot frequency and regulatory scrutiny compress slack and heighten sensitivity to documentation inefficiencies.

Together, these dimensions produce a tightly coupled system that is vulnerable to the accumulation of variability.

## 2.2 Gap Analysis
A structural mismatch exists between demand growth and documentation architecture. Manual transcription and review bottlenecks constrain throughput and increase hands-on time per sample. Capacity strain rises not because instruments are inadequate, but because workflow friction consumes analyst bandwidth.

## 2.3 System Synthesis
Workload, variability, and utilization interact through reinforcing dynamics. Increased demand elevates workload. Elevated workload increases cycle time variability. Variability reduces effective throughput, pushing utilization toward capacity limits. High utilization reduces scheduling flexibility, increasing the risk of instability.

Automation acts as a structural intervention by reducing manual friction and moderating these reinforcing loops.

## 2.4 Model Variables
The model includes:
Chance Variables

- External Demand (ED)
- Sample Volume (SV)
- Analyst Workload (AW)
- Cycle Time (CT)
- Instrument Utilization (IU)
- Regulatory Pressure (RP)

Decision Variable

- Automation Level (AL)

Outcome Variable

- QC Performance Utility (QCP)

$$QCP \propto TS \times \frac{1}{CTV} \times 1 - CSR \times MFR$$

| Variable | Definition | Desired State |
|---|---|---|
| TS | Throughput stability | Consistent |
| CTV | Cycle Time Variability | Controlled |
| CSR | Capacity Saturation Risk | Moderated |
| MFR | Manual Friction | Reduced |

## 2.5 KPI Framework

The dashboard and modeling notebook translate system variables into measurable indicators:

**Throughput** = Runs per instrument-hour

**Cycle Time** = Average processing time per sample

**Manual Entry Reduction** = Percent decrease in transcription touchpoints

**Instrument Utilization** = Percent capacity used per instrument type

**Failure Rate Stability** = Consistency of failure frequency over time

**Capacity Saturation Risk** = Modeled risk of instability as utilization approaches saturation thresholds.

Throughput and cycle time serve as observable indicators of analyst workload pressure. Instrument utilization and saturation risk reflect the system's structural strain. Manual entry reduction represents the primary control lever for the Automation Level.

## 2.6 Markov Network




Figure 1. Undirected Markov Network showing key interdependencies.

The undirected Markov network maps conditional dependencies among demand, volume, workload, utilization, cycle time, regulatory pressure, automation level, and performance. It highlights system tight coupling under demand growth.

This structural representation sets the stage for directional modeling of automation as an intervention variable.

# 3. Conceptual Bayesian Causal Model




Figure 2. Formal directional influence, modeling Automation Level as a policy lever
that shifts workload, cycle time, and utilization dynamics, which in turn, determine QC performance stability.

### 3.1 Model Rationale

This causal framing clarifies how workflow redesign shifts the operating equilibrium. Automation does not directly improve performance. It alters system dynamics that determine stability under load. Specifically, automation level influences performance indirectly through intermediate states:

- Automation → Reduced manual friction → Lower workload pressure
- Automation → Stabilized cycle time → Improved throughput consistency
- Automation → Moderated instrument utilization → Reduced saturation risk

These intermediate effects shift the system toward a more stable operating region, as demonstrated in the dashboard metrics and capacity-risk simulation.

## 4. Decision Analysis

### 4.1 Alternatives

Option 1: Maintain the current, highly manual workflow
Option 2: Implement semi-automation for sample handling and data capture

Expanded LIMS integration is excluded due to cost constraints.

### 4.2 Preferences & Utility Considerations

The decision-maker values:

- Compliance reliability
- Stable throughput
- Sustainable workload
- Acceptable validation risk

### 4.3 Reasoning

Manual workflows amplify workload pressure and increase cycle time variability under rising demand. Semi-automation reduces manual touchpoints, stabilizes intermediate states, and improves structural resilience despite short-term validation cost.

### 4.4 Conceptual Recommendation

Based on the modeled causal pathways and defined utility structure, semi-automation is the preferred option. It strengthens long-term workflow stability and capacity resilience while maintaining compliance integrity.

# 5. Conclusion

This analysis demonstrates that structural workflow constraints, rather than instrument limitations alone, drive QC instability under growth conditions. By modeling intermediate system states, automation emerges as a targeted intervention that improves stability by reducing manual touchpoints, moderating workload pressure, and controlling utilization.

## 5.1 Limitations

The model is conceptual and does not quantify probabilities or utilities. It abstracts operational complexity and does not account for detailed implementation constraints such as resource allocation or vendor variability.

## 5.2 Future Development

Future work could incorporate historical operational data, estimate probabilistic effects of automation levels using Bayesian inference, and model optimal rollout strategies through simulation or prescriptive optimization.