# Module Interface Specification for Time_Freq_Analysis

Elizabeth Hofer

November 23, 2020

# 1 Revision History

| Date | Version | Notes |
|---|---|---|
| 11.19.2020 | 1.0 | Initial Release |

# 2 Symbols, Abbreviations and Acronyms

See SRS Documentation at https://github.com/liziscool/cas741_project/blob/master/docs/SRS/SRS.pdf

# Contents

# 3 Introduction

The following document details the Module Interface Specifications for Time_Freq_Analysis, a program to compute the time-frequency analysis of a 1 dimensional signal.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at https://github.com/liziscool/cas741_project.

# 4 Notation

The structure of the MIS for modules comes from Hoffman and Strooper (1995), with the addition that template modules have been adapted from Ghezzi et al. (2003). The mathematical notation comes from Chapter 3 of Hoffman and Strooper (1995). For instance, the symbol := is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1|c_2 \Rightarrow r_2|...|c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by Time_Freq_Analysis.

| Data Type | Notation | Description |
|---|---|---|
| character | char | a single symbol or digit |
| integer | $\mathbb{Z}$ | a number without a fractional component in (-$\infty$, $\infty$) |
| natural number | $\mathbb{N}$ | a number without a fractional component in [1, $\infty$) |
| real | $\mathbb{R}$ | any number in (-$\infty$, $\infty$) |
| complex | $\mathbb{C}$ | a number with a real part $a$ and an imaginary part $b$ s.t. $a + bi$ where $i$ is the imaginary number |

The specification of Time_Freq_Analysis uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, Time_Freq_Analysis uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

# 5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

| **Level 1** | **Level 2** |
|---|---|
| Hardware-Hiding Module | |
| Behaviour-Hiding Module | Input Parameter Module<br>Specification Param Module<br>Read Data Module<br>Boundary Configuration Module<br>STFT Module<br>Wavelet Module<br>Output Verification Module<br>Output Module<br>Compute Transform Module<br>Control Module |
| Software Decision Module | Zero-Pad Module<br>Matrix Data Structure Module<br>Plotting Module<br>Fast Fourier Transform Module |

Table 1: Module Hierarchy

# 6 MIS of Control Module

## 6.1 Module

main

## 6.2 Uses

Compute Transform Module 15, Output Module 14, Output Verification Module, Plotting Module 18

## 6.3 Syntax

### 6.3.1 Exported Constants

None.

### 6.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| main | $argc$ : $\mathbb{N}$, $< argv_1, \ldots, argv_{argc} >$ s.t. $argv_n : string$ | - | - |

## 6.4 Semantics

### 6.4.1 State Variables

None.

### 6.4.2 Environment Variables

None.

### 6.4.3 Assumptions

- User enters correct inputs for calculation that is expected.
- User enters inputs in correct format.

### 6.4.4 Access Routine Semantics

main():

- transition: Controls the entire program, transition through the program as follows:
  1. Sets `param` from command line arguments `set_inputs()`.

2. Calls compute transform module with `comp_transform()`.
3. Plots output with `plot_matrix()`

### 6.4.5 Local Functions

None.

# 7 MIS of Specification Parameter Module

## 7.1 Module

spec_param

## 7.2 Uses

None.

## 7.3 Syntax

### 7.3.1 Exported Constants

| Name | Type |
|---|---|
| MIN_FREQ | $\mathbb{R}$ |
| MAX_FREQ | $\mathbb{R}$ |
| MIN_SIG_LEN | $\mathbb{N}$ |
| MAX_SIG_LEN | $\mathbb{N}$ |
| STEP_SIZE | $\mathbb{N}$ |
| WIN_SIZE | $\mathbb{N}$ |

### 7.3.2 Exported Access Programs

None.

## 7.4 Semantics

### 7.4.1 State Variables

None.

### 7.4.2 Environment Variables

None.

### 7.4.3 Assumptions

None.

### 7.4.4 Access Routine Semantics

None.

### 7.4.5 Local Functions

None.

## 7.5 Considerations

This module basically just holds all of the constants.

# 8 MIS of Input Param Module

## 8.1 Module

input_param

## 8.2 Uses

Specification Param Module 7, Hardware Hiding Module

## 8.3 Syntax

### 8.3.1 Exported Constants

None.

### 8.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| set_input | $argc$ : $\mathbb{N}$, $< argv_1, \ldots, argv_{argc} >$ s.t. $argv_n$ : $string$ | - | bad_arguments, bad_min_time, bad_max_time, bad_time_range, bad_min_freq, bad_max_freq, bad_freq_range , bad_transform_type |
| param.N | - | $\mathbb{N}$ | |
| $f_1$ | - | $\mathbb{R}$ | |
| $f_2$ | - | $\mathbb{R}$ | |
| $n_1$ | - | $\mathbb{R}$ | |
| $n_2$ | - | $\mathbb{R}$ | |
| transform_type | - | $\{`W', `S'\}$ | |
| param.time_res | - | $\mathbb{N}$ | |
| param.freq_res | - | $\mathbb{N}$ | |
| param.sig_file | - | string | |

## 8.4 Semantics

### 8.4.1 State Variables

None.

### 8.4.2 Environment Variables

None.

### 8.4.3 Assumptions

While there will be measures in place to check that the input values comply with the ability of the program, some additional assumptions are listed below

1. The user inputs the correct file path.
2. The bounds are appropriate for the signal.
3. The input parameters must be set (initialized) before they are accessed.

### 8.4.4 Access Routine Semantics

set_input():

- output: None.
- exception: exc:=

$$\begin{cases} bad\_arguments & \text{if any of the arguments are incorrectly flagged (i.e. using a flag that doesnt} \\ bad\_min\_time & \text{if } n_1 \geq n_2 \\ bad\_max\_time & \text{if } n_2 > N \\ bad\_time\_range & \text{if } (n_2 - n_1) > MAX\_SIG\_LEN \text{ or } (n_2 - n_1) < MIN\_SIG\_LEN \\ bad\_min\_freq & \text{if } f_1 < MIN\_FREQ \\ bad\_max\_freq & \text{if } f_2 < MAX\_FREQ \\ bad\_freq\_range & \text{if } (f_2 - f_1) > MAX\_FREQ\_RZANGE \text{ or } (f_2 - f_1) < MIN\_FREQ\_RAN \\ bad\_transform\_type & \text{if T is not 'W' or 'S'} \end{cases}$$

param.N :

- output: $out := N$
- exception: none

param.f1 :

- output: $out := f_1$
- exception: none

param.f2 :

- output: $out := f_2$

- exception: none

param.n1 :

- output: $out := n_1$
- exception: none

param.n2 :

- output: $out := n_2$
- exception: none

param.time_div :

- output: $out := time\_div$
- exception: none

param.freq_div :

- output: $out := freq\_div$
- exception: none

param.time_res :

- output: $out := time\_res$
- exception: none

param.freq_res :

- output: $out := freq\_res$
- exception: none

param.sig_filename :

- output: $out := sig\_filename$
- exception: none

### 8.4.5 Local Functions

None.

# 9 MIS of Read Data Module

## 9.1 Module

read_data

## 9.2 Uses

Input Param Module 8

## 9.3 Syntax

### 9.3.1 Exported Constants

None.

### 9.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| read_sig | sig_filename:string | $< x_1, \ldots, x_N > x_n : \mathbb{R}$ | bad_path, empty_file, file_wrong_format |

## 9.4 Semantics

### 9.4.1 State Variables

None.

### 9.4.2 Environment Variables

None.

### 9.4.3 Assumptions

1. File should be in correct format.

### 9.4.4 Access Routine Semantics

read_sig():

- output: out := $< x_1, \ldots, x_N >$

- exception: exc :=

$$\begin{cases} bad\_file & \text{if the file or a directory on the path does not exist} \\ empty\_file & \text{if the file has no data in it} \\ file\_format\_wrong & \text{if data in the folder is not in } \mathbb{R} \text{ or uses incorrect delimter} \end{cases}$$

#### 9.4.5 Local Functions

None.

# 10 MIS of Boundary Configuration Module

## 10.1 Module

bound_config

## 10.2 Uses

Specification Param Module 7

## 10.3 Syntax

### 10.3.1 Exported Constants

None.

### 10.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| calc_freq_res | $f_1 : \mathbb{R}$,$f_2 : \mathbb{R}$, win_size : $\mathbb{N}$ | $\mathbb{R}$ | - |
| calc_time_res | $n_1 : \mathbb{N}$,$n_2 : \mathbb{R}$, step_size : $\mathbb{N}$ | $\mathbb{N}$ | - |

## 10.4 Semantics

### 10.4.1 State Variables

None.

### 10.4.2 Environment Variables

None.

### 10.4.3 Assumptions

None.

### 10.4.4 Access Routine Semantics

calc_freq_res():

- output: out := $(f_2 - f_1) * win\_size$

calc_time_res():

- output: out := $\frac{(n_2 - n_1)}{\frac{win\_size}{step\_size}}$

### 10.4.5 Local Functions

None.

## 10.5 Considerations

At the time this document was written, the writer is not totally confident in the methods to calculate time_res or freq_res. The equations provided above are sufficient to communicate the point, but in execution it may be more complicated, and at that time this section of the document will be updated to reflect that.

# 11 MIS of STFT Module

## 11.1 Module

STFT

## 11.2 Uses

FFT Module, Boundary Configuration Module 10 Matrix Data Structure Module 17

## 11.3 Syntax

### 11.3.1 Exported Constants

None.

### 11.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| comp_stft | $< x_1, \ldots, x_N >$ where $x_n : \mathbb{R}$, $N : \mathbb{N}$, time_res: $\mathbb{N}$, freq_res: $\mathbb{N}$ | $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ where $x_{i,j} : \mathbb{C}$ | - |

## 11.4 Semantics

### 11.4.1 State Variables

None.

### 11.4.2 Environment Variables

None.

### 11.4.3 Assumptions

None.

### 11.4.4 Access Routine Semantics

comp_stft():

- output: out := $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ where $X_{i,j} : \mathbb{C}$ s.t.

$$X(i,j) = \sum_{i=0}^{WIN\_SIZE} x_i w_i e^{-\hat{i}\omega j} \tag{1}$$

  and $I[0, time\_res]$ and $J[0, freq\_res]$ and $\hat{i}$ is the imaginary number.

- This routine will utilize the fast Fourier transform.

### 11.4.5 Local Functions

window_function():

- output: out := $< w_0, \ldots, w_{WIN\_SIZE} >$ where

$$w_n = (\sin \frac{\pi * n}{WIN\_SIZE})^2 \tag{2}$$

# 12 MIS of Wavelet

## 12.1 Module

wavelet

## 12.2 Uses

FFT Module, Boundrey Configuration Module 10, Matrix Data Structure Module 17

## 12.3 Syntax

### 12.3.1 Exported Constants

None.

### 12.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| comp_waveletT | $< x_1, \ldots, x_N >$ where $x_n : \mathbb{R}$, $N : \mathbb{N}$, time_res: $\mathbb{N}$, freq_res : $\mathbb{N}$ | $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ where $x_{i,j} : \mathbb{C}$ | - |

## 12.4 Semantics

### 12.4.1 State Variables

None.

### 12.4.2 Environment Variables

None.

### 12.4.3 Assumptions

None.

### 12.4.4 Access Routine Semantics

comp_waveletT():

- output: out := $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ s.t.

$$X(a,b) = \frac{1}{\sqrt{a}} \Sigma_{n=0}^{wav\_scale\_a} \Psi_{a,b,n} x_n \tag{3}$$

  where $\Psi_{a,b,n}$ represents the wavelet scaled by $a$ and shifted by $b$.

### 12.4.5 Local Functions

wavelet_function():

- output: out := $< w_0, \ldots, w_{wav\_scale\_a} >$ where

$$w_n = c_\sigma \pi^{-\frac{1}{4}} e^{-\frac{1}{2}t} (e^{i\sigma n} - \kappa_\sigma) \tag{4}$$

  and where $\kappa_\sigma = e^{1\frac{1}{2}\sigma^2}$ and $c_\sigma = (1 + e^{-\sigma^2} - 2e^{-\frac{3}{4}\sigma^2})^{\frac{1}{2}}$, a.k.a. a Morlet Wavelet.

# 13 MIS of Output Verification Module

## 13.1 Module

output_verify

## 13.2 Uses

Matrix Data Module

## 13.3 Syntax

### 13.3.1 Exported Constants

None.

### 13.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| verify_output | $<$ $X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ where $x_{i,j} : \mathbb{R}$ | $b : \mathbb{B}$ | - |

## 13.4 Semantics

### 13.4.1 State Variables

None.

### 13.4.2 Environment Variables

None.

### 13.4.3 Assumptions

None.

### 13.4.4 Access Routine Semantics

verify_output():

- output: out :=
$$\begin{cases} T & \text{if transform passes verification} \\ F & \text{if transform fails verification} \end{cases}$$

To pass the verification the output matrix must pass the following conditions:

$$\Sigma_{j=0}^{freq\_res} X_{i,j} \leq \Sigma x_n \tag{5}$$

where $\Sigma x_n$ and corresponds to the portion of the signal represented by $i$ in $X_{i,j}$.

#### 13.4.5 Local Functions

None.

# 14 MIS of Output Module

## 14.1 Module

output

## 14.2 Uses

Hardware Hiding Module

## 14.3 Syntax

### 14.3.1 Exported Constants

### 14.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| get_output | - | $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ where $x_{i,j} : \mathbb{R}$ | - |

## 14.4 Semantics

### 14.4.1 State Variables

None.

### 14.4.2 Environment Variables

None.

### 14.4.3 Assumptions

1. The user requires the memory location of the output matrix, as in it does not need to be written to any external file.

### 14.4.4 Access Routine Semantics

get_output():

- output: out := $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ where $x_{i,j} : \mathbb{R}$
  where $X$ is the time frequency representation of the data as calculated by Time_Freq_Analysis.

### 14.4.5 Local Functions

None.

# 15 MIS of Compute Transform

## 15.1 Module

comp_transform

## 15.2 Uses

Read Data Module 9, Wavelet Module 12, STFT Module 11, Zero Pad Module 16, Matrix Data Structure Module 17

## 15.3 Syntax

### 15.3.1 Exported Constants

None.

### 15.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| comp_transform | $< x_1, \ldots, x_N >$ where $x_n : \mathbb{R}$, $N : \mathbb{N}$, $f_1 : \mathbb{R}$, $f_2 : \mathbb{R}$, $T : \{`W', `S'\}$ | $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ where $x_{i,j} : \mathbb{R}$ | - |

## 15.4 Semantics

### 15.4.1 State Variables

None.

### 15.4.2 Environment Variables

None.

### 15.4.3 Assumptions

None.

### 15.4.4 Access Routine Semantics

comp_transform():

- output: $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{I,J} >$ where $x_{i,j} : \mathbb{R}$

Such that $X$ is calculated in the following way:

1. The input signal is read using `read_data` 9 using the parameters specified by the Input Parameter Module 8.
2. The signal is zero-padded using Zero Pad Module.
3. Some computations are done regarding the boundary configuration using `calc_freq_res` and `calc_time_res` from 10 which are needed for the following step.
4. The signal is transformed using ether `comp_waveletT` if $T = `W'$ or `comp_STFT` if $T = `T'$
5. The matrix output from the transforms are complex, to convert them to a real power values the matrix is $X$ is computed from as followed:
   $X_{i,j} = \sqrt{X_{\mathbb{C}}.real^2 +_{\mathbb{C}} .im^2}$
   Where $X_{\mathbb{C}}.real$ is the real part of the transform and $X_{\mathbb{C}}.im$ is the imaginary part.

### 15.4.5 Local Functions

None.

## 15.5 Considerations

The Zero-Pad Module extends the size of the signal $x$ by 2 times the window size $WIN\_SIZE$, however, this doesn't affect the size of the output transform matrix.

# 16 MIS of Zero Pad Module

## 16.1 Module

zero_pad

## 16.2 Uses

None.

## 16.3 Syntax

### 16.3.1 Exported Constants

None.

### 16.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| zero_pad_sig | $< x_1, \ldots, x_N >$ where $x_n : \mathbb{R}$, $N : \mathbb{N}$, $WIN\_SIZE$ | $< x_1, \ldots, x_{N+2WIN\_SIZE} >$ | - |

## 16.4 Semantics

### 16.4.1 State Variables

None.

### 16.4.2 Environment Variables

None.

### 16.4.3 Assumptions

None.

### 16.4.4 Access Routine Semantics

zero_pad_sig():

- output: $< x_1, \ldots, x_{N+2WIN\_SIZE} >$ such that $x_n = 0$ from $n[0, WIN\_SIZE]$, $x_{n+WIN\_SIZE} = \hat{x}_n$ from $n[0, N]$ where $\hat{x}$ is the original signal and $N$ is the length of the original signal.

### 16.4.5 Local Functions

None.

# 17 MIS of Matrix Data Structure Module

## 17.1 Module

mat

## 17.2 Uses

None.

## 17.3 Syntax

### 17.3.1 Exported Constants

None.

### 17.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| init | $X : \mathbb{N}$, $Y : \mathbb{N}$ | $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{X,Y} >$ where $x_{x,y} : NULL$ | - |
| m | $x : \mathbb{N}, y : \mathbb{N}$ | $m : \mathbb{R}$ | - |

## 17.4 Semantics

### 17.4.1 State Variables

None.

### 17.4.2 Environment Variables

None.

### 17.4.3 Assumptions

None.

### 17.4.4 Access Routine Semantics

mat.init():

- output: $< X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{X,Y} >$
  Where $X_{x,y}$ is null but it is large able to hold type $\mathbb{R}$.

mat.m():

- output: $m : \mathbb{R}$
  $m$ is the data in the matrix at the specified index.

### 17.4.5 Local Functions

None.

# 18 MIS of Plotting Module

## 18.1 Module

plot

## 18.2 Uses

None.

## 18.3 Syntax

### 18.3.1 Exported Constants

None.

### 18.3.2 Exported Access Programs

| Name | In | Out | Exceptions |
|---|---|---|---|
| plot_matrix | $<$ $X_{0,0}, X_{0,1}, \ldots, X_{1,0}, X_{1,1}, \ldots, X_{X,Y} >$ where $x_{x,y} : \mathbb{R}$ | $b : \mathbb{B}$ | bad_path |

## 18.4 Semantics

### 18.4.1 State Variables

None.

### 18.4.2 Environment Variables

None.

### 18.4.3 Assumptions

None.

### 18.4.4 Access Routine Semantics

plot_matrix():

- output: out:=
$$\begin{cases} F & \text{if output file was not created sucessfully} \\ T & \text{if output file was created sucessfully} \end{cases}$$

- exception: exc:= bad_path if out file was not written successfully.

### 18.4.5 Local Functions

| Name | In | Out | Description |
|---|---|---|---|
| calc_colour | $x : \mathbb{R}$ | $R, B, G : \mathbb{R}$ | converts the matrix value into corresponding R,G,B values for heat map |

# References


Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. *Fundamentals of Software Engineering*. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.

Daniel M. Hoffman and Paul A. Strooper. *Software Design, Automated Testing, and Maintenance: A Practical Approach*. International Thomson Computer Press, New York, NY, USA, 1995. URL http://citeseer.ist.psu.edu/428727.html.

# 19 Appendix