

Compilation

William Hendrix

Lecture 23

Today

- Machine code
- Programming languages
- Compilation in C/C++
- Preprocessor directives
- `goto`

Machine code

- Binary instructions that are actually executed by the computer
 - Instruction set depends on architecture
- **Example:** 0x401046: 03 45 08
 - Adds 8 to the value in register `%ebp` and stores the result in register `%eax`
- Instructions encode for operations like arithmetic, branching (control flow/loops), store/load (from main memory), and jumps (e.g., function return)
- When an executable is running, instructions are loaded into memory
 - Also loads program data, like constant strings
- Program counter (instruction pointer) register keeps track of where we are in execution of program
 - Advances by one instruction each time, except when branching, looping, function return, etc.
- Machine code can be interpreted quickly by CPU, but essentially incomprehensible to humans

Assembly

- Lowest level programming language
- Defines a set of mnemonics for machine instructions
 - May vary by architecture
- **Example**
`addl 8 (%ebp), %eax`
- Improves readability for people
- Straightforward (one-to-one) conversion into machine code
- Assembler: program that translates assembly into machine code
- Disassembler: program that translates machine code back into assembly
- Assembly can be directly added to C/C++ programs with `__asm__` keyword
 - **Example**
`__asm__ volatile { "rdtsc": "=a" (low) "=d" (high) }`

Higher-level programming languages


- Languages that can be converted into assembly and machine code
 - Each language defines its own syntax and semantics
 - **Examples:** C++, Java, Python, FORTRAN, Lisp, Ruby, Lua, ...
 - Different languages may have different strengths/weaknesses
- Higher-level languages hide the details of assembly from the programmer
 - Simplify tasks
 - Improve productivity
- Compiler
 - Program that transforms code in a higher-level programming language into assembly
 - Checks code to ensure that it follows language syntax
 - May print errors or warnings

Linking

- Program that “binds” function calls to the function implementation
- Each source file (`.cpp`) is compiled to a separate *object file* (`.o`)
 - Object files are machine code with information about functions they define
- Function calls in object files are “linked” with the functions they call
 - Includes calls to built-in functions
 - Linker produces the final executable or library
 - Throws an error if it cannot find a function
 - “Unresolved symbol”
- Static linking (`.a`)
 - Code for library functions inserted directly into library/executable
- Dynamic linking (`.so`, `.dll`)
 - Stores offsets from library file
 - Library file must be present for the code to run
 - Executable size is much smaller (avoids replication)
 - Execution is slightly slower
 - Potential issues with different library versions

Compilation in C/C++

- C/C++ have an additional step before compilation
- Preprocessor
 - Modifies code before compilation (and syntax checking)
 - Controlled by # directives
 - E.g., `#include "menagerie.h"`
- **Compilation pipeline:**



Preprocessor directives

- `#include`: pastes contents of header file at this location
- `#define`: defines symbols or macro functions that are replaced before compilation

```
#define SECONDS_PER_MINUTE 60
```
- `#undef`: “undefines” a symbol

```
#undef SECONDS_PER_MINUTE
```
- `#line`: replaced by line number
- `#if`, `#ifdef`, `#ifndef`, `#elif`, `#else`, `#endif`
 - Act like `if`, `else if`, `else`
 - Code is removed if condition fails
 - Commonly used with `#define DEBUG`

Macro functions

- Function-like symbols that can insert a parameterized block of code
- **Warning:** can make your code more difficult to read and use

- **Example**

```
#define print_array(arr, len) \  
    for (int i = 0; i < (len); i++) \  
        cout << (arr)[i] << ' ';
```

- “Implementation” appears on the rest of the line
- Preprocessor replaces all “calls” to macro functions with function body
 - Inserts passed “parameters” in code
 - Expressions (e.g., `arr + 10`) just get pasted directly into code
 - Use parentheses around parameters
- Does not invoke a true function call
- Can cause syntax problems due to pasting behavior
 - E.g., calling macro inside `if` condition

Goto statement

- Statement that should never appear in your code
- “Jumps” to a label and continues execution of the program
- Label
 - Denoted by a name followed by :
- **goto example:**

```
int i = 0;
loop_begin:
total += arr[i];
i++;
if (i < len)
    goto loop_begin;
```
- “Go to statement considered harmful” (Dijkstra, 1968)
 - Made the case against `goto`
 - Replace with loops, functions, “structured” programming
 - Overuse of `goto` results in “spaghetti code” that is hard to follow
 - Makes testing/debugging difficult because you can jump to a label at any point in the code

Tonight

- **Lab 5** due Monday
- **Recommended reading:** Sections 12.1-3