

Clustering and PCA

```
library(ISLR)
library(factoextra)
library(gridExtra)
library(corrplot)
library(RColorBrewer)
library(gplots)
```


The dataset we use contains data on 166 first generation Pokemon, including their names and basic stats: HP, Attack, Defense, Special Attack, Special Defense, and Speed. The data is from Kaggle (<https://www.kaggle.com/abcsds/pokemon>). We will apply unsupervised learning methods on this data. The list of Pokemon can be found at (<https://pokemondb.net/pokedex/national>).

```
dat <- read.csv("Pokemon.csv")
dat1 <- dat[,2:7]
dat1 <- scale(dat1)
rownames(dat1) <- dat[,1]
```

K means clustering

Partitioning methods such as k-means clustering require the users to specify the number of clusters to be generated. The function `fviz_nbclust()` determines and visualizes the optimal number of clusters using different methods: within cluster sums of squares, average silhouette and gap statistics. We use average silhouette, and the greater the silhouette value the better.

```
fviz_nbclust(dat1,
             FUNcluster = kmeans,
             method = "silhouette")
```




```
set.seed(1)
km <- kmeans(dat1, centers = 2, nstart = 20)
```

The function `fviz_cluster()` provides ggplot2-based visualization of partitioning methods including K means. Observations are represented by points in the plot, using principal components if $p > 2$. An ellipse is drawn around each cluster.

```
km_vis <- fviz_cluster(list(data = dat1, cluster = km$cluster),
  ellipse.type = "convex",
  geom = c("point", "text"),
  labels = 5,
  palette = "Dark2") + labs(title = "K-means")
```

```
km_vis
```



Hierarchical clustering


We can also apply hierarchical clustering on this data. Here we use the Euclidean distance and different types of linkage.

```
hc.complete <- hclust(dist(dat1), method = "complete")
hc.average <- hclust(dist(dat1), method = "average")
hc.single <- hclust(dist(dat1), method = "single")
hc.centroid <- hclust(dist(dat1), method = "centroid")
```

The function `fviz_dend()` can be applied to visualize the dendrogram.

```
fviz_dend(hc.complete, k = 4,
  cex = 0.3,
  palette = "jco",
  color_labels_by_k = TRUE,
  rect = TRUE, rect_fill = TRUE, rect_border = "jco",
  labels_track_height = 2.5)
```

Cluster Dendrogram



```
ind4.complete <- cutree(hc.complete, 4)

# Who are in the fourth cluster?
dat[ind4.complete == 4,]
```

Who are in the fourth cluster?


```
dat[ind4.complete == 4,]
```

##	Name	HitPoints	Attack	Defense	SpecialAttack	SpecialDefense	Speed
## 45	Jigglypuff	115	45	20	45	25	20
## 46	Wigglytuff	140	70	45	85	50	45
## 122	Chansey	250	5	5	35	105	50
## 143	Lapras	130	85	80	85	95	60
## 146	Vaporeon	130	65	60	110	95	65
## 156	Snorlax	160	110	65	65	110	30
##	Legendary						
## 45	FALSE						
## 46	FALSE						
## 122	FALSE						
## 143	FALSE						
## 146	FALSE						
## 156	FALSE						

To display more details, we show the heatmap of the data.

```
#display.brewer.all(n=NULL, type="all", select=NULL, exact.n=TRUE)
col1 <- colorRampPalette(brewer.pal(9, "GnBu"))(100)
col2 <- colorRampPalette(brewer.pal(3, "Spectral"))(2)

heatmap.2(t(dat1),
  col = col1, keysize=.8, key.par = list(cex=.5),
  trace = "none", key = TRUE, cexCol = 0.75,
  labCol = as.character(dat[,1]),
  ColSideColors = col2[as.numeric(dat[, "Legendary"])+1],
  margins = c(10, 10))
```



PCA

The function `prcomp()` can be used to perform PCA.

```
pca <- prcomp(dat1)
pca$rotation
```

```
##           PC1          PC2          PC3          PC4          PC5
## HitPoints    0.3638022  0.2862972 -0.72425610  0.078135517 -0.42663445
## Attack       0.4363956  0.3149994  0.27779372  0.573757403 -0.12333177
## Defense      0.3031184  0.5812622  0.48929801 -0.361032760  0.03453292
## SpecialAttack 0.4378985 -0.3119077  0.03743076 -0.654754892 -0.29724064
## SpecialDefense 0.5204254 -0.1331800 -0.25037584  0.006718302  0.80453025
## Speed        0.3503261 -0.6049135  0.30786700  0.324966961 -0.25682461
##           PC6
## HitPoints   -0.27020899
## Attack       0.53736079
## Defense     -0.44643458
```


```
## SpecialAttack    0.43874986
## SpecialDefense -0.03766086
## Speed           -0.49498168
```

```
pca$sdev
```

```
## [1] 1.6238460 1.0848056 0.9487926 0.8345883 0.5670204 0.5177487
```


```
var <- get_pca_var(pca)
```

```
corrplot(var$cor)
```




The function `fviz_eig()` plots the eigenvalues/variances against the number of dimensions.

```
fviz_eig(pca, addlabels = TRUE)
```




The function `fviz_contrib()` can be used to visualize the contribution of variables from the results of PCA.

```
a <- fviz_contrib(pca, choice = "var", axes = 1)
b <- fviz_contrib(pca, choice = "var", axes = 2)
grid.arrange(a, b, nrow = 2)
```




The function `fviz_pca_biplot()` can be used to obtain the biplot of individuals and variables.

```
fviz_pca_biplot(pca, axes = c(1,2),
  habillage = ifelse(dat$Legendary==TRUE, "Legendary", "Not legendary"),
  label = c("var"),
  addEllipses = TRUE)
```



```
fviz_pca_var(pca, col.var = "steelblue", repel = TRUE)
```



```
fviz_pca_ind(pca,
  habillage = ifelse(dat$Legendary==TRUE,"Legendary","Not legendary"),
  label = "none",
  addEllipses = TRUE)
```

