chordx

A package to write song lyrics with chord diagrams in Typst.

v0.2.0

August 25, 2023

 $\underline{https://github.com/ljgago/typst\text{-}chords}$

Leonardo Javier Gago

Contents

1.]	Reference	3
	1.1. Chart Chords	3
	1.1.1. new-chart-chords	3
	1.1.2. chart-chord	3
	1.2. Piano Chords	5
	1.2.1. new-piano-chords	5
	1.2.2. piano-chord	
	1.3. Single Chords	
	1.3.1. new-single-chords	
	1 3 2. single-chord	

1. Reference

1.1. Chart Chords

- new-chart-chords()
- chart-chord()

1.1.1. new-chart-chords

Return a new function with default parameters to generate chart chords for stringed instruments.

Parameters

```
new-chart-chords(
  frets: int,
  scale: int float,
  style: str,
  font: str
) -> function
```

```
frets int
```

Presets the number of frets (rows of the grid). **Optional**.

Default: 5

```
scale int or float

Presets the scale. Optional.

Default: 1
```

```
style str

Sets the chart style. Optional.
• "normal: chart with right angles.
• "round: chart with round angles.

Default: "normal"
```

```
font str

Sets the name of the text font. Optional.

Default: "Linux Libertine"
```

1.1.2. chart-chord

Is the returned function by **new-chart-chords**.

Parameters

```
chart-chord(
  tabs: str,
  fingers: str,
  capos: str,
  frets: int,
  fret-number: int,
  scale: int,
  name: str content
) -> content
```

tabs str

Shows the tabs on the chart. **Optional**.

- **x**: mute note.
- **o**: air note.
- **n**: without note.
- **number**: note position on the fret.

The string length of tabs defines the number of strings on the instrument.

Example:

- "x32010" (6 strings C Guitar chord).
- "0003" (4 strings C Ukulele chord).

Default: ""

fingers str

Shows the finger numbers. **Optional**.

- **n**, **x**, **o**: without finger,
- **number**: one finger

Example: "n32n1n" - (Fingers for guitar chord: C)

Default: ""

capos str

Adds one or many capos on the chart. **Optional**.

- 1st digit **fret**: fret position.
- 2nd digit **start**: lowest starting string.
- 3rd digit **end**: highest ending string.

Example: "115" \equiv "1,1,5" \Rightarrow "fret,start,end"

With "|" you can add capos:

Example: "115|312" \equiv "1,1,5|3,1,2" \Rightarrow "fret,start,end|fret,start,end"

Default: ""

CHORDX

frets int

Sets the number of frets (rows of the chart grid). **Optional**.

Default: frets

fret-number int

Shows the fret number that indicates the starting position of the fretboard. **Optional**.

Default: none

scale int

Sets the scale. **Optional**.

Default: scale

```
name str or content
```


Shows the chord name. **Required**.


Example:


```
#import "@preview/chordx:0.2.0": *

#let chart-chord = new-chart-chords(scale: 1.5)
#let chart-chord-round = new-chart-chords(style: "round", scale: 1.5)

#chart-chord(tabs: "x32010", fingers: "n32n1n")[C]
#h(2em)
#chart-chord(tabs: "ooo3", fingers: "ooo3")[C]
#h(4em)
#chart-chord-round(tabs: "xn332n", fingers: "o13421", fret-number: 3, capos: "115")[Cm]
#h(2em)
#chart-chord-round(tabs: "onnn", fingers: "n111", capos: "313")[Cm]
```







1.2. Piano Chords

- new-piano-chords()
- piano-chord()

1.2.1. new-piano-chords

Return a new function with default parameters to generate piano chords.

Parameters

```
new-piano-chords(
  layout: str,
  scale: int float,
  fill: color,
  style: str,
  font: str
) -> function
```

layout str

Presets the layout and size of the piano, "C", "2C", "F", "2F". **Optional**.

- "C": the piano layout starts from key **C1** to **E2** (17 keys).
- "2C": the piano layout starts from key C1 to B2 (24 keys, two octaves).
- "F": the piano layout starts from key ${\bf F1}$ to ${\bf B2}$ (19 keys).
- "2F": the piano layout stars from key F1 to E3 (24 keys, two octaves).

Default: "C"

```
scale int or float
```

Presets the scale. **Optional**.

Default: 1

fill color

Presets the fill color of the pressed key. **Optional**.

Default: gray

style str

Sets the piano style. **Optional**.

- "normal: piano with right angles.
- "round: piano with round angles.

Default: "normal"

font str

Sets the name of the text font. **Optional**.

Default: "Linux Libertine"

1.2.2. piano-chord

Is the returned function by **new-piano-chords**.

Parameters

piano-chord(
 keys: str,

```
fill: color,
layout: str,
scale: int float,
name: str content
) -> content

keys str

Keys chord notes from C1 to E3 (Depends on your layout). Optional.

Example: "C1, E1b, G1" - (Cm chord)

Default: ""
```

fill color

Sets the fill color of the pressed key. **Optional**.

Default: fill

layout str

Sets the layout and size of the piano, "C", "2C", "F", "2F". **Optional**.

- "C": the piano layout starts from key **C1** to **E2** (17 keys).
- "2C": the piano layout starts from key **C1** to **B2** (24 keys, two octaves).
- "F": the piano layout starts from key **F1** to **B2** (19 keys).
- "2F": the piano layout stars from key **F1** to **E3** (24 keys, two octaves).

Default: layout

```
scale int or float

Sets the scale. Optional.

Default: scale
```

```
name str or content

Shows the chord name. Required.
```


Example:


```
#import "@preview/chordx:0.2.0": *

#let piano-chord = new-piano-chords(layout: "F", scale: 1.5)
#let piano-chord-round = new-piano-chords(layout: "F", scale: 1.5, style: "round")

#piano-chord(keys: "B1, D2#, F2#", fill: blue)[B]
#h(4em)
#piano-chord-round(keys: "B1, D2#, F2#", fill: red)[B]
```

CHORDX





1.3. Single Chords

- new-single-chords()
- single-chord()

1.3.1. new-single-chords

The single chords are chords without diagram used to show the chord name over a word.

Parameters

```
new-single-chords(..text-params: auto) -> function

..text-params auto

Are the same parameters of text from the standard library of typst. Required.
```

1.3.2. single-chord

Is the returned function by **new-single-chords**.

Parameters

```
single-chord(
  body: content,
  name: content,
  position: content
)
```

body content

Is the word or words where the chord goes. **Required**.

```
name content
```

Displays the chord name over the selected words in the body. **Required**.

```
position content
```

Positions the chord over a specific character in the body. **Required**.

- []: chord name centered on the body.
- [number]: the chord name starts over a specific body character. (First position [1])

Example:

```
#import "@preview/chordx:0.2.0": *

#let chord = new-single-chords(style: "italic", weight: "semibold")

#chord[Jingle][G][2] bells, jingle bells, jingle #chord[all][C][2] the #chord[way!][G][2] \
#chord[0h][C][] what fun it #chord[is][G][] to ride \
In a #chord[one-horse][A7][2] open #chord[sleigh,][D7][3] hey!
```

G C G

Jingle bells, jingle bells, jingle all the way!

C G

Oh what fun it is to ride

A7 D7

In a one-horse open sleigh, hey!