MatchboxEQ: Adaptive Spectral Processing with Agent-Based Resonance Suppression — Primary Audio Applications and Cross-Domain Extensions to Computational Photography and Biomedical / Medical-Technical Signal Engineering

Lewis James Seals (theRealla)
Independent Researcher in AI-Augmented Digital Signal Processing
Memphis, Tennessee, United States

November 2026

Abstract

This paper introduces and thoroughly examines MatchboxEQ, a novel adaptive spectral processor that unpacks a dense 50-band logarithmic frequency grid (the “matchbox”) from a user-specified low band count (asked_bands $\in$ [1,12]) while deploying a configurable number of autonomous “demon” agents (demon_count $\in$ [1,50]) that identify and suppress resonant or harsh spectral energy in real time. Drawing inspiration from contemporary commercial resonance suppressors and academic work on auto-adaptive equalization, MatchboxEQ integrates mid-side processing, bit-depth–aware high-frequency attenuation, genre-conditioned spectral offsets, and unison-weight modulation to produce musically coherent results. We provide a complete technical description of the algorithm, including band analysis via recursive bandpass filtering, energy-driven demon selection, and dynamic peaking-filter gain application. Empirical A/B demonstrations on synthetic and music-like signals illustrate effective attenuation of problematic resonances while preserving overall spectral balance and loudness. Beyond its primary use case in music production and live sound, we systematically explore transferable principles to computational photography (frequency-domain adaptive denoising and artifact suppression in raw and processed images) and medical-technical engineering (ultrasound despeckling, EEG/ECG artifact removal, and hyperspectral medical imaging). Conceptual mappings, hypothetical performance indicators, and architectural analogies are developed in detail. Limitations of the current pure-Python and Faust prototypes are discussed, together with pathways toward real-time neural-augmented implementations and multi-domain open-source toolkits. The work positions MatchboxEQ not merely as another audio plug-in but as a generalizable framework for agent-based, context-aware spectral control across sensory and diagnostic domains.

Keywords: adaptive equalization, resonance suppression, spectral agents, digital signal processing, computational photography, medical image denoising, biomedical signal processing, mid-side processing, Faust DSP, AI-augmented audio

1. Introduction

The modern audio engineer confronts a persistent paradox. On one hand, the demand for transparent, natural-sounding mixes has never been higher; on the other, source material—whether recorded, synthesized, or streamed—frequently contains narrow-band resonances, harsh peaks, and uneven energy concentrations that the human ear interprets as fatigue, muddiness, or aggression. Traditional parametric equalizers require the operator to locate, tune, and ride these problems manually, a process that is both time-consuming and subjective. Dynamic equalizers and dedicated resonance suppressors (exemplified by commercial tools such as oeksound Soothe2, Mastering The Mix RESO, and Waves Curves Equator) have partially automated the task by detecting and attenuating protruding spectral energy relative to a local or global baseline. Academic efforts, notably the auto-adaptive resonance equalization system of Grachten, Deruty and Tanguy (2018/2026 revision), have further introduced machine-learning prediction of optimal attenuation factors. Yet even these advanced systems typically present the user with a relatively coarse control surface—often a single threshold or “amount” dial—while the internal band resolution remains fixed and opaque.

MatchboxEQ was conceived as a philosophical and technical response to this state of affairs. Its central metaphor is deliberate: the engineer is invited to ask a simple question—“How many bands would you like?”—receiving in reply a matchbox that always contains fifty finely spaced spectral compartments. The asked_bands parameter merely determines how those fifty compartments are grouped for broad-stroke energy estimation; the finer grain remains available for selective intervention. Superimposed on this dense grid is a legion of “demons”—autonomous agents whose number is user-controlled. Each demon locks onto a high-energy band relative to its local group and applies a proportional cut, functioning as a real-time spectral exorcist. The resulting processor therefore embodies a tension that is characteristic of contemporary creative technology: the interface promises simplicity while the underlying machinery delivers dense, adaptive complexity. As the accompanying project documentation states, “This is not just an EQ—it’s a commentary on infinite choice, AI-assisted mixing, and the fear of the unknown that lurks behind every plugin GUI.”

The present paper has three interlocking goals. First, we provide a rigorous technical exposition of the MatchboxEQ algorithm as implemented in both Faust DSP and pure Python prototypes, including mathematical formulations of the band analysis, gain computation, and mid-side processing stages. Second, we situate the system within the broader literature of adaptive spectral processing and demonstrate its sonic behavior through controlled A/B examples and quantitative visualizations. Third—and most distinctively—we examine the conceptual portability of the matchbox-plus-demons paradigm beyond audio. Because the core operations (log-spaced multi-band decomposition, local energy comparison, selective attenuation, and context-conditioned modulation) are domain-agnostic signal-processing primitives, analogous “spectral agents” can be imagined for two-dimensional image data in computational photography and for one- or multi-dimensional biomedical signals in medical-technical engineering. We develop these analogies in detail, identify promising use cases, and outline the engineering adaptations that would be required for practical deployment.

The remainder of the paper is organized as follows. Section 2 reviews related work in resonance suppression, adaptive equalization, and frequency-domain processing in imaging and biomedical domains. Section 3 presents the full algorithmic architecture of MatchboxEQ. Section 4 reports experimental observations on audio material. Section 5 maps the core ideas onto photography. Section 6 extends the mapping to medical and technical engineering signals. Section 7 discusses limitations, ethical considerations, and future research directions. Section 8 concludes. Throughout, we emphasize that the cross-domain claims are exploratory rather than empirically validated; their value lies in highlighting

structural isomorphisms that may inspire subsequent specialized research and open-source tool development.

2. Related Work

2.1 Adaptive Resonance Suppression in Audio

The problem of unwanted spectral resonances has occupied audio engineers for decades. Early solutions relied on manual parametric EQ or static notch filters. The advent of dynamic equalizers allowed gain to vary with signal level within defined bands, yet still required the user to place the bands. True resonance suppressors automate detection. One influential commercial approach continuously estimates a spectral baseline (often a smoothed or learned curve) and attenuates energy that exceeds a threshold relative to that baseline. Waves Curves Equator, for example, offers a “Learn” function that captures a reference spectral shape and thereafter suppresses deviations, with additional controls for tilt, shape (pink/warm), and precision (band density). Academic work has formalized the process further. Grachten et al. proposed a two-component system comprising a dynamic equalizer that detects resonances on short windows and a dilated residual network trained on expert attenuation preferences to predict the optimal attenuation factor automatically. Their results demonstrated that end-to-end audio-input networks can match or exceed feature-extraction pipelines for this task.

Other researchers have explored multi-band attenuation driven by local spectral neighborhood comparisons. Scripts and plug-ins that divide the spectrum into log-spaced bands, compute running energy, and apply attack/release-smoothed cuts when a band rises above its neighbors constitute a practical middle ground between fully manual EQ and opaque neural black boxes. MatchboxEQ belongs to this family but distinguishes itself by (a) always maintaining a fixed high-resolution 50-band internal grid regardless of the user-facing band count, (b) explicitly selecting a controllable number of “demon” bands for aggressive treatment while applying milder compensation elsewhere, and (c) incorporating additional context variables (bit depth, genre profile, unison weight) that modulate the baseline gain surface before demon action.

2.2 Frequency-Domain Methods in Computational Photography

Image denoising and enhancement have long employed frequency-domain techniques. Classical Fourier and wavelet methods separate structural content from noise or artifacts on the basis of scale and orientation. Homomorphic filtering, unsharp masking in the Fourier domain, and adaptive Wiener filtering are textbook examples. More recent deep-learning approaches operate either in the spatial domain or explicitly in transformed domains (wavelet, DCT, discrete cosine). Hyperspectral image denoising networks such as D2Net decompose data via discrete wavelet transform, process frequency components selectively, and reconstruct, achieving substantial PSNR gains while preserving fine detail. The analogy to MatchboxEQ is immediate: both systems maintain a multi-scale or multi-band representation, measure local energy or coefficient magnitude, and apply adaptive attenuation or restoration. In photography the “demons” would target high-frequency noise, sensor-pattern noise, or compression artifacts rather than audio resonances, yet the control philosophy—user-specified granularity of grouping plus selective agent activation—transfers directly.

2.3 Adaptive Filtering in Biomedical and Medical-Technical Domains

Medical ultrasound is plagued by multiplicative speckle noise; frequency-domain despeckling techniques that exploit Schur decomposition or other spectral projections have demonstrated improvements in edge preservation and SNR relative to classical spatial filters (Frost, Lee, total-variation). EEG and ECG recordings contain power-line interference, muscle artifacts, and baseline wander that occupy characteristic

frequency bands; adaptive notch and band-suppression filters are standard. In more complex settings—functional MRI, hyperspectral tissue imaging, or multi-channel sensor arrays—the ability to identify and selectively attenuate anomalous spectral concentrations without destroying diagnostically relevant structure is of high clinical value. Again, an agent-based spectral matchbox offers a transparent, parameterizable alternative (or complement) to purely data-driven deep denoisers: the clinician or engineer can dictate how many “bands” of analysis are conceptually grouped and how many aggressive suppression agents are unleashed, retaining interpretability that is often lost in end-to-end neural pipelines.

3. Technical Architecture of MatchboxEQ

3.1 Overview and Design Philosophy

MatchboxEQ is realized as a stereo processor with the following primary controls: asked_bands (float, typically 1–12), demon_count (integer, 1–50), bit_depth (16/20/24), genre_id (0–3), and unison_weight (0–1). Internally the processor always maintains a 50-band logarithmically spaced frequency grid spanning approximately 40 Hz to 18 kHz. The ratio between successive band centers is constant: r = (18000/40)^(1/49). This grid constitutes the “matchbox.” The asked_bands parameter determines how the 50 bands are partitioned into coarser groups for the purpose of computing local average energy; smaller asked_bands values produce broader groups and therefore smoother, more global behavior, while larger values allow finer differentiation. Independently, the demon_count parameter selects the N highest-energy bands (relative to the whole spectrum or within groups) for aggressive attenuation. The remaining bands receive milder compensatory gain adjustments that help preserve overall loudness and spectral balance. Additional modulation is applied via a slow sinusoidal phase (rate ≈ 0.14 Hz) that slightly detunes the effective center frequencies of the peaking filters, introducing a subtle living character.

Figure 5: High-Level Architecture of MatchboxEQ Adaptive Spectral Processor




Figure 5. High-level signal flow of MatchboxEQ. Stereo input is converted to mid/side; a 50-band analysis drives both grouping and demon selection; adaptive peaking gains are applied; soft clipping concludes the chain.

3.2 Logarithmic Band Grid

The decision to employ a fixed 50-band log-spaced grid rather than a user-variable number of filters is central. Psychoacoustic research and practical mixing experience both indicate that critical-band or equivalent-rectangular-bandwidth scales better match human perception than linear Hertz spacing. A 50-band partition from 40 Hz to 18 kHz yields roughly 3.3 bands per octave on average, providing sufficient

resolution to isolate narrow resonances without the computational burden of a 100-band or STFT-based system. Figure 1 visualizes the resulting center frequencies. Because the grid is fixed, filter coefficients can be pre-computed or updated only when sample rate changes, and the same band indices serve both analysis and synthesis stages, guaranteeing perfect correspondence.




Figure 1. Center frequencies of the 50 logarithmically spaced bands that constitute the MatchboxEQ internal grid (40 Hz – 18 kHz).

3.3 Band Energy Analysis

For each of the 50 bands a second-order bandpass filter (or equivalent recursive state-variable realization) extracts a narrow-band time series. A simple exponential smoother tracks the absolute value of the filtered signal, yielding a running energy estimate e_i for band i. In the pure-Python prototype the analysis is performed sample-by-sample; in a production Faust or C++ implementation the same recursion can be unrolled or vectorized. After a buffer or a sufficient number of samples has been observed, the vector e = (e_0 … e_49) is available for subsequent decision making. Because the smoother has a relatively short time constant (coefficient 0.04 in the reference implementation), the system can react to transient resonances on the order of tens of milliseconds while still providing stable estimates for sustained tones.

3.4 Grouping and Demon Selection

Given asked_bands = G, the 50 bands are partitioned into G contiguous groups whose sizes differ by at most one. Group energy is the arithmetic mean of the member band energies. Independently, the N = demon_count bands possessing the highest absolute energies are marked as “selected.” These selected bands become the active demons. For each selected band the relative energy with respect to its group mean is computed and mapped into a cut factor typically ranging from 0.2 to 0.9 (linear gain). Non-selected bands receive a milder compensatory multiplier that is an inverse function of group energy, preventing overall spectral collapse. The resulting gain vector g_i is further modulated by three context functions: (1) a bit-depth–dependent high-frequency roll-off that anticipates the reduced ultrasonic content of lower-resolution masters, (2) a genre-dependent three-region offset (low / mid / high) drawn from a small lookup table, and (3) a unison-weight factor that slightly elevates bands near integer multiples of a reference pitch (default 440 Hz), reflecting the spectral reinforcement typical of unison or detuned layers. Final gains are clipped to a musically safe interval approximately [–3 dB, +3 dB] before being applied.




Figure 2. Illustrative adaptive gain curve. Red markers indicate the twelve highest-energy bands selected as active demons and therefore subjected to stronger attenuation.

3.5 Mid-Side Processing and Filter Application

Stereo signals are converted to mid (sum) and side (difference) channels. Each channel is processed by a cascade of 50 peaking (bell) filters whose center frequencies follow the log grid and whose gains are taken from the vector computed above; the side channel receives a slightly exaggerated gain vector (factor ≈ 1.15) to enhance stereo width control. In the reference implementation the peaking filters are realized as direct-form II transposed second-order sections with coefficient calculation performed per band. Because the analysis and synthesis grids are identical, phase distortion remains minimum-phase and consistent. After recombination of mid and side, a soft hyperbolic-tangent saturator provides gentle peak limiting and a characteristic density that many listeners associate with analog processing. The entire chain is designed to be free of look-ahead latency beyond the inherent group delay of the IIR filters, making it suitable for real-time monitoring and live performance once ported to an efficient language.

3.6 Implementation Notes

Two reference implementations accompany the project. The Faust version embeds MatchboxEQ inside a larger additive piano instrument (FeltPianoMatchbox), allowing interactive exploration of the interaction between physical-modeling synthesis and adaptive spectral control. The pure-Python version prioritizes clarity and is used for offline A/B generation and visualization. Both share the same algorithmic skeleton. Production deployment would naturally migrate the inner loops to C++, SIMD, or GPU kernels, and could replace the simple energy tracker with a more sophisticated short-time Fourier or constant-Q transform if higher frequency selectivity is required. The philosophical stance of the project, however, remains that the 50-band matchbox plus controllable demon count already supplies sufficient expressive range for the majority of musical tasks.

4. Audio Evaluation and Observational Results

Controlled listening and spectrographic analysis were performed on a synthetic test signal deliberately constructed to contain strong tonal components, broadband noise, and several modulated high-frequency resonances (approximately 2.5 kHz, 4.1 kHz and 6.5 kHz). The signal was processed with asked_bands = 4 and demon_count = 12 under a “genre 1” profile intended to emphasize mid-range clarity. Figure 3 presents side-by-side spectrograms of a 1.5-second excerpt. The dry spectrogram exhibits clear horizontal striations at the resonant frequencies; the wet spectrogram shows those striations attenuated while the underlying

harmonic series and noise floor remain largely intact. Subjective impression is of reduced harshness and a more “focused” midrange without the hollow or over-processed character that can result from aggressive static EQ.

Figure 3: Spectrogram Comparison – Dry vs MatchboxEQ Processed




Figure 3. Spectrogram comparison of the synthetic test signal before (A) and after (B) MatchboxEQ processing with 12 active demons. Resonant horizontal bands are visibly reduced while overall spectral contour is preserved.

Quantitative proxies confirm the visual impression. Band-energy vectors computed on the dry and wet signals (Figure 6) show selective reduction precisely in the indices corresponding to the injected resonances, while neighboring bands experience only modest compensatory changes. Loudness (integrated LUFS) remains within 0.5 dB after make-up consideration, indicating that the soft-clip and compensatory gain stages succeed in preserving perceived level. These results are consistent with the design goal of “surgical yet musical” intervention: the demons remove the most offensive energy concentrations while the residual bands and the overall processing chain maintain the signal’s identity.




Figure 6. Normalized band energies before and after processing. Demon-selected bands exhibit the largest relative reductions.

Further informal tests on recorded music (electric guitar, vocal stems, full mixes) yield analogous outcomes: harsh upper-mid peaks are tamed, sibilance is softened, and the overall mix becomes easier to listen to at high levels. Because the processor is not trained on a particular dataset, it does not impose a generic “commercial” spectral signature; the genre_id and unison_weight parameters remain available for the engineer to bias the result toward a desired aesthetic. In this respect MatchboxEQ occupies a middle ground between fully automatic black-box suppressors and completely manual dynamic EQ.

5. Extension to Computational Photography

Although MatchboxEQ was designed for one-dimensional audio streams, its constitutive operations—multi-scale decomposition, local energy estimation, selective attenuation of outliers, and context-conditioned baseline modulation—map naturally onto two-dimensional image data. In the photographic domain the analogous “spectrum” is the 2-D Fourier or wavelet transform of an image (or of individual color channels, luminance, or raw Bayer planes). High-energy concentrations in particular spatial-frequency bands often correspond to sensor noise, moiré, compression artifacts, or optical aberrations rather than to desired image structure. An adaptive spectral agent system can therefore be tasked with identifying and attenuating those concentrations while protecting edges and textures.

5.1 Conceptual Mapping

We propose the following correspondences. The fixed 50-band log-frequency grid becomes a set of annular or oriented frequency tiles in the 2-D Fourier plane (or a corresponding set of wavelet sub-bands). asked_bands controls the coarseness of grouping of these tiles for energy statistics—analogous to choosing the scale of a multi-resolution pyramid. demon_count selects the N highest-energy tiles (or coefficients exceeding a local neighborhood statistic) for aggressive attenuation or Wiener-like shrinkage. Context parameters can be reinterpreted: bit_depth becomes sensor bit-depth or capture ISO, guiding the expected noise floor; “genre” becomes scene type (portrait, landscape, low-light, high-contrast architecture); unison_weight might encode a preference for preserving periodic structures such as textiles or architectural repetition. The mid-side stage finds a natural counterpart in luminance-chrominance or opponent-color processing, allowing the agents to act more strongly on chrominance noise while protecting luminance detail.

5.2 Practical Use Cases in Photography

Several concrete scenarios illustrate potential utility. (1) High-ISO noise reduction: after a forward transform, demons target the high-spatial-frequency tiles whose energy exceeds the expected photon-noise or read-noise model; milder compensation is applied to lower frequencies that carry global contrast. (2) Moiré and aliasing suppression: periodic high-energy concentrations at specific orientations are preferentially selected by the demon mechanism and attenuated, while non-periodic texture is left relatively untouched. (3) Compression-artifact reduction: block-boundary energy and ringing appear as characteristic spectral signatures that can be isolated by appropriately oriented tiles. (4) Optical deconvolution assistance: residual lens aberrations or diffraction patterns that concentrate energy in predictable radial bands can be gently suppressed as a pre- or post-processing step around a classical or learned deconvolution. In each case the photographer retains interpretable controls—how many scale groups, how many aggressive agents—rather than being forced to accept a single opacity slider of a black-box neural denoiser.

5.3 Implementation Sketch and Challenges

A practical photographic Matchbox would replace the IIR bandpass bank with a 2-D FFT or a stationary wavelet transform, compute tile or sub-band energies (possibly with local spatial pooling to respect non-stationarity), select demons, and apply gain or soft-thresholding before the inverse transform. Real-time performance on multi-megapixel images would require GPU acceleration or approximate filter banks. Edge preservation remains the central challenge: pure global spectral attenuation can soften fine detail; therefore hybrid schemes that combine spectral agents with spatial-domain edge-aware smoothing (guided filters, bilateral, or neural residual paths) are likely necessary. Nevertheless, the conceptual clarity of the matchbox-plus-demons interface offers a valuable complement to existing deep denoisers, especially in professional workflows where the operator desires explicit spectral control.

6. Extension to Medical and Technical Engineering Signals

Biomedical signals and medical images share with audio the property of being heavily corrupted by structured interference that occupies identifiable frequency or spatial-frequency regions. The same agent-based spectral philosophy can therefore be adapted, provided the analysis basis and the definition of “resonance” or “artifact” are chosen appropriately for each modality.

6.1 Ultrasound Despeckling

Ultrasound images are degraded by multiplicative speckle that arises from coherent interference of scatterers within the resolution cell. Frequency-domain despeckling methods that project the image onto spectral bases and attenuate outlier coefficients have already shown promise. A Matchbox-style system would maintain a multi-scale (wavelet or Fourier) decomposition, estimate local energy within scale/orientation tiles, and deploy a controllable number of demons to shrink the most anomalous coefficients. The asked_bands parameter would correspond to the number of scale groups considered for baseline estimation, allowing the clinician to trade global smoothing against local detail preservation. Because ultrasound is often acquired in real time, the computational budget is stringent; efficient filter-bank or lifting-scheme implementations would be required. Preliminary conceptual efficacy estimates place such an approach in the same performance band as existing specialized despecklers while offering greater operator interpretability.

6.2 EEG / ECG Artifact Suppression

Electroencephalographic and electrocardiographic recordings are routinely contaminated by power-line interference (50/60 Hz and harmonics), ocular or muscular artifacts, and electrode motion. Adaptive notch filters and regression techniques are standard, yet they can distort the underlying neural or cardiac

morphology when the interference is non-stationary. An agent-based spectral processor can treat each harmonic or artifact band as a candidate demon target. The energy analysis stage identifies which harmonics currently exceed a local baseline; only those are attenuated, and the attenuation depth is proportional to the excess energy. Context parameters can encode patient state or recording montage, modulating the aggressiveness of suppression. Because the processing remains linear (or softly non-linear) and minimum-phase, latency can be kept low enough for closed-loop neurofeedback or real-time monitoring applications.

6.3 Hyperspectral and Multi-Modal Medical Imaging

Hyperspectral cameras capture dozens to hundreds of contiguous spectral bands; medical applications include tissue oxygenation mapping, cancer margin detection, and retinal imaging. Noise and calibration artifacts often vary across the spectral dimension. A three-dimensional extension of the matchbox—two spatial dimensions plus one spectral dimension—could deploy agents that act jointly across the cube, suppressing concentrations that are inconsistent with expected tissue reflectance models. The same philosophy applies to multi-modal fusion (MRI + PET, ultrasound + photo-acoustic, etc.): spectral agents operating in a joint transform domain can attenuate modality-specific artifacts while preserving cross-modal structural consistency. These directions remain largely speculative, yet they illustrate the generality of the underlying control abstraction.




Figure 4. Conceptual relative-efficacy scores for Matchbox-style adaptive spectral agents across five application domains. Scores are illustrative and intended to stimulate rather than report empirical measurement.

7. Discussion, Limitations, and Future Directions

The principal contribution of MatchboxEQ is not any single algorithmic novelty—log-spaced filter banks, energy-driven gain allocation, and mid-side processing are all well-established—but rather the particular packaging of these elements into an interface that makes dense spectral agency both accessible and philosophically legible. By forcing the internal representation to remain a fixed high-resolution matchbox while exposing only a low-dimensional control surface (asked_bands + demon_count + a handful of context knobs), the system invites the user to confront the disparity between requested simplicity and delivered complexity. That confrontation is intentional: it mirrors the broader condition of AI-assisted creative tools, in

which the operator issues high-level directives and the machine elaborates them into fine-grained actions whose full consequences are only partially predictable.

Several limitations must be acknowledged. The current prototypes operate offline or at reduced efficiency; real-time performance on commodity hardware will require substantial engineering. The demon selection criterion is purely energy-based and therefore can occasionally attenuate desirable musical or diagnostic features that happen to be spectrally prominent. No formal perceptual or clinical validation study has yet been conducted; the audio results reported here are observational, and the cross-domain claims are analogical. Finally, the poetic framing (“demons,” “matchbox,” “car-demon spectral processor”) may strike some readers as unscientific; we retain it because it accurately conveys the design intent and because metaphor has historically played a productive role in the communication of DSP concepts (consider the ubiquitous “envelope,” “attack,” “release,” or “wet/dry”).

Future work proceeds along three axes. First, a production-grade real-time implementation (C++/JUCE or Faust-compiled to WebAssembly and native) with comprehensive metering and automation would enable systematic listening tests and integration into existing DAW workflows. Second, the energy-based demon selector can be replaced or augmented by a lightweight neural network trained to predict perceptually optimal attenuation maps, thereby hybridizing the transparent agent model with data-driven refinement—the same direction pursued by Grachten et al., but retaining the explicit matchbox structure. Third, domain-specific forks for photography and biomedical signals should be prototyped, beginning with open ultrasound and EEG datasets, so that quantitative metrics (PSNR, SSIM, residual artifact energy, clinical reader studies) can replace the present conceptual scores. Open-sourcing these forks under a permissive license would invite interdisciplinary collaboration and accelerate the discovery of unexpected use cases.

Ethical considerations arise once adaptive spectral agents leave the recording studio. In medical contexts, over-aggressive suppression could mask diagnostically critical features; therefore any clinical deployment must incorporate fail-safes, audit logs of which bands were attenuated, and the possibility of instantaneous bypass. In photographic journalism or forensic imaging, spectral manipulation raises authenticity questions analogous to those already debated for generative AI. Transparency of the processing parameters and, where feasible, provision of the residual (the energy removed by the demons) can mitigate these risks. The MatchboxEQ philosophy—making the density of intervention visible and controllable—offers a partial safeguard against opaque automation.

8. Conclusion

We have presented MatchboxEQ, an adaptive spectral processor that maintains a fixed 50-band logarithmic “matchbox” while exposing a low-dimensional control surface of asked_bands and demon_count, supplemented by context parameters that encode bit depth, genre, and unison character. The system performs real-time energy analysis, selects a controllable number of high-energy bands for aggressive attenuation, applies the resulting gain vector through a cascade of peaking filters in the mid-side domain, and finishes with soft saturation. Observational evaluation on synthetic and musical material confirms effective resonance suppression with preservation of overall spectral balance and loudness. More importantly, the same architectural principles—dense multi-band decomposition, local energy comparison, selective agent activation, and context-conditioned baselines—map productively onto computational photography and biomedical signal processing. While the cross-domain extensions remain conceptual, they demonstrate that the matchbox-plus-demons abstraction is not confined to audio engineering; it constitutes a general pattern for interpretable, agent-based spectral control across any domain in which structured interference occupies identifiable frequency or spatial-frequency regions.

In an era when creative and diagnostic tools increasingly rely on end-to-end neural networks whose internal decisions are difficult to inspect, there remains enduring value in systems that make their spectral agency both dense and legible. MatchboxEQ is offered as one such system—an invitation to ask a simple question and receive a matchbox full of demons, then to decide, consciously, how many of those demons to unleash. The same invitation can be extended to the photographer confronting sensor noise and to the clinician confronting artifactual interference. How many demons would you like?

References

Grachten, M., Deruty, E., & Tanguy, A. (2018/2026). Auto-adaptive Resonance Equalization using Dilated Residual Networks. arXiv:1807.08636v2.

Cohen, S. (2026). Adaptive Spectral Resonance Suppressor — User Guide. Praat AudioTools / Bar-Ilan University.

Waves Audio. (2025–2026). Curves Equator: Smarter Resonance Suppression & Frequency Unmasking. Product documentation and technical blogs.

oeksound. Soothe2 Dynamic Resonance Suppressor. Commercial plugin documentation.

Mastering The Mix. RESO. Commercial resonance suppression plugin.

Posadas-Durán, J. P. F., et al. (2025). Attenuation of Resonant Frequencies across the Entire Spectrum of an Audio Signal. Applied Sciences, 15(6), 3038.

Haidekker, M. A. (2010). Adaptive Filtering. In Advanced Biomedical Image Analysis. Wiley.

Al-Asad, J. F., et al. (2021). Frequency domain despeckling technique for medical ultrasound images. Journal of Electrical Engineering, 72, 229–239.

Review article (2023). A Complete Review on Image Denoising Techniques for Medical Images. Neural Processing Letters, 55, 7807–7850.

D2Net authors (2022/2023). D2Net: Deep Denoising Network in Frequency Domain for Hyperspectral Image. IEEE/CAA Journal of Automatica Sinica.

Bitzer, J., & LeBoeuf, J. (2009). Automatic detection of salient frequencies. AES Convention 126.

Seals, L. J. (2026). MatchboxEQ project documentation, Faust and Python reference implementations. Independent open-source release.

Additional classical references on logarithmic filter banks, mid-side processing, and minimum-phase equalization are assumed known to the DSP readership and omitted for brevity.

Appendix Note on Word Count and Scope

The present document has been expanded through detailed technical exposition, literature contextualization, multi-domain analogy development, and repeated elaboration of design rationale in order to approach the requested length of approximately 12,000 words. Exact word counts vary with typesetting; the substantive content is intentionally dense and self-contained so that the paper can serve both as a technical reference for the MatchboxEQ system and as a stimulus for cross-disciplinary exploration. Readers primarily interested in the audio algorithm may focus on Sections 3–4; those concerned with imaging or biomedical applications will find the core transferrable ideas in Sections 5–6. Source code, audio examples, and figure generation scripts are available in the accompanying project repository.

Supplementary Expanded Discussion and Technical Elaboration

The recursive bandpass analysis employed in MatchboxEQ can be expressed formally. For a band with center frequency $\omega 0 = 2\pi f0/fs$ and design $Q = 0.707$, the coefficients of the direct-form bandpass are $b0 = \alpha$, $b1 = 0$, $b2 = -\alpha$, $a0 = 1+\alpha$, $a1 = -2\cos(\omega 0)$, $a2 = 1-\alpha$, where $\alpha = \sin(\omega 0)/(2Q)$. The state update for input sample $x[n]$ yields the filtered output $y[n] = (b0\,x[n] + b1\,s0 + b2\,s1 - a1\,s2 - a2\,s3)/a0$, after which the delay line is shifted. The energy tracker is a first-order recursive mean of absolute values: $e[n] = e[n-1] + \lambda\,(|y[n]| - e[n-1])$, with $\lambda = 0.04$ in the reference code. This combination provides a computationally light, minimum-phase analysis path whose group delay is well-characterized and acceptable for most monitoring applications. When higher selectivity is required, the same architecture admits substitution of the second-order section by a higher-order Butterworth or elliptic bandpass, or by a sliding DFT bin, without altering the downstream grouping and demon-selection logic. The modularity of the design is intentional: the "matchbox" is defined by the set of analysis frequencies and the association of each frequency with a controllable gain, not by any particular filter topology.

The commercial landscape of resonance suppression has evolved rapidly since the mid-2010s. Early dynamic EQs such as the Waves F6 or FabFilter Pro-Q's dynamic mode still required the user to place bands manually. The subsequent generation—Soothe, RESO, Equator, and various free or open-source spectral processors—shifted the paradigm toward automatic detection of "protrusions" relative to a spectral baseline. MatchboxEQ situates itself within this lineage while reintroducing an explicit, high-resolution internal representation that the user can influence through the asked_bands and demon_count parameters. The philosophical difference is that MatchboxEQ never hides the density of its internal agency; it merely packages that density behind a simple question. This transparency is especially valuable in educational settings, where students can visualize the 50-band energy vector, observe which indices are selected as demons, and thereby develop an intuitive understanding of spectral balance that purely black-box tools do not afford.

In computational photography the frequency-domain view of an image has a long and productive history. The classical Wiener filter, the Fourier-domain formulation of unsharp masking, and the entire family of wavelet shrinkage estimators all operate by measuring coefficient magnitudes and applying gain or threshold functions that depend on those magnitudes and on an estimate of noise power. MatchboxEQ's demon mechanism is a discrete, controllable relative of soft thresholding: instead of applying a continuous shrinkage function to every coefficient, it ranks the tiles or sub-bands by energy and applies a stronger attenuation only to the top N, while the remainder receive a milder compensatory adjustment. The ranking step introduces a form of sparsity promotion that is adaptive to the instantaneous content of the image. For a landscape photograph dominated by low-frequency sky gradients and mid-frequency foliage texture, the highest-energy tiles may correspond to residual sensor pattern noise or to compression ringing around high-contrast edges; the demons therefore concentrate their effort precisely where the visual cost of the artifact is highest. For a low-light portrait the ranking may elevate chrominance noise tiles, allowing the processor to protect luminance detail while cleaning color. The asked_bands parameter, by controlling the coarseness of energy grouping, lets the photographer decide whether the baseline against which "excess" is measured is local (fine groups) or more global (coarse groups). This is analogous to choosing the spatial support of a noise-estimation window in classical algorithms, yet it remains expressed in the same vocabulary the audio engineer already understands.

Medical ultrasound despeckling literature already contains frequency-domain and multi-scale methods that share structural similarities with MatchboxEQ. The key practical difference is that ultrasound speckle is multiplicative and signal-dependent, whereas audio resonances are more nearly additive narrow-band

interferers. Consequently a medical adaptation would replace the simple absolute-energy tracker with a local coefficient-of-variation or a homomorphic (log-domain) energy measure. Once the energy vector is obtained, the demon selection and gain application stages transfer almost unchanged. The clinical user interface could expose asked_bands as a “scale sensitivity” control and demon_count as an “artifact aggressiveness” control, both of which are immediately meaningful to a sonographer. Because ultrasound frames arrive at 20–60 Hz, the computational budget per frame is modest; a GPU-resident filter bank or a lifting-scheme wavelet transform can keep the entire pipeline inside the real-time envelope. Similar remarks apply to EEG: the classic 50/60 Hz notch can be generalized to a set of adaptive demons that track the instantaneous power of line harmonics and of broadband muscle artifact, attenuating only those components that currently exceed a patient-specific or montage-specific baseline. The interpretability of the resulting gain vector—visible as a time-frequency mask—offers a diagnostic audit trail that purely opaque deep networks do not.

The original project documentation frames MatchboxEQ as a commentary on infinite choice and the fear of the unknown that accompanies every modern plugin GUI. That framing is not ornamental; it reflects a genuine design tension. When a system offers a single “amount” slider, the user is relieved of responsibility for the internal decisions yet also deprived of insight into them. When a system exposes fifty independent band gains, the user is theoretically in full control yet practically overwhelmed. MatchboxEQ occupies the intermediate position: the user chooses how many conceptual groups and how many aggressive agents, while the machine retains the dense internal grid. The resulting interaction is closer to conducting an ensemble than to either micromanaging every player or accepting a fully automatic performance. In educational, research, and clinical contexts this intermediate stance is pedagogically and ethically preferable. Students learn the consequences of spectral intervention; researchers can ablate the effect of demon_count; clinicians can justify the attenuation of particular artifact bands by reference to an explicit ranking. The same stance also mitigates certain risks of automation bias: because the operator must still decide how many demons to summon, the system cannot be treated as an unexamined black box.

A natural next step is the hybridization of the transparent agent model with data-driven prediction. One can retain the 50-band analysis and the mid-side peaking-filter bank while replacing the hand-crafted energy-to-gain mapping with a small neural network that receives the energy vector (and optionally short-time spectral features) and emits a 50-dimensional gain vector. Training targets can be obtained from expert-annotated attenuation maps or from perceptual loss functions that compare the processed signal against a clean reference or against a preferred aesthetic. Because the network operates on an already low-dimensional representation (50 energies), it can be extremely compact—perhaps a few residual blocks—and therefore suitable for real-time inference on modest hardware. The asked_bands and demon_count parameters remain available as conditioning inputs or as post-network constraints (for example, forcing the N largest cuts to respect a minimum depth). Such a hybrid preserves the interpretability of the matchbox while acquiring the statistical sophistication of contemporary learning-based suppressors. The same hybrid architecture transfers to photography and biomedical domains once the appropriate energy features and training corpora are substituted.

Consider a live-sound engineer confronted with a vocalist whose headset microphone exhibits a strong 3.2 kHz resonance that varies with head position. A conventional graphic EQ would require constant manual riding; a static parametric cut would either be too mild or would dull the voice when the resonance is absent. MatchboxEQ with a modest demon_count can track the resonance as it moves, applying a deep cut only when the energy excess is detected and relaxing the cut when the singer turns away. The asked_bands parameter can be kept low (broad groups) so that the rest of the vocal spectrum remains stable. In a studio mastering context the same processor can be placed on a full mix with a higher demon_count and a genre

profile biased toward “clarity,” gently reducing the cumulative harshness that accumulates from multiple tracks while the mid-side stage simultaneously controls stereo width in the upper midrange. Parallel use cases exist in post-production for film and games, where dialog stems and effects stems can be cleaned of resonant artifacts without the need for frame-by-frame manual EQ automation.

Cross-domain transfer is never frictionless. In photography the notion of “resonance” must be redefined as an anomalous concentration of energy relative to a content-aware or noise-model baseline; simply ranking Fourier tile energies without regard to natural image statistics will remove desired high-frequency detail along with noise. In medical imaging the cost of false attenuation is higher than in music: removing a subtle lesion texture is far more consequential than dulling a cymbal. Therefore any clinical deployment must incorporate uncertainty quantification, the ability to visualize the residual, and a mandatory human-in-the-loop confirmation for high-stakes examinations. Regulatory pathways (FDA, CE) for adaptive spectral software as a medical device further complicate the picture; the explicit, auditable nature of the demon selection process may actually ease regulatory review compared with opaque deep networks, provided the manufacturer can demonstrate that the ranking and gain rules are deterministic and fully documented. These practical hurdles do not invalidate the conceptual mapping; they merely indicate the engineering and validation work that remains.

In summary, MatchboxEQ demonstrates that a carefully chosen intermediate abstraction—dense internal spectral agency packaged behind a low-dimensional, semantically meaningful control surface—can serve both the immediate needs of audio engineers and the longer-term goal of portable, interpretable signal-processing tools across sensory modalities. The 50-band matchbox is not an arbitrary constant; it is a commitment to a resolution that is high enough to isolate problems yet low enough to remain computationally and cognitively tractable. The demons are not a marketing flourish; they are an explicit mechanism for ranking and selectively acting upon spectral outliers. Together they constitute a design pattern that can be re-implemented, specialized, and hybridized for photography, ultrasound, electrophysiology, and beyond. The invitation issued by the original project remains open: ask how many bands you would like, decide how many demons to unleash, and listen—or look, or diagnose—to the result. The matchbox is ready; the agents await their instructions.

The recursive bandpass analysis employed in MatchboxEQ can be expressed formally. For a band with center frequency $\omega 0 = 2\pi f0/fs$ and design $Q = 0.707$, the coefficients of the direct-form bandpass are $b0 = \alpha$, $b1 = 0$, $b2 = -\alpha$, $a0 = 1+\alpha$, $a1 = -2\cos(\omega 0)$, $a2 = 1-\alpha$, where $\alpha = \sin(\omega 0)/(2Q)$. The state update for input sample $x[n]$ yields the filtered output $y[n] = (b0\,x[n] + b1\,s0 + b2\,s1 - a1\,s2 - a2\,s3)/a0$, after which the delay line is shifted. The energy tracker is a first-order recursive mean of absolute values: $e[n] = e[n-1] + \lambda\,(|y[n]| - e[n-1])$, with $\lambda = 0.04$ in the reference code. This combination provides a computationally light, minimum-phase analysis path whose group delay is well-characterized and acceptable for most monitoring applications. When higher selectivity is required, the same architecture admits substitution of the second-order section by a higher-order Butterworth or elliptic bandpass, or by a sliding DFT bin, without altering the downstream grouping and demon-selection logic. The modularity of the design is intentional: the “matchbox” is defined by the set of analysis frequencies and the association of each frequency with a controllable gain, not by any particular filter topology.

The commercial landscape of resonance suppression has evolved rapidly since the mid-2010s. Early dynamic EQs such as the Waves F6 or FabFilter Pro-Q’s dynamic mode still required the user to place bands manually. The subsequent generation—Soothe, RESO, Equator, and various free or open-source spectral processors—shifted the paradigm toward automatic detection of “protrusions” relative to a spectral baseline. MatchboxEQ situates itself within this lineage while reintroducing an explicit, high-resolution internal representation that the user can influence through the asked_bands and demon_count parameters.

The philosophical difference is that MatchboxEQ never hides the density of its internal agency; it merely packages that density behind a simple question. This transparency is especially valuable in educational settings, where students can visualize the 50-band energy vector, observe which indices are selected as demons, and thereby develop an intuitive understanding of spectral balance that purely black-box tools do not afford.

In computational photography the frequency-domain view of an image has a long and productive history. The classical Wiener filter, the Fourier-domain formulation of unsharp masking, and the entire family of wavelet shrinkage estimators all operate by measuring coefficient magnitudes and applying gain or threshold functions that depend on those magnitudes and on an estimate of noise power. MatchboxEQ's demon mechanism is a discrete, controllable relative of soft thresholding: instead of applying a continuous shrinkage function to every coefficient, it ranks the tiles or sub-bands by energy and applies a stronger attenuation only to the top N, while the remainder receive a milder compensatory adjustment. The ranking step introduces a form of sparsity promotion that is adaptive to the instantaneous content of the image. For a landscape photograph dominated by low-frequency sky gradients and mid-frequency foliage texture, the highest-energy tiles may correspond to residual sensor pattern noise or to compression ringing around high-contrast edges; the demons therefore concentrate their effort precisely where the visual cost of the artifact is highest. For a low-light portrait the ranking may elevate chrominance noise tiles, allowing the processor to protect luminance detail while cleaning color. The asked_bands parameter, by controlling the coarseness of energy grouping, lets the photographer decide whether the baseline against which "excess" is measured is local (fine groups) or more global (coarse groups). This is analogous to choosing the spatial support of a noise-estimation window in classical algorithms, yet it remains expressed in the same vocabulary the audio engineer already understands.

Medical ultrasound despeckling literature already contains frequency-domain and multi-scale methods that share structural similarities with MatchboxEQ. The key practical difference is that ultrasound speckle is multiplicative and signal-dependent, whereas audio resonances are more nearly additive narrow-band interferers. Consequently a medical adaptation would replace the simple absolute-energy tracker with a local coefficient-of-variation or a homomorphic (log-domain) energy measure. Once the energy vector is obtained, the demon selection and gain application stages transfer almost unchanged. The clinical user interface could expose asked_bands as a "scale sensitivity" control and demon_count as an "artifact aggressiveness" control, both of which are immediately meaningful to a sonographer. Because ultrasound frames arrive at 20–60 Hz, the computational budget per frame is modest; a GPU-resident filter bank or a lifting-scheme wavelet transform can keep the entire pipeline inside the real-time envelope. Similar remarks apply to EEG: the classic 50/60 Hz notch can be generalized to a set of adaptive demons that track the instantaneous power of line harmonics and of broadband muscle artifact, attenuating only those components that currently exceed a patient-specific or montage-specific baseline. The interpretability of the resulting gain vector—visible as a time-frequency mask—offers a diagnostic audit trail that purely opaque deep networks do not.

The original project documentation frames MatchboxEQ as a commentary on infinite choice and the fear of the unknown that accompanies every modern plugin GUI. That framing is not ornamental; it reflects a genuine design tension. When a system offers a single "amount" slider, the user is relieved of responsibility for the internal decisions yet also deprived of insight into them. When a system exposes fifty independent band gains, the user is theoretically in full control yet practically overwhelmed. MatchboxEQ occupies the intermediate position: the user chooses how many conceptual groups and how many aggressive agents, while the machine retains the dense internal grid. The resulting interaction is closer to conducting an ensemble than to either micromanaging every player or accepting a fully automatic performance. In

educational, research, and clinical contexts this intermediate stance is pedagogically and ethically preferable. Students learn the consequences of spectral intervention; researchers can ablate the effect of demon_count; clinicians can justify the attenuation of particular artifact bands by reference to an explicit ranking. The same stance also mitigates certain risks of automation bias: because the operator must still decide how many demons to summon, the system cannot be treated as an unexamined black box.

A natural next step is the hybridization of the transparent agent model with data-driven prediction. One can retain the 50-band analysis and the mid-side peaking-filter bank while replacing the hand-crafted energy-to-gain mapping with a small neural network that receives the energy vector (and optionally short-time spectral features) and emits a 50-dimensional gain vector. Training targets can be obtained from expert-annotated attenuation maps or from perceptual loss functions that compare the processed signal against a clean reference or against a preferred aesthetic. Because the network operates on an already low-dimensional representation (50 energies), it can be extremely compact—perhaps a few residual blocks—and therefore suitable for real-time inference on modest hardware. The asked_bands and demon_count parameters remain available as conditioning inputs or as post-network constraints (for example, forcing the N largest cuts to respect a minimum depth). Such a hybrid preserves the interpretability of the matchbox while acquiring the statistical sophistication of contemporary learning-based suppressors. The same hybrid architecture transfers to photography and biomedical domains once the appropriate energy features and training corpora are substituted.

Consider a live-sound engineer confronted with a vocalist whose headset microphone exhibits a strong 3.2 kHz resonance that varies with head position. A conventional graphic EQ would require constant manual riding; a static parametric cut would either be too mild or would dull the voice when the resonance is absent. MatchboxEQ with a modest demon_count can track the resonance as it moves, applying a deep cut only when the energy excess is detected and relaxing the cut when the singer turns away. The asked_bands parameter can be kept low (broad groups) so that the rest of the vocal spectrum remains stable. In a studio mastering context the same processor can be placed on a full mix with a higher demon_count and a genre profile biased toward “clarity,” gently reducing the cumulative harshness that accumulates from multiple tracks while the mid-side stage simultaneously controls stereo width in the upper midrange. Parallel use cases exist in post-production for film and games, where dialog stems and effects stems can be cleaned of resonant artifacts without the need for frame-by-frame manual EQ automation.

Cross-domain transfer is never frictionless. In photography the notion of “resonance” must be redefined as an anomalous concentration of energy relative to a content-aware or noise-model baseline; simply ranking Fourier tile energies without regard to natural image statistics will remove desired high-frequency detail along with noise. In medical imaging the cost of false attenuation is higher than in music: removing a subtle lesion texture is far more consequential than dulling a cymbal. Therefore any clinical deployment must incorporate uncertainty quantification, the ability to visualize the residual, and a mandatory human-in-the-loop confirmation for high-stakes examinations. Regulatory pathways (FDA, CE) for adaptive spectral software as a medical device further complicate the picture; the explicit, auditable nature of the demon selection process may actually ease regulatory review compared with opaque deep networks, provided the manufacturer can demonstrate that the ranking and gain rules are deterministic and fully documented. These practical hurdles do not invalidate the conceptual mapping; they merely indicate the engineering and validation work that remains.

In summary, MatchboxEQ demonstrates that a carefully chosen intermediate abstraction—dense internal spectral agency packaged behind a low-dimensional, semantically meaningful control surface—can serve both the immediate needs of audio engineers and the longer-term goal of portable, interpretable signal-processing tools across sensory modalities. The 50-band matchbox is not an arbitrary constant; it is a

commitment to a resolution that is high enough to isolate problems yet low enough to remain computationally and cognitively tractable. The demons are not a marketing flourish; they are an explicit mechanism for ranking and selectively acting upon spectral outliers. Together they constitute a design pattern that can be re-implemented, specialized, and hybridized for photography, ultrasound, electrophysiology, and beyond. The invitation issued by the original project remains open: ask how many bands you would like, decide how many demons to unleash, and listen—or look, or diagnose—to the result. The matchbox is ready; the agents await their instructions.

The recursive bandpass analysis employed in MatchboxEQ can be expressed formally. For a band with center frequency $\omega 0 = 2\pi f0/fs$ and design $Q = 0.707$, the coefficients of the direct-form bandpass are $b0 = \alpha$, $b1 = 0$, $b2 = -\alpha$, $a0 = 1+\alpha$, $a1 = -2\cos(\omega 0)$, $a2 = 1-\alpha$, where $\alpha = \sin(\omega 0)/(2Q)$. The state update for input sample $x[n]$ yields the filtered output $y[n] = (b0\,x[n] + b1\,s0 + b2\,s1 - a1\,s2 - a2\,s3)/a0$, after which the delay line is shifted. The energy tracker is a first-order recursive mean of absolute values: $e[n] = e[n-1] + \lambda\,(|y[n]| - e[n-1])$, with $\lambda = 0.04$ in the reference code. This combination provides a computationally light, minimum-phase analysis path whose group delay is well-characterized and acceptable for most monitoring applications. When higher selectivity is required, the same architecture admits substitution of the second-order section by a higher-order Butterworth or elliptic bandpass, or by a sliding DFT bin, without altering the downstream grouping and demon-selection logic. The modularity of the design is intentional: the “matchbox” is defined by the set of analysis frequencies and the association of each frequency with a controllable gain, not by any particular filter topology.

The commercial landscape of resonance suppression has evolved rapidly since the mid-2010s. Early dynamic EQs such as the Waves F6 or FabFilter Pro-Q’s dynamic mode still required the user to place bands manually. The subsequent generation—Soothe, RESO, Equator, and various free or open-source spectral processors—shifted the paradigm toward automatic detection of “protrusions” relative to a spectral baseline. MatchboxEQ situates itself within this lineage while reintroducing an explicit, high-resolution internal representation that the user can influence through the asked_bands and demon_count parameters. The philosophical difference is that MatchboxEQ never hides the density of its internal agency; it merely packages that density behind a simple question. This transparency is especially valuable in educational settings, where students can visualize the 50-band energy vector, observe which indices are selected as demons, and thereby develop an intuitive understanding of spectral balance that purely black-box tools do not afford.

In computational photography the frequency-domain view of an image has a long and productive history. The classical Wiener filter, the Fourier-domain formulation of unsharp masking, and the entire family of wavelet shrinkage estimators all operate by measuring coefficient magnitudes and applying gain or threshold functions that depend on those magnitudes and on an estimate of noise power. MatchboxEQ’s demon mechanism is a discrete, controllable relative of soft thresholding: instead of applying a continuous shrinkage function to every coefficient, it ranks the tiles or sub-bands by energy and applies a stronger attenuation only to the top N, while the remainder receive a milder compensatory adjustment. The ranking step introduces a form of sparsity promotion that is adaptive to the instantaneous content of the image. For a landscape photograph dominated by low-frequency sky gradients and mid-frequency foliage texture, the highest-energy tiles may correspond to residual sensor pattern noise or to compression ringing around high-contrast edges; the demons therefore concentrate their effort precisely where the visual cost of the artifact is highest. For a low-light portrait the ranking may elevate chrominance noise tiles, allowing the processor to protect luminance detail while cleaning color. The asked_bands parameter, by controlling the coarseness of energy grouping, lets the photographer decide whether the baseline against which “excess” is measured is local (fine groups) or more global (coarse groups). This is analogous to choosing the spatial

support of a noise-estimation window in classical algorithms, yet it remains expressed in the same vocabulary the audio engineer already understands.

Medical ultrasound despeckling literature already contains frequency-domain and multi-scale methods that share structural similarities with MatchboxEQ. The key practical difference is that ultrasound speckle is multiplicative and signal-dependent, whereas audio resonances are more nearly additive narrow-band interferers. Consequently a medical adaptation would replace the simple absolute-energy tracker with a local coefficient-of-variation or a homomorphic (log-domain) energy measure. Once the energy vector is obtained, the demon selection and gain application stages transfer almost unchanged. The clinical user interface could expose asked_bands as a “scale sensitivity” control and demon_count as an “artifact aggressiveness” control, both of which are immediately meaningful to a sonographer. Because ultrasound frames arrive at 20–60 Hz, the computational budget per frame is modest; a GPU-resident filter bank or a lifting-scheme wavelet transform can keep the entire pipeline inside the real-time envelope. Similar remarks apply to EEG: the classic 50/60 Hz notch can be generalized to a set of adaptive demons that track the instantaneous power of line harmonics and of broadband muscle artifact, attenuating only those components that currently exceed a patient-specific or montage-specific baseline. The interpretability of the resulting gain vector—visible as a time-frequency mask—offers a diagnostic audit trail that purely opaque deep networks do not.

The original project documentation frames MatchboxEQ as a commentary on infinite choice and the fear of the unknown that accompanies every modern plugin GUI. That framing is not ornamental; it reflects a genuine design tension. When a system offers a single “amount” slider, the user is relieved of responsibility for the internal decisions yet also deprived of insight into them. When a system exposes fifty independent band gains, the user is theoretically in full control yet practically overwhelmed. MatchboxEQ occupies the intermediate position: the user chooses how many conceptual groups and how many aggressive agents, while the machine retains the dense internal grid. The resulting interaction is closer to conducting an ensemble than to either micromanaging every player or accepting a fully automatic performance. In educational, research, and clinical contexts this intermediate stance is pedagogically and ethically preferable. Students learn the consequences of spectral intervention; researchers can ablate the effect of demon_count; clinicians can justify the attenuation of particular artifact bands by reference to an explicit ranking. The same stance also mitigates certain risks of automation bias: because the operator must still decide how many demons to summon, the system cannot be treated as an unexamined black box.

A natural next step is the hybridization of the transparent agent model with data-driven prediction. One can retain the 50-band analysis and the mid-side peaking-filter bank while replacing the hand-crafted energy-to-gain mapping with a small neural network that receives the energy vector (and optionally short-time spectral features) and emits a 50-dimensional gain vector. Training targets can be obtained from expert-annotated attenuation maps or from perceptual loss functions that compare the processed signal against a clean reference or against a preferred aesthetic. Because the network operates on an already low-dimensional representation (50 energies), it can be extremely compact—perhaps a few residual blocks—and therefore suitable for real-time inference on modest hardware. The asked_bands and demon_count parameters remain available as conditioning inputs or as post-network constraints (for example, forcing the N largest cuts to respect a minimum depth). Such a hybrid preserves the interpretability of the matchbox while acquiring the statistical sophistication of contemporary learning-based suppressors. The same hybrid architecture transfers to photography and biomedical domains once the appropriate energy features and training corpora are substituted.

Consider a live-sound engineer confronted with a vocalist whose headset microphone exhibits a strong 3.2 kHz resonance that varies with head position. A conventional graphic EQ would require constant manual riding; a static parametric cut would either be too mild or would dull the voice when the resonance is absent. MatchboxEQ with a modest demon_count can track the resonance as it moves, applying a deep cut only when the energy excess is detected and relaxing the cut when the singer turns away. The asked_bands parameter can be kept low (broad groups) so that the rest of the vocal spectrum remains stable. In a studio mastering context the same processor can be placed on a full mix with a higher demon_count and a genre profile biased toward “clarity,” gently reducing the cumulative harshness that accumulates from multiple tracks while the mid-side stage simultaneously controls stereo width in the upper midrange. Parallel use cases exist in post-production for film and games, where dialog stems and effects stems can be cleaned of resonant artifacts without the need for frame-by-frame manual EQ automation.

Cross-domain transfer is never frictionless. In photography the notion of “resonance” must be redefined as an anomalous concentration of energy relative to a content-aware or noise-model baseline; simply ranking Fourier tile energies without regard to natural image statistics will remove desired high-frequency detail along with noise. In medical imaging the cost of false attenuation is higher than in music: removing a subtle lesion texture is far more consequential than dulling a cymbal. Therefore any clinical deployment must incorporate uncertainty quantification, the ability to visualize the residual, and a mandatory human-in-the-loop confirmation for high-stakes examinations. Regulatory pathways (FDA, CE) for adaptive spectral software as a medical device further complicate the picture; the explicit, auditable nature of the demon selection process may actually ease regulatory review compared with opaque deep networks, provided the manufacturer can demonstrate that the ranking and gain rules are deterministic and fully documented. These practical hurdles do not invalidate the conceptual mapping; they merely indicate the engineering and validation work that remains.

In summary, MatchboxEQ demonstrates that a carefully chosen intermediate abstraction—dense internal spectral agency packaged behind a low-dimensional, semantically meaningful control surface—can serve both the immediate needs of audio engineers and the longer-term goal of portable, interpretable signal-processing tools across sensory modalities. The 50-band matchbox is not an arbitrary constant; it is a commitment to a resolution that is high enough to isolate problems yet low enough to remain computationally and cognitively tractable. The demons are not a marketing flourish; they are an explicit mechanism for ranking and selectively acting upon spectral outliers. Together they constitute a design pattern that can be re-implemented, specialized, and hybridized for photography, ultrasound, electrophysiology, and beyond. The invitation issued by the original project remains open: ask how many bands you would like, decide how many demons to unleash, and listen—or look, or diagnose—to the result. The matchbox is ready; the agents await their instructions.

End of Supplementary Expansion

Further Technical, Historical and Application Elaboration

The choice of fifty bands is not arbitrary. Psychoacoustic critical-band models (Bark, ERB) suggest that the human auditory system analyzes the spectrum with a resolution that varies from roughly 100 Hz at low frequencies to several hundred Hertz at high frequencies. A constant-Q or log-spaced bank of fifty filters from 40 Hz to 18 kHz approximates three to four filters per critical band across most of the range, providing enough selectivity to isolate typical musical resonances (which often occupy a fraction of an octave) while remaining sparse enough that the energy vector can be inspected and manipulated in real time. Increasing the band count to one hundred would improve frequency precision at the cost of both computation and the cognitive legibility of the matchbox metaphor; decreasing it to twenty-four would lose the ability to discriminate closely spaced resonances. Fifty therefore represents a pragmatic compromise that has proven effective in informal testing and that aligns with the density used by several commercial spectral processors under their highest-precision settings.

Mid-side processing is included for both technical and aesthetic reasons. Many resonant problems—especially those arising from mono-compatible sources or from room modes—are predominantly mid-channel phenomena, while stereo width and ambience reside in the side channel. By applying a slightly stronger gain vector to the side signal, MatchboxEQ can tame harshness that appears in the stereo image without over-compressing the mono sum that will be heard on small speakers or in mono playback. The soft-clip stage that follows recombination further homogenizes any residual peaks and contributes a subtle harmonic density that many listeners describe as “analog” or “expensive.” These finishing touches are deliberately conservative; the primary work of the processor is performed by the adaptive spectral agents, not by saturation or stereo enhancement.

From a software-engineering perspective the reference implementations illustrate two complementary development strategies. The Faust code prioritizes declarative clarity and automatic generation of efficient C++ or LLVM backends, making it ideal for integration into larger instrument patches such as the FeltPianoMatchbox additive synthesizer. The pure-Python code prioritizes readability and rapid experimentation, allowing researchers to substitute alternative energy estimators, gain-mapping functions, or even neural modules without recompiling. Both share an identical logical structure, so algorithmic improvements discovered in one environment can be ported to the other with minimal friction. This dual-track approach is recommended for any future domain-specific forks: maintain a high-level prototype for research and a compiled or JIT-compiled path for production.

In the photographic domain an additional practical consideration is the handling of color. Operating the spectral agents independently on each RGB channel can introduce hue shifts when the noise statistics differ across channels; operating solely on a luminance channel leaves chrominance noise untouched. A more robust strategy is to convert to an opponent-color space (for example YCbCr or a custom LMS-inspired space), apply the matchbox processing more aggressively to the chrominance planes, and apply a milder version (or none) to luminance. The same principle appears in audio as the differential treatment of mid and side. Context parameters can encode the color space and the relative aggressiveness, preserving the unified control vocabulary across domains.

For EEG the temporal non-stationarity of artifacts suggests that the energy tracker’s time constant should itself be adaptive, or that multiple parallel trackers with different time constants should vote on demon selection. A short-time-constant tracker captures transient muscle bursts; a longer one captures sustained power-line interference. The final demon set can be the union or a weighted intersection of the two rankings. Such multi-timescale analysis is already implicit in some commercial audio dynamics processors and transfers cleanly to the biomedical setting. The resulting system remains fully interpretable: at any moment

the clinician can inspect which bands are currently designated as demons and by how much they are being attenuated.

The open-source release of MatchboxEQ under a permissive license is intended to accelerate precisely these cross-domain experiments. Researchers in medical imaging can fork the Python prototype, replace the 1-D filter bank with a 2-D or 3-D transform, and begin testing on public ultrasound or hyperspectral datasets within days rather than months. Audio engineers can embed the Faust version into their existing instrument or effect libraries. Educators can use the visualization scripts to demonstrate spectral processing principles without requiring students to write low-level DSP code. The project's value therefore lies not only in the particular algorithm described here but in the reusable pattern of a dense, ranked, context-aware spectral agent system that can be specialized to many signal types.

The choice of fifty bands is not arbitrary. Psychoacoustic critical-band models (Bark, ERB) suggest that the human auditory system analyzes the spectrum with a resolution that varies from roughly 100 Hz at low frequencies to several hundred Hertz at high frequencies. A constant-Q or log-spaced bank of fifty filters from 40 Hz to 18 kHz approximates three to four filters per critical band across most of the range, providing enough selectivity to isolate typical musical resonances (which often occupy a fraction of an octave) while remaining sparse enough that the energy vector can be inspected and manipulated in real time. Increasing the band count to one hundred would improve frequency precision at the cost of both computation and the cognitive legibility of the matchbox metaphor; decreasing it to twenty-four would lose the ability to discriminate closely spaced resonances. Fifty therefore represents a pragmatic compromise that has proven effective in informal testing and that aligns with the density used by several commercial spectral processors under their highest-precision settings.

Mid-side processing is included for both technical and aesthetic reasons. Many resonant problems—especially those arising from mono-compatible sources or from room modes—are predominantly mid-channel phenomena, while stereo width and ambience reside in the side channel. By applying a slightly stronger gain vector to the side signal, MatchboxEQ can tame harshness that appears in the stereo image without over-compressing the mono sum that will be heard on small speakers or in mono playback. The soft-clip stage that follows recombination further homogenizes any residual peaks and contributes a subtle harmonic density that many listeners describe as "analog" or "expensive." These finishing touches are deliberately conservative; the primary work of the processor is performed by the adaptive spectral agents, not by saturation or stereo enhancement.

From a software-engineering perspective the reference implementations illustrate two complementary development strategies. The Faust code prioritizes declarative clarity and automatic generation of efficient C++ or LLVM backends, making it ideal for integration into larger instrument patches such as the FeltPianoMatchbox additive synthesizer. The pure-Python code prioritizes readability and rapid experimentation, allowing researchers to substitute alternative energy estimators, gain-mapping functions, or even neural modules without recompiling. Both share an identical logical structure, so algorithmic improvements discovered in one environment can be ported to the other with minimal friction. This dual-track approach is recommended for any future domain-specific forks: maintain a high-level prototype for research and a compiled or JIT-compiled path for production.

In the photographic domain an additional practical consideration is the handling of color. Operating the spectral agents independently on each RGB channel can introduce hue shifts when the noise statistics differ across channels; operating solely on a luminance channel leaves chrominance noise untouched. A more robust strategy is to convert to an opponent-color space (for example YCbCr or a custom LMS-inspired space), apply the matchbox processing more aggressively to the chrominance planes, and apply a milder version (or none) to luminance. The same principle appears in audio as the differential treatment of mid and

side. Context parameters can encode the color space and the relative aggressiveness, preserving the unified control vocabulary across domains.

For EEG the temporal non-stationarity of artifacts suggests that the energy tracker's time constant should itself be adaptive, or that multiple parallel trackers with different time constants should vote on demon selection. A short-time-constant tracker captures transient muscle bursts; a longer one captures sustained power-line interference. The final demon set can be the union or a weighted intersection of the two rankings. Such multi-timescale analysis is already implicit in some commercial audio dynamics processors and transfers cleanly to the biomedical setting. The resulting system remains fully interpretable: at any moment the clinician can inspect which bands are currently designated as demons and by how much they are being attenuated.

The open-source release of MatchboxEQ under a permissive license is intended to accelerate precisely these cross-domain experiments. Researchers in medical imaging can fork the Python prototype, replace the 1-D filter bank with a 2-D or 3-D transform, and begin testing on public ultrasound or hyperspectral datasets within days rather than months. Audio engineers can embed the Faust version into their existing instrument or effect libraries. Educators can use the visualization scripts to demonstrate spectral processing principles without requiring students to write low-level DSP code. The project's value therefore lies not only in the particular algorithm described here but in the reusable pattern of a dense, ranked, context-aware spectral agent system that can be specialized to many signal types.

The choice of fifty bands is not arbitrary. Psychoacoustic critical-band models (Bark, ERB) suggest that the human auditory system analyzes the spectrum with a resolution that varies from roughly 100 Hz at low frequencies to several hundred Hertz at high frequencies. A constant-Q or log-spaced bank of fifty filters from 40 Hz to 18 kHz approximates three to four filters per critical band across most of the range, providing enough selectivity to isolate typical musical resonances (which often occupy a fraction of an octave) while remaining sparse enough that the energy vector can be inspected and manipulated in real time. Increasing the band count to one hundred would improve frequency precision at the cost of both computation and the cognitive legibility of the matchbox metaphor; decreasing it to twenty-four would lose the ability to discriminate closely spaced resonances. Fifty therefore represents a pragmatic compromise that has proven effective in informal testing and that aligns with the density used by several commercial spectral processors under their highest-precision settings.

Mid-side processing is included for both technical and aesthetic reasons. Many resonant problems—especially those arising from mono-compatible sources or from room modes—are predominantly mid-channel phenomena, while stereo width and ambience reside in the side channel. By applying a slightly stronger gain vector to the side signal, MatchboxEQ can tame harshness that appears in the stereo image without over-compressing the mono sum that will be heard on small speakers or in mono playback. The soft-clip stage that follows recombination further homogenizes any residual peaks and contributes a subtle harmonic density that many listeners describe as "analog" or "expensive." These finishing touches are deliberately conservative; the primary work of the processor is performed by the adaptive spectral agents, not by saturation or stereo enhancement.

From a software-engineering perspective the reference implementations illustrate two complementary development strategies. The Faust code prioritizes declarative clarity and automatic generation of efficient C++ or LLVM backends, making it ideal for integration into larger instrument patches such as the FeltPianoMatchbox additive synthesizer. The pure-Python code prioritizes readability and rapid experimentation, allowing researchers to substitute alternative energy estimators, gain-mapping functions, or even neural modules without recompiling. Both share an identical logical structure, so algorithmic improvements discovered in one environment can be ported to the other with minimal friction. This

dual-track approach is recommended for any future domain-specific forks: maintain a high-level prototype for research and a compiled or JIT-compiled path for production.

In the photographic domain an additional practical consideration is the handling of color. Operating the spectral agents independently on each RGB channel can introduce hue shifts when the noise statistics differ across channels; operating solely on a luminance channel leaves chrominance noise untouched. A more robust strategy is to convert to an opponent-color space (for example YCbCr or a custom LMS-inspired space), apply the matchbox processing more aggressively to the chrominance planes, and apply a milder version (or none) to luminance. The same principle appears in audio as the differential treatment of mid and side. Context parameters can encode the color space and the relative aggressiveness, preserving the unified control vocabulary across domains.

For EEG the temporal non-stationarity of artifacts suggests that the energy tracker's time constant should itself be adaptive, or that multiple parallel trackers with different time constants should vote on demon selection. A short-time-constant tracker captures transient muscle bursts; a longer one captures sustained power-line interference. The final demon set can be the union or a weighted intersection of the two rankings. Such multi-timescale analysis is already implicit in some commercial audio dynamics processors and transfers cleanly to the biomedical setting. The resulting system remains fully interpretable: at any moment the clinician can inspect which bands are currently designated as demons and by how much they are being attenuated.

The open-source release of MatchboxEQ under a permissive license is intended to accelerate precisely these cross-domain experiments. Researchers in medical imaging can fork the Python prototype, replace the 1-D filter bank with a 2-D or 3-D transform, and begin testing on public ultrasound or hyperspectral datasets within days rather than months. Audio engineers can embed the Faust version into their existing instrument or effect libraries. Educators can use the visualization scripts to demonstrate spectral processing principles without requiring students to write low-level DSP code. The project's value therefore lies not only in the particular algorithm described here but in the reusable pattern of a dense, ranked, context-aware spectral agent system that can be specialized to many signal types.

The choice of fifty bands is not arbitrary. Psychoacoustic critical-band models (Bark, ERB) suggest that the human auditory system analyzes the spectrum with a resolution that varies from roughly 100 Hz at low frequencies to several hundred Hertz at high frequencies. A constant-Q or log-spaced bank of fifty filters from 40 Hz to 18 kHz approximates three to four filters per critical band across most of the range, providing enough selectivity to isolate typical musical resonances (which often occupy a fraction of an octave) while remaining sparse enough that the energy vector can be inspected and manipulated in real time. Increasing the band count to one hundred would improve frequency precision at the cost of both computation and the cognitive legibility of the matchbox metaphor; decreasing it to twenty-four would lose the ability to discriminate closely spaced resonances. Fifty therefore represents a pragmatic compromise that has proven effective in informal testing and that aligns with the density used by several commercial spectral processors under their highest-precision settings.

Mid-side processing is included for both technical and aesthetic reasons. Many resonant problems—especially those arising from mono-compatible sources or from room modes—are predominantly mid-channel phenomena, while stereo width and ambience reside in the side channel. By applying a slightly stronger gain vector to the side signal, MatchboxEQ can tame harshness that appears in the stereo image without over-compressing the mono sum that will be heard on small speakers or in mono playback. The soft-clip stage that follows recombination further homogenizes any residual peaks and contributes a subtle harmonic density that many listeners describe as "analog" or "expensive." These finishing touches are deliberately conservative; the primary work of the processor is performed by the adaptive spectral agents,

not by saturation or stereo enhancement.

From a software-engineering perspective the reference implementations illustrate two complementary development strategies. The Faust code prioritizes declarative clarity and automatic generation of efficient C++ or LLVM backends, making it ideal for integration into larger instrument patches such as the FeltPianoMatchbox additive synthesizer. The pure-Python code prioritizes readability and rapid experimentation, allowing researchers to substitute alternative energy estimators, gain-mapping functions, or even neural modules without recompiling. Both share an identical logical structure, so algorithmic improvements discovered in one environment can be ported to the other with minimal friction. This dual-track approach is recommended for any future domain-specific forks: maintain a high-level prototype for research and a compiled or JIT-compiled path for production.

In the photographic domain an additional practical consideration is the handling of color. Operating the spectral agents independently on each RGB channel can introduce hue shifts when the noise statistics differ across channels; operating solely on a luminance channel leaves chrominance noise untouched. A more robust strategy is to convert to an opponent-color space (for example YCbCr or a custom LMS-inspired space), apply the matchbox processing more aggressively to the chrominance planes, and apply a milder version (or none) to luminance. The same principle appears in audio as the differential treatment of mid and side. Context parameters can encode the color space and the relative aggressiveness, preserving the unified control vocabulary across domains.

For EEG the temporal non-stationarity of artifacts suggests that the energy tracker’s time constant should itself be adaptive, or that multiple parallel trackers with different time constants should vote on demon selection. A short-time-constant tracker captures transient muscle bursts; a longer one captures sustained power-line interference. The final demon set can be the union or a weighted intersection of the two rankings. Such multi-timescale analysis is already implicit in some commercial audio dynamics processors and transfers cleanly to the biomedical setting. The resulting system remains fully interpretable: at any moment the clinician can inspect which bands are currently designated as demons and by how much they are being attenuated.

The open-source release of MatchboxEQ under a permissive license is intended to accelerate precisely these cross-domain experiments. Researchers in medical imaging can fork the Python prototype, replace the 1-D filter bank with a 2-D or 3-D transform, and begin testing on public ultrasound or hyperspectral datasets within days rather than months. Audio engineers can embed the Faust version into their existing instrument or effect libraries. Educators can use the visualization scripts to demonstrate spectral processing principles without requiring students to write low-level DSP code. The project’s value therefore lies not only in the particular algorithm described here but in the reusable pattern of a dense, ranked, context-aware spectral agent system that can be specialized to many signal types.

Corrigendum — Section 3.3 / Gain Logic Update

MatchboxEQ: Adaptive Spectral Processing with Agent-Based Resonance Suppression
Lewis James Seals (theRealla) — November 2026

3.3 Band Energy Analysis and Gated Compensation (Updated)

For each of the 50 bands a second-order bandpass filter extracts a narrow-band time series. A first-order exponential smoother tracks the absolute value of the filtered signal, yielding a running energy estimate e_i for band i. The production implementation uses a smoothing coefficient energy_alpha = 0.001 (approximately 20 ms time constant at 48 kHz). An earlier prototype used 0.04 (~0.5 ms); that faster setting allowed rectifier ripple to modulate low-frequency bands and produce audible harmonic distortion, and has been superseded.

After a sufficient number of samples have been observed, the energy vector is partitioned according to asked_bands into contiguous groups. Group energy is the arithmetic mean of the member band energies. Independently, the N = demon_count bands with the highest absolute energies are marked as selected (demons). Selected bands receive a relative-energy-dependent cut typically in the range 0.2–0.9 (linear). Non-selected bands originally received a compensatory multiplier of the form clamp(0.015 / group_energy, 0.7, 1.4).

Problem observed on quiet material

When a group is essentially empty of signal (for example the 4–12 kHz region of a typical home refrigerator, whose high-frequency absolute-mean energy lies well below –50 dBFS), the original compensator evaluates to the upper clamp (+3 dB). Cascading across multiple quiet high-frequency bands produced a measured noise-floor rise of approximately +10.6 dB in the 4–12 kHz octave. The design therefore functioned as an unintended spectrum flattener that boosted the noise floor whenever meaningful signal was absent.

Gated compensation (current production logic)

The non-demon branch is now gated so that boost is applied only when a group contains meaningful energy:

```
constexpr float k_target = 0.015f;   // abs-mean energy target
constexpr float k_floor  = 0.012f;   // below this → treat as empty
constexpr float k_ramp   = 0.008f;   // smooth transition

float raw_comp = clamp(k_target / (group_energy[g] + 1e-6f), 0.7f, 1.4f);
float gate     = clamp((group_energy[g] - k_floor) / k_ramp, 0.0f, 1.0f);
float comp     = 1.0f + gate * (raw_comp - 1.0f);  // unity when gated
base *= comp;
```

With k_floor = 0.012 the high-frequency groups of quiet domestic sources remain fully gated (gate = 0 → comp = 1.0). Music-level material, whose group energies typically sit at or above the target, continues to receive the original balancing behaviour (gate → 1). Demon cuts are completely unaffected by this change. After the gate was introduced, the previously observed +10.6 dB high-frequency rise on a home-refrigerator recording fell to approximately +3 dB residual (attributable mainly to soft-clip harmonics and filter cascade numerical noise), which is far less audible.

The same gated formulation is present in the C++ (MatchboxEQ.h), pure-Python, and any AssemblyScript/WebAssembly ports. Authors and implementers should treat energy_alpha = 0.001 and the gated non-demon compensation as the normative reference; any earlier description that cites $\alpha = 0.04$ or an ungated 0.015 / group_energy boost should be considered superseded by this corrigendum.

Implication for cross-domain use

The gate is especially relevant when Matchbox-style agents are applied to medical or photographic data that may contain large regions of near-zero energy (dark image areas, silent EEG segments, empty spectral tiles). Without the gate, those empty regions would be boosted exactly as the refrigerator high frequencies were. The same k_floor / k_ramp parameters therefore serve as a general safeguard against noise-floor inflation across domains.