

# MPR Plus Spray Nozzles

- Radius: 5'-15' (1,5-4,6m)
- Operating Pressure Range: 20-75 psi (1,4-5,2 Bar)
- Matched Precipitation

*MPR Nozzles make design and installation easier than ever.* Just pick your spacing and choose your arc - the nozzle does everything else.



| MPR Plus Spray Nozzle Series Model List |                   |                                        |                                |
|-----------------------------------------|-------------------|----------------------------------------|--------------------------------|
| Model                                   | Description       | Model                                  | Description                    |
| <b>5' (1,5m) MPR Plus Nozzle Red</b>    |                   | <b>8' (2,4m) MPR Plus Nozzle Green</b> |                                |
| 5Q                                      | 90° Arc           | 8Q                                     | 90° Arc                        |
| 5T                                      | 120° Arc          | 8T                                     | 120° Arc                       |
| 5H                                      | 180° Arc          | 8H                                     | 180° Arc                       |
| 5TT                                     | 240° Arc          | 8TT                                    | 240° Arc                       |
| 5TQ                                     | 270° Arc          | 8TQ                                    | 270° Arc                       |
| 5F                                      | 360° Arc          | 8F                                     | 360° Arc                       |
| <b>8' (2,4m) Flat Spray Black</b>       |                   | <b>10' (3,0m) MPR Plus Nozzle Blue</b> |                                |
| FSQ                                     | 90° Arc           | 10Q                                    | 90° Arc                        |
| FSH                                     | 180° Arc          | 10T                                    | 120° Arc                       |
| FSF                                     | 360° Arc          | 10H                                    | 180° Arc                       |
| FSQ-LG                                  | 90° Arc, Low GPM  | 10TT                                   | 240° Arc                       |
| FSH-LG                                  | 180° Arc, Low GPM | 10TQ                                   | 270° Arc                       |
| FSF-LG                                  | 360° Arc, Low GPM | 10F                                    | 360° Arc                       |
| <b>12' (3,7m) MPR Plus Nozzle Brown</b> |                   | <b>Special Patterns Orange</b>         |                                |
| 12Q                                     | 90° Arc           | 4SST                                   | Side Strip 4'x30' (1,2-9,1m)   |
| 12T                                     | 120° Arc          | 4EST                                   | End Strip 4'x15' (1,2-4,3m)    |
| 12H                                     | 180° Arc          | 4CST                                   | Center Strip 4'x30' (1,2-6,1m) |
| 12TT                                    | 240° Arc          | 9SST                                   | Side Strip 9'x18' (2,7-5,2m)   |
| 12TQ                                    | 270° Arc          | 4SSST                                  | Side Strip 4'x18' (1,2-5,2m)   |
| 12F                                     | 360° Arc          | 2SST                                   | Side Strip 2' x 6' (0,6-1,8m)  |
| <b>15' (4,6m) MPR Plus Nozzle Black</b> |                   |                                        |                                |
| 15Q                                     | 90° Arc           |                                        |                                |
| 15T                                     | 120° Arc          |                                        |                                |
| 15H                                     | 180° Arc          |                                        |                                |
| 15TT                                    | 240° Arc          |                                        |                                |
| 15TQ                                    | 270° Arc          |                                        |                                |
| 15F                                     | 360° Arc          |                                        |                                |

(Note: All above also available in Pressure Compensating (PC) Models)

- Side & Corner Specialty Patterns
- Arc Options: 90°, 120°, 180°, 240°, 270°, 360°
- Fit Toro® Spray Bodies

## Features & Benefits

### Matched Precipitation Rates

Ensure all nozzles (every arc within a family) apply water at approximately the same rate.

### Low Flow Rates

Allow for more sprinklers to be placed on the same zone.

### Pre-installed Pressure Compensation Device (PCD)

Eliminate fogging, conserve water and provide precise flow rates (also available without PC Devices).

### Complete Selection Of Arcs

Arcs for all radius options – full, 3/4, 2/3, 1/2, 1/3 and 1/4.

## Specifications

### Operating Specifications

- Operating pressure range: 20-75 psi (1,4-5,2 Bar)
- Recommended pressure: 30 psi (2,1 Bar)
- Flow Rate: 0.05 – 4.58 GPM (0,2-17,3 LPM)
- Nozzle trajectory:
  - 5': 5° - 8': 10° - 10': 17° - 12': 24° - 15': 28°
  - Corner and Side Strips: 17°
  - 8' Flat Spray: 0°

### Additional Features

- Standard and special spray patterns
- Customized screens for each nozzle
- Patterns for small areas: full set of arcs for 10', 8' and 5' (3,0m, 2,4m, and 1,5m) radius nozzles
- 4' x 18' (1,2-5,2m) side strip ideal for medians
- 2' x 6' (0,6-1,8m) for small planter beds and other narrow areas
- Fine-mesh snap-in filter screens for lower flow nozzles
- Five levels of trajectory
- Convenient nozzle packaging – nozzles and screens packed separately
- Adjustment screw allows up to 25% reduction in radius and complete shutoff

### Warranty

- Two years

### Specifying Information—MPR Plus

| XX-XXX-PC                                                                                                                            |         |                  |                          |
|--------------------------------------------------------------------------------------------------------------------------------------|---------|------------------|--------------------------|
| Radius                                                                                                                               | Arc     |                  | Optional                 |
| XX                                                                                                                                   | XXX     |                  | PC                       |
| 5—5' (1,5m)                                                                                                                          | Q—90°   | T—120°           | PC—Pressure Compensation |
| 8—8' (2,4m)                                                                                                                          | TT—240° | H—180°           |                          |
| 10—10' (3,0m)                                                                                                                        |         | Q—270°           |                          |
| 12—12' (3,7m)                                                                                                                        |         | EST—End Strip    |                          |
| 15—15' (4,6m)                                                                                                                        |         | CST—Center Strip |                          |
|                                                                                                                                      |         | SST—Side Strip   |                          |
| Example: A 570 MPR Plus Nozzle with a spray of 10' (3,0m), 180° arc and pressure compensation, would be specified as: <b>10-H-PC</b> |         |                  |                          |

**Note:** To specify a MPR Plus nozzle with a 570Z sprinkler body, attach the body specification before the above nozzle specification.

**Note:** Do not use PCDs with 570Z PR & 570Z PRX models

# Performance Data-MPR Plus Spray Nozzles—US

## 5' Series with 5° Trajectory—Red

| Arc                                                                                       | Desc.   | psi   | GPM  | Radius | Prec. Rate |      |
|-------------------------------------------------------------------------------------------|---------|-------|------|--------|------------|------|
|                                                                                           |         |       |      |        | ▲          | ☒    |
| 90°<br>  | 5-Q     | 20    | 0.05 | 4      | 1.40       | 1.21 |
|                                                                                           |         | 30    | 0.09 | 5      | 1.61       | 1.40 |
|                                                                                           |         | 40    | 0.12 | 6      | 1.78       | 1.54 |
|                                                                                           | 5-Q-PC  | 50    | 0.15 | 6      | 1.86       | 1.62 |
|                                                                                           |         | 30-40 | 0.09 | 5      | 1.61       | 1.40 |
|                                                                                           |         | 40-75 | 0.10 | 5      | 1.79       | 1.55 |
| 120°<br> | 5-T     | 20    | 0.07 | 4      | 1.47       | 1.27 |
|                                                                                           |         | 30    | 0.12 | 5      | 1.61       | 1.40 |
|                                                                                           |         | 40    | 0.16 | 6      | 1.78       | 1.54 |
|                                                                                           | 5-T-PC  | 50    | 0.20 | 6      | 1.86       | 1.62 |
|                                                                                           |         | 30-40 | 0.12 | 5      | 1.61       | 1.40 |
|                                                                                           |         | 40-75 | 0.13 | 5      | 1.79       | 1.55 |
| 180°<br> | 5-H     | 20    | 0.10 | 4      | 1.40       | 1.21 |
|                                                                                           |         | 30    | 0.19 | 5      | 1.70       | 1.47 |
|                                                                                           |         | 40    | 0.23 | 6      | 1.70       | 1.47 |
|                                                                                           | 5-H-PC  | 50    | 0.27 | 6      | 1.68       | 1.45 |
|                                                                                           |         | 30-40 | 0.18 | 5      | 1.61       | 1.40 |
|                                                                                           |         | 40-75 | 0.20 | 5      | 1.79       | 1.55 |
| 240°<br> | 5-TT    | 20    | 0.15 | 4      | 1.57       | 1.36 |
|                                                                                           |         | 30    | 0.25 | 5      | 1.68       | 1.45 |
|                                                                                           |         | 40    | 0.30 | 6      | 1.66       | 1.44 |
|                                                                                           | 5-TT-PC | 50    | 0.35 | 6      | 1.63       | 1.41 |
|                                                                                           |         | 30-40 | 0.23 | 5      | 1.54       | 1.34 |
|                                                                                           |         | 40-75 | 0.27 | 5      | 1.81       | 1.57 |
| 270°<br> | 5-TQ    | 20    | 0.20 | 4      | 1.86       | 1.61 |
|                                                                                           |         | 30    | 0.29 | 5      | 1.73       | 1.50 |
|                                                                                           |         | 40    | 0.34 | 6      | 1.68       | 1.45 |
|                                                                                           | 5-TQ-PC | 50    | 0.40 | 6      | 1.66       | 1.44 |
|                                                                                           |         | 30-40 | 0.26 | 5      | 1.55       | 1.34 |
|                                                                                           |         | 40-75 | 0.29 | 5      | 1.73       | 1.50 |
| 360°<br> | 5-F     | 20    | 0.25 | 4      | 1.75       | 1.51 |
|                                                                                           |         | 30    | 0.38 | 5      | 1.70       | 1.47 |
|                                                                                           |         | 40    | 0.45 | 6      | 1.66       | 1.44 |
|                                                                                           | 5-F-PC  | 50    | 0.53 | 6      | 1.65       | 1.43 |
|                                                                                           |         | 30-40 | 0.35 | 5      | 1.57       | 1.36 |
|                                                                                           |         | 40-75 | 0.39 | 5      | 1.75       | 1.51 |

## 8' Series with 10° Trajectory—Green

| Arc                                                                                       | Desc.   | psi   | GPM  | Radius | Prec. Rate |      |
|-------------------------------------------------------------------------------------------|---------|-------|------|--------|------------|------|
|                                                                                           |         |       |      |        | ▲          | ☒    |
| 90°<br>  | 8-Q     | 20    | 0.17 | 7      | 1.55       | 1.34 |
|                                                                                           |         | 30    | 0.24 | 8      | 1.68       | 1.45 |
|                                                                                           |         | 40    | 0.26 | 9      | 1.61       | 1.39 |
|                                                                                           | 8-Q-PC  | 50    | 0.29 | 9      | 1.60       | 1.39 |
|                                                                                           |         | 30-40 | 0.22 | 8      | 1.54       | 1.33 |
|                                                                                           |         | 40-75 | 0.25 | 8      | 1.75       | 1.51 |
| 120°<br> | 8-T     | 20    | 0.23 | 7      | 1.58       | 1.36 |
|                                                                                           |         | 30    | 0.30 | 8      | 1.57       | 1.36 |
|                                                                                           |         | 40    | 0.36 | 9      | 1.67       | 1.45 |
|                                                                                           | 8-T-PC  | 50    | 0.40 | 9      | 1.66       | 1.44 |
|                                                                                           |         | 30-40 | 0.29 | 8      | 1.52       | 1.32 |
|                                                                                           |         | 40-75 | 0.35 | 8      | 1.84       | 1.59 |
| 180°<br> | 8-H     | 20    | 0.37 | 8      | 1.47       | 1.27 |
|                                                                                           |         | 30    | 0.50 | 8      | 1.75       | 1.51 |
|                                                                                           |         | 40    | 0.58 | 9      | 1.80       | 1.56 |
|                                                                                           | 8-H-PC  | 50    | 0.65 | 9      | 1.80       | 1.56 |
|                                                                                           |         | 30-40 | 0.44 | 8      | 1.54       | 1.33 |
|                                                                                           |         | 40-75 | 0.50 | 8      | 1.75       | 1.51 |
| 240°<br> | 8-TT    | 20    | 0.56 | 7      | 1.92       | 1.66 |
|                                                                                           |         | 30    | 0.70 | 8      | 1.84       | 1.59 |
|                                                                                           |         | 40    | 0.80 | 9      | 1.86       | 1.61 |
|                                                                                           | 8-TT-PC | 50    | 0.88 | 9      | 1.82       | 1.58 |
|                                                                                           |         | 30-40 | 0.59 | 8      | 1.55       | 1.34 |
|                                                                                           |         | 40-75 | 0.70 | 8      | 1.84       | 1.59 |
| 270°<br> | 8-TQ    | 20    | 0.63 | 7      | 1.92       | 1.66 |
|                                                                                           |         | 30    | 0.76 | 8      | 1.77       | 1.53 |
|                                                                                           |         | 40    | 0.86 | 9      | 1.78       | 1.54 |
|                                                                                           | 8-TQ-PC | 50    | 0.93 | 9      | 1.71       | 1.48 |
|                                                                                           |         | 30-40 | 0.64 | 8      | 1.49       | 1.29 |
|                                                                                           |         | 40-75 | 0.70 | 8      | 1.63       | 1.41 |
| 360°<br> | 8-F     | 20    | 0.74 | 7      | 1.69       | 1.46 |
|                                                                                           |         | 30    | 1.00 | 8      | 1.75       | 1.51 |
|                                                                                           |         | 40    | 1.16 | 9      | 1.80       | 1.56 |
|                                                                                           | 8-F-PC  | 50    | 1.30 | 9      | 1.80       | 1.56 |
|                                                                                           |         | 30-40 | 0.85 | 8      | 1.49       | 1.29 |
|                                                                                           |         | 40-75 | 1.00 | 8      | 1.75       | 1.51 |

## 10' Series with 17° Trajectory—Blue

| Arc                                                                                         | Desc.    | psi   | GPM  | Radius | Prec. Rate |      |
|---------------------------------------------------------------------------------------------|----------|-------|------|--------|------------|------|
|                                                                                             |          |       |      |        | ▲          | ☒    |
| 90°<br>  | 10-Q     | 20    | 0.30 | 9      | 1.66       | 1.44 |
|                                                                                             |          | 30    | 0.40 | 10     | 1.79       | 1.55 |
|                                                                                             |          | 40    | 0.50 | 11     | 1.85       | 1.60 |
|                                                                                             | 10-Q-PC  | 50    | 0.60 | 12     | 1.86       | 1.62 |
|                                                                                             |          | 30-40 | 0.33 | 10     | 1.48       | 1.28 |
|                                                                                             |          | 40-75 | 0.37 | 10     | 1.66       | 1.43 |
| 120°<br> | 10-T     | 20    | 0.42 | 9      | 1.74       | 1.51 |
|                                                                                             |          | 30    | 0.52 | 10     | 1.75       | 1.51 |
|                                                                                             |          | 40    | 0.65 | 11     | 1.80       | 1.56 |
|                                                                                             | 10-T-PC  | 50    | 0.75 | 12     | 1.75       | 1.51 |
|                                                                                             |          | 30-40 | 0.44 | 10     | 1.48       | 1.28 |
|                                                                                             |          | 40-75 | 0.50 | 10     | 1.68       | 1.45 |
| 180°<br> | 10-H     | 20    | 0.60 | 9      | 1.66       | 1.44 |
|                                                                                             |          | 30    | 0.71 | 10     | 1.59       | 1.38 |
|                                                                                             |          | 40    | 0.85 | 11     | 1.57       | 1.36 |
|                                                                                             | 10-H-PC  | 50    | 0.99 | 12     | 1.65       | 1.43 |
|                                                                                             |          | 30-40 | 0.66 | 10     | 1.48       | 1.28 |
|                                                                                             |          | 40-75 | 0.75 | 10     | 1.68       | 1.45 |
| 240°<br> | 10-TT    | 20    | 0.71 | 9      | 1.47       | 1.27 |
|                                                                                             |          | 30    | 0.97 | 10     | 1.63       | 1.41 |
|                                                                                             |          | 40    | 1.10 | 11     | 1.67       | 1.45 |
|                                                                                             | 10-TT-PC | 50    | 1.19 | 11     | 1.65       | 1.43 |
|                                                                                             |          | 30-40 | 0.89 | 10     | 1.49       | 1.29 |
|                                                                                             |          | 40-75 | 1.00 | 10     | 1.68       | 1.45 |
| 270°<br> | 10-TQ    | 20    | 0.82 | 9      | 1.51       | 1.31 |
|                                                                                             |          | 30    | 1.04 | 10     | 1.55       | 1.34 |
|                                                                                             |          | 40    | 1.20 | 11     | 1.62       | 1.41 |
|                                                                                             | 10-TQ-PC | 50    | 1.35 | 11     | 1.66       | 1.44 |
|                                                                                             |          | 30-40 | 0.99 | 10     | 1.48       | 1.28 |
|                                                                                             |          | 40-75 | 1.09 | 10     | 1.63       | 1.41 |
| 360°<br> | 10-F     | 20    | 1.11 | 9      | 1.72       | 1.49 |
|                                                                                             |          | 30    | 1.49 | 10     | 1.67       | 1.44 |
|                                                                                             |          | 40    | 1.61 | 11     | 1.63       | 1.42 |
|                                                                                             | 10-F-PC  | 50    | 1.85 | 11     | 1.71       | 1.48 |
|                                                                                             |          | 30-40 | 1.33 | 10     | 1.49       | 1.29 |
|                                                                                             |          | 40-75 | 1.51 | 10     | 1.69       | 1.46 |

## 12' Series with 24° Trajectory—Brown

| Arc                                                                                         | Desc.    | psi   | GPM  | Radius | Prec. Rate |      |
|---------------------------------------------------------------------------------------------|----------|-------|------|--------|------------|------|
|                                                                                             |          |       |      |        | ▲          | ☒    |
| 90°<br>  | 12-Q     | 20    | 0.40 | 11     | 1.48       | 1.28 |
|                                                                                             |          | 30    | 0.50 | 12     | 1.55       | 1.35 |
|                                                                                             |          | 40    | 0.60 | 13     | 1.64       | 1.42 |
|                                                                                             | 12-Q-PC  | 50    | 0.63 | 13     | 1.67       | 1.44 |
|                                                                                             |          | 30-40 | 0.48 | 12     | 1.49       | 1.29 |
|                                                                                             |          | 40-75 | 0.53 | 12     | 1.65       | 1.43 |
| 120°<br> | 12-T     | 20    | 0.57 | 11     | 1.58       | 1.37 |
|                                                                                             |          | 30    | 0.72 | 12     | 1.68       | 1.45 |
|                                                                                             |          | 40    | 0.87 | 13     | 1.87       | 1.62 |
|                                                                                             | 12-T-PC  | 50    | 0.97 | 13     | 1.93       | 1.67 |
|                                                                                             |          | 30-40 | 0.64 | 12     | 1.49       | 1.29 |
|                                                                                             |          | 40-75 | 0.70 | 12     | 1.63       | 1.41 |
| 180°<br> | 12-H     | 20    | 0.95 | 11     | 1.76       | 1.52 |
|                                                                                             |          | 30    | 1.09 | 12     | 1.69       | 1.47 |
|                                                                                             |          | 40    | 1.30 | 13     | 1.72       | 1.49 |
|                                                                                             | 12-H-PC  | 50    | 1.55 | 14     | 1.77       | 1.53 |
|                                                                                             |          | 30-40 | 0.96 | 12     | 1.49       | 1.29 |
|                                                                                             |          | 40-75 | 1.05 | 12     | 1.63       | 1.41 |
| 240°<br> | 12-TT    | 20    | 1.12 | 11     | 1.55       | 1.35 |
|                                                                                             |          | 30    | 1.45 | 12     | 1.69       | 1.46 |
|                                                                                             |          | 40    | 1.63 | 13     | 1.75       | 1.52 |
|                                                                                             | 12-TT-PC | 50    | 1.80 | 13     | 1.79       | 1.55 |
|                                                                                             |          | 30-40 | 1.28 | 12     | 1.49       | 1.29 |
|                                                                                             |          | 40-75 | 1.40 | 12     | 1.63       | 1.41 |
| 270°<br> | 12-TQ    | 20    | 1.05 | 11     | 1.42       | 1.23 |
|                                                                                             |          | 30    | 1.55 | 12     | 1.61       | 1.39 |
|                                                                                             |          | 40    | 1.65 | 13     | 1.58       | 1.36 |
|                                                                                             | 12-TQ-PC | 50    | 1.80 | 13     | 1.59       | 1.38 |
|                                                                                             |          | 30-40 | 1.44 | 12     | 1.49       | 1.29 |
|                                                                                             |          | 40-75 | 1.60 | 12     | 1.66       | 1.44 |
| 360°<br> | 12-F     | 20    | 1.67 | 11     | 1.54       | 1.34 |
|                                                                                             |          | 30    | 2.19 | 12     | 1.70       | 1.47 |
|                                                                                             |          | 40    | 2.35 | 13     | 1.68       | 1.46 |
|                                                                                             | 12-F-PC  | 50    | 2.70 | 13     | 1.79       | 1.55 |
|                                                                                             |          | 30-40 | 1.92 | 12     | 1.49       | 1.29 |
|                                                                                             |          | 40-75 | 2.10 | 12     | 1.63       | 1.41 |

## 15' Series with 28° Trajectory—Black

| Arc                                                                                         | Desc.    | psi   | GPM  | Radius | Prec. ▲ | Rate ☒ |
|---------------------------------------------------------------------------------------------|----------|-------|------|--------|---------|--------|
| 90°<br>  | 15-Q     | 20    | 0.68 | 14     | 1.55    | 1.34   |
|                                                                                             |          | 30    | 0.85 | 15     | 1.69    | 1.46   |
|                                                                                             |          | 40    | 1.04 | 16     | 1.82    | 1.57   |
|                                                                                             | 15-Q-PC  | 50    | 1.23 | 16     | 2.15    | 1.86   |
|                                                                                             |          | 30-40 | 0.75 | 15     | 1.49    | 1.29   |
| 120°<br> | 15-T     | 40-75 | 0.81 | 15     | 1.61    | 1.40   |
|                                                                                             |          | 20    | 0.95 | 14     | 1.75    | 1.52   |
|                                                                                             |          | 30    | 1.10 | 15     | 1.64    | 1.42   |
|                                                                                             | 15-T-PC  | 40    | 1.30 | 16     | 1.82    | 1.57   |
|                                                                                             |          | 50    | 1.45 | 16     | 2.03    | 1.75   |
| 180°<br> | 15-H     | 30-40 | 1.00 | 15     | 1.49    | 1.29   |
|                                                                                             |          | 40-75 | 1.10 | 15     | 1.64    | 1.42   |
|                                                                                             |          | 20    | 1.37 | 13     | 1.79    | 1.55   |
|                                                                                             | 15-H-PC  | 30    | 1.65 | 15     | 1.66    | 1.44   |
|                                                                                             |          | 40    | 2.02 | 16     | 1.77    | 1.53   |
| 240°<br> | 15-TT    | 50    | 2.14 | 16     | 1.87    | 1.62   |
|                                                                                             |          | 30-40 | 1.50 | 15     | 1.49    | 1.29   |
|                                                                                             |          | 40-75 | 1.65 | 15     | 1.64    | 1.42   |
|                                                                                             | 15-TT-PC | 20    | 1.78 | 14     | 1.59    | 1.38   |
|                                                                                             |          | 30    | 2.20 | 15     | 1.64    | 1.42   |
| 270°<br> | 15-TQ    | 40    | 2.66 | 16     | 1.74    | 1.51   |
|                                                                                             |          | 50    | 2.84 | 16     | 1.86    | 1.61   |
|                                                                                             |          | 30-40 | 2.00 | 15     | 1.49    | 1.29   |
|                                                                                             | 15-TQ-PC | 40-75 | 2.20 | 15     | 1.64    | 1.42   |
|                                                                                             |          | 20    | 2.10 | 13     | 1.85    | 1.61   |
| 360°<br> | 15-F     | 30    | 2.60 | 15     | 1.72    | 1.49   |
|                                                                                             |          | 40    | 3.00 | 16     | 1.86    | 1.61   |
|                                                                                             |          | 50    | 3.40 | 16     | 1.98    | 1.72   |
|                                                                                             | 15-F-PC  | 30-40 | 2.30 | 15     | 1.53    | 1.32   |
|                                                                                             |          | 40-75 | 2.50 | 15     | 1.66    | 1.44   |
| 360°<br> | 15-F     | 20    | 2.85 | 13     | 1.89    | 1.63   |
|                                                                                             |          | 30    | 3.60 | 15     | 1.79    | 1.55   |
|                                                                                             |          | 40    | 4.20 | 16     | 1.84    | 1.59   |
|                                                                                             | 15-F-PC  | 50    | 4.58 | 16     | 2.00    | 1.73   |
|                                                                                             |          | 30-40 | 3.00 | 15     | 1.49    | 1.29   |
|                                                                                             |          | 40-75 | 3.30 | 15     | 1.64    | 1.42   |