TECHNISCHE UNIVERSITÄT
KAISERSLAUTERN

# Seminar Seminar: Distributed Computer Systems SS23

On the Reliability of LTE Random Access: Performance Bounds for Machine-to-Machine Burst Resolution Time

Leonard Kleinberger
(lkleinbe@rhrk.uni-kl.de)

Table of Contents

1. LTE Networks

2. RACH as Bottleneck

3. RACH Procedure in Detail

4. Access Class Barring

5. Analysis

6. Simulation

LTE Networks

RACH Procedure as Bottleneck

RACH Procedure as Bottleneck

RACH Procedure in Detail

RACH Procedure

Objectives of UE:

- Synchronization
- Sending signal power
- Cell Configuration

RACH Procedure

UE   eNodeB

Cell Configuration
- Reference Signal, PSS, SSS
- MIB, SIB 1, SIB2, …

Random Access
- PRACH Preamble
- PRACH Preamble Response

RRC Setup
- RRC Connection Request
- RRC Connection Setup
- RRC Connection Setup Complete

UE:
- Send one of M Preambles on PRACH

eNodeB:
- Reply containing UL Grant on PRACH

RACH Procedure

Objective:
- Exchange UE specific Data
- Uses granted Resources

→ UE is signed up at eNodeB

RACH Procedure

UE   eNodeB

Cell Configuration
- Reference Signal, PSS, SSS
- MIB, SIB 1, SIB2, …

Random Access
- PRACH Preamble
- PRACH Preamble Response

RRC Setup
- RRC Connection Request

Preamble:
- Contains no UE specific Data
→ Will collide constructivly

Preamble Response:
- Assigns Grant to multiple Ues

Connection Request:
- Contains UE specific Data
Will collide destructivly

Access Class Barring

```
< LTE SIB2 >

sib2
  ac-BarringInfo
    ...1 .... ac-BarringForEmergency: True
    ac-BarringForMO-Signalling
      ac-BarringFactor: p00 (0)
      ac-BarringTime: s4 (0)
      ac-BarringForSpecialAC: 10000 (bitmap)
    ac-BarringForMO-Data
      ac-BarringFactor: p00 (0)
      ac-BarringTime: s4 (0)
      ac-BarringForSpecialAC: 00000 (bitmap)
  ....
  ssac-BarringForMMTEL-Voice-r9
    ac-BarringFactor: p00 (0)
    ac-BarringTime: s4 (0)
    ac-BarringForSpecialAC: 00000 (bitmap)
  ssac-BarringForMMTEL-Video-r9
    ac-BarringFactor: p00 (0)
    ac-BarringTime: s4 (0)
    ac-BarringForSpecialAC: 00000 (bitmap)
```

Different Access Class Barring Policies:

1. No Access Class Barring
2. Static Access Class Barring
   $\rightarrow$ Set p staticly
   $$p = x$$
3. Optimal Dynamic Access Class Barring
   $\rightarrow$ Change p every Frame
   $$p = min\left\{1, \frac{M}{B(i)}\right\}$$
4. Estimated Dynamic Access Class Barring
   Observe # of idle preambles
   Complex Algorithm based on Bayesian Algorithm

Analysis Quality of Service

$$qos = (b^\epsilon, t, \epsilon)$$

- b^ϵ is the allowed Backlog

- t is the time by which we demand that $B(t) \leq b^\epsilon$

- ϵ the allowed probability of violating the backlog condition

Analysis System Characteristics

$$sc = (N, M, a_i, acb)$$

- M is the number of Preambles

- N is the number of UEs arriving at t_0

- a_i is the number of UEs arriving at t_i

- acb is the Access Barring Policy

- $B(i)$ is the Backlog at t_i

Recursive Analysis

$$s_{i,m} = \begin{cases} 1 & if\ chosen\ by\ 1\ UE \\ 0 & else \end{cases}$$

$$B(i+1) = \max\{0, B(i) + a_i - s\_i\}$$

- Enables recursive calculations of Backlog

- Access Barring Policies can be applied every step

- Slow

Probabilistic Analysis

On the Reliability of LTE Random Access: Performance Bounds for Machine-to-Machine Burst Resolution Time

Mikhail Vilgelm[*], Sebastian Schiessl[†], Hussein Al-Zubaidy[†], Wolfgang Kellerer[*], James Gross[†]
[*] Chair of Communication Networks, Technical University of Munich, Germany
[†] School of Electrical Engineering, KTH Royal Institute of Technology, Stockholm, Sweden
Email: [*]{mikhail.vilgelm, wolfgang.kellerer}@tum.de, [†]{schiessl, hzubaidy, jamesgr}@kth.se

Abstract—Random Access Channel (RACH) has been identified as one of the major bottlenecks for accommodating massive number of Machine-to-Machine (M2M) devices in LTE networks, especially in the case of bursty arrivals of connection requests. As a consequence, the burst resolution problem has sparked a large number of works analyzing and optimizing the expected performance of RACH. In this paper, we go beyond the study of performance in expectation by investigating the probabilistic performance limits of RACH with access class barring. We model RACH as a queuing system, and apply stochastic network calculus to derive probabilistic performance bounds for burst resolution time, i.e., the time it takes to connect a burst of M2M devices to the base station. We illustrate the accuracy of the proposed methodology and its potential applications in performance assessment and system dimensioning.

I. INTRODUCTION

One of the main goals for the evolution from current wireless systems to 5G is to support massive Machine-to-Machine (M2M) communications. This could enable a number of promising applications, such as large scale sensor and actuator networks, smart grid monitoring, and many more [1]. Main challenges for enabling massive M2M are: improving scalability, enhancing energy efficiency, and decreasing the

developed [2], for instance, by means of back-off or barring, e.g., pseudo-Bayesian broadcast [6], or tree resolution algorithms [5]. For LTE, standardized mechanism to deal with burst arrivals is Access Class Barring (ACB) [3]: re-shaping the burst by broadcasting a RACH access probability for all UEs.

In the state-of-the-art, the performance of ACB and its derivatives [7], [8] has been extensively studied *in the expectation*, i.e., with respect to the *average* burst resolution time and resulting RACH efficiency [8]–[12]. In [9] and the follow-up work [10], the authors devised an analytical framework to assess the expected performance of the standardized ACB and Extended Access Class Barring (EAB) procedures, respectively. Jian *et al.* [12] have proposed another iterative approach to the ACB analysis, and Koseoglu [11] derived the lower bound on the average random access delay.

However, for many applications on the border between massive M2M and ultra reliable M2M [13], e.g., in-cabin communication in an aircraft or large-scale industrial automation [14], assessing the average performance is insufficient. For instance, if all the sensors in a factory need to re-connect after an emergency shutdown within a certain time limit [14]. In that case, *reliability guarantees for the RACH performance*

- Model Backlog Probability distribution with Moment Generating Functions

$$\mathbb{P}\left[s_i = k \mid b'_i = x\right] = \binom{x}{k}\binom{M}{k}\frac{k!}{M^x} \times$$
$$\times \sum_{i=1}^{j_{\max}} (-1)^j \binom{M-k}{j}\binom{x-k}{j} j! \, (M-k-j)^{x-k-j}$$

- Fast Analysis
- Compute satisfiable QoS Requirements
- Dimension LTE Networks
- Compare different Access Barring Policies

Simulation

Algorithm 2 Simulation Loop

1: Initialize N and $p_0 = 1/M$
2: **while** $B > b^\epsilon$ or $t_c < t$ **do**
3:     $t_c + = 1$
4:     draw B samples from a binomial distribution to get m admitted ues a
5:     draw a random integer samples from a uniform distribution $[0..M]$
6:     count the number of occurences of each preamble
7:     s_i = number of preambles chosen exactly once
8:     $B- = s_i$
9:     update p for dynamic ACB policies
10: **end while**
11: **if** $B > b^\epsilon$ **then**
12:     return success
13: **else**
14:     return failure
15: **end if**

FIXME:
improve vis

Simulation Result: Backlog over Time

Backlog over Time for different ACB, m = 20, N = 170

FIXME:
REMOVE NO ACB ON NEXT SLIDE

Simulation Results

maximum number of supported UEs vs total burst resolution violation probability for M = 10