
CS 6023 - GPU Programming Parallelisation Thinking

23/09/2018

Setting and Agenda

- What are the patterns of parallel programming in general (ie. beyond GPUs)?
- What are the specific characteristics of GPU programming?
- How to approach a new parallelisation task

Steps in Parallelisation



Dr. Rodric Rabbah, 6.189 MIT

Parallelising Programs

Patterns for Parallel Programming. Mattson, Sanders, and Massingill (2005) Identify the 4 aspects to parallelising programs:

1. Algorithm expression

- a. **Finding concurrency** Expose concurrent tasks
- b. **Algorithm structure** Map tasks to units of execution

2. Software construction

- a. **Supporting structures** Code and data structuring patterns
- b. **Implementation mechanisms** Low level programming mechanisms

Finding concurrency

- Types of concurrency:
 - Data
 - Geometric decomposition
 - Recursive data
 - Task
 - Linear task decomposition
 - Divide and conquer
 - Dataflow
 - Pipeline
 - Event-driven

Finding concurrency

- Types of concurrency:
 - Data
 - Geometric decomposition matrices
 - Recursive data tree, graph
 - Task
 - Linear task decomposition ray tracing, particle simulation
 - Divide and conquer merge sort
 - Dataflow
 - Pipeline digital signal processing
 - Event-driven process control

For GPUs ...

- The primary type of concurrency in GPUs is (geometric) data concurrency
 - Why? SPMD / SIMD semantics
 - Architecture evolved with graphics workload
- Applications can have range of data concurrency
 - Some can be embarrassingly parallel
 - Example $y_i = f(x_i)$ where f has no side-effects
 - Some can have control dependencies
 - Example: barrier synchronization, atomic operations
- Task parallelism also found, but limited in application
 - Example: ray tracing, particle physics

Algorithm structure

- Mapping application to units of execution
- This is a major challenge in distributed parallel programming (eg. cluster of PCs)
- However, with GPUs we are not concerned with mapping of tasks to SMs
 - Instead, we map tasks to threads, warps, blocks, and grids with well identified semantics
- Mapping decisions are driven by shared memory, registers, memory access patterns, synchronisation

Memory considerations in GPU

- We use the shared memory paradigm for GPUs, again inheriting form the graphics workload
 - Sharp contrast to message passing (eg. MPI) which could have point-to-point or broadcast communication patterns
- Memory shared between threads improves effective memory bandwidth
- But sharing memory between all threads can be a bottleneck too (atomics, serialization, large multi-ported memories)
- GPUs provide a mid-way solution: threads in the same block share faster memory, all threads share slower global memory

Software construction

- Code and data structuring patterns
 - In the non-GPU parallel world, these are significant challenges
 - For GPUs:
 - Code: careful alignment of warps to avoid control divergence
 - Data: patterns like tiling, privatisation, cached constant memory
- Low level programming mechanisms
 - o Again, in non-GPU parallel world, these are major focus areas
 - For GPUs:
 - Memcopies, atomics, synchronization, streams (yet to cover)

Parallel paradigms other than SPMD

- Loop parallelism
 - Assign each iteration of a loop to a different unit
- Master / worker
 - Master maintains a list of tasks to complete and workers register for pending work when free
- Fork / join
 - Each process can fork and join when new work is created and completed dynamically

Which works well where

	Task-level decomposition		Data decomposition		Data-flow based	
	Linear tasks	Divide and conquer	Geometric	Recursive	Pipeline	Event-driven
SPMD	***	**	****	**	***	*
Loop	***	**	***			
Master/worker	****	**	*	*	***	*
Fork/join	**	***	**		****	****

Exercise: Add another dimension between shared memory and message passing

Modified version from Dr. Rodric Rabbah, 6.189 MIT