

# kinetic-kit

## API Reference

v0.1.0

---

This document lists all public symbols exported by kinetic-kit.

### 1 Templates

#### 1.1 dissertation

- dissertation()

##### 1.1.1 dissertation

KIT doctoral dissertation template.

- author-title (str | none): Academic title preceding the author's name (e.g. "M.Sc. ").

### 1.1.1.1 Parameters

```
dissertation(  
  author-title,  
  author-firstname: str,  
  author-surname: str,  
  author-male: bool,  
  title: content,  
  doc-degree: str,  
  doc-degree-f: str,  
  department: str,  
  university-genitive: str,  
  status-approved: bool,  
  exam-date,  
  main-advisor,  
  main-advisor-male: bool,  
  co-advisor,  
  co-advisor-male: bool,  
  format,  
  lang,  
  margin-preset,  
  binding-correction: length,  
  colored-links: bool,  
  draft: bool,  
  draft-info,  
  serif-headings: bool,  
  heading-numbering-depth: int,  
  abstract-en,  
  abstract-de,  
  acknowledgements,  
  notation,  
  abbreviations,  
  show-lof: bool,  
  show-lot: bool,  
  show-lol: bool,  
  figure-kinds: array,  
  own-publications,  
  own-patents,  
  supervised-theses,  
  bibliography,  
  appendix,  
  doc: content  
) -> content
```

#### 1.1.1.1.1 author-firstname str

Author's first name.

Default: "Max"

#### 1.1.1.1.2 author-surname `str`

Author's surname.

Default: `"Mustermann"`

#### 1.1.1.1.3 author-male `bool`

true for male, false for female grammatical forms.

Default: `true`

#### 1.1.1.1.4 title `content`

Dissertation title.

Default: `[Your Thesis Title]`

#### 1.1.1.1.5 doc-degree `str`

Degree name in masculine form.

Default: `"Doktors der Ingenieurwissenschaften (Dr.-Ing.)"`

#### 1.1.1.1.6 doc-degree-f `str`

Degree name in feminine form.

Default: `"Doktorin der Ingenieurwissenschaften (Dr.-Ing.)"`

#### 1.1.1.1.7 department `str`

Faculty / department name.

Default: `"KIT-Fakultät für Maschinenbau"`

#### 1.1.1.1.8 university-genitive `str`

University name in genitive case.

Default: `"des Karlsruher Instituts für Technologie (KIT)"`

#### 1.1.1.1.9 status-approved `bool`

false = submitted, true = approved.

- exam-date (str | none): Date of oral examination (when approved).
- main-advisor (str | none): Main referee (when approved).

Default: `false`

#### 1.1.1.1.10 main-advisor-male bool

Grammatical gender for main advisor label.

- co-advisor (str | none): Co-referee (when approved).

Default: **true**

#### 1.1.1.1.11 co-advisor-male bool

Grammatical gender for co-advisor label.

- format ("a5" | "17x24" | "a4"): Paper format — "a5" (148×210 mm, default), "17x24" (170×240 mm), or "a4" (210×297 mm, discouraged by KSP). Font sizes and margins are set automatically.
- lang ("de" | "en"): Document language.
- margin-preset ("short" | "medium" | "long"): Margin profile keyed on page count.

Default: **true**

#### 1.1.1.1.12 binding-correction length

BCOR added to inside margin. Default 0mm.

Default: **0mm**

#### 1.1.1.1.13 colored-links bool

KIT Blue links when true, black when false.

Default: **true**

#### 1.1.1.1.14 draft bool

Show "ENTWURF" watermark when true.

- draft-info (str | none): Optional version string below watermark. Default none.

Default: **false**

#### 1.1.1.1.15 serif-headings bool

Use serif font for headings when true. Default false (sans-serif).

Default: **false**

#### 1.1.1.1.16 heading-numbering-depth `int`

Deepest heading level to number. Default 3.

- abstract-en (content | none): English abstract. none = omit.
- abstract-de (content | none): German abstract. none = omit.
- acknowledgements (content | none): Acknowledgements. none = omit.
- notation (content | none): Notation list. none = omit.
- abbreviations (content | none): Abbreviations list. none = omit.

Default: `3`

#### 1.1.1.1.17 show-lof `bool`

Include List of Figures.

Default: `true`

#### 1.1.1.1.18 show-lot `bool`

Include List of Tables.

Default: `true`

#### 1.1.1.1.19 show-lol `bool`

Include List of Listings.

Default: `false`

#### 1.1.1.1.20 figure-kinds `array`

Figure kinds beyond image, table and raw, as dictionaries with kind, supplement, and optionally list-title and show-list. supplement and list-title take either one value or one per language, e.g. (de: [Algorithmus], en: [Algorithm]). The built-in kinds are not declared here — their list pages are governed by show-lof / show-lot / show-lol. Declared kinds get a list page after the built-in ones, in declaration order.

- own-publications (content | none): Own publications content (heading added by template). none = omit.
- own-patents (content | none): Own patents content (heading added by template). none = omit.
- supervised-theses (content | none): Supervised theses content (heading added by template). none = omit.
- bibliography (content | none): Bibliography content. Pass bibliography("refs.bib", title: none, style: "ieee"). The template adds a translated heading. none = omit.
- appendix (content | none): Appendix chapters. Template applies A, A.1, ... numbering and places the appendix before the back-matter lists. none = omit.

Default: `()`

#### 1.1.1.1.21 doc content

Main document body (chapters only).

## 1.2 thesis

- thesis()

### 1.2.1 thesis

KIT Master's / Bachelor's / Diploma thesis template.

#### 1.2.1.1 Parameters

```
thesis(  
  author-firstname: str,  
  author-surname: str,  
  title: content,  
  thesis-type: str,  
  department: str,  
  university-genitive: str,  
  examiner,  
  supervisor,  
  date-submitted,  
  format,  
  lang,  
  margin-preset,  
  binding-correction: length,  
  colored-links: bool,  
  draft: bool,  
  draft-info,  
  serif-headings: bool,  
  heading-numbering-depth: int,  
  abstract-en,  
  abstract-de,  
  acknowledgements,  
  abbreviations,  
  show-lof: bool,  
  show-lot: bool,  
  show-lol: bool,  
  figure-kinds: array,  
  bibliography,  
  appendix,  
  doc: content  
) -> content
```

##### 1.2.1.1.1 author-firstname str

Author's first name.

Default: "Max"

#### 1.2.1.1.2 author-surname `str`

Author's surname.

Default: `"Mustermann"`

#### 1.2.1.1.3 title `content`

Thesis title.

Default: `[Your Thesis Title]`

#### 1.2.1.1.4 thesis-type `str`

e.g. `"Masterarbeit"`, `"Bachelorarbeit"`.

Default: `"Masterarbeit"`

#### 1.2.1.1.5 department `str`

Faculty / department name.

Default: `"KIT-Fakultät für Maschinenbau"`

#### 1.2.1.1.6 university-genitive `str`

University name in genitive case.

- `examiner (str | none)`: First examiner. `none` if unknown.
- `supervisor (str | none)`: Supervisor. `none` if unknown.
- `date-submitted (str | none)`: Submission date string. `none` if unknown.
- `format ("a5" | "17x24" | "a4")`: Paper format — `"a5"` (148×210 mm, default), `"17x24"` (170×240 mm), or `"a4"` (210×297 mm). Font sizes and margins are set automatically.
- `lang ("de" | "en")`: Document language.
- `margin-preset ("short" | "medium" | "long")`: Margin profile keyed on page count.

Default: `"des Karlsruher Instituts für Technologie (KIT)"`

#### 1.2.1.1.7 binding-correction `length`

BCOR added to inside margin. Default 0mm.

Default: `0mm`

#### 1.2.1.1.8 colored-links `bool`

KIT Blue links when `true`, black when `false`.

Default: `true`

#### 1.2.1.1.9 draft bool

Show “ENTWURF” watermark when true.

- draft-info (str | none): Optional version string below watermark. Default none.

Default: false

#### 1.2.1.1.10 serif-headings bool

Use serif font for headings when true. Default false (sans-serif).

Default: false

#### 1.2.1.1.11 heading-numbering-depth int

Deepest heading level to number. Default 3.

- abstract-en (content | none): English abstract. none = omit.
- abstract-de (content | none): German abstract. none = omit.
- acknowledgements (content | none): Acknowledgements. none = omit.
- abbreviations (content | none): Abbreviations list. none = omit.

Default: 3

#### 1.2.1.1.12 show-lof bool

Include List of Figures.

Default: true

#### 1.2.1.1.13 show-lot bool

Include List of Tables.

Default: true

#### 1.2.1.1.14 show-lol bool

Include List of Listings.

Default: false

#### 1.2.1.1.15 figure-kinds array

Figure kinds beyond image, table and raw, as dictionaries with kind, supplement, and optionally list-title and show-list. supplement and list-title take either one value or one per language, e.g. (de: [Algorithmus], en: [Algorithm]). The built-in kinds are not declared here — their list pages are governed by show-lof / show-lot / show-lol. Declared kinds get a list page after the built-in ones, in declaration order.

- bibliography (content | none): Bibliography content. Pass bibliography("refs.bib", title: none, style: "ieee"). The template adds a translated heading. none = omit.
- appendix (content | none): Appendix chapters. Template applies A, A.1, ... numbering and places the appendix before the back-matter lists. none = omit.

Default: ()

#### 1.2.1.1.16 doc content

Main document body (chapters only).

## 2 Style Constants

The kit-style dictionary exposes the template's visual constants so that custom figures, diagrams, and other content can match the document's typography and KIT color palette exactly.

```
#import "@local/kinetic-kit:0.1.0": kit-style

#let font-sizes = kit-style.font-sizes-by-format.at("a5")
#set text(font: kit-style.fonts.sans, size: font-sizes.small)
#rect(fill: kit-style.colors.green15, stroke: kit-style.colors.green)
```

### 2.1 Fonts

| Field       | Value                 | Description                                             |
|-------------|-----------------------|---------------------------------------------------------|
| fonts.serif | ("Libertinus Serif",) | Serif body text                                         |
| fonts.sans  | ("Libertinus Sans",)  | Sans-serif headings and headers                         |
| fonts.mono  | ("Libertinus Mono",)  | Code listings                                           |
| leading     | 0.75em                | Paragraph line spacing ( $\approx 1.15\times$ at 10 pt) |

### 2.2 Font Sizes

font-sizes-by-format is a dictionary keyed by format string ("a5", "17x24", "a4"). Each entry contains the sizes below. Access them with `kit-style.font-sizes-by-format.at(format)`.

All fields are length. Example values shown for the "a5" format (10 pt base).

| Field         | A5 / 17x24 | A4   | Description                      |
|---------------|------------|------|----------------------------------|
| base          | 10pt       | 11pt | Body text                        |
| chapter       | 18pt       | 25pt | Chapter heading (level 1)        |
| section       | 14pt       | 17pt | Section heading (level 2)        |
| subsection    | 12pt       | 14pt | Subsection heading (level 3)     |
| subsubsection | 10pt       | 11pt | Subsubsection heading (level 4+) |

| Field      | A5 / 17×24 | A4   | Description                          |
|------------|------------|------|--------------------------------------|
| small      | 8pt        | 9pt  | Running headers, footnotes, captions |
| footnote   | 8pt        | 9pt  | Footnote text                        |
| title      | 18pt       | 25pt | Title page — document title          |
| author     | 14pt       | 14pt | Title page — author name             |
| title-info | 14pt       | 14pt | Title page — info lines              |

## 2.3 Colors

All values are color. KIT brand colors follow a systematic naming scheme: base name plus optional opacity suffix (70, 50, 30, 15 = 70 %, 50 %, 30 %, 15 % tint).

| Field            | Hex     | Description                          |
|------------------|---------|--------------------------------------|
| colors.green     | #009682 | KIT Green — primary brand color      |
| colors.green70   | #4CB5A7 |                                      |
| colors.green50   | #7FCAC0 |                                      |
| colors.green30   | #B2DFD9 |                                      |
| colors.green15   | #D9EFEC |                                      |
| colors.blue      | #4664AA | KIT Blue — links and accents         |
| colors.blue70    | #7D92C3 |                                      |
| colors.blue50    | #A2B1D4 |                                      |
| colors.blue30    | #C7D0E5 |                                      |
| colors.blue15    | #E3E8F2 |                                      |
| colors.black     | #000000 |                                      |
| colors.black70   | #4D4D4D |                                      |
| colors.black50   | #808080 |                                      |
| colors.black30   | #B3B3B3 |                                      |
| colors.black15   | #D9D9D9 |                                      |
| colors.palegreen | #82BE3C | KIT extended palette                 |
| colors.yellow    | #FAE614 |                                      |
| colors.orange    | #DCA01E |                                      |
| colors.brown     | #A08232 |                                      |
| colors.red       | #A01E28 |                                      |
| colors.lilac     | #A00078 |                                      |
| colors.cyanblue  | #50AAE6 |                                      |
| colors.keyword   | #0000C8 | Syntax highlighting — keyword        |
| colors.comment   | #3F7F5F | Syntax highlighting — comment        |
| colors.string    | #700055 | Syntax highlighting — string literal |

## 3 Components

The components module exports the individual building blocks for assembling a document without the full `dissertation()` / `thesis()` orchestrator. All symbols are accessed through the components namespace:

```
#import "@local/kinetic-kit:0.1.0": components

#let format = "a5"

#show: components.setup-page.with(format: format, margin-preset: "short", lang: "de")
#show: components.setup-front-matter
#components.print-toc(lang: "de")
```

You are responsible for applying the wrappers in the correct order: setup-page → setup-front-matter → content → setup-content → (optionally) setup-appendix.

## 3.1 Page Setup

### 3.2 page-setup

- setup-page()
- setup-front-matter()
- setup-content()
- setup-appendix()

#### 3.2.1 setup-page

Apply the full KIT document style: page geometry, running headers, KSP typography, heading styles, figure captions, equations, and code blocks. Use as a show rule: `#show: setup-page.with(...)`.

##### 3.2.1.1 Parameters

```
setup-page(
  format: str,
  margin-preset: str,
  lang: str,
  binding-correction: length,
  colored-links: bool,
  draft: bool,
  draft-info: content,
  serif-headings: bool,
  heading-numbering-depth: int,
  figure-kinds: array,
  doc: content
) -> content
```

##### 3.2.1.1.1 format str

Paper format — "a5" (148×210 mm, default), "17x24" (170×240 mm), or "a4" (210×297 mm). Font sizes and margins are set automatically per KSP specifications.

Default: "a5"

##### 3.2.1.1.2 margin-preset str

Margin profile keyed on expected page count — "short" (under 200 pp), "medium" (200–399 pp), "long" (400+ pp).

Default: "short"

#### 3.2.1.1.3 lang `str`

Document language — "de" or "en".

Default: "de"

#### 3.2.1.1.4 binding-correction `length`

Extra inside margin added for binding (e.g. 3mm).

Default: 0mm

#### 3.2.1.1.5 colored-links `bool`

Render external hyperlinks in KIT blue when true.

Default: true

#### 3.2.1.1.6 draft `bool`

Show the draft watermark on every page when true.

Default: false

#### 3.2.1.1.7 draft-info `content`

Optional extra text appended to the watermark (e.g. a git SHA).

Default: none

#### 3.2.1.1.8 serif-headings `bool`

Use Libertinus Serif for headings when true. Default false

Default: false

#### 3.2.1.1.9 heading-numbering-depth `int`

Deepest heading level that receives a number. Default 3. Headings deeper than this are styled normally but rendered without a number or indent grid.

Default: 3

#### 3.2.1.1.10 figure-kinds `array`

Figure kind declarations, merged onto the built-in image, table and raw entries. Supplies the caption supplements; printing the matching list pages is the caller's job.

Default: ()

#### 3.2.1.1.11 doc `content`

Document body (injected automatically by the show rule).

### 3.2.2 setup-front-matter

Switch to Roman numeral page numbering and remove heading numbering. Apply before front-matter content: #show: setup-front-matter.

#### 3.2.2.1 Parameters

```
setup-front-matter(doc: content) -> content
```

#### 3.2.2.1.1 doc `content`

Document body (injected automatically by the show rule).

### 3.2.3 setup-content

Switch to Arabic page numbering and enable 1.1 heading numbering. Apply before the main content: #show: setup-content.

#### 3.2.3.1 Parameters

```
setup-content(doc: content) -> content
```

#### 3.2.3.1.1 doc `content`

Document body (injected automatically by the show rule).

### 3.2.4 setup-appendix

Switch to A.1 heading numbering and reset the heading counter. Apply before appendix chapters: #show: setup-appendix.

#### 3.2.4.1 Parameters

```
setup-appendix(doc: content) -> content
```

#### 3.2.4.1.1 doc `content`

Document body (injected automatically by the show rule).

## 3.3 Title Pages

### 3.4 title-page

- print-dissertation-title()
- print-thesis-title()

### 3.4.1 print-dissertation-title

Render the KIT dissertation title page (German legal format). All text on this page is always in German regardless of document language.

#### 3.4.1.1 Parameters

```
print-dissertation-title(  
  title: content,  
  author-title: content,  
  author-firstname: str,  
  author-surname: str,  
  author-male: bool,  
  doc-degree: str,  
  doc-degree-f: str,  
  department: str,  
  university-genitive: str,  
  status-approved: bool,  
  exam-date: content,  
  main-advisor: content,  
  main-advisor-male: bool,  
  co-advisor: content,  
  co-advisor-male: bool,  
  format: str  
) -> content
```

##### 3.4.1.1.1 title content

Dissertation title.

##### 3.4.1.1.2 author-title content

Academic title preceding the author's name (none = omit).

Default: "M.Sc."

##### 3.4.1.1.3 author-firstname str

Author's first name.

Default: "Max"

##### 3.4.1.1.4 author-surname str

Author's surname.

Default: "Mustermann"

##### 3.4.1.1.5 author-male bool

Selects grammatical gender for the degree article.

Default: true

#### 3.4.1.1.6 doc-degree `str`

Degree name in masculine form (e.g. "Doktor-Ingenieur").

Default: "Doktors der Ingenieurwissenschaften (Dr.-Ing.)"

#### 3.4.1.1.7 doc-degree-f `str`

Degree name in feminine form (e.g. "Doktor-Ingenieurin").

Default: "Doktorin der Ingenieurwissenschaften (Dr.-Ing.)"

#### 3.4.1.1.8 department `str`

KIT department or faculty.

Default: "KIT-Fakultät für Maschinenbau"

#### 3.4.1.1.9 university-genitive `str`

University name in genitive (e.g. "des Karlsruher Instituts...").

Default: "des Karlsruher Instituts für Technologie (KIT)"

#### 3.4.1.1.10 status-approved `bool`

false = submitted version, true = approved version.

Default: false

#### 3.4.1.1.11 exam-date `content`

Date of oral examination — shown only when status-approved is true.

Default: none

#### 3.4.1.1.12 main-advisor `content`

Main referee — shown only when status-approved is true.

Default: none

#### 3.4.1.1.13 main-advisor-male `bool`

Selects gendered label for the main advisor.

Default: true

#### 3.4.1.1.14 co-advisor `content`

Co-referee — shown only when status-approved is true.

Default: `none`

#### 3.4.1.1.15 co-advisor-male `bool`

Selects gendered label for the co-advisor.

Default: `true`

#### 3.4.1.1.16 format `str`

Paper format — "a5", "17x24", or "a4". Determines font sizes and title-page margins.

Default: `"a5"`

### 3.4.2 print-thesis-title

Render the KIT master's / bachelor's thesis title page (German legal format). All text on this page is always in German regardless of document language.

#### 3.4.2.1 Parameters

```
print-thesis-title(  
  title: content,  
  thesis-type: str,  
  author-firstname: str,  
  author-surname: str,  
  department: str,  
  university-genitive: str,  
  examiner: content,  
  supervisor: content,  
  date-submitted: content,  
  format: str  
) -> content
```

##### 3.4.2.1.1 title `content`

Thesis title.

##### 3.4.2.1.2 thesis-type `str`

Thesis type (e.g. "Masterarbeit", "Bachelorarbeit").

Default: `"Masterarbeit"`

#### 3.4.2.1.3 author-firstname `str`

Author's first name.

Default: `"Max"`

#### 3.4.2.1.4 author-surname `str`

Author's surname.

Default: `"Mustermann"`

#### 3.4.2.1.5 department `str`

KIT department or faculty.

Default: `"KIT-Fakultät für Maschinenbau"`

#### 3.4.2.1.6 university-genitive `str`

University name in genitive (e.g. "des Karlsruher Instituts...").

Default: `"des Karlsruher Instituts für Technologie (KIT)"`

#### 3.4.2.1.7 examiner `content`

First examiner (Erstprüfer).

Default: `none`

#### 3.4.2.1.8 supervisor `content`

Supervisor (Betreuer).

Default: `none`

#### 3.4.2.1.9 date-submitted `content`

Submission date string.

Default: `none`

#### 3.4.2.1.10 format `str`

Paper format — "a5", "17x24", or "a4". Determines font sizes and title-page margins.

Default: `"a5"`

## 3.5 Outlines

### 3.6 outlines

- `setup-outlines()`

- `print-toc()`
- `print-list-of()`
- `print-lof()`
- `print-lot()`
- `print-lol()`

### 3.6.1 `setup-outlines`

Shared outline styling, applied as a show rule so every outline in the document — including a user's own — matches.

#### 3.6.1.1 Parameters

```
setup-outlines(body: content) -> content
```

##### 3.6.1.1.1 `body` `content`

Document body (injected automatically by the show rule).

### 3.6.2 `print-toc`

Print the table of contents.

#### 3.6.2.1 Parameters

```
print-toc(lang: str) -> content
```

##### 3.6.2.1.1 `lang` `str`

Document language — "de" or "en".

Default: "de"

### 3.6.3 `print-list-of`

Print a back-matter list page for one figure kind.

Handles the in-outline state that switches flex-caption to its short form, which a hand-rolled `outline(target: ...)` would miss.

- `kind` (function | str): Figure kind to list — an element function such as `image`, or a string such as "algorithm".
- `title` (content | str): Heading of the list page.

#### 3.6.3.1 Parameters

```
print-list-of(
  kind,
  title
) -> content
```

### 3.6.4 print-lof

Print the list of figures.

#### 3.6.4.1 Parameters

```
print-lof(lang: str) -> content
```

##### 3.6.4.1.1 lang str

Document language — "de" or "en".

Default: "de"

### 3.6.5 print-lot

Print the list of tables.

#### 3.6.5.1 Parameters

```
print-lot(lang: str) -> content
```

##### 3.6.5.1.1 lang str

Document language — "de" or "en".

Default: "de"

### 3.6.6 print-lol

Print the list of listings.

#### 3.6.6.1 Parameters

```
print-lol(lang: str) -> content
```

##### 3.6.6.1.1 lang str

Document language — "de" or "en".

Default: "de"

## 3.7 Figures

### 3.8 figures

- flex-caption()
- setup-figures()

#### 3.8.1 flex-caption

Two-part caption: short version for LoF/LoT, long version under the figure.

Usage: `#figure(..., caption: flex-caption(short: [Short], long: [Long.] )`

### 3.8.1.1 Parameters

```
flex-caption(  
  short: content,  
  long: content  
) -> content
```

#### 3.8.1.1.1 short content

Short caption shown in List of Figures / Tables.

Default: none

#### 3.8.1.1.2 long content

Full caption shown below the figure in the document body.

Default: none

### 3.8.2 setup-figures

Shared figure, caption, and table styling. Apply as a show rule.

#### 3.8.2.1 Parameters

```
setup-figures(  
  font-sizes: dict,  
  lang: str,  
  figure-kinds: array,  
  body: content  
) -> content
```

##### 3.8.2.1.1 font-sizes dict

Format-specific font sizes resolved by the template.

##### 3.8.2.1.2 lang str

Document language — "de" or "en".

Default: "de"

##### 3.8.2.1.3 figure-kinds array

Figure kind declarations, merged onto the built-in ones. Only the supplements are read here; list pages are printed by the template's back matter.

Default: ()

#### 3.8.2.1.4 body content

Document body (injected automatically by the show rule).

### 3.9 Figure Kinds

Typst keeps a separate counter and supplement for every figure kind. The template carries strings for Typst's own image, table and raw, because those names are template chrome; their list pages are governed by the `show-lo*` booleans. Any other kind — pseudocode, theorems, whatever a document needs — is declared through the `figure-kinds` parameter of `dissertation()` / `thesis()`, which supplies the caption supplement and, optionally, a back-matter list page.

Per-chapter counter resets are not part of this registry. `setup-headings` derives them from the figures present in the document, so every kind restarts each chapter whether or not it has been declared.

```
#show: dissertation.with(  
  figure-kinds: (  
    (  
      kind: "algorithm",  
      supplement: (de: [Algorithmus],          en: [Algorithm]),  
      list-title: (de: [Algorithmenverzeichnis], en: [List of Algorithms]),  
      show-list: true,  
    ),  
    // Supplement only — no list page.  
    (kind: "theorem", supplement: (de: [Satz], en: [Theorem])),  
  ),  
)
```

### 3.10 figure-kinds

- `resolve-localized()`
- `resolve-figure-kinds()`

#### 3.10.1 resolve-localized

Pick the variant of a per-language value that matches a language.

Values may be plain content or a dictionary keyed by language code. A plain value is used for every language; a dictionary is looked up by `lang`, then by `fallback`, and fails loudly if neither is present.

- `value` (content | str | dict): Plain value, or one variant per language code.

##### 3.10.1.1 Parameters

```
resolve-localized(  
  value,  
  lang: str,  
  fallback,  
  kind,  
  field: str  
) -> content | str
```

#### 3.10.1.1.1 lang `str`

Language to look up first — usually `text.lang` at the use site.

- `fallback` (`str` | `none`): Language to fall back to, usually the document language.
- `kind` (`function` | `str` | `none`): Figure kind, used in the error message only.

#### 3.10.1.1.2 field `str`

Field name, used in the error message only.

Default: `"value"`

### 3.10.2 resolve-figure-kinds

Resolve the document's figure kinds into one ordered list.

The built-in kinds come first, in the canonical order of their list pages, with visibility taken from the three booleans. Kinds the document declares follow, in declaration order. Declaring a built-in kind is an error.

#### 3.10.2.1 Parameters

```
resolve-figure-kinds(  
  figure-kinds: array,  
  show-lof: bool,  
  show-lot: bool,  
  show-lol: bool  
) -> array
```

##### 3.10.2.1.1 figure-kinds `array`

Entries declared by the document.

##### 3.10.2.1.2 show-lof `bool`

Whether the list of figures is printed.

Default: `true`

##### 3.10.2.1.3 show-lot `bool`

Whether the list of tables is printed.

Default: `true`

##### 3.10.2.1.4 show-lol `bool`

Whether the list of listings is printed.

Default: `false`

## 3.11 Headings

### 3.12 headings

- setup-headings()

#### 3.12.1 setup-headings

Shared heading styling: per-level sizes and spacing, chapter page breaks and counter resets, and number-body alignment. Apply as a show rule.

##### 3.12.1.1 Parameters

```
setup-headings(  
  font-sizes: dict,  
  serif-headings: bool,  
  heading-numbering-depth: int,  
  body: content  
) -> content
```

###### 3.12.1.1.1 font-sizes dict

Format-specific font sizes resolved by the template.

###### 3.12.1.1.2 serif-headings bool

Use Libertinus Serif for headings when true.

Default: `false`

###### 3.12.1.1.3 heading-numbering-depth int

Deepest heading level that receives a number.

Default: `3`

###### 3.12.1.1.4 body content

Document body (injected automatically by the show rule).