```
init()
        - controller state \mathbf{C} = \mathsf{TRAJ}
        - number of joints {\it J}
        - noise threshold \epsilon
       - joint times \mathbf{t}_{i,0} = 0 \ \forall i \in J
        - joint states \mathbf{j}_{i,0} = \mathsf{NO\_CONTACT} \ \forall i \in J
        - forces \mathbf{f}_{i,0} s \mathbf{f}_{i,t-1} = 0 \ \forall i \in J
        - feather constant estimator \bar{k}_{i,0} = 0 \ \forall i \in J
update(Period p)
update sensors();
// update joint states & timing
for i in \left[0...J-1\right] do
       \begin{array}{l} \text{if } \mathbf{f}_{i,t-1} \leq \epsilon \text{ \&\& } \mathbf{f}_{i,t} > \epsilon \text{ then} \\ \mid \mathbf{s}_{i,t} = \text{GOT\_CONTACT} \end{array}
         else if \mathbf{f}_{i,t-1} > \epsilon && \mathbf{f}_{i,t} \leq \epsilon then \mathbf{s}_{i,t} = \mathsf{LOST\_CONTACT}
       else if \mathbf{f}_{i,t-1}
       \begin{array}{l} \text{else if } \mathbf{f}_{i,t-1} > \epsilon \text{ \&\& } \mathbf{f}_{i,t} > \epsilon \text{ then} \\ \mid \mathbf{s}_{i,t} = \text{IN\_CONTACT} \end{array}
        \mathbf{s}_{i,t} = \mathsf{NO} \mathsf{\_CONTACT}
       end
       if \mathbf{s}_{i,t} == \mathsf{NO\_CONTACT} \parallel \mathbf{s}_{i,t} == \mathsf{LOST\_CONTACT} then
        | \mathbf{t}_{i,t} \leftarrow \mathbf{t}_{i,t} + p |
end
// update controller state
if C == TRANS then
      \mathbf{C} = \mathbf{F} \mathbf{\_CTRL}
else if \mathbf{C} == \text{TRAJ} then
       \begin{array}{c|c} \text{if } \textbf{check\_contro} \\ & C = \textbf{TRANS} \end{array}
                          _controller_transition() then
              for i in \left[0,J-1\right] do
                    \mathbf{f}_{i,T} \leftarrow \mathbf{f}_{i.t}
                     \mathbf{j}_{i,T} \leftarrow \mathbf{j}_{i,t}
              end
// joint position calculations
for i in [0, J - 1] do
       if \mathbf{C} == \text{TRAJ} \mid\mid \mathbf{C} == \text{TRANS} then
            \mathbf{j}_{\mathsf{des}_{i,t}} \leftarrow \mathbf{sample\_trajectory\_for\_joint}(\mathsf{Joint}\ i, \mathsf{Time}\ \mathbf{t}_{i,t})
       else
              // calculate new deltas, estimate \bar{k} and calculate new \mathbf{j}_{\mathsf{des}_{i,t}}
              TIAGo
                                                                   \Delta \mathbf{f}_{i,t} = \mathbf{f}_{i,t} - \mathbf{f}_{i,T}
                                                                   \Delta \mathbf{j}_{i,t} = \mathbf{j}_{i,t} - \mathbf{j}_{i,T}
                                                                          k_{i,t} = \frac{\mathbf{f}_{i,t}}{\mathbf{j}_{i,t}}
                                                           \bar{k}_{i,t} = (1 - \lambda)k_{i,t} + \lambda \bar{k}_{i,t}
                                                            \mathbf{f}_{\mathsf{des}_{i,t}} = 1.1 * \mathbf{f}_{\mathsf{max}_i} - \mathbf{f}_{i,t}
                                                              \mathbf{j}_{\mathsf{des}_{i,t}} = rac{\mathbf{f}_{\mathsf{des}_{i,t}}}{ar{k}_{i,t}} + \mathbf{j}_{i,t}
               Shadow
                                                                                                                                                  (1)
       end
end
publish_debug_info();
if C == TRAJ then
       if last Segment successfully executed then
             goal_succeeded();
else
       if \mathbf{f}_{i,t} \geq \mathbf{f}_{\mathsf{max}_i} \forall i \in [0, J-1] then
             force_finished();
              goal_succeeded();
end
// store data for next loop
for i in [0, J-1] do
       \mathbf{f}_{i,t-1} \leftarrow \mathbf{f}_{i,t}
      \mathbf{s}_{i,t-1} \leftarrow \mathbf{s}_{i,t}
end
                   Algorithm 1: Platform-Independent Force Controller
```