

Day03_MCQ_Questions



1.

```
#include <stdio.h>
int main ()
{
    float f = 2.9;
    int i = (int)f;
    printf ("%-*d", i+2, i);
    printf ("%8.6f \n", f - i);
    return 0;
}
```

- A) 2 0.900000
- B) 2.9 0.9
- C) 2 0
- D) compile time error

Answer: A

2.

```
#include<stdio.h>
int main ()
{
    printf ("sunbeam\r%d", sizeof (2+3.5));
    return 0;
}
```

- A) sunbeam8
- B) 8unbeam
- C) 4unbeam
- D) sunbeam

Answer: B

Day03_MCQ_Questions

3.

```
#include<stdio.h>
int main ()
{
    signed char a=322;
    unsigned char b = -1;
    printf ("%d %d %c", b-a, sizeof(a=1), a);
    return 0;
}
```

- A) 127, 4, -124
- B) -323,1, 322
- C) 127, 4, A
- D) 189,1, B

Answer: D

4.

What is the range of values for a signed short data type in C?

- A) -128 to 127
- B) -32,768 to 32,767
- C) -2^{31} to $2^{31} - 1$
- D) 0 to 65,535

Answer: B

5.

What will be the output of the following code?

```
#include <stdio.h>
int main () {
    short x = 32767;
    x = x + 1;
    printf ("%d\n", x);
    return 0;
}
```

- A) 32768
- B) -32768
- C) 0
- D) 32767

Answer: B