

Day04_MCQ_Questions



SUNBEAM
Exploring New Ideas Reaching New Heights

1.
`#include<stdio.h>`
`void main ()`
`{`
 `int i = 10;`
 `i = !i > !14;`
 `printf ("%d", i);`
`}`

- A. 10
- B. 14
- C. 0
- D. 1
- E. None of these

Answer: C

2.
`#include<stdio.h>`
`int main ()`
`{`
 `unsigned int a = 65535;`
 `signed int b = -2;`
 `int c= (a > b) + 65535;`
 `printf ("%d", c);`
 `return 0;`
`}`

- A.65534
- B.65535
- C.65536
- D.65533

Answer: B

3.
`#include <stdio.h>`
`int main ()`
`{`
 `int a, b;`
 `a = 4, b = 0;`
 `int result = printf ("%d ", (a--) + sizeof(++b));`
 `printf ("%d %d %d", a, b, result);`

 `return 0;`
`}`

- A. 8 3 0 2
- B. 8 4 1 2
- C. 4 4 0 8
- D. 8 3 0 1

Answer: A

4.
`#include<stdio.h>`
`int main ()`
`{`
 `int a, b, c;`
 `a = 8, b = 2;`
 `c = ~ (a ^ b / a << b);`
 `printf ("%d", c);`
 `return 0;`
`}`

- A. 8
- B. -9
- C. -5
- D. 4

Answer: B

5.

```
#include<stdio.h>
int main ()
{
    int a=0, b=-1, c=0, d=-1, e;
    e= a++&&--b|| c++ && --d;
    printf ("%d %d %d %d %d\n" ,a, b, c, d, e);
    e=a++&&--b||c++&&--d;
    printf ("%d %d %d %d %d", a, b, c, d, e);
}
```

- A. 1 -1 1 -1 0 2 -2 2 -2 0
- B. 0 -1 0 -1 1 2 -2 2 -2 0
- C. 1 -1 1 -1 1 2 -2 2 -2 1
- D. 1 -1 1 -1 0 1 -1 1 -1 0

Answer: A