

1)

```
#include<stdio.h>
int main ()
{
    ~printf ("")? printf("true"): printf ("false");
    return 0;
}
```

- A) true
- B) false
- C) 1
- D) 0

Answer: A

2)

```
#include<stdio.h>
int main ()
{
    int num1 = 12, num2 = 15;

    if (num1 < 10 || num2 > 20)
        printf ("Inside If! \n");
    else if (num1 < 10 && num2 >= 15)
        printf ("Inside 1st Else if! \n");
    else if (num1 < 20 || num2 > 20)
        printf ("Inside 2nd else if! \n");
    else
        printf ("Inside Else! \n");

    return 0;
}
```

- A) Inside If
- B) Inside 1st Else if
- C) Inside 2nd Else if
- D) Inside Else

Answer: C

3)

```
#include<stdio.h>
int main ()
{
    int b=15, c=5, d=8, e=8, a;
    a = b> c? c>d? 12: d>e? 13: 14: 15;
    printf ("%d", a);
    return 0;
}
```

A) 13

B) 14

C) 15

D) 12

Answer: B

4)

```
#include<stdio.h>
int main ()
{
    int x = 30;
    if (x > 10, ~x > 10) {
        if (x < 25) {
            printf("Hello");
        }
        else {
            printf("World");
        }
    }
    else {
        if (~~x < 5) {
            printf("hello");
        }
        else {
            printf("world");
        }
    }
    return 0;
}
```

- A) Hello
- B) World
- C) hello
- D) world

Answer: D

5)
`#include<stdio.h>`

```
int main ()  
{  
    int num1 = 67, num2 = 99;  
  
    if (num1 == 'A')  
        printf ("A \n");  
    else if (num1 == 'C' && num2 == 'c')  
        printf ("C and c \n");  
    else if (num2 >= 90 || num1 >= 65)  
        printf ("99 and 67 \n");  
    else  
        printf ("Invalid Comparison! \n");  
    return 0;  
}
```

- A) Error: type Mismatch
- B) Prints A
- C) Prints C and c
- D) Prints 99 and 67
- E) Invalid Comparison

Answer: C