



Day10_MCQ_Questions

1.

```
#include<stdio.h>
int main ()
{
    char *ptr = "Sunbeam";
    printf ("%cn", *&*&ptr);
    return 0;
}
```

- A) n
- B) S
- C) Sn
- D) garbage value

Answer: C

2.

What is the correct syntax to set the value at the location as constant?

- A) const type *pointer_name;
- B) type const *pointer_name;
- C) Both A. and B.
- D) None of the above

Answer: C

3.

```
#include <stdio.h>
int main () {
    int *ptr, a = 100;
    ptr = &a;
    *ptr += 1;
    printf ("%d, %d\n", *ptr, a+1);
}
```

- A) 100, 101
- B) 100, 100
- C) 101, 100
- D) 101, 102

Answer: D

Day10_MCQ_Questions

4.

```
#include <stdio.h>
int fun (int n, int *p)
{
    int t, f;
    if (n <= 1)
    {
        *p = 1;
        return 1;
    }
    t = fun (n- 1, p);
    f = t+ * p;
    *p = t;
    return f;
}
```

```
int main ()
{
    int x = 15;
    printf (" %d \n", fun (5, &x));
    return 0;
}
```

- A) 8 \n
- B) 8
- C) 15
- D) stack overflow

Answer: A

Day10_MCQ_Questions

5.

```
#include <stdio.h>
int main ()
{
    int *ptr;
    int x;
    ptr = &x;
    *ptr = 0;
    printf (" x = %d\n", x);
    printf (" *ptr = %d\n", *ptr);
    *ptr += 5;
    printf (" x = %d\n", x);
    printf (" *ptr = %d\n", *ptr);
    *ptr++;
    printf (" x = %d\n", x);
    printf (" *ptr = %d\n", *ptr);
    return 0;
}
```

A) x = 0
*ptr = 0
x = 0
*ptr = 0
x = 0
*ptr = 0

B) Compile time error

C) x = 0
*ptr = 0
x = 5
*ptr = 5
x = 6
*ptr = garbage value

D) x = 0
*ptr = 0
x = 5
*ptr = 5
x = 5
*ptr = garbage value

Answer: D