

1.

What will be the output of the following C code?

```
int main () {  
    int i;  
    float arr [5] = {5.2,2.2};  
    for (i = 0; i < 5; i++)  
        printf ("%0.1f ", arr[i]);  
    return 0;  
}
```

- A) 5.2, 2.2
- B) 5.2, 2.2, 0.0, 0.0, 0.0
- C) 5.2, 2.2, (garbage), (garbage), (garbage)
- D) (garbage), (garbage), (garbage), 2.2, 5.2

Answer: B

2.

```
#include<stdio.h>
```

```
int main () {  
    int i;  
    int arr [5] = {1};  
    for (i = 0; i < 5; i++)  
        printf ("%d ", arr[i]);  
    return 0;  
}
```

- A) 1 1 1 1 1
- B) 1 0 0 0 0
- C) Compile time error
- D) garbage

Answer: D

3.

```
#include<stdio.h>
int main () {
    int i;
    float arr [5] = {1.2, 2.2, 3.1, 4.4, 5.5};
    for (i = 0; i < 5; i++) {
        if(arr[i] % 2.0f == 0)
            printf ("%0.2f ", arr[i]);
        continue;
    }
    return 0;
}
```

- A) 2.20, 4.40
- B) Runtime error
- C) 1.2, 2.2, 3.1, 4.4, 5.5
- D) Compile time error

Answer: D

4.

```
#include <stdio.h>
int main () {
    int arr [] = {1, 2, 3, 4};
    int *p = arr;
    printf ("%d, ", p[2] + arr[1]);
    p++;
    printf ("%d", *(p+2));
    return 0;
}
```

- A) 2, 1
- B) 3, 2
- C) 5, 4
- D) Array out of bound

Answer: C

5.

```
#include <stdio.h>
```

```
int main () {
```

```
    int arr [] = {1, 2, 3, 4, 5};
```

```
    int *p = arr;
```

```
    *(p + 3) += *(p + 1) + *(p + 2);
```

```
    printf ("%d", arr [3]);
```

```
    return 0;
```

```
}
```

A) 7

B) 5

C) 4

D) 9

Answer: C