

1.

What will be the output of the following C code?

```
#include<stdio.h>
int main()
{
    int num1, num2;

    num1= sizeof(float)*4;
    num2= sizeof(double)*8;

    printf("%+d %+d %+d",num1,num2,num1-num2);

    return 0;
}
```

- A. +16 +64 -48
- B. 16 +64 +48
- C. +16 64 +48
- D. 16 64 48

Answer: A

2

What are the entities whose values can be changed called?

- A. Constants
- B. Variables
- C. Modules
- D. Tokens

Answer: B

3. . Which data type is most suitable for storing a number 65000 in a 32-bit system?

- A. signed short
- B. unsigned short
- C. long
- D. int

Answer: B

4. What will be the output of the following C code?

```
#include<stdio.h>
int main()
{
    signed char ch;
    ch = 128;
    printf("%d\n", ch);

    return 0;
}
```

- A. 128
- B. -128
- C. Depends on the compiler
- D. None of the mentioned

Answer: B

5.

What will be the output of the following C code?

```
#include<stdio.h>
int main()
{
    signed char ch=-129;
    unsigned char ch1=-7;

    printf("%c",ch1-ch);

    return 0;
}
```

- A.122
- B.Z
- C.z
- D.136
- E.-136

Answer: C