

1.

What will be the output of the following C code?

```
#include<stdio.h>
int main()
{
    int a=2,b=3;

    int result=printf("XOR=%d\n", a^b);
    int result1=printf("AND=%d\n",a&b);

    printf("%d\n",result);
    printf("%d\n",result1);
    return 0;
}
```

- A. XOR=3 AND=3 6 6
B. XOR=1 AND=2 6 6
C. XOR=3 AND=3 5 5
D. XOR=1 AND= 2 5 5

Answer:B

2.

What will be the output of the following C code?

```
#include<stdio.h>
int main()
{
    int a,b,c;
    a=8,b=2;
    c=a<<b && a>>b;
    printf("%d ,%d ,%d",a,b,c);
    return 0;
}
```



Day04_Poll_Questions

- ☒ A. 8 , 2 , 1
- B. 16 , 2 , 1
- C. 8 , 10 , 0
- D. 8 , 2 , 0

Answer:A

3. What will be the output of the following C code?

```
#include<stdio.h>
int main()
{
    int a,b,c,d,e;
    d=(a=printf("PG-DMC "), b=printf("PG-DESD"),
    printf(" ") , c=printf("PG-DITISS"));
    e=++a, b++, c--, --d;
    printf(" %d %d %d % d",a++,--b,++c,d++);
    return 0;
}
```

- A. PG-DMC PG-DESDPG-DITISS 8 7 8 7
- B. 8 7 9 8
- C. PG-DMC PG-DESD PG-DITISS
- ☒ D. PG-DMC PG-DESD PG-DITISS 8 7 9 8

Answer:D

4.

#include<stdio.h>

int main()

```
{
    signed char a=-3;
    unsigned char b;

    printf("\n sunbeam%d\r-%d \n",a==b,b=a);
    return 0;
}
```

- A. -253 eam0
 B. sunbeam 0 -3
 C. sunbeam 0 253
 D. sunbeam 0 -253

Answer:A

5.

#include <stdio.h>

int main()

```
{
    int y = 1;
    y = (y & (y = 2)),y++;
    printf(" y=%d\n", y);
    return 0;
}
```

- A. y=2
 B. y=3
 C. y=1
 D. Error

Answer:B

```
0010
0010
-----
0000
```