

1.

What will be the output of the following C code?

```
#include<stdio.h>
int main( void )
{
    int SunBeam;
    if (printf("0"))
        SunBeam = 120;
    else;
        SunBeam = 240;
    printf("%d", SunBeam);
    return 0;
}
```

- A. 120
- B. 240
- C. 0120240
- ☒ D. 0240
- E. 0120

Answer: D

2.

```
#include <stdio.h>
int main(void)
{
    if(printf("Welcome To ");)
    if((printf(" Sunbeam ") + 2) % 2 == 1)
        printf(" Pune ");
    else if ("" )
        printf(" Karad ");
    else
        printf(" CDAC ");
    return 0;
}
```

- A. Welcome to Sunbeam pune
- B. Welcome to Sunbeam karad
- C. Welcome to CDAC
- D. Compile time error
- E. Run time error

Answer : D

3. What will be the output of the following C code?

```
#include <stdio.h>
int main()
{
    int DacCapacity=120;
    if(DacCapacity=240);
        printf("Sunbeam Pune");
    else if(DacCapacity=120)
        printf("Sunbeam Karad");
    else
        printf("Sunbeam Market Yard");

    return 0;
}
```

- A. Sunbeam Pune
- B. Sunbeam karad
- C. Sunbeam MarkrtYard
- ☒ D. Compiler Time Error
- E. Run Time Error

Answer:D

4. What will be the output of the following C code?

```
#include <stdio.h>
int main()
{
    int var1=1,var2=0;
    int var;
    (var = ((var1,var2)?var1++:var2--));
    printf("var1=%d var2=%d var=%d",var1, var2, var);
    return 0;
}
```

- A. var1=2 var2=0 var=1
- ☒ B. var1=1 var2=-1 var=0
- C. var1=1 var2=-1 var=1
- D. Compile time error
- E. var1=2 var2=0 var=0

Answer: B

5. In which of the following is not an appropriate scenario to use the conditional operator?

- A. Assigning a value based on a comparison
- ☒ B. Returning a value from a function based on a condition

e.g. condition? return true part : return false part ;

- C. Performing complex logical operations involving multiple conditions
- D. Shortening an if-else statement

Answer: B