

1.

What will be the output of the following C code?

```
#include<stdio.h>
int main()
{
    int a=5;
    for (int i = 1; i<5; i++,a++)
        printf("%d\t", a*i);

    return 0;
}
```

- A. 5,12,21,32
- B. 5,10,15,20
- C. 5,12,21,24
- D. 5,15,25,35

Answer:A

2.

```
#include <stdio.h>
int main()
{
    int i = 10;
    while (i >= 0)
    {
        printf("%d\n", i);
        i -= 5+i==5;
    }

    return 0;
}
```

- A. its print 10 infinite times (infinite loop)
- B. its print 0
- C. No output
- D. Compile Time Error

Answer:A

3.

```
#include <stdio.h>
int main()
{
    int i = 10;
    int j = 0;
    while (i > 0)
    {
        printf("%d\n", i);
        if (i == 5)
        {
            i = (j++ % 2 == 0) ? (i - 5) : (i - 1);
        }
        else
        {
            i--;
        }
    }
    return 0;
}
```

- A. 10, 9, 8, 7, 6, 5
- B. 10,9,8,7,6
- C. 9,4,3,2,1,0,-1,-2
- D. 10,9,8,7,6,5,3,2

Answer:A

4.
What will be the output of the following C code?

```
#include <stdio.h>
int main()
{
    int i, j;

    for (i = 0; i < 2; i++)
    {
        for (j = 0; j < 2; j++)
        {
            if (i == 1 && j == 1) break;
            if (i == 2 && j == 2) continue;
            printf("i=%d, j=%d ", i, j);
        }
    }

    return 0;
}
```

- A. i=0, j=0 i=0, j=1 i=1, j=0
- B. i=0, j=1 i=0, j=1 i=1, j=1
- C. i=0, j=0 i=0, j=1 i=1, j=1
- D. i=0, j=1 i=0, j=1 i=1, j=1

Answer:A

5. What will be the output of the following C code?

```
#include <stdio.h>
int main()
{
    short i = 0;
    float f = 1.0;

    do
    {
        printf("i=%d\t", i);
        f += 0.1;
        i++;
    } while ((i < 5 && f < 2.0) || (i == 5 && f >= 2.0));

    return 0;
}
```

- A. i=0 i=1 i=2 i=3 i=4
- B. i=0 i=0 i=0 i=0 i=0
- C. i=0 i=2 i=4 i=6 i=8
- D. i=1 i=2 i=3 i=4 i=5

Answer:A

-