

1.

What will be the output of the following C code?

```
#include <stdio.h>
```

```
int x=12;
```

```
void fun();
```

```
int main()
```

```
{
```

```
    int x=10;
```

```
    fun(x);
```

```
    return 0;
```

```
}
```

```
void fun()
```

```
{
```

```
    printf("%2d",x-=2);
```

```
    if(x)
```

```
        fun();
```

```
    return ;
```

```
}
```

A. 10 8 6 4 2 0

B. 12 10 8 6 4 2

C. 8 6 4 2 0

D. 10 6 4 2

E. Compile time error

Answer: A

2. What will be the output of the following C code?

```
#include<stdio.h>
int fun1(int x, int y)
{
    if (x == 0)
        return y;
    else
        return fun1(x - 1, x + y);
}
int main()
{
    int k = fun1(5,3);

    printf("%d ",k);

    return 0;
}
```

- A. 3
- B. 5
- C. 18
- D. 12
- E. Run Time Error

Answer: C

3. What will be the output of the following C code?

```
#include<stdio.h>
int f1(int c)
{
    if(c==0)
        return 0;
    else
    {
        printf("i");
        f1(c--);
    }
}
int main()
{
    int a;

    a=f1(5);

    printf("%d",a);
    return 0;
}
```

- A. iiiii0
- B. iii0
- C. Compile Time Error
- D. Run Time Error(Stack OverFlow)
- E. Compile time Error

Answer: D

4.

What will be the output of the following C code?

```
#include<stdio.h>
static int num=8;

int main(void)
{
    if(num<0)
    {
        return 0;
    }
    else if(num%2==0)
    {
        num--;
        printf("%3d,",num-=1);
    }
    else
    {
        printf("%3d,",num-=2);
    }
    main();
    return 0;
}
```

- A. 6, 4, 2, 0, -2,
- B. 8, 6, 4, 2, 0, -2,
- C. 6, 4, 2, -2,
- D. 6, 4, 2, 0,
- E. Compile time error

Answer: A

5.

What will be the output of the following C code?

```
#include<stdio.h>
void rec(char c);
int main()
{
    int n1 = 57;
    rec(n1);
}
void rec(char c)
{
    if(c<48)
        return ;
    rec(c-1);
    printf(" %c ",c);
}
```

- A. 0 1 2 3 4 5 6 7 8 9
- B. 9 8 7 6 5 4 3 2 1 0
- C. 1 2 3 4 5 6 7 8 9
- D. 9 8 7 6 5 4 3 2 1
- E. Stack overflow error

Answer: A