

1.

What will be the output of the following C code

```
#include <stdio.h>
#include <string.h>
int main(void)
{
    char dest[] = "Advance Computer", src[] = "Java";
    puts(strcpy(&dest[8], src) - 8);
    return 0;
}
```

- A. Advance
- B. Computer
- C. Java
- D. Advance Java

Answer: D

2.

What will be the output of the following C code

```
#include <stdio.h>
#include <string.h>
int main(void)
{
    char* str1 = "Sunbeam", str2 = "Pune";
    char* str3 = NULL;
    str3 = strcat(str1, str2);
    printf("%s %s", str3, str1);
    return 0;
}
```

- A. Compile time error
- B. Runtime error
- C. NULL Sunbeam
- D. None of above

Answer: B

3. What will be the output of the following C code

```
#include<stdio.h>
#include<string.h>
int main( void )
{
    char str1[] = "SunbeamKarad";
    char str2[] = {'S', 'u', 'n', 'b', 'e', 'a', 'm', 'K', 'a', 'r', 'a', 'd', '\0'};
    int n1 = sizeof(str1)/sizeof(str1[0]);
    int n2 = strlen(str2)/sizeof(str2[1]);
    printf("n1 = %d, n2 = %d", n1, n2);
    return 0;
}
```

- A.n1 = 13, n2 = 12
- B.n1 = 13, n2 = 13
- C.n1 = 12, n2 = 12
- D.n1 = 12, n2 = 13

Answer: A

4. What will be the output of the following C code

```
#include<stdio.h>
int main( void )
{
    int i = 0 ;
    char str[] = "\0";
    if(printf("%s", str))
        printf("empty string i=%d\n", i);
    else
        printf("not empty string \n");
    return 0;
}
```

- A empty string
- B not empty string
- C No output
- D 0
- E empty string i=0

Answer: B

5. What will be the output of the following C code

```
#include<stdio.h>
int main()
{
    char str1[] = "Sunbeam Pune and Karad";
    char str2[40];
    int index=0;
    char *t=NULL, *s=NULL;
    s = str1;
    t = str2;
    while(*(t+index)=*(s+index))
    {
        *t++ = *s++;
    }
    printf("%s", str2);
    return 0;
}
```

- A. Sunbeam
- B. Karad
- C. Sunbeam Pune and Karad
- D. infinite loop

Answer: C