

1.

What will be the output of the following C code?

```
#include<stdio.h>
void fun(int **pp);
int main(void)
{
    int arr[4][4] = {{1, 2},{4, 3, 2},{1, 3},{7}};
    int *ptr=NULL;
    ptr = &arr[1][1];

    printf("%d\t",sizeof(arr)/sizeof(arr[1][2]));
    fun(&ptr);

    return 0;
}
void fun(int **pp)
{
    printf("- %d", **pp);
    return;
}
```

- A. 16 - 3
- B. 8 - 3
- C. 16 - 2
- D. 8 - 2
- E. Compile time error

Answer: A

2.

What will be the output of the program assuming that the array begins at the location 1000 and size of an integer is 4 bytes?

```
#include<stdio.h>
int main(void)
{
    int arr[3][4] = { 11, 22, 33, 44, 55, 66, 77, 88, 99 };
    printf("%u %u, %u",arr[1]+1, *(arr[1]+1), (*(arr+1)+1));

    return 0;
}
```

- A. 1016 , 55, 55
- B. 1020, 66, 66
- C. 1020 , 55, 55
- D. 1016 , 66, 55,
- D. 1020 , 55, 66,

Answer: B

3.

What will be the output of the following C code?

```
#include<stdio.h>
int main(void)
{
    static char *s[] = {"PG-DAC", "PG-DMC", "PG-DITIS",
                       "PG-DBDA", "PG-DESD"};
    char **ptr[] = {s+4, s+3, s+2, s+1, s};
    char ***p=NULL;
    p = ptr;
    ++p;
    p++;
    printf("%s", 2 + **p -1*2, p--);
    return 0;
}
```

- A. PG-DBDA
- B. PG-DMC
- C. PG-DAC
- D. PG-DESD
- E. PG-DITIS

Answer: A

4. What will be the output of the following C code?

```
#include<stdio.h>
int main(void)
{
    static char arr[6][9] = {"PRECAT",
                             "PG-DAC",
                             "PG-DMC",
                             "PG-DITIS",
                             "PG-DBDA",
                             "PG-DESD"};

    printf("%c, %s", *(arr[3]+6)-6, (*(arr+3)+6)-6);

    return 0;
}
```

- A. C, DITIS
- B. C, PG-DITIS
- C. -, PG-DITIS
- D. -, DITIS
- E. Compile Time error

Answer: B

5.

What will be the output of the following C code?

```
#include<stdio.h>
int main(void)
{
    char arr0[] = "DAC";
    char arr1[] = "DESD";
    char arr2[] = "DMC";
    char arr3[] = "DBDA";
    char arr4[] = "PreCAT";

    char *ptr_arr[5]= {arr0,arr1, arr2 ,arr3, arr4 };
    char *ptr = ptr_arr[4];

    printf("%c-%s\n",*(ptr+3) + *(ptr+3) - ptr[3],
           (ptr+3) - *(ptr+1) + ptr[1]);

    return 0;
}
```

- A.P-CAT
- B.E-CAT
- C.C-CAT
- D.None of the above
- E.Compiler error

Answer: C