

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 470, y: 283

PC-PT PC0

PC-PT PC1

Time: 00:05:20

Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```
$LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/1, changed state to up
$LINK-5-CHANGED: Interface FastEthernet2/1, changed state to up
$LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet2/1, changed state to up
$LINK-5-CHANGED: Interface FastEthernet3/1, changed state to up
$LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet3/1, changed state to up

Switch>show vlan

VLAN Name                Status    Ports
-----
1    default                  active    Fa0/1, Fa1/1, Fa2/1, Fa3/1
                                         Fa4/1, Fa5/1

1002 fddi-default           active
1003 token-ring-default    active
1004 fddinet-default        active
1005 trnet-default         active

VLAN Type  SAID      MTU   Parent RingNo BridgeNo Stp  BrgdMode Trans1 Trans2
-----
1    enet    100001    1500  -     -     -     -   -       0       0
1002 fddi    101002    1500  -     -     -     -   -       0       0
1003 tr     101003    1500  -     -     -     -   -       0       0
1004 fdnet  101004    1500  -     -     -     -   ieee    0       0
1005 trnet  101005    1500  -     -     -     -   ibm     0       0

VLAN Type  SAID      MTU   Parent RingNo BridgeNo Stp  BrgdMode Trans1 Trans2
-----
Remote SPAN VLANs
--More--
```

Copy Paste

Realtime Simulation

Type Color Time(sec) Periodic Num Edit

9:54 08.02.2025