```
GET DATA  /TYPE=TXT
  /FILE="/Users/loren/Desktop/grades copy.csv"
  /DELCASE=LINE
  /DELIMITERS=","
  /ARRANGEMENT=DELIMITED
  /FIRSTCASE=2
  /IMPORTCASE=ALL
  /VARIABLES=
  Final F3.0
  MT1 F2.0
  MT2 F2.0
  Project F2.0
  HW F2.0.
CACHE.
EXECUTE.
DATASET NAME DataSet1 WINDOW=FRONT.
CORRELATIONS
  /VARIABLES=Final MT1 MT2 Project HW
  /PRINT=TWOTAIL NOSIG
  /STATISTICS DESCRIPTIVES
  /MISSING=PAIRWISE.
```

Correlations

Notes

Output Created		**27-JUL-2015 14:44:25**
Comments		
Input	**Data**	**/Users/loren/Desktop/g rades copy.csv**
	Active Dataset	**DataSet1**
	Filter	**<none>**
	Weight	**<none>**
	Split File	**<none>**
	N of Rows in Working Data File	**6 4**
Missing Value Handling	**Definition of Missing**	**User-defined missing values are treated as missing.**
	Cases Used	**Statistics for each pair of variables are based on all the cases with valid data for that pair.**
Syntax		**CORRELATIONS /VARIABLES=Final MT1 MT2 Project HW /PRINT=TWOTAIL NOSIG /STATISTICS DESCRIPTIVES /MISSING=PAIRWISE.**
Resources	**Processor Time**	**00:00:00.01**
	Elapsed Time	**00:00:00.00**

[DataSet1]

Descriptive Statistics

	Mean	Std. Deviation	N
Final	154.98	26.631	6 4
MT1	86.09	11.508	6 4
MT2	74.23	18.591	6 4
Project	10.08	1.159	6 4
HW	72.25	11.693	6 4

Correlations

		Final	MT1	MT2	Project	HW
Final	Pearson Correlation	1	.715**	.543**	.087	.273*
	Sig. (2-tailed)		.000	.000	.492	.029
	N	64	64	64	64	64
MT1	Pearson Correlation	.715**	1	.454**	.101	.301*
	Sig. (2-tailed)	.000		.000	.429	.016
	N	64	64	64	64	64
MT2	Pearson Correlation	.543**	.454**	1	-.032	.218
	Sig. (2-tailed)	.000	.000		.803	.084
	N	64	64	64	64	64
Project	Pearson Correlation	.087	.101	-.032	1	.098
	Sig. (2-tailed)	.492	.429	.803		.441
	N	64	64	64	64	64
HW	Pearson Correlation	.273*	.301*	.218	.098	1
	Sig. (2-tailed)	.029	.016	.084	.441	
	N	64	64	64	64	64

**. Correlation is significant at the 0.01 level (2-tailed).

*. Correlation is significant at the 0.05 level (2-tailed).

```
REGRESSION
 /DESCRIPTIVES MEAN STDDEV CORR SIG N
 /MISSING LISTWISE
 /STATISTICS COEFF OUTS R ANOVA
 /CRITERIA=PIN(.05) POUT(.10)
 /NOORIGIN
 /DEPENDENT Final
 /METHOD=ENTER MT1.
```

Regression

Notes

Output Created		**27-JUL-2015 14:51:10**
Comments		
Input	**Data**	**/Users/loren/Desktop/grades copy.csv**
	Active Dataset	**DataSet1**
	Filter	**<none>**
	Weight	**<none>**
	Split File	**<none>**
	N of Rows in Working Data File	**64**
Missing Value Handling	**Definition of Missing**	**User-defined missing values are treated as missing.**
	Cases Used	**Statistics are based on cases with no missing values for any variable used.**
Syntax		**REGRESSION /DESCRIPTIVES MEAN STDDEV CORR SIG N /MISSING LISTWISE /STATISTICS COEFF OUTS R ANOVA /CRITERIA=PIN(.05) POUT(.10) /NOORIGIN /DEPENDENT Final /METHOD=ENTER MT1.**
Resources	**Processor Time**	**00:00:00.02**
	Elapsed Time	**00:00:00.00**
	Memory Required	**2528 bytes**
	Additional Memory Required for Residual Plots	**0 bytes**

Descriptive Statistics

	Mean	Std. Deviation	N
Final	154.98	26.631	64
MT1	86.09	11.508	64

Correlations

		Final	MT1
Pearson Correlation	Final	1.000	.715
	MT1	.715	1.000
Sig. (1-tailed)	Final	.	.000
	MT1	.000	.
N	Final	64	64
	MT1	64	64

Variables Entered/Removed[a]

Model	Variables Entered	Variables Removed	Method
1	MT1[b]	.	Enter

a. Dependent Variable: Final

b. All requested variables entered.

Model Summary

Model	R	R Square	Adjusted R Square	Std. Error of the Estimate
1	.715[a]	.512	.504	18.759

a. Predictors: (Constant), MT1

ANOVA[a]

Model		Sum of Squares	df	Mean Square	F	Sig.
1	Regression	22861.837	1	22861.837	64.969	.000[b]
	Residual	21817.147	62	351.889		
	Total	44678.984	63			

a. Dependent Variable: Final

b. Predictors: (Constant), MT1

Coefficients[a]

Model		Unstandardized Coefficients		Standardized Coefficients	t	Sig.
		B	Std. Error	Beta		
1	(Constant)	12.471	17.836		.699	.487
	MT1	1.655	.205	.715	8.060	.000

a. Dependent Variable: Final